



# Quantile Plot

- Displays all of the data
  - Allowing the user to assess both the overall behavior and unusual occurrences




# Quantile Plot

- Plots **quantile** information
  - For a data  $x_i$  data sorted in increasing order,  $f_i$  indicates that approximately 100  $f_i\%$  of the data are below or equal to the value  $x_i$




# Quantile-Quantile (Q-Q) Plot

- Displays the quantiles of one univariate distribution against the corresponding quantiles of another
- View: Is there is a shift in going from one distribution to another?




# Quantile-Quantile (Q-Q) Plot

- Example: Shows unit price of items sold at Branch 1 vs. Branch 2 for each quantile.
  - Unit prices of items sold at Branch 1 tend to be lower than those at Branch 2.






# Scatter plot

- Each pair of values is treated as a pair of coordinates and plotted as a point in the plane
- Provides a first look at bivariate data to see clusters of points, outliers, etc





# Positively and Negatively Correlated Data



- The left half fragment is positively correlated
- The right half is negative correlated




# Uncorrelated Data



# Chapter 2: Getting to Know Your Data

---

- Data Objects and Attribute Types
- Basic Statistical Descriptions of Data
- Measuring Data Similarity and Dissimilarity 
- Summary





# Similarity and Dissimilarity

---

- **Similarity**

- Numerical measure of **how much alike** two data objects are
- This value is higher when objects are more alike
- Often falls in the range  $[0,1]$

- **Dissimilarity** (e.g., distance)

- Numerical measure of **how much different** two data objects are
- Lower when objects are more alike
- Minimum dissimilarity is often 0
- Upper limit varies

- **Proximity** refers to a similarity or dissimilarity



# Data Matrix and Dissimilarity Matrix

## ■ Data matrix

- n data points with p dimensions (attributes)
- Two modes

$$\begin{bmatrix} x_{11} & \dots & x_{1f} & \dots & x_{1p} \\ \dots & \dots & \dots & \dots & \dots \\ x_{i1} & \dots & x_{if} & \dots & x_{ip} \\ \dots & \dots & \dots & \dots & \dots \\ x_{n1} & \dots & x_{nf} & \dots & x_{np} \end{bmatrix}$$

## ■ Dissimilarity matrix

- n data points, but registers only the distance
- A triangular matrix
- Single mode

$$\begin{bmatrix} 0 & & & & \\ d(2,1) & 0 & & & \\ d(3,1) & d(3,2) & 0 & & \\ \vdots & \vdots & \vdots & & \\ d(n,1) & d(n,2) & \dots & \dots & 0 \end{bmatrix}$$



# Proximity Measure for Nominal Attributes

---

- Can take 2 or more states, e.g., red, yellow, blue, green (generalization of a binary attribute)
- Method 1: Simple matching
  - $m$ : # of matches,  $p$ : total # of variables

$$d(i, j) = \frac{p - m}{p}$$

- Method 2: Use a large number of binary attributes
  - creating a new binary attribute for each of the  $M$  nominal states



# Proximity Measure for Binary Attributes

- A contingency table for binary data

		O j		
		1	0	sum
O i	1	q	r	q + r
	0	s	t	s + t
sum		q + s	r + t	p

- Distance measure for **symmetric** binary variables:
- Distance measure for **asymmetric** binary variables:
- Jaccard coefficient (**similarity** measure for **asymmetric** binary variables):

$$d(i, j) = \frac{r + s}{q + r + s + t}$$

$$d(i, j) = \frac{r + s}{q + r + s}$$

$$sim_{Jaccard}(i, j) = \frac{q}{q + r + s}$$



# Dissimilarity between Binary Variables

## ■ Example

Name	Gender	Fever	Cough	Test-1	Test-2	Test-3	Test-4
Jack	M	Y	N	P	N	N	N
Mary	F	Y	N	P	N	P	N
Jim	M	Y	P	N	N	N	N

- Gender is a symmetric attribute (**ignored** in this case)
- The remaining attributes are **asymmetric** binary
- Let the values **Y** and **P** be **1**, and the value **N** 0

$$d(jack, mary) = \frac{0 + 1}{2 + 0 + 1} = 0.33$$

$$d(jack, jim) = \frac{1 + 1}{1 + 1 + 1} = 0.67$$

$$d(jim, mary) = \frac{1 + 2}{1 + 1 + 2} = 0.75$$



# Standardizing Numeric Data

---

- Z-score: 
$$Z = \frac{x - \mu}{\sigma}$$
  - X: raw score to be standardized,  $\mu$ : mean of the population,  $\sigma$ : standard deviation
  - Meaning: the distance between the raw score and the population mean in units of the standard deviation
    - “-” when the raw score is **below** the mean
    - “+” when the raw score is **above** the mean



# Standardizing Numeric Data

- An alternative way: Calculate the **mean absolute deviation**

$$s_f = \frac{1}{n} (|x_{1f} - m_f| + |x_{2f} - m_f| + \dots + |x_{nf} - m_f|)$$

where

$$m_f = \frac{1}{n} (x_{1f} + x_{2f} + \dots + x_{nf}).$$


- standardized measure (*z-score*):  $z_{if} = \frac{x_{if} - m_f}{s_f}$

- Using mean absolute deviation is more robust than using standard deviation (when outliers exist)



# Example:

## Data Matrix and Dissimilarity Matrix



Data Matrix

point	attribute1	attribute2
$x1$	1	2
$x2$	3	5
$x3$	2	0
$x4$	4	5

Dissimilarity Matrix  
(with Euclidean Distance)

	$x1$	$x2$	$x3$	$x4$
$x1$	0			
$x2$	3.61	0		
$x3$	5.1	5.1	0	
$x4$	4.24	1	5.39	0





# Distance on Numeric Data: Minkowski Distance

---

- *Minkowski distance*: A popular distance measure

$$d(i, j) = \sqrt[h]{|x_{i1} - x_{j1}|^h + |x_{i2} - x_{j2}|^h + \cdots + |x_{ip} - x_{jp}|^h}$$

where  $i = (x_{i1}, x_{i2}, \dots, x_{ip})$  and  $j = (x_{j1}, x_{j2}, \dots, x_{jp})$  are two  $p$ -dimensional data objects, and  $h$  is the order (the distance so defined is also called **L- $h$  norm**)

# Distance on Numeric Data: Minkowski Distance

- *Minkowski distance*: A popular distance measure

$$d(i, j) = \sqrt[h]{|x_{i1} - x_{j1}|^h + |x_{i2} - x_{j2}|^h + \cdots + |x_{ip} - x_{jp}|^h}$$



- Properties
  - $d(i, j) > 0$  if  $i \neq j$ , and  $d(i, i) = 0$  (Positive definiteness)
  - $d(i, j) = d(j, i)$  (Symmetry)
  - $d(i, j) \leq d(i, k) + d(k, j)$  (Triangle Inequality)
- A distance that satisfies these properties is a *metric*

# Special Cases of Minkowski Distance

- $h = 1$ : **Manhattan** (city block,  $L_1$  norm) **distance**
  - E.g., the Hamming distance: the number of bits that are different between two binary vectors

$$d(i, j) = |x_{i1} - x_{j1}| + |x_{i2} - x_{j2}| + \dots + |x_{ip} - x_{jp}|$$



- $h = 2$ : ( $L_2$  norm) **Euclidean** distance

$$d(i, j) = \sqrt{(|x_{i1} - x_{j1}|^2 + |x_{i2} - x_{j2}|^2 + \dots + |x_{ip} - x_{jp}|^2)}$$


- $h \rightarrow \infty$ . **Supremum** ( $L_{\max}$  norm,  $L_{\infty}$  norm) distance
  - This is the maximum difference between any component (attribute) of the vectors

$$d(i, j) = \lim_{h \rightarrow \infty} \left( \sum_{f=1}^p |x_{if} - x_{jf}|^h \right)^{\frac{1}{h}} = \max_f |x_{if} - x_{jf}|$$



# Example: Minkowski Distance

point	attribute 1	attribute 2
x1	1	2
x2	3	5
x3	2	0
x4	4	5



## Manhattan ( $L_1$ )

L	x1	x2	x3	x4
x1	0			
x2	5	0		
x3	3	6	0	
x4	6	1	7	0

## Euclidean ( $L_2$ )

L2	x1	x2	x3	x4
x1	0			
x2	3.61	0		
x3	2.24	5.1	0	
x4	4.24	1	5.39	0

## Supremum

$L_\infty$	x1	x2	x3	x4
x1	0			
x2	3	0		
x3	2	5	0	
x4	3	1	5	0

# Ordinal Variables

---

- Order is important, e.g., rank
- Can be treated like interval-scaled
  - replace  $x_{if}$  by their *rank*
  - map the range of each variable onto  $[0, 1]$  by replacing  $i$ -th object in the  $f$ -th variable by  $r_{if} \in \{1, \dots, M_f\}$

$$z_{if} = \frac{r_{if} - 1}{M_f - 1}$$

- compute the dissimilarity using methods for interval-scaled variables



# Attributes of Mixed Type

- A database may contain all attribute types
  - Nominal, symmetric binary, asymmetric binary, numeric, ordinal
- One may use a weighted formula to combine their effects

$$d(i, j) = \frac{\sum_{f=1}^p \delta_{ij}^{(f)} d_{ij}^{(f)}}{\sum_{f=1}^p \delta_{ij}^{(f)}}$$

- $f$  is binary or nominal:  
 $d_{ij}^{(f)} = 0$  if  $x_{if} = x_{jf}$ , or  $d_{ij}^{(f)} = 1$  otherwise
- $f$  is numeric: use the normalized distance
- $f$  is ordinal
  - Compute ranks  $r_{if}$  and
  - Treat  $z_{if}$  as interval-scaled

$$z_{if} = \frac{r_{if} - 1}{M_f - 1}$$

# Cosine Similarity

- A **document** can be represented by thousands of attributes, each recording the *frequency* of a particular word (such as keywords) or phrase in the document.

Document	team	coach	hockey	baseball	soccer	penalty	score	win	loss	season
Document1	5	0	3	0	2	0	0	2	0	0
Document2	3	0	2	0	1	1	0	1	0	1
Document3	0	7	0	2	1	0	0	3	0	0
Document4	0	1	0	0	1	2	2	0	3	0

- Applications: information retrieval, biologic taxonomy, gene feature mapping, ...
- Cosine measure: If  $d_1$  and  $d_2$  are two vectors (e.g., term-frequency vectors), then

$$\cos(d_1, d_2) = (d_1 \bullet d_2) / (||d_1|| ||d_2||),$$

where  $\bullet$  indicates vector dot product,  $||d||$ : the length of vector  $d$



# Example: Cosine Similarity

- $\cos(d_1, d_2) = (d_1 \bullet d_2) / (||d_1|| ||d_2||)$ ,  
where  $\bullet$  indicates vector dot product,  $||d||$ : the length of vector  $d$
- Ex: Find the **similarity** between documents 1 and 2.

$$d_1 = (5, 0, 3, 0, 2, 0, 0, 2, 0, 0)$$

$$d_2 = (3, 0, 2, 0, 1, 1, 0, 1, 0, 1)$$

$$d_1 \bullet d_2 = 5*3 + 0*0 + 3*2 + 0*0 + 2*1 + 0*1 + 0*1 + 2*1 + 0*0 + 0*1 = 25$$

$$\begin{aligned} ||d_1|| &= (5*5 + 0*0 + 3*3 + 0*0 + 2*2 + 0*0 + 0*0 + 2*2 + 0*0 + 0*0)^{0.5} = (42)^{0.5} \\ &= 6.481 \end{aligned}$$


$$\begin{aligned} ||d_2|| &= (3*3 + 0*0 + 2*2 + 0*0 + 1*1 + 1*1 + 0*0 + 1*1 + 0*0 + 1*1)^{0.5} = (17)^{0.5} \\ &= 4.12 \end{aligned}$$

$$\cos(d_1, d_2) = 0.94$$



# Chapter 2: Getting to Know Your Data

---

- Data Objects and Attribute Types
- Basic Statistical Descriptions of Data
- Data Visualization
- Measuring Data Similarity and Dissimilarity
- Summary 

# Summary

---

- Data attribute types: nominal, binary, ordinal, interval-scaled, ratio-scaled
- Many types of data sets, e.g., numerical, text, graph, Web, image.
- Gain insight into the data by:
  - Basic statistical data description: central tendency, dispersion, graphical displays
  - Measure data similarity
- Above steps are the beginning of data preprocessing
- Many methods have been developed but still an active area of research



# References

- W. Cleveland, Visualizing Data, Hobart Press, 1993
- T. Dasu and T. Johnson. Exploratory Data Mining and Data Cleaning. John Wiley, 2003
- U. Fayyad, G. Grinstein, and A. Wierse. Information Visualization in Data Mining and Knowledge Discovery, Morgan Kaufmann, 2001
- L. Kaufman and P. J. Rousseeuw. Finding Groups in Data: an Introduction to Cluster Analysis. John Wiley & Sons, 1990.
- H. V. Jagadish, et al., Special Issue on Data Reduction Techniques. Bulletin of the Tech. Committee on Data Eng., 20(4), Dec. 1997
- D. A. Keim. Information visualization and visual data mining, IEEE trans. on Visualization and Computer Graphics, 8(1), 2002
- D. Pyle. Data Preparation for Data Mining. Morgan Kaufmann, 1999
- S. Santini and R. Jain, "Similarity measures", IEEE Trans. on Pattern Analysis and Machine Intelligence, 21(9), 1999
- E. R. Tufte. The Visual Display of Quantitative Information, 2nd ed., Graphics Press, 2001
- C. Yu , et al., Visual data mining of multimedia data for social and behavioral studies, Information Visualization, 8(1), 2009