

Chapter 5: Mining Frequent Patterns, Association and Correlations

- Basic concepts and a road map
- Efficient and scalable frequent itemset mining methods
- Mining various kinds of association rules
- From association mining to correlation analysis
- Constraint-based association mining
- Summary



What Is Frequent Pattern Analysis?

- **Frequent pattern**: a pattern (a set of items, subsequences, substructures, etc.) that occurs frequently in a data set
- First proposed by Agrawal, Imielinski, and Swami [AIS93] in the context of **frequent itemsets** and **association rule mining**
- Motivation: Finding inherent regularities in data
 - What products were often purchased together?— Beer and diapers?!
 - What are the subsequent purchases after buying a PC?
 - What kinds of DNA are sensitive to this new drug?
- Applications
 - Basket data analysis, cross-marketing, catalog design, sale campaign analysis, Web log (click stream) analysis, and DNA sequence analysis.



Why Is Freq. Pattern Mining Important?


- Discloses an intrinsic and important property of data sets
- Forms the foundation for many essential data mining tasks
 - Association, correlation, and causality analysis
 - Sequential, structural (e.g., sub-graph) patterns
 - Pattern analysis in spatiotemporal, multimedia, time-series, and stream data
 - Classification: associative classification
 - Cluster analysis: frequent pattern-based clustering
 - Semantic data compression
 - Broad applications



Basic Concepts: Frequent Patterns and Association Rules

Transaction-id	Items bought
10	A, B, D
20	A, C, D
30	A, D, E
40	B, E, F
50	B, C, D, E, F

- Itemset $X = \{x_1, \dots, x_k\}$
- Find all the association rules $X \rightarrow Y$ with minimum support and confidence
 - **support**, s , **probability** that a transaction contains $X \cup Y$
 - **confidence**, c , **conditional probability** that a transaction having X also contains Y



Let $sup_{min} = 50\%$, $conf_{min} = 50\%$
Freq. Pat.: $\{A:3, B:3, D:4, E:3, AD:3\}$

Association rules:

$A \rightarrow D$ (60%, 100%)

$D \rightarrow A$ (60%, 75%)



Closed Patterns and Max-Patterns

- A long pattern contains a combinatorial number of sub-patterns, e.g., $\{a_1, \dots, a_{100}\}$ contains $\binom{100}{1} + \binom{100}{2} + \dots + \binom{100}{100} = 2^{100} - 1 = 1.27 \times 10^{30}$ sub-patterns!
- Solution: Mine *closed patterns* and *max-patterns* instead
- An itemset X is **closed** if X is *frequent* and there exists *no super-pattern* $Y \supset X$, with the same support as X (proposed by Pasquier, et al. @ ICDT'99)
- An itemset X is a **max-pattern** if X is frequent and there exists no frequent super-pattern $Y \supset X$ (proposed by Bayardo @ SIGMOD'98)
- Closed pattern is a lossless compression of freq. patterns
 - Reducing the # of patterns and rules




Closed Patterns and Max-Patterns

- Exercise. $DB = \{ \langle a_1, \dots, a_{100} \rangle, \langle a_1, \dots, a_{50} \rangle \}$
 - $Min_sup = 1.$
- What is the set of **all frequent patterns**?
 - $2^{100} - 1$
- What is the set of **closed itemset**?
 - $\langle a_1, \dots, a_{100} \rangle: 1$
 - $\langle a_1, \dots, a_{50} \rangle: 2$
- What is the set of **max-pattern**?
 - $\langle a_1, \dots, a_{100} \rangle: 1$



Chapter 5: Mining Frequent Patterns, Association and Correlations

- Basic concepts and a road map
- Efficient and scalable frequent itemset mining methods 
- Mining various kinds of association rules
- From association mining to correlation analysis
- Constraint-based association mining
- Summary



Scalable Methods for Mining Frequent Patterns

- The **downward closure** property of frequent patterns
 - Any subset of a frequent itemset must be frequent
 - If **{beer, diaper, nuts}** is frequent, so is **{beer, diaper}**
 - i.e., every transaction having {beer, diaper, nuts} also contains {beer, diaper}
- Scalable mining methods: Three major approaches
 - Apriori (Agrawal & Srikant@VLDB'94)
 - Freq. pattern growth (FPgrowth—Han, Pei & Yin @SIGMOD'00)
 - Vertical data format approach (Charm—Zaki & Hsiao @SDM'02)




Apriori: A Candidate Generation-and-Test Approach

- Apriori pruning principle: If there is **any** itemset which is infrequent, its superset should not be generated/tested! (Agrawal & Srikant @VLDB'94, Mannila, et al. @ KDD' 94)
- Method:
 - Initially, scan DB once to get frequent 1-itemset
 - **Generate candidate** itemsets of length $(k+1)$ from **frequent** itemsets of length k
 - **Test** the candidates against DB
 - Terminate when no frequent or candidate set can be generated



The Apriori Algorithm—An Example



The Apriori Algorithm

- Pseudo-code:

C_k : Candidate itemset of size k

L_k : frequent itemset of size k

$L_1 = \{\text{frequent items}\};$

for ($k = 1; L_k \neq \emptyset; k++$) **do begin**

C_{k+1} = candidates generated from L_k ;

for each transaction t in database **do**

increment the count of all candidates in C_{k+1}
that are contained in t

L_{k+1} = candidates in C_{k+1} with min_support

end

return $\cup_k L_k$;



Important Details of Apriori

- How to generate candidates?
 - Step 1: self-joining L_k (what is a [join](#)?)
 - Step 2: pruning
- How to count supports of candidates?
- Example of Candidate-generation
 - $L_3 = \{abc, abd, acd, ace, bcd\}$
 - Self-joining: $L_3 * L_3$
 - $abcd$ from abc and abd
 - $acde$ from acd and ace
 - Pruning:
 - $acde$ is removed because ade is not in L_3
 - $C_4 = \{abcd\}$



Challenges of Frequent Pattern Mining

- Challenges
 - Multiple scans of a transaction database
 - Huge number of candidates
 - Tedious workload of support counting for candidates
- Improving Apriori: general ideas
 - Reduce the number of transaction database scans
 - Shrink the number of candidates
 - Facilitate support counting of candidates



