

Security Trends

Attacks and Services

Prepared by
T. Sree Sharmila



OSI Security Architecture

- ITU-T (International Telecom Union – Telecom Standardization Sector recommends X.800 Security Architecture for OSI, defines a systematic approach.
- This is useful for managers to organize the task of providing security.
- This focuses on security services, mechanisms and attacks.



Services, Mechanisms, Attacks

- need systematic way to define requirements
- consider three aspects of information security:
 - **security attack**
 - **security mechanism**
 - **security service**
- consider in reverse order



Security Service

- is something that enhances the security of the data processing systems and the information transfers of an organization
- intended to counter security attacks
- make use of one or more security mechanisms to provide the service
- replicate functions normally associated with physical documents
 - eg have signatures, dates; need protection from disclosure, tampering, or destruction; be notarized or witnessed; be recorded or licensed



Security Mechanism

- a mechanism that is designed to detect, prevent, or recover from a security attack
- no single mechanism that will support all functions required
- however one particular element underlies many of the security mechanisms in use: **cryptographic techniques**



Security Attack

- any action that compromises the security of information owned by an organization
- information security is about how to prevent attacks, or failing that, to detect attacks on information-based systems
- have a wide range of attacks
- can focus of generic types of attacks
- note: often *threat* & *attack* mean same



OSI Security Architecture

- ITU-T X.800 Security Architecture for OSI
- defines a systematic way of defining and providing security requirements
- for us it provides a useful, if abstract, overview of concepts we will study



Security Services

- X.800 defines it as: a service provided by a protocol layer of communicating open systems, which ensures adequate security of the systems or of data transfers
- RFC 2828 defines it as: a processing or communication service provided by a system to give a specific kind of protection to system resources
- X.800 defines it in 5 major categories



Security Services (X.800)

- **Authentication** - assurance that the communicating entity is the one claimed
- **Access Control** - prevention of the unauthorized use of a resource
- **Data Confidentiality** –protection of data from unauthorized disclosure
- **Data Integrity** - assurance that data received is as sent by an authorized entity
- **Non-Repudiation** - protection against denial by one of the parties in a communication



Security Mechanisms (X.800)

- specific security mechanisms:
 - encipherment, digital signatures, access controls, data integrity, authentication exchange, traffic padding, routing control, notarization
- pervasive security mechanisms:
 - trusted functionality, security labels, event detection, security audit trails, security recovery




Classify Security Attacks as

- **passive attacks** - eavesdropping on, or monitoring of, transmissions to:
 - obtain message contents, or
 - monitor traffic flows
- **active attacks** – modification of data stream to:
 - masquerade of one entity as some other
 - replay previous messages
 - modify messages in transit
 - denial of service




Passive Attacks


- Reading contents of messages
- Also called **eavesdropping**
- Difficult to detect passive attacks
- Defense: to prevent their success




Active Attacks

- Modification or creation of messages (by attackers)
- Four categories: modification of messages, replay, masquerade, denial of service
- Easy to detect but difficult to prevent
- Defense: detect attacks and recover from damages






(b) Replay



(a) Masquerade



(d) Denial of service