

KARMA — TECHNICAL DOCUMENTATION

API Quick Reference

Every screen, every API call, every payload — on one page each

Project Karma (Antra CRM field app) — Flutter / GetX

Source generated from the codebase, branch `main`

Date 2 September 2026

Companion API-DOCUMENTATION.pdf

One table per screen. Every API call it makes, and exactly what it sends. No theory — just what each screen asks the server for. Full detail: [API-DOCUMENTATION.md](#) · Who can see what: [ROLE-ACCESS-DOCUMENTATION.md](#)

How to read this

Every call in this app uses the same URL. Only **DATA** and **ACTION** ever change:

```
https://gateway.tallyhelp.com/crm/UpdateData.aspx?DATA=<pay load>&ACTION=<name>&ENCKEY=<key>&SRC=KARMA&ISNEW=YES
```

what you send what you want identical on every call

So each screen below is **just a table**. Take its **ACTION** and **DATA** from the row and drop them into the template above — that is the full call.

Example — the Contact List row says **ANTRAUSER** with no DATA, so the call is:

```
https://gateway.tallyhelp.com/crm/UpdateData.aspx?DATA=&ACTION=ANTRAUSER&ENCKEY=ABC123XYZ&SRC=KARMA&ISNEW=YES
```

6 screens do not follow the template. Those — and only those — show their URL in full, marked . They are: Login, Customer Tickets, Ticket Details, Ticket Status Details, AGH Dashboard, Products.

Demo values used throughout: **ENCKEY** = **ABC123XYZ** · **UID** = **1234** · **UNAME** = **vinod** · **DPID** = **56789** · **CALLID** = **9001** · **OPPID** = **4501** · **TICKET** = **TCK00123** · **ENROLLID** = **EMP0042** · **PID** = **7**

Every screen block has:

Line	What it tells you
Reach it:	How to get to that screen in the running app — tap by tap
	Shown only when a role cannot open the screen at all. No lock = everyone can open it.
the table	Every API call the screen makes

Navigation paths are taken from the **Karma User Manual (L1 Sales edition, v12.0.35)** and verified against the **Get.to(...)** calls in the code.

Screens where a *button or field* is hidden for some roles — but the screen still opens — are **not** marked here. That belongs in [ROLE-ACCESS-DOCUMENTATION.md](#) §3.

Legend:

	Fires the moment the screen opens . The first  row is the screen's main call.
(no star)	Only fires when the user taps something
submit	Writes to the server, rather than just reading

Totals

	Count
Screens in the app	84
Screens that call the server	57
Screens with no API call	27
Total API calls	101
Distinct ACTION names	88

All screens at a glance

59 screens make API calls. Every row: who can open it, how many calls it makes, and which.

On the role columns. **L1** is  on **every single row** — nothing in this app is hidden from an L1 user. The only screens anyone loses are the **7 hidden from support users**.

L2 and **L3** share one column because **the code does not tell them apart** — both are simply "not L1" and take the identical path. There is no L3 check anywhere in the source.

Captain (`tcId == "7"`) is **additive**, not a rank — a Captain is still an L1 or a support user. It only changes what they see **inside AGH** (marked  *).

#	Page	L1	L2 / L3	Captain	Calls	Actions it uses
1	Splash Screen				3	APPVERSION LOGIN REGISTERID
2	Login Page				3	LOGIN REGISTERID + 1 legacy
3	Home / Dashboard				11	ACHIVEDTARGET ×2 SUPDASHBOARD LEADDASHBOARD ×3 GETOPP GETTOPCUSTOMER TEAMMEMBER GETSUPRANK CALLBOOK
4	Top Customers 				1	GETTOPCUSTOMERDETAILS
5	Contact List				1	ANTRAUSER
6	Customer List				1	GETDATAPOINT
7	Customer 360				5	GETDPINF GETCALLENTYDATA BROCHUREMASTER GETUSER BROCHEREMAIL
8	Create Customer				3	LEADSRC EPICMAST NEWDATAPOINT
9	Contact Details				2	GETUSER ADDCONTACT
10	Products & Services				1	GETDPPRODUCTINFO
11	Recent Activity				1	OPPRECENTACTIVITY
12	Tally Serial				1	GETCALLENTYDATA
13	Visit History				1	CALLENTYDETAILS
14	Delivery Request 				1	DELIVERYREQDATA
15	Customer Tickets				1	GETSUPPALLTICKET
16	Book a Call				3	GETCALLENTYDATA L1USER CALLENTY

#	Page	L1	L2 / L3	Captain	Calls	Actions it uses
17	Call Booking	✓	✓	✓	7	CALLBOOK TEAMMEMBER ISWORKSHOP DELETECALLBOOK CALLAPPROVE GETCALLEDESC CHKINOUTDATA
18	Call Booking L2	✓	✓	✓	5	CALLBOOK TEAMMEMBER CALLAPPROVE GETCALLEDESC CHKINOUTDATA
19	Call Booking Details	✓	✓	✓	3	CALLBOOK CHKINOUTDATA ISWORKSHOP
20	Add Support Entry	✓	✓	✓	5	CATEGORYTYPE UPDATECALL + 3 ChatGPT (external)
21	Conveyance Entry (travel expense)	✓	✓	✓	7	GETSOURCE CALLBOOK GETCONVAYANCE DELETECONVAYANCE PASSCONV PETROLRATE SETCONVAYANCE
22	PIW / Workshop Form	✓	✓	✓	2	WORKSHOPMST SAVEWORKSHOPREF
23	Support List	✓	✓	✓	1	EXISTSUPENTRY
24	Support Details	✓	✓	✓	1	SUPENTRY
25	Create Lead	✓	✓	✓	4	LEADSRC x2 GETTALLYSRLOC NEWLEAD
26	Lead	✓	✓	✓	1	LEADDASHBOARD
27	Lead Received	✓	✓	✓	3	LEADLIST TCKLEADSTYPE LEADTICKET
28	Create Lead 1	✓	✓	✓	2	LEADSRC NEWLEAD
29	Update Lead	✓	✓	✓	2	GIVENLEAD UPDATELEAD
30	Opportunity Details	✓	✓	✓	1	GETOPP
31	Opportunity Data	✓	✓	✓	3	OPPRECENTACTIVITY PROPOSALLIST PREFORMAINVOIC
32	Change Status	✓	✓	✓	2	CLOSEREASONMAST OPPSTATUSUPDATE
33	Update Opportunity	✓	✓	✓	2	PROPOSALSOURCE GETCALLENTYDATA
34	Antra Ticket System	✓	✓	✓	1	GETANTRATICKET
35	Create Ticket	✓	✓	✓	2	GETTCKMAST ANTRATICKET
36	Remark List	✓	✓	✓	1	ANTRATICKETREMARK
37	Ticket Status	✓	✓	✓	2	GETSUPPALLPENDTICKET ACTTCKUPDATE
38	Ticket Details	✓	✓	✓	1	TICKETDETAILS
39	Ticket Status Details	✓	✓	✓	1	TICKETDETAILS
40	Support Availability ⚠	✓	✓	✓	1	AVAILABLEUSER
41	My Customer Call	✓	✗	✓	2	MYCALDRTL SUPCALLCANCEL
42	Leave Report	✓	✓	✓	3	ATTENDANCE ANTRAHOLIDAY CREATELEAVE
43	Holidays List	✓	✓	✓	1	ANTRAHOLIDAY
44	Leave Status	✓	✓	✓	5	TEAMMEMBER GETLEAVEDATA DELETELEAVE UPDATELEAVE APPROVELEAVE
45	Conveyance Report	✓	✓	✓	2	GETUSERDITAILS CONVREPORT
46	Target Report	✓	✗	✓	2	TEAMMEMBER + 1 action passed in at runtime
47	Outstanding	✓	✓	✓	1	USEROUTSTANDING
48	Epicenter Details	✓	✓	✓	1	GETEPCDATA

#	Page	L1	L2 / L3	Captain	Calls	Actions it uses
49	Epicenters Page 2	✓	✓	✓	—	<i>none</i>
50	Escalation — Internal	✓	✓	✓	2	ESCALATIONMST SAVEESCALATION
51	Escalation — From Ticket	✓	✓	✓	3	ESCALATIONMST DPTICKETINFO SAVEESCALATION
52	AGH Dashboard	✓	✗	✓*	4	GETAGH GETTOPIC AGHSCHEDULE SAVEAGH
53	ANS Report	✓	✗	✓	2	GETANS ANSUSER
54	Create ANS	✓	✗	✓	2	ANSUSER ANS
55	PBL Report	✓	✗	✓	2	GETPBL ANSUSER
56	Create PBL	✓	✗	✓	2	ANSUSER ANS
57	Products	✓	✓	✓	4	GETMODULELIST GETAPPLIST GETBOOSTERCAT GETBOOSTERLIST
58	Edit Profile	✓	✓	✓	2	UPDATEUSERDETAILS + 1 legacy (image)
59	Notifications	✓	✓	✓	—	AGH JSON URL UID UNAME DPID PID ENROLLID ENCKEY

⚠ = **unreachable** — the screen makes API calls but nothing in the app navigates to it: Top Customers, Delivery Request, Support Availability (its *Get.to* is commented out).

✗ = **hidden from support users** — Antra Golden Hour, ANS Report, Create ANS, PBL Report, Create PBL, My Customer Call, Target Report.

Counts are per screen. Screens that share a controller (Call Booking / Call Booking L2, the AGH screens) repeat the same underlying call, so these add up to more than the 101 call sites that exist in the code.

Login & startup

Splash Screen • `SplashScreen.dart` • 3 calls

Reach it: App launch — shows while Karma checks the version and signs you in

ACTION	DATA sent	What it does
★ <code>APPVERSION</code>	<code>10.0.0</code>	Checks if an update exists
★ LOGIN	<code>{"USER":"vinod","PWD":"pass@123","VERSION":"536","DEVICETYPE":"ANDROID"}</code>	Auto-login with saved details
<code>REGISTERID</code>	<code>{"TOKEN":"fcm_abc...","DEVICEID":"...", "MODEL":"..."}</code>	Registers phone for notifications

Login Page • `LoginPage.dart` • 3 calls

Reach it: App launch, first time or after Logout

⚠ THIS SCREEN'S URL IS DIFFERENT – ENCKEY is empty (no session yet):
https://gateway.tallyhelp.com/crm/UpdateData.aspx?DATA=%7B%22USER%22%3A%22vinod%22%2C%22PWD%22%3A%22pass%40123%22%2C%22VERSION%22%3A%22536%22%2C%22DEVICETYPE%22%3A%22ANDROID%22%7D&ACTION=LOGIN&ENCKEY=&SRC=KARMA&ISNEW=YES

DATA before URL-encoding:
{ "USER": "vinod", "PWD": "pass@123", "VERSION": "536", "DEVICETYPE": "ANDROID" }

|---|---|---| | **LOGIN** | the JSON above, URL-encoded | **submit** — signs in | | **REGISTERID** |
|{"TOKEN": "fcm_abc...", "DEVICEID": "..."} | Registers the device | | (legacy) | device info | Registration follow-up |

Yes — the app has a real login. Username and password are issued by your reporting manager. There is **no sign-up screen and no forgot-password link**. With *Remember Me* ticked the credentials are stored in the phone's secure keychain and Karma signs in automatically on every launch. A login is tied to one handset — a second device gives "Cannot login in this device" until a manager releases it. (*User Manual §2*)

LOGIN fills every global used afterwards — **UID** , **ENCKEY** , **DESCAT** , **ROLLID** , **TCID** , **TITLEID** . **ENCKEY** is empty on this one call, because you don't have a session yet.

Home

Home / Dashboard · **DashboardNew.dart** · 11 calls ← **heaviest screen**

Reach it: Where you land after signing in

ACTION	DATA sent	What it does
★ ACHIVEDTARGET	{ "UID": "1234", "PID": "7", "UNAME": "vinod" }	Target achieved
★ ACHIVEDTARGET	(same again)	Second target widget
★ SUPDASHBOARD	{ "UID": "1234", "PID": "7", "UNAME": "vinod", "ENROLLID": "EMP0042", "REQTYPE": "MONTH" }	Support counts
★ LEADDASHBOARD	{ "UID": "1234", "LEADTYPE": "GIVEN" }	Leads given
★ GETOPP	{ "UID": "1234", "DPID": "" }	Open opportunities
★ GETTOPCUSTOMER	{ "UID": "1234" }	Top customers
★ LEADDASHBOARD	{ "UID": "1234" }	Lead counts
★ TEAMMEMBER	1234	Team dropdown (managers)
★ GETSUPRANK	{ "UNAME": "vinod", "REQTYPE": "MONTH" }	Support ranking
★ CALLBOOK	vinod	Today's booked calls
LEADDASHBOARD	{ "UID": "1234", "LEADTYPE": "GIVEN" }	Refresh after an action

10 of these fire on a single screen open. `LEADDASHBOARD` runs 3× and `ACHIVEDTARGET` 2×.

Top Customers · `top_list.dart` · 1 call

Reach it: **UNREACHABLE** — nothing in the app navigates here

ACTION	DATA sent	What it does
★ <code>GETTOPCUSTOMERDETAILS</code>	<code>{"UID":"1234"}</code>	Top-customer detail list

Contacts

Contact List · `Contacts.dart` · 1 call

Reach it: Menu ≡ → Contact List

ACTION	DATA sent	What it does
★ <code>ANTRAUSER</code>	<i>(nothing)</i>	Whole company staff directory

Search does **not** call the server — it filters the list already downloaded.

Customers ("Data Point")

`DPID` = customer id.

Customer List · `DataPoints.dart` · 1 call

Reach it: Home → **Datapoint** card

ACTION	DATA sent	What it does
★ <code>GETDATAPOINT</code>	<code>vinod</code>	Customers assigned to this user

Customer 360 · `DataPointInfo.dart` · 5 calls

Reach it: Home → Datapoint card → tap a customer · or Home → **Datapoint Search**

ACTION	DATA sent	What it does
★ <code>GETDPINF</code>	<code>{"DPID":"56789"}</code>	Customer master record
★ <code>GETCALLENTRYDATA</code>	<code>56789</code>	Visit & call history
★ <code>BROCHUREMASTER</code>	<i>(nothing)</i>	Brochure dropdown
★ <code>GETUSER</code>	<code>56789</code>	Contact people there
<code>BROCHEREMAIL</code>	brochure id + email	submit — emails a brochure

The first four fire together in parallel on open.

Create Customer · `CreateDataPoint.dart` · 3 calls

Reach it: Home → Datapoint card → + (top bar)

ACTION	DATA sent	What it does
★ <code>LEADSRC</code>	<i>(nothing)</i>	Lead-source dropdown
★ <code>EPICMAST</code>	<code>{"UID":"1234"}</code>	Epicenter dropdown
<code>NEWDATAPOINT</code>	the form fields — see below ↓	submit — creates the customer

`NEWDATAPOINT` payload:

```
{"MOBILE":"9876543210","EMAIL":"a@b.com","TALLYUSE":"Yes","URT":"1","WEBSITE":"","TALLYSRNO":"790012345","LOCATION":"Ahmedabad","PRODUCT":"Prime","EPICID":"12","LDSRC":"3"}
```

Contact Details · `ContactDetails.dart` · 2 calls

Reach it: Customer record → **Contact Details** tile

ACTION	DATA sent	What it does
★ <code>GETUSER</code>	<code>56789</code>	Contacts at this customer
<code>ADDCONTACT</code>	name, mobile, email, designation	submit — adds a contact

Products & Services · `ProductAndServices.dart` · 1 call

Reach it: Customer record → **Live Products** tile

ACTION	DATA sent	What it does
★ <code>GETDPPRODUCTINFO</code>	<code>{"DPID":"56789"}</code>	What this customer owns

Recent Activity · `RecentActivity.dart` · 1 call

Reach it: Customer record → **Recent Activity** tile

ACTION	DATA sent	What it does
★ <code>OPPRECENTACTIVITY</code>	<code>{"OPPID":"","DPID":"56789"}</code>	Activity log

Tally Serial · `TallySerial.dart` · 1 call

Reach it: Customer record → **Tally Serial Number** tile

ACTION	DATA sent	What it does
★ <code>GETCALLENTRYDATA</code>	<code>56789</code>	Serial / call entry data

Visit History · `VisitHistory.dart` · 1 call

Reach it: Customer record → **FT History** tile

ACTION	DATA sent	What it does
★ <code>CALLENTRYDETAILS</code>	<code>vinod 56789</code>	All visits to this customer

Delivery Request · `DeliveryRequest.dart` · 1 call

Reach it: **UNREACHABLE** — nothing in the app navigates here

ACTION	DATA sent	What it does
★ <code>DELIVERYREQDATA</code>	<code>{"UID":"1234"}</code>	Delivery requests

Customer Tickets · `Tickets.dart` · 1 call

Reach it: Customer record → **Tickets** tile

⚠ THIS SCREEN'S URL IS DIFFERENT — other host, and no "ACTION=" at all:
https://gateway.tallyhelp.com/crm/CustomerApp.aspx?data=GETSUPPALLTICKET|30|56789&ENCKEY=ABC123XYZ&SRC=KARMA

|---|---|---| | ★ `GETSUPPALLTICKET` | `GETSUPPALLTICKET|30|56789` | Last 30 days of tickets |

Book a Call · `CallBookingPage.dart` · 3 calls

Reach it: Customer record → **Call Booking** tile — *the only place a visit can be created*

ACTION	DATA sent	What it does
★ <code>GETCALLENTRYDATA</code>	<code>56789</code>	Existing entries
★ <code>L1USER</code>	<i>(nothing)</i>	"Assign to" dropdown
<code>CALLENTRY</code>	<code>vinod 56789 2026-09-02 ...</code>	submit — books the call

Call Booking

Call Booking · `CallBooking.dart` · 7 calls

Reach it: Home → **Call Booking** card

ACTION	DATA sent	What it does
★ <code>CALLBOOK</code>	<code>1234</code>	Booked-call list
★ <code>TEAMMEMBER</code>	<code>1234</code>	Team filter (managers)
<code>ISWORKSHOP</code>	<code>{"DPID":"56789","CALLID":"9001"}</code>	Is it a workshop?
<code>DETECECALLBOOK</code>	<code>{"CALLID":"9001"}</code>	submit — deletes a booking
<code>CALLAPPROVE</code>	<code>{"CALLID":"9001","STATUS":"Yes"}</code>	submit — approves a call
<code>GETCALLEDESC</code>	<code>{"CALLID":"9001"}</code>	Notes on a call
<code>CHKINOUTDATA</code>	<code>9001 IN 2026-09-02 10:15 23.02,72.57</code>	submit — check in / out

Call Booking L2 · `CallBookingL2.dart` · 5 calls

Reach it: Home → Call Booking card (*the support-track version of the same screen*)

ACTION	DATA sent	What it does
★ <code>CALLBOOK</code>	<code>1234</code>	Booked-call list
★ <code>TEAMMEMBER</code>	<code>1234</code>	Team dropdown
<code>CALLAPPROVE</code>	<code>{"CALLID":"9001","STATUS":"Yes"}</code>	submit — approves
<code>GETCALLEDESC</code>	<code>{"CALLID":"9001"}</code>	Call notes
<code>CHKINOUTDATA</code>	<code>9001 OUT 2026-09-02 12:40 ...</code>	submit — check in / out

Call Booking Details · `CallBookingDetails.dart` · 3 calls

Reach it: Home → Call Booking card → tap a visit

ACTION	DATA sent	What it does
★ <code>CALLBOOK</code>	<code>1234</code>	The booking list
<code>CHKINOUTDATA</code>	<code>9001 IN ...</code>	submit — check in / out
<code>ISWORKSHOP</code>	<code>{"DPID":"56789","CALLID":"9001"}</code>	Show workshop form?

Add Support Entry · `AddSupportEntry.dart` · 5 calls

Reach it: Visit → ▾ menu → Support/Visit History → +

ACTION	DATA sent	What it does
★ <code>CATEGORYTYPE</code>	<code>vinod</code>	Category dropdown
<code>UPDATECALL</code>	call id, remark, observation, requirement	submit (POST) — saves the entry
<code>ChatGPT</code> ×3	the typed text	Rewrites remark / observation / requirement

The 3 ChatGPT calls go to an **external AI service**, not to the CRM server.

Conveyance Entry (travel expense) · `ConveyanceEntry.dart` · 7 calls

Reach it: Visit → ▾ menu → Conveyance Entry

ACTION	DATA sent	What it does
★ <code>GETSOURCE</code>	<i>(nothing)</i>	Travel-source dropdown
★ <code>CALLBOOK</code>	<code>vinod</code>	Visits to attach the expense to
★ <code>GETCONVAYANCE</code>	<code>1234</code>	Existing expense entries
<code>DELETECONVAYANCE</code>	<code>301</code>	submit — deletes an entry
<code>PASSCONV</code>	<code>{"CONVID":"301","STATUS":"Pass"}</code>	submit — approves
<code>PETROLRATE</code>	<i>(nothing)</i>	Current petrol rate
<code>SETCONVAYANCE</code>	date, km, source, amount	submit — saves the claim

Server spells it **CONVAYANCE**, not "conveyance". Copy it exactly.

PIW / Workshop Form • **PiwForm.dart** • 2 calls

Reach it: Home → Call Booking card → **PIW** button (*only on calls flagged for a workshop*)

ACTION	DATA sent	What it does
★ WORKSHOPMST	{"CALLID":"9001"}	The question list
SAVEWORKSHOPREF	{"DATA":[{"QID":"1","ANS":"Yes"}, ...]}	submit (POST) — saves answers

Support List • **SupportList.dart** • 1 call

Reach it: Visit → ▾ **menu** → Support/Visit History

ACTION	DATA sent	What it does
★ EXISTSUPENTRY	9001	Support entries for a call

Support Details • **SupportDetails.dart** • 1 call

Reach it: Visit → ▾ **menu** → Support/Visit History → tap an entry

ACTION	DATA sent	What it does
★ SUPENTRY	9001	One support entry

Create Lead • **CreateLead.dart** • 4 calls

Reach it: Visit → ▾ **menu** → Create Lead (*only when the booking has a Tally serial*)

ACTION	DATA sent	What it does
★ LEADSRC	<i>(nothing)</i>	Lead-source dropdown
LEADSRC	<i>(nothing)</i>	The same call again
GETTALLYSRLOC	{"TALLYSRNO":"790012345"}	Location from serial no.
NEWLEAD	company, contact, mobile, source	submit — creates the lead

Leads

Lead • **Lead.dart** • 1 call

Reach it: Home → **Lead** card

ACTION	DATA sent	What it does
★ LEADDASHBOARD	{"LEADTYPE":"GIVEN","UID":"1234"}	Lead list

LEADTYPE is the on-screen filter uppercased — **GIVEN** or **RECEIVED**.

Lead Received · `LeadReceived.dart` · 3 calls

Reach it: Home → Lead card → tap **Untouched** / **In progress** / **Accepted** / **Rejected**

ACTION	DATA sent	What it does
★ <code>LEADLIST</code> / <code>RCVLEADLIST</code>	<code>{"USERID":"1234","LEADTYPE":"Given"}</code>	Given or received leads
★ <code>TCKLEADSTYPE</code>	<i>(nothing)</i>	Lead-type dropdown
<code>LEADTICKET</code>	<code>{"LEADID":"77","LEADTYPE":"2","DESCR":"Follow-up needed"}</code>	submit — lead → ticket

Create Lead 1 · `CreateLead1.dart` · 2 calls

Reach it: Home → Lead card → + (top bar)

ACTION	DATA sent	What it does
★ <code>LEADSRC</code>	<i>(nothing)</i>	Lead-source dropdown
<code>NEWLEAD</code>	company, contact, mobile, source	submit — creates the lead

Update Lead · `UpdateLead.dart` · 2 calls

Reach it: Home → Lead card → a tile → open a lead

ACTION	DATA sent	What it does
★ <code>GIVENLEAD</code>	<code>77</code>	One lead's details
<code>UPDATELEAD</code>	<code>77~2~Followed up~1234~56789</code>	submit — updates the status

The only call in the app using ~ separators: `leadId ~ status ~ comment ~ userId ~ DPID` .

Opportunity

Opportunity Details · `OpportunityDetails.dart` · 1 call

Reach it: Home → **Opportunity** card · or Customer record → Opportunity tile

ACTION	DATA sent	What it does
★ <code>GETOPP</code>	<code>{"UID":"1234","DPID":""}</code> from the drawer · <code>{"UID":"","DPID":"56789"}</code> from a customer	Opportunity list

Opportunity Data · `OpportunityData.dart` · 3 calls

Reach it: Opportunity list → open one

ACTION	DATA sent	What it does
★ <code>OPPRECENTACTIVITY</code>	<code>{"OPPID":"4501","DPID":"56789"}</code>	Activity log
★ <code>PROPOSALLIST</code>	<code>{"OPPID":"4501","DPID":"56789"}</code>	Proposals sent
★ <code>PREFORMAINVOIC</code>	<code>{"OPPID":"4501","DPID":"56789","ISMAIL":"220"}</code>	Proforma invoice

All three fire on open.

Change Status · `Status.dart` · 2 calls

Reach it: Opportunity → open one → **Change Status**

ACTION	DATA sent	What it does
★ <code>CLOSEREASONMAST</code>	<i>(nothing)</i>	Close-reason dropdown
<code>OPPSTATUSUPDATE</code>	<code>{"DPID":"56789","OPPID":"4501","STATUS":"Closed","REASONID":"3","REMARK":"Budget not approved","POSDATE":""}</code>	submit — changes status

Update Opportunity · `UpdateOpportunity.dart` · 2 calls

Reach it: Opportunity → open one → **Update Opportunity**

ACTION	DATA sent	What it does
★ <code>PROPOSALSOURCE</code>	<code>{"DPID":"56789"}</code>	Proposal-source dropdown
★ <code>GETCALLENTRYDATA</code>	56789	Call entry data

Tickets

Antra Ticket System · `Ticket.dart` · 1 call

Reach it: Menu ≡ → **Antra Ticket System**

ACTION	DATA sent	What it does
★ <code>GETANTRATICKET</code>	<code>{"uid":"1234","status":"Open"}</code>	The user's tickets

Create Ticket · `CreateTicket.dart` · 2 calls

Reach it: Menu ≡ → Antra Ticket System → +

ACTION	DATA sent	What it does
★ <code>GETTCKMAST</code>	<i>(nothing)</i>	Category & subject dropdowns
<code>ANTRATICKET</code>	<code>{"categoryid":"12","descr":"Printer not working","uid":"1234","priority":"High","duplicate":"0"}</code>	submit (POST) — raises the ticket

This payload uses **lowercase** keys, unlike most of the app.

Remark List · `RemarkList.dart` · 1 call

Reach it: Menu ≡ → Antra Ticket System → a ticket → **Show Remark**

ACTION	DATA sent	What it does
★ ANTRATICKETREMARK	{"tckid":"TCK00123"}	Comments on a ticket

Ticket Status • TicketStatus.dart • 2 calls

Reach it: Menu ≡ → Ticket Status

ACTION	DATA sent	What it does
★ GETSUPPALLPENDTICKET	30 1234 (days userId)	Pending tickets
ACTTCKUPDATE	TCK00123 1234	submit — updates a ticket

Ticket Details • TickerDetails.dart • 1 call

Reach it: Home → : → Search Ticket • or Ticket Status → open a ticket

⚠ THIS SCREEN'S URL IS DIFFERENT – other host, and no "ACTION=" at all:
https://gateway.tallyhelp.com/crm/CustomerApp.aspx?data=TICKETDETAILS|TCK00123|&ENCKEY=ABC123XYZ&SRC=KARMA

|---|---|---| | ★ TICKETDETAILS | TICKETDETAILS|TCK00123| | One ticket + its full history |

Ticket Status Details • TicketStatusDetails.dart • 1 call

Reach it: Menu ≡ → Ticket Status → open a ticket

⚠ THIS SCREEN'S URL IS DIFFERENT – other host, and no "ACTION=" at all:
https://gateway.tallyhelp.com/crm/CustomerApp.aspx?data=TICKETDETAILS|TCK00123|&ENCKEY=ABC123XYZ&SRC=KARMA

|---|---|---| | ★ TICKETDETAILS | TICKETDETAILS|TCK00123| | Same call, second screen |

Support

Support Availability • Support.dart • 1 call

Reach it: UNREACHABLE — the drawer opens a web page instead; the Get.to is commented out

ACTION	DATA sent	What it does
★ AVAILABLEUSER	(nothing)	Who is free right now

My Customer Call • MyCustomerCall.dart • 2 calls

Reach it: Menu ≡ → My Customer Call • 🗝 L1 only — not in the support menu

ACTION	DATA sent	What it does
★ MYCALLDTLS	{"UID":"1234"}	This user's customer calls
SUPCALLCANCEL	{"CALLID":"9001","REMARK":"Customer unavailable"}	submit — cancels a call

Reports ("Operations")

Leave Report · `LeaveReport.dart` · 3 calls

Reach it: Menu ≡ → Operations → Leave

ACTION	DATA sent	What it does
★ ATTENDANCE	EMP0042 Sep 2026	Monthly attendance
★ ANTRAHOLIDAY	(nothing)	Holiday list
CREATELEAVE	{"ENROLLID":"EMP0042","FROMDATE":"...","TODATE":"...","REASON":"..."}	submit — applies for leave

Holidays List · `HolidaysList.dart` · 1 call

Reach it: Menu ≡ → Operations → Leave → List of Holidays

ACTION	DATA sent	What it does
★ ANTRAHOLIDAY	(nothing)	Company holidays

Leave Status · `LeaveStatus.dart` · 5 calls

Reach it: Menu ≡ → Operations → Leave → Leave Status

ACTION	DATA sent	What it does
★ TEAMMEMBER	1234	Team dropdown (managers)
★ GETLEAVEDATA	{"ENROLLID":"EMP0042","MONTH":"9","STATUS":"All"}	Leave records
DELETELEAVE	{"LEAVEID":"301"}	submit — cancels a request
UPDATELEAVE	{"LEAVEID":"301","FROMDATE":"...","TODATE":"..."}	submit — edits a request
APPROVELEAVE	{"LEAVEID":"301","UID":"1234","UNAME":"vinod","STATUS":"Approved","REASON":"OK"}	submit — approves / rejects

Conveyance Report · `ConveyReport.dart` · 2 calls

Reach it: Menu ≡ → Operations → Conveyance

ACTION	DATA sent	What it does
★ GETUSERDETAILS	vinod	User details (server-side typo)
★ CONVREPORT	{"UNAME":"vinod","FROMDATE":"1 Sep 2026"}	Travel expense report

Target Report · `TargetReport.dart` · 2 calls

Reach it: Menu ≡ → Operations → **Individual Target / Team Target** (Weekly or Monthly) ·  **L1 only** — the target cards are hidden from support users

ACTION	DATA sent	What it does
★ passed in <code>args['action']</code>	<code>{"UID":"1234","MONTH":9}</code>	The report itself
★ <code>TEAMMEMBER</code>	<code>1234</code>	Team dropdown

One screen serves several report types. You cannot tell which endpoint it hits from this file alone.

Outstanding

Outstanding · `Outstanding.dart` · 1 call

Reach it: Home → **View more** → Outstanding card

ACTION	DATA sent	What it does
★ <code>USEROUTSTANDING</code>	<code>{"UNAME":"vinod","UID":"1234","UST":"USER"}</code>	Unpaid customer invoices

Epicenters

Epicenter Details · `EpicentersDetails.dart` · 1 call

Reach it: Menu ≡ → **Epicenter**

ACTION	DATA sent	What it does
★ <code>GETEPCDATA</code>	<code>{"UID":"1234","UNAME":"vinod"}</code>	Epicenter data

Epicenters Page 2 · `EpicentersPage2.dart` · 0 calls

Reach it: Menu ≡ → Epicenter → tap an area

No main call — it filters the list the previous screen already handed it.

Escalation

Escalation — Internal · `EscalationInternalForm.dart` · 2 calls

Reach it: Menu ≡ → **Raise Escalation** → Internal → Continue

ACTION	DATA sent	What it does
★ <code>ESCALATIONMST</code>	<code>{"uid":"1234"}</code>	Categories, areas, users
<code>SAVEESCALATION</code>	the form fields — see below ↓	submit (POST) — raises it

`SAVEESCALATION` payload:

```
{"userid":"1234","dpid":"0","exeid":"0","catid":"5","imprid":"2","touserid":"88",
  "subcatid":"0","background":"...","observation":"...","Recommendation":"..."}
```

Escalation — From Ticket · `EscalationTicketForm.dart` · 3 calls

Reach it: Menu ≡ → Raise Escalation → Customer → Continue · or Ticket Status → a ticket → **Raise Escalation**

ACTION	DATA sent	What it does
★ <code>ESCALATIONMST</code>	<code>{"uid":"1234"}</code>	Master data
<code>DPTICKETINFO</code>	<code>{"dpid":"56789"}</code>	That customer's tickets
<code>SAVEESCALATION</code>	same as above plus <code>"ticket":"TCK00123"</code> , a real <code>dpid</code> and <code>exeid</code>	submit (POST) — raises it

Antra Golden Hour (AGH)

AGH Dashboard · `AGHDashboard.dart` · 4 calls

Reach it: Menu ≡ → **Antra Golden Hour** · 🗝️ **L1 only** — not in the support menu

⚠️ THIS SCREEN'S URL IS DIFFERENT — "&ISNEW=YES" is glued onto the ACTION value:
[https://gateway.tallyhelp.com/crm/UpdateData.aspx?DATA={"captain_id":"1234"}&ACTION=GETAGH&ISNEW=YES&ENCKEY=ABC123XYZ&SRC=KARMA](https://gateway.tallyhelp.com/crm/UpdateData.aspx?DATA={)

|---|---|---| | ★ `GETAGH` | `{"captain_id":"1234"}` | This user's AGH sessions | | ★ `GETTOPIC` | *(nothing)* | Topic list | | `AGHSCHEDULE` | date, topic, member id | **submit** (POST) — schedules a session | | `SAVEAGH` | outcome text + `"role":"7"` | **submit** (POST) — saves the outcome |

`captain_id` always carries the current user's id — even when they are not a captain. `SAVEAGH` is the **only** call in the whole app that tells the server the user's role.

The other 6 AGH screens (`AGHCheckIn`, `AGHCompleted`, `AGHMemberLearn`, `AGHNotifications`, `AGHOutcome`, `AGHScheduleSession`) share this controller and add **no new calls**.

ANS & PBL

ANS Report · `ans_screen.dart` · 2 calls

Reach it: Menu ≡ → **ANS Report** · 🗝️ **L1 only** — not in the support menu

ACTION	DATA sent	What it does
★ GETANS	{"login_id":"1234"}	ANS entries
ANSUSER	{"login_id":"1234"}	User dropdown

Create ANS · create_ans_screen.dart · 2 calls

Reach it: Menu ≡ → ANS Report → + · 🔒 L1 only — not in the support menu

ACTION	DATA sent	What it does
★ ANSUSER	{"login_id":"1234"}	User dropdown
ANS	entry fields	submit — saves the entry

PBL Report · PblReport.dart · 2 calls

Reach it: Menu ≡ → PBL Report · 🔒 L1 only — not in the support menu

ACTION	DATA sent	What it does
★ GETPBL	{"login_id":"1234"}	PBL entries
ANSUSER	{"login_id":"1234"}	User dropdown

Create PBL · create_pbl_screen.dart · 2 calls

Reach it: Menu ≡ → PBL Report → + · 🔒 L1 only — not in the support menu

ACTION	DATA sent	What it does
★ ANSUSER	{"login_id":"1234"}	User dropdown
ANS	entry fields	submit — saves the entry

PBL reuses the ANS endpoints — same backend feature.

Products

Products · Products.dart · 4 calls — all on the other URL

Reach it: Menu ≡ → Products

⚠ THIS SCREEN'S URL IS DIFFERENT — other host, and no ISNEW:
https://gateway.tallyhelp.com/crm/CustomerApp.aspx?DATA=&ACTION=GETMODULELIST&ENCKEY=ABC123XYZ&SRC=KARMA

|---|---|---| | ★ GETMODULELIST | (nothing) | Tally modules | | ★ GETAPPLIST | (nothing) | Apps | | ★ GETBOOSTERCAT | (nothing) | Booster categories | | GETBOOSTERLIST | 45 | (action only, no DATA) | Boosters in a category |

https://gateway.tallyhelp.com/crm/CustomerApp.aspx?ACTION=GETBOOSTERLIST | 45&ENCKEY=ABC123XYZ&SRC=KARMA

Profile

Edit Profile · `EditProfile.dart` · 2 calls

Reach it: Menu ≡ → tap your photo → **pencil** (top right)

ACTION	DATA sent	What it does
<code>UPDATEUSERDETAILS</code>	<code>Vinod Sharma Sr. Executive 9876543210 vinod@antraweb.co.in vinod</code>	submit — saves the profile
<i>(legacy)</i>	image data	Profile picture

This screen makes **no call on open** — it fills the form from values already in memory.

Notifications

Notifications · `NotificationScreen.dart` · 0 CRM calls

Reach it: **Bell** icon in the top bar

No main call. Runs on Firebase push plus one raw `http.get`. No `ACTION` is used.

The 27 screens with no API call

They show data handed to them by the previous screen, or are static. **No main call.**

Group	Screens
Customers	Address Details · Data Point Details · Tally Serial Number
Call Booking	Cold Calling · Near By Customer
Epicenters	Epicenters Page 2 · Epicenter Details 2 · Epicenter Screen
Escalation	Choose Type · Success · From Ticket
Products	Product Details
Reports	Reports (menu) · Monthly Report
Profile	Profile
Company	Company · Company Details
Startup	Onboarding · Sync Progress
Other	Data Scope · Drawer
AGH	Check In · Completed · Member Learn · Notifications · Outcome · Schedule Session <i>(share the AGH controller)</i>

Payload cheat sheet

Six formats. Check which one a screen uses before you change it.

Format	Example	Screens that use it
Empty	DATA=	Contacts · dropdowns · Support
Plain value	DATA=vinod	Customer List · Call Booking · Team dropdowns
Pipe	DATA=vinod 56789	Visit History · Attendance · Ticket Status · Edit Profile
Tilde ~	DATA=77~2~text~1234~56789	Update Lead only
JSON	DATA={"UID": "1234"}	most screens
URL-encoded JSON	DATA=%7B%22UID%22...	Login · Create Customer · Update Leave

⚠ JSON is **not** consistently URL-encoded across the app. If a payload can contain `&`, `#` or `+`, un-encoded JSON breaks and the screen silently shows nothing. **Always encode when you write new code.**

Where the values come from

Every payload is built from these, set once at login.

In the payload	Global	Demo
UID · USERID · uid · login_id · captain_id	DataInfo.userId	1234
UNAME · USER	DataInfo.username	vinod
DPID	DataInfo.dpId	56789
PID	DataInfo.pid	7
ENROLLID	DataInfo.enrollId	EMP0042
ENCKEY (every call)	DataInfo.encKey	ABC123XYZ
role (AGH only)	DataInfo.tcId	7

Full detail, response shapes and engineering notes: `API-DOCUMENTATION.md` . Who can see which screen: `ROLE-ACCESS-DOCUMENTATION.md` .