

Karma — Who Can See What

Which screen is visible to which role — and what changes inside it. Companion to `API-QUICK-REFERENCE.md` (what each screen calls) and `API-DOCUMENTATION.md` (full technical detail).

1. Read this in one minute

The five kinds of user

There are **two base roles** (you are one or the other) and **three add-ons** (you may also have any of these on top).

Base roles — everyone is exactly one of these

	Role name	Who they are	How the code knows
A	L1 Executive	Field sales person	<code>desCat = "L1"</code>
C	Support User	Support desk staff	<code>desCat</code> is anything except <code>"L1"</code>

Add-on roles — these stack on top of A or C

	Role name	What it grants	How the code knows
B	Manager	Team dropdowns; approve leave and calls	<code>rollId = "1"</code>
D	Captain	The captain side of AGH coaching sessions	<code>tcId = "7"</code>
E	ANS / PBL Author	The "+" create button on ANS and PBL Report	<code>titleId = "24"</code> , <code>"25"</code> or <code>"26"</code> or <code>userId = "176"</code> , <code>"177"</code> or <code>"365"</code>

None of B, D or E is a rank. Each sits *on top of* A or C, and each is a separate server field, so any combination is possible. A Support User can be a Manager. A Support User can be a Captain. The three do not imply one another.

 **An add-on never unlocks a hidden screen**

Screen visibility is decided by the **base role only** (`desCat`). B, D and E change what you see *inside* a screen you can already open — they never put a new item in your menu.

A Support User who is a Captain still cannot open AGH. The AGH menu item is gated on `desCat == "L1"` alone (`DrawerWidget.dart:114`); `tcId` is never consulted there. The same is true of ANS, PBL and My Customer Call. Do not read "Captain  " anywhere as "can reach the screen".

Where each role is documented

Role	Which screens they get	Every button it unlocks
A · L1 Executive	Section 2 master table — column A	— (<i>base role</i>)
C · Support User	Section 2 master table — column C	— (<i>base role</i>)
B · Manager	(<i>same as their base role</i>)	Section 4.1 — 9 controls on 6 screens
D · Captain	(<i>same as their base role</i>)	Section 4.2 — the AGH side switch + 3 buttons
E · ANS / PBL Author	(<i>same as their base role</i>)	Section 4.3 — one "+" button on 2 screens

Sections 2 and 3 are organised by screen. Section 4 is organised by role — go there to answer "what does a Manager actually get?"

 There is no "L3"

The team says **L1 / L2 / L3 / Captain**. The code does not work that way.

What people say	What the code actually checks	Role above
"L1"	<code>desCat == "L1"</code> — exists	A
"L2"	<i>no check exists</i> — it is just "not L1"	C
"L3"	does not exist anywhere in the source	—
"Captain"	<code>tcId == "7"</code> — exists, but it is a separate add-on	D

Every non-L1 user — whatever the business calls them — takes the **same** code path. Two people both called "L2" can see different screens if their `rollId` differs.

The business vocabulary has no word at all for **B (Manager)** or **E (ANS / PBL Author)**, even though both change what a user can do. That gap is why this section exists.

The three access levels used in this document

Symbol	Meaning
✓	Full access — sees the whole screen
⚠	Partial — can open it, but some buttons or fields are hidden
✗	No access — the screen is not even in their menu

2. The master table — every screen, every role

This is the answer to "which page can which role see?" Read across the row. **A** = L1 Executive · **B** = Manager (on the L1 track) · **C** = Support User.

Why D and E have no column. Captain and ANS / PBL Author never make a hidden screen appear — see the warning in Section 1. A Captain reads the column for their **base** role (A or C), then **Section 4.2** for what they gain. An ANS / PBL Author reads their base column, then **Section 4.3**.

Column **B** assumes an L1 Manager, which is the common case. A Manager on the **support** track reads column C for visibility, and gains the controls listed in **Section 4.1**.

This table answers "can I open it?" only. For "which buttons do I get?", go to Section 4.

Menu (the drawer)

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
Home / Dashboard	⚠	✓	⚠	Manager gets a team dropdown. Support sees a chart; L1 sees cards instead.
Antra Golden Hour	✓	✓	✗	Hidden from the menu for support users
Raise Escalation	✓	✓	✓	—
Epicenter	✓	✓	✓	—
Operations (Reports)	✓	✓	⚠	L1 sees 3 report groups; support sees 1
Products	✓	✓	✓	—
Antra Ticket System	✓	✓	✓	—
ANS Report	⚠	✓	✗	Hidden for support. "+" button needs extra rights — see Section 3.5
PBL Report	⚠	✓	✗	Hidden for support. Same "+" rule as ANS
Ticket Status	✓	✓	⚠	Support cannot filter by user
Contact List	✓	✓	✓	Identical for everyone
Support Availability	✓	✓	✓	Opens an external web page
CertiKit ISO27001	✓	✓	✓	External link
Product Requirement	✓	✓	✓	External Google Form
Karma Enhancement	✓	✓	✓	External Google Form
My Customer Call	✓	✓	✗	Hidden from the menu for support users
Update App	✓	✓	✓	Android only — a platform rule, not a role rule
Logout	✓	✓	✓	—

Only 4 things are hidden from the menu: Antra Golden Hour, ANS Report, PBL Report, My Customer Call. Everything else is in everyone's menu.

The drawer has no manager check at all. An executive and a manager see an identical menu. The difference appears *inside* the screens.

Customers

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
Customer List	✓	✓	✓	—
Customer 360	✓	✓	✓	—
Create Customer	✓	✓	✓	—
Contact Details	✓	✓	✓	—

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
Products & Services	✓	✓	✓	—
Recent Activity	✓	✓	✓	—
Tally Serial	✓	✓	✓	—
Tally Serial Number	✓	✓	✓	—
Visit History	✓	✓	✓	—
Delivery Request	✓	✓	✓	—
Customer Tickets	✓	✓	✓	—
Address Details	✓	✓	✓	—
Data Point Details	✓	✓	✓	—
Book a Call	⚠	⚠	⚠	Payload is encoded differently for L1 — see Section 6, risk 2

Call Booking

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
Call Booking	⚠	✓	⚠	7 role gates — the most of any screen. See Section 3.2
Call Booking L2	⚠	✓	⚠	Approve icon is manager-only; visit-entry icon is L1-only
Call Booking Details	✓	✓	✓	—
Add Support Entry	✓	✓	⚠	Observation / requirement block hidden from support
Support Details	✓	✓	⚠	2 fields hidden from support — see Section 3.4
Support List	✓	✓	✓	—
Conveyance Entry	✓	✓	✓	—
PIW / Workshop Form	✓	✓	✓	—
Create Lead	✓	✓	✓	—
Cold Calling	✓	✓	✓	—
Near By Customer	✓	✓	✓	—

Leads & Opportunity

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
Lead	✓	✓	✓	Default filter differs: L1 opens on Received , support on Given
Lead Received	✓	✓	✓	Title reads "Lead Received" for L1, "Lead Given" for support
Create Lead 1	✓	✓	✓	—
Update Lead	✓	✓	✓	Title flips the same way. Edit rights are not role-based — see Section 3.7
Opportunity Details	✓	✓	✓	—
Opportunity Data	✓	✓	✓	—
Change Status	✓	✓	✓	—
Update Opportunity	✓	✓	✓	—

Tickets

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
Antra Ticket System	✓	✓	✓	—
Create Ticket	✓	✓	✓	—

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
Remark List	✓	✓	✓	—
Ticket Status	✓	✓	⚠	User filter dropdown hidden from support
Ticket Details	✓	✓	✓	—
Ticket Status Details	✓	✓	✓	—

Reports ("Operations")

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
Reports (the menu)	✓	✓	⚠	Support sees 1 card , L1 sees 3
Leave Report	✓	✓	✓	—
Holidays List	✓	✓	✓	—
Leave Status	⚠	✓	⚠	Only managers get the team picker + approve / reject
Conveyance Report	✓	✓	✓	—
Target Report	✓	✓	✗	Unreachable for support. All 4 entry points sit inside the two L1-only card groups — see below
Monthly Report	✓	✓	✓	—

Target Report is not gated by its own screen — it has no role check inside it. It is hidden because the only 4

`Get.to(TargetReport)` calls in the app (`Reports.dart:93, 108, 152, 167`) all sit inside the two `desCat == "L1"` blocks at `Reports.dart:63-121` and `122-179` . A support user has no route to it.

Everything else

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
Outstanding	✓	✓	✓	—
Epicenter Details	✓	✓	✓	—
Epicenters Page 2	✓	✓	✓	—
Epicenter Screen	✓	✓	✓	—
Escalation — Choose Type	✓	✓	✓	—
Escalation — Internal	✓	✓	✓	—
Escalation — From Ticket	✓	✓	✓	—
Escalation — Success	✓	✓	✓	—
Products / Product Details	✓	✓	✓	—
Profile / Edit Profile	✓	✓	✓	—
Notifications	✓	✓	✓	—
Company / Company Details	✓	✓	✓	—
Contact List	✓	✓	✓	—
Support Availability	✓	✓	✓	—
Login / Splash / Onboarding / Sync	✓	✓	✓	—
Data Scope	✓	✓	✓	—

Screen	A · L1 Exec	B · L1 Mgr	C · Support	What is different
My Customer Call	✓	✓	✗	Hidden from the menu
ANS Report / Create ANS	⚠	✓	✗	Hidden from the menu
PBL Report / Create PBL	⚠	✓	✗	Hidden from the menu
AGH — all 7 screens	✓	✓	✗	Hidden from the menu. Captain sees different content — see Section 3.6

The bottom line

	Count
Screens in the app	84
Screens with any role logic	~14
Screens where every role sees the same thing	~70
Screens completely hidden from support users	13 — see the breakdown below
Base roles	2 (A, C)
Add-on roles	3 (B, D, E)

The 13 screens support users cannot reach:

Source	Screens	Count
Antra Golden Hour menu item	AGH Dashboard, Check In, Completed, Member Learn, Notifications, Outcome, Schedule Session	7
ANS Report menu item	ANS Report, Create ANS	2
PBL Report menu item	PBL Report, Create PBL	2
My Customer Call menu item	My Customer Call	1
Operations report cards	Target Report	1

Only **4 menu items** are hidden, but they take 12 screens with them; Target Report is the 13th and is hidden by a card group rather than a menu item.

Access control is concentrated in about 14 files. Most of the app is identical for everyone.

3. The screens that actually differ

Only these need reading. Everything else is the same for all roles.

This section is organised by screen — open a screen, see what changes for whom. For the same facts organised **by role** — "I am a Manager, what do I get?" — see **Section 4**.

3.1 Home / Dashboard — `DashboardNew.dart`

What	L1 Executive	L1 Manager	Support user
Team-member dropdown	✗	✓	✗
Main chart	hidden	hidden	shown
Card list instead of chart	shown	shown	hidden
Data Points shortcut	shown	shown	hidden
Tab taps	update the chart in place	same	also jump the page

Code: `DashboardNew.dart:643, 723, 802, 880, 1027` · `Dashboard.dart:32`

⚠ **The most important behaviour in the whole app**

When a **manager picks a team member** from the dropdown, the app **overwrites its own identity** (`dashboardController.dart:110–111`):

```
dart DataInfo.enrollId.value = selected['ENROLLID']; DataInfo.desCat.value = selected['DESCAT']; // ← the manager's own role is now gone
```

If the manager picks a **support-track** member, `desCat` stops being `"L1"` **globally**. From that moment the manager's own drawer loses AGH, ANS, PBL and My Customer Call, and every screen renders as a support user — until they pick someone else or log out.

This is a bug, not a design. See Section 6, risk 1.

3.2 Call Booking — `CallBooking.dart`

The most role-gated screen in the app — 7 separate checks.

Feature	L1 Exec	L1 Mgr	Support	Rule in code
Team-member filter	✗	✓	✗	<code>rollId == "1"</code>
Edit check-in / check-out	✗	✓	✗	<code>rollId == "1"</code> and time is <code>"00"</code>
Manual check-in entry	✓	✓	✗	<code>CHKIN == "00"</code> and <code>desCat == "L1"</code>
Info dialog button	✓	✓	✗	<code>desCat == "L1"</code>
"Call approved status" row	✓	✓	✗	<code>desCat == "L1"</code> and <code>SUPCNT == "Yes"</code>
Visit Entry tile	Captain only	Captain only	✗	<code>(rollId=="1" or "2")</code> and <code>desCat=="L1"</code> and <code>tcId=="7"</code> and <code>SUPCNT=="Yes"</code>
Notes tile	✓	✓	✗	<code>desCat == "L1"</code>

Code: `CallBooking.dart:31, 206, 331, 527, 588, 803, 908`

The Visit Entry tile is the only place in the app that needs **three roles at once** — **A** (`desCat=="L1"`) and **B** or second-tier (`rollId` `"1"` / `"2"`) and **D** (`tcId=="7"`) — plus the call's own `SUPCNT=="Yes"` data flag. In practice almost nobody sees it.

3.3 Call Booking L2 — CallBookingL2.dart

Feature	Who sees it	Rule
Approve-call check icon	L1 Manager only	rollId == "1" and desCat == "L1"
Visit-entry file icon	any L1	desCat == "L1"

Code: CallBookingL2.dart:530, 586

3.4 Support Details — SupportDetails.dart

Field	L1	Support
Remark	✓	✓
Observation (RECOMMENDATION)	✓	✗
Requirement (REQUIREMENT)	✓	✗

Code: SupportDetails.dart:77, 90

 The server sends **all three fields to everyone**. Two are simply not drawn for support users. Anyone who inspects the response sees them. See Section 6, risk 3.

3.5 ANS Report & PBL Report — ans_screen.dart · PblReport.dart

This is the home of role E — ANS / PBL Author.

Both screens are **L1-only** (hidden from the support menu). Inside, two things are gated:

Feature	Who gets it	Roles
The "+" create button	anyone matching any one of the 8 conditions below	B, D or E
Team-member dropdown	managers only (rollId == "1")	B

The "+" button appears if **ANY** of these is true:

rollId == "1"

← B · Manager

tcId == "7"

← D · Captain

titleId == "24" or "25" or "26"

← E · ANS / PBL Author, by designation

userId == "176" or "177" or "365"

← E · ANS / PBL Author, THREE SPECIFIC PEOPLE

So role E is defined by elimination: an L1 Executive who is neither a Manager nor a Captain, but still gets the create button because of their designation (titleId) or because their personal (userId) is written into the source. There is no server field named "author" — role E exists only as the bottom six lines of that expression.

Role E is granted by	Values	Meaning
titleId	"24", "25", "26"	Three designations. Nobody has documented which three.
userId	"176", "177", "365"	Three named individuals, hardcoded

Code: ans_screen.dart:37–44 · PblReport.dart:32 (create button) · ans_screen.dart:55 · PblReport.dart:40 (team dropdown)

 **Three individual user IDs are hardcoded into the app.** If any of those three people change role or leave, the app must be rebuilt and re-released. See Section 6, risk 5.

 **Nobody knows what titleId 24, 25 and 26 mean.** The numbers appear in these two files and nowhere else — no constant, no comment, no enum. Ask the backend team what the TITLEID table holds and record the answer here.

The identical 8-condition expression is copy-pasted into both files. See Section 6, risk 6.

3.6 Antra Golden Hour — Application/AGH/*

This is the home of role D — Captain.

L1 only. Inside, the role that matters is **Captain (D) vs Member** (tcId == "7").

"Member" is not a sixth role — it is simply *not* a Captain. Any L1 user without tcId == "7" is the member side of a session.

 Being a Captain does **not** get you into AGH. The menu item checks desCat == "L1" only. A Captain on the support track never reaches these screens — see Section 1.

AGH is the only module with a real two-sided model: every session has one Captain and one Member, and each sees the *other* person's name and edits their *own* fields.

What	Captain sees	Member sees
Name on a session card	the member's name	the captain's name
Check-in slot label	CAPTAIN	MEMBER
Timestamps used	captain_start / captain_end	user_start / user_end
Text field edited	captainOutput	memberOutput
ChatGPT "enhance" writes to	captainOutput	memberOutput
Their own record in the upcoming list	hidden	shown
Check-out pending message	"pending from you" / "from {member}"	"pending from {captain}"

Code: aghController.dart:289, 318, 423, 485, 513, 844, 946 · AGHDashboard.dart:102, 562, 834, 848 · AGHCheckIn.dart:89, 97, 175, 269, 282, 316 · AGHOutcome.dart:415

Role in the API:

Call	Payload	Note
GETAGH	{"captain_id":"1234"}	Sends the current user as captain_id — even for members
SAVEAGH	{..., "role":"7"}	The only call in the whole app that tells the server a role

3.7 Update Lead — a gate that is *not* about roles

Easy to mistake for a role check. It isn't.

Edit rights come from a showData value handed over by the previous screen:

"showData": lead != "Given" && (leadType == "InProgress" || leadType == "UNTOUCHED")

When showData is false, every field is read-only and the submit button disappears. **That depends on the lead's status, not on who is logged in.**

Code: UpdateLead.dart:16, 81, 132 · LeadReceived.dart:41

3.8 Other partial screens

Screen	What is hidden from support users	Code
Add Support Entry	observation / requirement input block	AddSupportEntry.dart:642
Reports (Operations)	2 of the 3 report card groups	Reports.dart:63, 122
Ticket Status	the user filter dropdown	TicketStatus.dart:36
Leave Status	team picker + approve/reject (<i>non-managers</i>)	LeaveStatus.dart:19

4. The add-ons — exactly what each one unlocks

Sections 2 and 3 are organised **by screen**. This section is the same information organised **by role**: pick an add-on, and see every button it turns on and where.

Read this if you are asking "what does a Manager actually get?"

Remember the rule from Section 1: **an add-on never adds a menu item**. Everything below is a control *inside* a screen the user can already open.

4.1 Add-on B — Manager • `rollId == "1"`

In one line: "let me see and approve for my team."

Nine live controls across six screens. Every one is either a team picker or an approval.

#	Screen	Button / control	What it does	Code
1	Home Dashboard	Team-member picker	Taps open a bottom sheet listing your team; picking one reloads the dashboard as that person	<code>Dashboard.dart:32</code>
2	Call Booking	Team-member filter	Same bottom sheet — filters the booked-call list to one member	<code>CallBooking.dart:31</code>
3	Call Booking	 Edit icon	Opens "Update check In/Out Time" — only shown when <code>CHKIN</code> or <code>CHKOUT</code> is <code>"00"</code> (i.e. missing)	<code>CallBooking.dart:206</code>
4	Call Booking L2	Team-member filter	Support-track version of #2	<code>CallBookingL2.dart:26</code>
5	Call Booking L2	 Edit icon	Support-track version of #3	<code>CallBookingL2.dart:436</code>
6	Call Booking L2	✓ Circle icon	Opens the "Call Status" approve dialog. Green when <code>SUPCNT == "Yes"</code> , red otherwise. Also needs <code>desCat == "L1"</code>	<code>CallBookingL2.dart:530</code>
7	Leave Status	Team-member picker + approve / reject	The only place leave is approved	<code>LeaveStatus.dart:19</code>
8	ANS Report	Team-member dropdown	Filter ANS entries by person	<code>ans_screen.dart:55</code>
9	PBL Report	Team-member dropdown	Filter PBL entries by person	<code>PblReport.dart:40</code>

Manager also counts toward two shared buttons (it is one of several ways to qualify):

Screen	Button	See
ANS Report · PBL Report	the "+" create button	Section 4.3
Call Booking	the Visit Entry tile	Section 4.4

⚠ `rollId == "2"` exists, and it is almost dead. It appears **once** in the whole app — `CallBooking.dart:804` — inside `(rollId == "1" || rollId == "2")`, where it grants exactly the same thing as `"1"`. It looks like a second manager tier that was started and never finished. Today it unlocks one tile on one screen and nothing else.

⚠ **The drawer's manager check is commented out.** `DrawerWidget.dart:165` still carries `// DataInfo.rollId.value == "1"` && above the live ANS Report gate. Someone disabled it and left it in place, which is why a manager and a junior executive see an identical menu.

4.2 Add-on D — Captain • `tcId == "7"`

In one line: "I run the coaching session, I don't attend it."

Captain is different from B and E: **most of the time it is not a button at all — it is a side switch**. Of its 21 uses, 18 are inside Antra Golden Hour, where every session has one Captain and one Member, both using the same screens.

Inside AGH — what the switch flips

What	Captain gets	Member gets	Code
Name shown on a session card	the member's name	the captain's name	<code>aghController.dart:423, 485, 513</code>
Check-in slot label	<code>CAPTAIN</code>	<code>MEMBER</code>	<code>AGHCheckIn.dart:175</code>
Timestamps read & written	<code>captain_start</code> / <code>captain_end</code>	<code>user_start</code> / <code>user_end</code>	<code>AGHCheckIn.dart:316</code> · <code>AGHOutcome.dart:415</code>
Which text box you type into	<code>captainOutput</code>	<code>memberOutput</code>	<code>AGHCheckIn.dart:269</code>
Output field hint text	" <i>what you observed and decisions taken</i> "	" <i>what you shared and committed to</i> "	<code>AGHCheckIn.dart:269</code>
ChatGPT Enhance writes to	<code>captainOutput</code>	<code>memberOutput</code>	<code>AGHCheckIn.dart:89</code>
Previous button restores	<code>captainOutput</code>	<code>memberOutput</code>	<code>AGHCheckIn.dart:97</code>
Which output is submitted	<code>captainOutput</code>	<code>memberOutput</code>	<code>aghController.dart:289, 318</code>
Your own row in the upcoming list	hidden	shown	<code>aghController.dart:844</code>
Check-out pending message	" <i>pending from you</i> " / " <i>from {member}</i> "	" <i>pending from {captain}</i> "	<code>AGHDashboard.dart:834</code>
Total meeting time calculated from	captain timestamps	member timestamps	<code>AGHOutcome.dart:415</code>

Neither side is "more" than the other. They are two halves of one meeting, and the app reuses the same widgets for both. `aghController.dart:946` exposes this as `isCurrentUserCaptain`.

Outside AGH — 3 real buttons

Screen	Button	Note
ANS Report	the "+" create button	one of several ways to qualify — Section 4.3
PBL Report	the "+" create button	same
Call Booking	the Visit Entry tile	Captain is required here, not optional — Section 4.4

4.3 Add-on E — ANS / PBL Author · `titleId` or `userId`

In one line: "I'm allowed to create entries."

The smallest add-on in the app. It unlocks **one button, on two screens** — and nothing else.

Screen	Button	What it opens	Code
ANS Report	the "+" in the top bar	Create ANS screen	<code>ans_screen.dart:37-44</code>
PBL Report	the "+" in the top bar	Create PBL screen	<code>PblReport.dart:32-33</code>

The full "+" rule — any ONE of these is enough

```
rollId == "1"           ← B · Manager
tcId   == "7"           ← D · Captain
titleId == "24" or "25" or "26" ← E · by designation
userId == "176" or "177" or "365" ← E · three named people
```

So the "+" button is shared by **three different add-ons**. Role E is the part that is *only* about this button — a user who is neither Manager nor Captain, but still allowed to create, because of their designation or because their id is written into the source.

Role E is granted by	Values	Meaning
<code>titleId</code>	<code>"24"</code> , <code>"25"</code> , <code>"26"</code>	Three designations. Nobody has documented which three.
<code>userId</code>	<code>"176"</code> , <code>"177"</code> , <code>"365"</code>	Three named individuals, hardcoded

⚠ The same 8-condition expression is copy-pasted into both files — see Section 6, risk 6. Three user ids are hardcoded — see Section 6, risk 5.

4.4 The one button that needs three add-ons at once

The **Visit Entry** tile on Call Booking (`CallBooking.dart:803-806`) is the most gated control in the app. All four conditions must be true together:

```
(rollId == "1" || rollId == "2") // B · Manager (or the near-dead tier 2)
&& desCat == "L1"              // A · L1 Executive
&& tcId == "7"                  // D · Captain
&& data['SUPCNT'] == "Yes"       // the call's own data, not a role
```

An L1 Manager who is also a Captain, looking at a call already marked `SUPCNT == "Yes"`. In practice almost nobody sees this tile.

4.5 Add-on summary

Add-on	Field	Screens touched	What it really gives you
B · Manager	<code>rollId == "1"</code>	6	Team pickers and approvals
D · Captain	<code>tcId == "7"</code>	7 AGH + 3 others	The captain side of a session
E · ANS / PBL Author	<code>titleId</code> / <code>userId</code>	2	One "+" button

Verified counts — live comparisons in `lib/`, commented-out code excluded:

Field	Live	Commented out
<code>desCat</code>	35	2
<code>tcId</code>	21	0
<code>rollId</code>	13	3
<code>titleId</code>	6	0
<code>userId</code>	6	0
Total	81	5

5. Developer reference

5.1 The five flags — where they come from

All five are set **once, at login**, from the server's `LOGIN` response, and live in `lib/Constants/dataInfo.dart` as globals every screen reads directly.

Set in: `LoginController.dart:135–149` and `authController.dart:156–163`

Flag	Server field	Values in code	Decides	Role
<code>DataInfo.desCat</code>	<code>DESCAT</code>	<code>"L1"</code> / anything else	Department — sales vs support	A / C
<code>DataInfo.rollId</code>	<code>ROLLID</code>	<code>"1"</code> , <code>"2"</code>	Seniority — <code>1</code> = manager	B
<code>DataInfo.tcId</code>	<code>TCID</code>	<code>"7"</code>	Captain	D
<code>DataInfo.titleId</code>	<code>TITLEID</code>	<code>"24"</code> , <code>"25"</code> , <code>"26"</code>	Designation	E
<code>DataInfo.userId</code>	<code>UID</code>	<code>"176"</code> , <code>"177"</code> , <code>"365"</code>	Three hardcoded people	E

`desCat` is the only flag that decides **whether a screen exists** for a user. The other four decide **what is drawn inside** a screen the user can already open.

Note that `userId` is doing double duty: it is the session's user id on every API call, *and* — for three specific values — a permission flag. Nothing in the code marks it as the latter.

Also derived: `DataInfo.showData = (desCat == "L1")`.

5.2 Every role check in the codebase — 81 live comparisons

Counted by occurrence, not by line — a single line can hold several. Commented-out code is excluded (there are 5 more in comments: `desCat` ×2, `rollId` ×3).

`desCat == "L1"` — 35 occurrences

File	Line	Guards
<code>Drawer/DrawerWidget.dart</code>	114	Antra Golden Hour menu item
<code>Drawer/DrawerWidget.dart</code>	166	ANS Report menu item
<code>Drawer/DrawerWidget.dart</code>	175	PBL Report menu item
<code>Drawer/DrawerWidget.dart</code>	246	My Customer Call menu item
<code>Dashboard/Dashboard.dart</code>	104	legacy dashboard section
<code>Dashboard/DashboardNew.dart</code>	643, 723, 802	tab page-jump (<i>inverted</i> : <code>!= "L1"</code>)
<code>Dashboard/DashboardNew.dart</code>	880	chart widget (<i>inverted</i>)
<code>Dashboard/DashboardNew.dart</code>	1027	Data Points shortcut
<code>Report/Reports.dart</code>	63, 122	two report card groups
<code>TicketStatus/TicketStatus.dart</code>	36	user filter dropdown
<code>CallBooking/CallBooking.dart</code>	212, 331, 527, 588, 805, 908	check-in, info, approval, visit entry, notes
<code>CallBooking/CallBookingL2.dart</code>	530, 586	approve icon, visit-entry icon
<code>CallBooking/SupportDetails.dart</code>	77, 90	Observation, Requirement fields
<code>CallBooking/AddSupportEntry.dart</code>	642	observation input block
<code>Lead/UpdateLead.dart</code>	15	screen title
<code>Lead/LeadReceived.dart</code>	16	screen title
<code>Controller/leadController.dart</code>	13	default lead filter
<code>Controller/callBookingController.dart</code>	74, 451	branch + payload encoding

File	Line	Guards
Controller/dashboardController.dart	138, 569	target + opportunity sections

rollId == "1" — Manager — 13 occurrences

Twelve are == "1" ; one is == "2" (CallBooking.dart:804). Full walkthrough in Section 4.1.

File	Line	Guards
Dashboard/Dashboard.dart	32	team-member picker
Report/LeaveStatus.dart	19	team-member picker + approve / reject
ANS/ans_screen.dart	37, 55	create button, team dropdown
PblReport/PblReport.dart	32, 40	create button, team dropdown
CallBooking/CallBooking.dart	31, 206, 803, 804	filter, edit check-in, visit entry (804 is the lone == "2")
CallBooking/CallBookingL2.dart	26, 436, 530	team filter, edit check-in, approve icon

Plus 3 commented out: DrawerWidget.dart:165 · CallBooking.dart:1236, 1348 .

tcId == "7" — Captain — 21 occurrences

18 inside AGH, 3 outside. Full walkthrough in Section 4.2.

File	Line	Guards
Controller/aghController.dart	289, 318, 423, 485, 513, 844, 946	which output is saved/read, whose name shows, own-record filter, isCurrentUserCaptain
AGH/AGHCheckIn.dart	89, 97, 175, 269, 282, 316	enhance target, previous-output target, slot label, output field, output length, check-out timestamps
AGH/AGHDashboard.dart	102, 562, 834, 848	card layout, session card, pending-from label
AGH/AGHOutcome.dart	415	total meeting time
ANS/ans_screen.dart	38	create button
PblReport/PblReport.dart	32	create button
CallBooking/CallBooking.dart	806	Visit Entry tile

titleId ∈ {24, 25, 26} — 6 occurrences

ans_screen.dart:39, 40, 41 · PblReport.dart:32 ×3 — the ANS / PBL "+" button only. Section 4.3.

userId ∈ {176, 177, 365} — 6 occurrences

ans_screen.dart:42, 43, 44 · PblReport.dart:33 ×3 — the ANS / PBL "+" button only. Section 4.3.

6. Risks — in priority order

Risk 1 — A manager's role is overwritten, not layered

`dashboardController.dart:110–111` replaces `desCat` with the selected team member's value. The manager's own identity is destroyed for the rest of the session.

Fix: hold the viewed user separately (`viewingUserId`, `viewingDesCat`) and never mutate the logged-in user's own flags.

Risk 2 — The same endpoint is encoded differently per role

`callBookingController.dart:451`

```
data: desCat == "L1" ? Uri.encodeComponent(callBookingData) // L1 → encoded
      : callBookingData                                     // support → raw
```

A support user whose booking text contains `&`, `#` or `+` sends a corrupted payload.

Fix: always encode.

Risk 3 — Hidden is not the same as protected

`RECOMMENDATION` and `REQUIREMENT` on Support Details, and the whole staff directory on Contacts, are **returned to every user** and merely not rendered.

Fix: filter server-side if the data is genuinely restricted. If it isn't, drop the UI gate so the app stops implying a protection that doesn't exist.

Risk 4 — No role is ever sent to the server

Of ~101 API calls, exactly **one** sends a role (`SAVEAGH`). `APPROVELEAVE`, `CALLAPPROVE`, `ACTTCKUPDATE` and `OPPSTATUSUPDATE` carry only a user id.

All role enforcement in this app is UI-only. A modified client, or a direct URL, performs a manager action with an executive's credentials.

Fix: confirm with the backend team that the server validates `UID` against its own permission table. The app is not helping.

Risk 5 — Permissions hardcoded to three named people

`ans_screen.dart:42–44` and `PblReport.dart:32` grant rights to `userId` `176`, `177`, `365`. A personnel change requires an app release.

Fix: a server-driven permission flag on the `LOGIN` response.

Risk 6 — The ANS / PBL permission expression is duplicated

The same 8-condition expression is copy-pasted into two files. They match today; the next edit to one will silently diverge.

Fix: one shared getter.

Risk 7 — "L3" does not exist

If the business expects three tiers, the third was never built.

Fix: decide whether L3 is real. If it is, it needs a check. If it isn't, stop using the word in specs and tickets.

7. What good would look like

Replace the five scattered globals with one object:

```
class UserPermissions {
    final String department; // A / C - was desCat == "L1"
    final bool   isManager;  // B    - was rollId == "1"
    final bool   isCaptain;  // D    - was tcId   == "7"
    final Set<String> grants; // E    - from the server: {"ANS_CREATE", "PBL_CREATE", ...}

    bool can(String grant) => grants.contains(grant);
}
```

Note how the five roles collapse into **three fields plus a grant set**. Role **E** stops being a list of magic numbers and becomes what it always was: a set of grants.

Call sites then read as intent instead of magic numbers:

```
// today
if (DataInfo.rollId.value == "1" || DataInfo.tcId.value == "7" ||
    DataInfo.titleId.value == "24" || DataInfo.userId.value == "176") { ... }

// instead
if (perms.can("ANS_CREATE")) { ... }
```

Because `grants` comes from the server, permission changes ship **without an app release** — which removes Risk 5 and Risk 6 outright.

What each screen calls: `API-QUICK-REFERENCE.md` · Full technical detail: `API-DOCUMENTATION.md`