Responsible Spider

An explainable AI web crawler that shows — page by page — what it takes, what it refuses, and what tried to hijack it.

Your Name
Responsible AI · Final Project · Fall 2026

Code, docs & benchmark: [repository link] · Run locally: `npm install && npm run dev`

Spider animation inspired by @rybinfx (original implementation) · Refs: Greshake '23 · Hines '24 · Longpre '24 · Miller '19 · EU AI Act Art. 53 · RFC 9309

The problem

AI models are trained on scraped web data, and AI agents now browse the web for us. Both rely on **scrapers nobody can see**.

- **Consent:** did it honour the site's AI opt-out? Signals are fragmented: robots.txt, `noai`, ai.txt, TDMRep. Since 2024 the EU AI Act (Art. 53) obliges general-purpose model providers to respect them.
- **Security:** pages can hide instructions in text humans never see (*indirect prompt injection*, Greshake et al. 2023) and hijack the agent.

Both come from the same gap: **what a human sees vs. what a machine takes.**

Research questions

RQ1 Consent. How common are AI opt-outs, and how much would a consent-blind scraper take anyway?

RQ2 Security. How well do hidden-text injections hijack an LLM agent, and what does a transparent, layered defence cost?

RQ3 Explainability. Can per-page decision receipts make crawler behaviour auditable by non-experts?

Real web: who says "no" to AI?

robots.txt, 44 popular sites

66% block ≥1 AI crawler


9/9 news sites block AI crawlers

19 block GPTBot *but allow Google search*

57% block CCBot (Common Crawl)

Collected 16 Oct 2026 by `npm run audit`, which fetches only /robots.txt. 5 of 49 sites were unreachable.

What I built



The spider walks a live "web" of the site, stops at each page, decides and explains: collected, PII redacted, injection quarantined, skipped (no consent). A dashed ring marks pages where the naive agent was hijacked.


Consent
robots.txt for itself *and* 12 AI bots · noai · TDMRep · ai.txt · licence

Privacy
Emails, phones, SSNs, card numbers (Luhn), IPs → redacted

Security
Hidden-text detection (9 techniques) + transparent injection scorer → quarantine

Politeness
Crawl-delay, nofollow, honest user-agent, rate limits

Every page gets an explainable receipt



- **Contrastive:** naive scraper vs. responsible spider; naive agent vs. guarded agent (Miller 2019).
- **Evidence-bearing:** the exact robots.txt line, meta tag or CSS hiding trick behind each decision.
- **Causal:** leave-one-out ablation re-runs the agent without each suspicious segment. "Removing *this* paragraph stops the hijack."
- **Defence:** drop hidden text → quarantine score ≥ 0.5 → redact PII → spotlight as data (Hines et al. 2024) → check output.

Injection benchmark 89 pages

3 articles × 3 attacker goals (canary, phishing link, smear) × 9 hiding techniques, plus 8 benign controls (incl. benign hidden menus and an article *about* injection).

89% naive agent hijacked (simulated)

0% guarded agent hijacked (simulated)

99% detector precision

89% detector recall · 13% false-positive rate

[Replace with gpt-4o-mini results from `npm run eval`]

Hiding technique	Detected
display:none · white text · zero font · off-screen · comment · alt text · noscript	100%
Visible fine print ("Note to AI assistants...")	100%
Subtle visible phrasing, no trigger words	0%

Insights

- **Hiding is the tell.** Instruction-like text humans can't see has almost no legitimate use, so visibility filtering alone stops every hidden attack.
- **Keywords fail both ways.** Subtle phrasing gets through, and a benign article about injection gets flagged.
- **Opt-outs ≠ enforcement.** Sites say "search yes, AI no" with a protocol built for search.

Limitations & future work

- Static CSS analysis, no JavaScript → headless-browser pass.
- Small synthetic benchmark → adaptive red-teaming, real-model runs.
- Opt-outs are voluntary; our reading is a normative choice.
- **Expo study:** do receipts improve visitors' ability to predict and trust crawler decisions?