AUDIOLOGICAL EVALUATION & CLINICAL PATHOLOGY REPORT
Hardware-Grade Diagnostic Software Audiometer | ISO 8253-1 Compliant

Patient ID: 8733
Name: Vishal
Age: 18 years
Date / Time: 2026-10-14T15:47

Clinician / Operator: Dr. S. Sharma, Au.D.
Transducer Profile: Sennheiser_HDA200
Calibration Status: Calibrated (ISO 389-1)
Deployment: Rural Tele-Audiology Field Unit

PURE TONE AUDIOGRAM (BINAURAL)

Freq (Hz)	125	250	500	750	1000	1500	2000	3000	4000	6000	8000	PTA (4F)
Right AC (dB	35	35	45	45	40	-	70	85	-	45	-	51.7 dB
Left AC (dB)	45	45	35	40	40	-	-	85	-	-	-	37.5 dB
Right BC (dB	-	-	-	-	-	-	-	-	-	-	-	-
Left BC (dB)	-	-	-	-	-	-	-	-	-	-	-	-

SPEECH AUDIOMETRY SUMMARY
- Right Ear: SRT = None dB HL | WRS = None%
- Left Ear: SRT = None dB HL | WRS = None%
- Test Materials: Spondee & Phonetically Balanced Word Lists

RELIABILITY & QUALITY ASSURANCE
- Patient Reliability Score: 100.0%
- Ambient Room Noise Level: 20.299999237060547 dB SPL (ISO 8253-1 Permissible)
- Transducer Output Check: Digital Safety Limit Active (0 dBFS Clamping)

⚠ AC-ONLY INFERENCE — Approximate. Confirm with BC testing if available.
Diagnostic Classification: UNCERTAIN — REFER FOR BC TESTING (Certainty: 44.6%)
Clinical Recommendation: Ambiguous air-conduction configuration. Diagnostic certainty below threshold (<70%). Refer for bone-conduction audiometry.
Model Architecture: Random Forest Ensemble (AC_Only_Inference_v1) | Offline Local Inference