



BUSINESS BLUEPRINT AOP AUTOMATION FOR HMD PE PLANT (PE-1,PE-2)

Honeywell

Site Name	Reliance Industries Ltd.
Track Name	RIL AOP Automation for HMD PE 1&2 Plant
Rev. No.	Rev 1.0
Rev. Date	18 Aug. 25
Honeywell Doc No.	
RIL Doc No.	

Business Blueprint

AOP Automation for HMD PE1&2 Plant

Prepared for:

Reliance Industries Ltd

Submitted by:

Honeywell Automation India Ltd (“Honeywell”)



Revision History

Rev.	Date	Originated By	Description of status and changes
0.0	01-09-2024	HON	Issued for Review
1.0	16-09-2024	HON	Issued for Review (revised norms logic)
2.0	10-02-2025	HON	Issued for Review (updated RIL comments)
3.0	20-02-2025	HON	Issued for Review (Resolved RIL comments)
4.0	25-04-2025	HON	Issued for Approval
5.0	18-07-2025	HON	Site Specific Changes done and logic updated. Issued for approval
6.0	09-08-2025	HON	Norms Logic and Shutdown allocation logic update.

Table of Contents

1.	Introduction.....	6
1.1	Executive Summary	6
1.2	Reference Documents.....	6
2.	AOP Design Basis	8
2.1	Process and Operations Function	8
2.1.1	Budget Production.....	9
2.1.2	Norms	16
2.1.3	Feedstock Availability.....	19
3.	AOP Reports	20
4.	Key Assumptions and Exemptions	21

List of Figures

Figure 1 Digitized AOP Flow Diagram	8
Figure 2 Digitized AOP screen for Configuration/manual Inputs	11
Figure 3 Digitized AOP Steps to derive MC values for HMD PE1&2.....	12
Figure 4 Digitized AOP screen for Production Target.....	12
Figure 5 Grade-wise Business demand	13
Figure 6 Digitized AOP screen for Shutdown activities	13
Figure 7 Digitized AOP screen for Slowdown Activities.....	14
Figure 8 Number of operating hours	14
Figure 9 Grade wise Budget Production	16
Figure 10 Norm Calculation Flow-Best Achieved	17
Figure 11 Digitized AOP screen for Best Achieved Norms.....	18
Figure 12 Digitized AOP screen for Month-wise Overall AOP Consumption	19

List of Tables

Table 1 Reference Documents	7
Table 2 AOP Functional Scope.....	8

1. Introduction

The purpose of this document is to capture the detailed specifications for the Digitalized Annual Operating Plan (AOP) for HMD PE 1&2 plant for HMD site.

This document is based on the Technical Proposal submitted by Honeywell to Reliance. It also refers to data collected during the workshop conducted at RCP with various Polyethylene plant users across RIL sites.

1.1 Executive Summary

Reliance Industries Limited is India's leading private sector organization operating in various business verticals. The manufacturing sector is one such business vertical. RIL owns and operates multiple polyethylene plants across various sites.

Defining and finalizing the Annual Operating Plan is a critical annual business process carried out by different functional teams. At present this activity is carried out manually.

A Rev-0 budget is usually completed in Nov / Dec for the succeeding Financial Year (FY) and reviewed. The comments are addressed with updated information from the Business as the next revised budget by the end of Jan. Further revisions (if any) are incorporated in Feb / March to reflect updated business input as applicable.

The entries from the final rev of the budget are finalized in BPC before the beginning of the succeeding FY.

RIL aims to automate the AOP preparation process using a Data-Driven Model. This model leverages the last five years of AOP data from MIIS and incorporates plant-specific business rules (such as plant availability, running hours, feedstock availability, seasonal impact on production, etc.) to derive AOP figures in the expected formats.

As part of digitalization, Honeywell will support building a platform that will automate the Annual Operations Planning process for PE technology.

1.2 Reference Documents

Document ID	Revision	Title	Document
O-836243B24R01	R01	AOP Automation for O2C Proposal	 O-836243B24R01 RIL AOP Automation f
PE effective Operating Hours calculation	-	RIL AOP - PE Maintenance Screen – Reliance to Confirm on logic	

HMD PE DCT	-	Digital AOP HMD PE DCT	 PE DCT_HMD.xlsx
------------	---	------------------------	--

Table 1 Reference Documents

2. AOP Design Basis

The below table captures different functions for the scope of AOP digitization design –

Sr. No.	Functions	Covered in Document
1.	Health, Safety and Environment (HSE)	For later release post review and discussion
2.	Process/Operations	Covered
3.	Reliability and Maintenance	For later release post review and discussion

Table 2 AOP Functional Scope

Function-wise detailed design basis is captured in the below sections.

2.1 Process and Operations Function

In this section, the budgeted Production and Norms for a plant are derived, using a standard approach as briefed in the sections below for the following criteria

- Budget Production/Production AOP
- Norms/Consumption AOP

Steps to generate the Production and Consumption AOP are captured in the below flow diagram.




Figure 1 Digitized AOP Flow Diagram

2.1.1 Budget Production

Below are the steps captured to derive the budgeted AOP production values.

2.1.1.1 Configuration

The configuration screen serves as the foundation for the digital AOP process, allowing users to input essential data for production and consumption AOP calculations.

Plant-specific data are required to calculate Production and consumption. data, Startup losses for raw material & Utilities, other losses. There are different tabs available to configure the above parameter under the Configuration screen to support Production and Consumption Norms calculations and reports generation.

By default, the values manual entries entered for the current year will be automatically carried forward to the next year.

In configuration screen, below additional features and tabs are provided.

- **AOP historical period** basis added where Start and End date is provided to select historical period to calculate MCU and Norms data for selected period by default 05 years data will be loaded. AOP Design basis will reflect the selected period as AOP basis, users can add additional basis points for summary.
- **import and export** options to import and export manual entry parameters from configuration screen is provided.
- **Startup losses** are material wise losses during the startup period.
- **Other losses** are material wise other losses.
- **Shutdown Rate (Per HR)** is rate of losses during shutdown period.

The screenshot below highlights the details captured in the digitized AOP platform
Historical Period Basis.

Production & Norms Basis

Year: 2025-26
Vertical: PE
Site: HMD
Plant: PE1

1
2
3
4
5
6
7
8
9
10
11
12

Production & Norms Basis
Shutdown/TA Activities
Slowdown Activities
Production Target
Business Demand
Maintenance Details
Month wise Production plan
Steady State Consumption (Norm/Quantity)
Shutdown Consumption (Quantity)
Slowdown Consumption (Norm/Quantity)
Overall AOP Consumption (Norm/Quantity)
Feed Stock Availability

PE / HMD / PE1

AOP Historical Period Basis

Start Date: 01-04-2024
End Date: 31-10-2024
Load
(Last refreshed data on: 13-08-2025 04:11 PM for the period from 01-04-2024 to 31-10-2024)

AOP Design Basis

PE 1 &2 (Manual Input configuration screens)

❖ Startup Losses

Startup Losses														
Other Losses														
Shutdown Rate (Per Hr)														
Receipe														
Export														
Import														
Save														
Particulars	UOM	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Jan	Feb	Mar	Remark
Raw Material														
Cyclohexane	Kg	1.5	2.5	3.5	5.5	0	0	0	0	0	0	0	0	Test
Ethylene	MT	1.5	1.55	0.5	0	0	0	0	0	0	0	0	0	ok1
Octene	Kg	1.6	1.5	0	0	0	0	0	0	0	0	0	0	Test
Butene-1	Kg	1.5	2.5	1.5	0	0	0	0	0	0	0	0	0	Test1
By Products														
Butene II	MBT	1.5	1.5	0	0	0	0	0	0	0	0	0	0	TEST
Spent Alumina	MT	2.1	0	0	0	0	0	0	0	0	0	0	0	Test
PE OFFGAS	MT	3.1	0	0	0	0	0	0	0	0	0	0	0	Test

❖ Other Losses

❖ Shutdown Rate

Figure 2 Digitized AOP screen for Configuration/manual Inputs

The Max Capacity (MC) of HMD PE1&2 plants is defined on MC values captured in MCU portal. Last value for each grade in selected AOP basis period is selected as MC for that grade.

With this logic All grade MC is derived for HMD PE 1&2

NOTE- AOP historical period basis added in configuration screen where user can change Start date and End date to change the AOP design basis, accordingly MCU and Norms historical data will be considered for calculation.

The following logic has been formulated to derive MC values.




Figure 3 Digitized AOP Steps to derive MC values for HMD PE1&2

If the user needs to modify the production rate this can be done by providing a specific reason.

This information is captured in the AOP digitization portal as seen in the screenshot below.



Production Target Year: 2025-26 Vertical: PE Site: HMD Plant: PE1

1 Production & Norms Basis 2 Shutdown/TA Activities 3 Slowdown Activities 4 **Production Target** 5 Business Demand 6 Maintenance Details 7 Month wise Production plan 8 Steady State Consumption (Norm/Quantity) 9 Shutdown Consumption (Quantity) 10 Slowdown Consumption (Norm/Quantity) 11 Overall AOP Consumption (Norm/Quantity) 12 Feed Stock Availability

PE / HMD / PE1

Current Operating Capacity

Export Import Save Select UOM TPH

Particulars	Apr-2	May-2	Jun-2	Jul-2	Aug-2	Sep-2	Oct-2	Nov-2	Dec-2	Jan-2	Feb-2	Mar-2	Remark
F19010	28.25	28.25	28.25	28.25	28.25	28.25	28.25	28.25	28.25	28.25	28.25	28.25	Click to add remark
P15807	24.983	24.983	24.983	24.983	24.983	24.983	24.983	24.983	24.983	24.983	24.983	24.983	Click to add remark
M24300	31.571	31.571	31.571	31.571	31.571	31.571	31.571	31.571	31.571	31.571	31.571	31.571	Click to add remark
M60075	32.15	32.15	32.15	32.15	32.15	32.15	32.15	32.15	32.15	32.15	32.15	32.15	Click to add remark

Figure 4 Digitized AOP screen for Production Target

The '**Calculate**' button on this screen allows the user to compute the MC value if any manual changes have been made to the AOP basis selection on the configuration screen

2.1.1.3 Business Demand

The grade mix demand will be provided by the Business team and added in AOP portal manually. In the AOP digitization application, Percent monthly demand for each individual grade will be recorded.

An example of the same is mentioned in the table below.




Figure 5 Grade-wise Business demand

2.1.1.4 Maintenance/Shutdown

The operations team will provide the shutdown and slowdown plan to calculate month-wise operating hours available for production.

The screenshot below depicts the shutdown activities planned, as will be captured in the AOP digitized platform.

The user has to enter the SD-From and SD-To date and time to calculate the duration in hours, or SD-From and Duration (hrs) to calculate the SD-To date/time.





Figure 6 Digitized AOP screen for Shutdown activities

The slowdown activities can be calculated based on the slowdown rate and hours. This is called Basis Shutdown, equivalent of Slowdown.

$$\text{Basis shutdown equivalent of Slowdown hrs} = (\text{Slowdown rate} * \text{Slowdown hrs}) / \text{MCU}$$

The screen below depicts slowdown activities planned as will be captured in the digitized platform.




Slowdown Desc	Particulars	SD- From	SD- To	Duration (hrs)	Rate (TPH)	Remarks	Action
Test	F19010	08-04-2025 01:30 PM	09-04-2025 01:30 PM	24:00	15	Test1	

Figure 7 Digitized AOP screen for Slowdown Activities

Using this number, the operating hours available in a month will be calculated as -

$$\text{Number of Operating Hours in a month} = \text{Total Number of hrs in a month} - (\text{Shutdown Hrs} + \text{Slowdown converted to equivalent SD Hrs})$$

The screenshot below captures an example of the number of operating hours, Shutdown hours, and effective slowdown loads available in a month wise.



Description	Apr-25	May-25	Jun-25	Jul-25	Aug-25	Sep-25	Oct-25	Nov-25	Dec-25	Jan-26	Feb-26	Mar-26
AvailableHoursInMonth	720.00	744.00	720.00	744.00	744.00	720.00	744.00	720.00	744.00	744.00	672.00	744.00
AvgSlowdownLoadPVT	0.58	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
EffectiveOperatingHrs	682.00	744.00	720.00	744.00	744.00	720.00	744.00	720.00	744.00	744.00	672.00	744.00
NonShutdownHrs	696.00	744.00	720.00	744.00	744.00	720.00	744.00	720.00	744.00	744.00	672.00	744.00
ShutdownHrs	24.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
SlowdownLoadReduction	13.90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Figure 8 Number of operating hours

Note: RIL to validate slowdown and shut down hours calculated in System and raise any exception observed.

2.1.1.5 Calendar Year Based Production Calculations

Using the Production Target data, business demand, and maintenance plan, the month-wise and grade-wise budgeted production quantity will be derived.

The calculation logic is as below.

For a single-grade


$$\begin{aligned} \text{Total Budgeted Monthly Production} \\ &= \text{Average MCU of All grades captured in section 2.1.1.2(TPH)} \\ &\quad * \text{Operating hours in a month (hr)} \end{aligned}$$

$$\begin{aligned} \text{Each Grade Production for a month} &= (\text{Total Budgeted Monthly Production} * \\ &\quad \text{Percentage of Grade production demand (\%)}) / 100 \end{aligned}$$

Calendar based production calculation explained above will be used to calculate monthly production of both PE1&2.

Hence, Month – wise production would be,

The screenshot below captures the calculated budgeted production values.



Products	Apr-25	May-25	Jun-25	Jul-25	Aug-25	Sep-25	Oct-25	Nov-25	Dec-25	Jan-26	Feb-26	Mar-26	Total
F19010	970.8	1057.1	1023	1057.1	1057.1	1023	1057.1	1023	1057.1	1057.1	954.8	1057.1	12394.35
P15807	970.8	1057.1	1023	1057.1	1057.1	1023	1057.1	1023	1057.1	1057.1	954.8	1057.1	12394.35
M24300	970.8	1057.1	1023	1057.1	1057.1	1023	1057.1	1023	1057.1	1057.1	954.8	1057.1	12394.35
M60075	1164.96	1268.53	1227.61	1268.53	1268.53	1227.61	1268.53	1227.61	1268.53	1268.53	1145.77	1268.53	14873.22
B56003	776.64	845.68	818.4	845.68	845.68	818.4	845.68	818.4	845.68	845.68	763.84	845.68	9915.48
F46003	582.48	634.26	613.8	634.26	634.26	613.8	634.26	613.8	634.26	634.26	572.88	634.26	7436.61




Figure 9 Grade wise Budget Production

2.1.2 Norms

Below are the steps captured to derive the Norms value.

2.1.2.1 Steady-state Operations

At a high level, the norms calculation are categorized as below –

1. Best Achieved –

PE 1&2:

Raw material, byproduct & utilities norms are generally covered under this calculation basis. Based on the Selected basis AOP Period corresponding to the MCU derived in section 2.1.1.2. High and Low range of MCU (+/- 10% of MCU) is calculated. Based on derived high and low range of production MIIS data for selected period is filtered for consecutive days production. Consecutive days' selection is preferably 5 days, or if not available, 4, 3, 2, or 1 day. the days in which production lies within the high and low range and have consecutive days production are selected for norms calculation. Norms are calculated for each material and each day from the filtered data. respective material norms are then averaged out for Final norm value.

Below is the formulated logic for deriving the Best Achieved Norms




Figure 10 Norm Calculation Flow-Best Achieved

2. SAP Process order basis –

PE 1&2 catalyst-chemicals norms are generally covered under this calculation basis. Based on the Selected basis AOP Period, SAP data for each process order is filter for catalyst & chemicals for each grade. Process order wise consumption aggregation is calculated. For the same process order Production is aggregated to calculate final production number for the process order. Further each material norm is calculated for each process order using the formula below.

$$\begin{aligned}
 \text{Norms(per processorder)} \\
 &= \text{Aggregated Consumption(per processorder)} \\
 &\quad / \text{Aggregated Production (per processorder)}
 \end{aligned}$$

With the above logic applied on AOP period basis data we will get an array of data sets for each material for each grade per process order wise, now it is time to find final norm from the available data points. For specific to PE catalyst-chemicals logic used to calculate final norm is average out all norms after removing outlier to remove outlier logic used is explained below.

Outlier Removal:

Let's assume x, y, z are norms data set calculated with above explained logic.

Step 1 (A): Find average from all data points for each material (per grade).

Step 2 (B): Find standard deviation from all data points for each material (per grade).

Step 3(xi,yi,zi): calculate delta using norm data point average and standard deviation using below formula.

$$xi = Abs\left(\frac{x - A}{B}\right), yi = Abs\left(\frac{y - A}{B}\right), zi = Abs\left(\frac{z - A}{B}\right)$$

Step 4: removing data point (x,y,z...) (outlier removal) with condition remove norm data point if xi,yi,zi,...>1.

Step 5: average remaining norms data point which pass above condition.

The below screenshots depict the best-achieved feed state-wise value captured in the AOP digitized platform




Figure 11 Digitized AOP screen for Best Achieved Norms

2.1.2.2 Shutdown & Slowdown Consumption.

Shutdown consumption is calculated by shutdown hours which is calculated based on shutdown schedule and shutdown consumption per hour which either constants or manual entry

$$\text{Shutdown Consumption} = \text{Number of shutdown hours} * \text{Shutdown consumption rate}$$

2.1.2.3 Budget Norms/ Consumption AOP

The shutdown consumption quantities will be summed with the steady-state operation norms, to derive the budgeted norms which will be inclusive of shutdown conditions. The intent here is to derive budgeted norms for the steady-state and shutdown months separately, using the logic below—

PE 1&2

Consumption Norm

$$\begin{aligned} &= \text{Steady State Norms as captured in section 2.1.2.1} \\ &+ ((\text{Number of hours plant shutdown planned} * \text{Shutdown consumption per hour}) \\ &+ \text{Startuploss} + \text{Other losses}) / \text{Total Production} \end{aligned}$$

$$\text{Consumption AOP} = \text{Consumption Norm} * \text{Grade Production AOP}$$

If shutdown consumption is not applicable for any month, its value will be 0. Hence, the above formula is applicable for all the months.




Figure 12 Digitized AOP screen for Month-wise Overall AOP Consumption

2.1.3 Feedstock Availability

This section to be updated after discussion in detail with RIL on Site wide feedstock/AOP Production screen.

3. AOP Reports

- Dataset (Basis)
- Annual AOP Cost.
- Plant Production Summary (T-14).
- Month wise Production Plan (T – 16)
- Month wise Raw data (T – 18).
- Turnaround Report (T – 19A).
- Annual Production Plan (T – 15).
- Plant Contribution (T – 21).

4. Key Assumptions and Exemptions

The above scope of work should be read with the following assumptions made

1. Data Acceptance
2. DCT provided by HMD Site team