Assessing Data Quality with Dataplex

Overview

This lab demonstrates how to assess data quality in Google Cloud using **the Dataplex Universal Catalog**. The objective is to run automated data quality checks on a Big Query dataset using a YAML-based configuration and review the results to identify issues in the dataset.

Dataplex helps organize, secure, and catalog data at scale. A key feature is the ability to run **data quality tasks**, which is crucial for maintaining clean and reliable datasets for analytics and machine learning pipelines.


Objectives

- Create Dataplex resources: Lake, Zone, and Asset
- Query Big Query data to identify potential data quality issues
- Define and upload a CloudDQ YAML specification file
- Create and run a data quality task
- Review and interpret data quality results

Tools & Technologies

Tools & Technologies

- Google Cloud Platform
 - Dataplex Universal Catalog
 - o BigQuery
 - Cloud Storage
 - o Cloud Shell
- CloudDQ YAML specification
- gcloud CLI
- SQL



Task 1. Create a lake, zone, and asset in Dataplex

To define and run data quality tasks, you first need to create some Dataplex Universal Catalog resources.

In this task, you create a new Dataplex Universal Catalog lake to store ecommerce customer information, add a raw zone to the lake, and then attach a pre-created BigQuery dataset as a new asset in the zone.

Create a lake

1. In the Google Cloud Console, in the Navigation menu (≡)> View All Products, navigate to Analytics > Dataplex Universal Catalog.


If prompted Welcome to the new Dataplex Universal Catalog experience, click Close.

- 2. Under Manage lakes, click Manage.
- 3. Click Create lake.
- 4. Enter the required information to create a new lake:

Property	Value
Display Name	Ecommerce Lake
ID	Leave the default value.
Region	

Leave the other default values.

5. Click Create.



Add a zone to the lake

- 1. On the **Manage** tab, click on the name of your lake.
- 2. Click +ADD ZONE.
- 3. Enter the required information to create a new zone:


Property	Value	

Display Name	Customer Contact Raw Zone
ID	Leave the default value.
Туре	Raw zone
Data locations	Regional

Leave the other default values.

For example, the option for **Enable metadata discovery** under **Discovery settings** is enabled by default and allows authorized users to discover the data in the zone.

4. Click Create.



Attach an asset to a zone


- 1. On the **Zones** tab, click on the name of your zone.
- 2. On the Assets tab, click +ADD ASSET.
- 3. Click Add an asset.
- 4. Enter the required information to attach a new asset:

Property	Value
Туре	BigQuery dataset
Display Name	Contact Info
ID	Leave the default value.

Dataset	customers

Leave the other default values.

- 5. Click Done.
- 6. Click Continue.
- 7. For **Discovery settings**, select **Inherit** to inherit the Discovery settings from the zone level, and then click **Continue**.
- 8. Click Submit.



Task 2. Query a BigQuery table to review data quality

In the previous task, you created a new Dataplex Universal Catalog asset from a BigQuery dataset named **customers** that has been pre-created for this lab. This dataset contains a table named **contact_info** which contains raw contact information for customers of a fictional ecommerce company.


In this task, you query this table to start identifying some potential data quality issues that you can include as checks in a data quality job. You also identify another precreated dataset that you can use to store data quality job results in a later task.

- 1. In the Google Cloud Console, in the **Navigation menu** (=), navigate to **BigQuery**.
- 2. In the Explorer pane, expand the arrow next to your project ID to list the contents: _____
 In addition to the customer_contact_raw_zone dataset created by Dataplex Universal
 Catalog to manage that zone, there are two BigQuery datasets that were precreated for this lab:
- customers
- customers_dq_dataset

The dataset named **customers** contains one table named **contact_info**, which contains contact information for customers such as a customer ID, name, email, and more. This is the table that you explore and check for data quality issues throughout this lab.

The dataset named **customers_dq_dataset** does not contain any tables. When you define a data quality job in a later task, you use this dataset as the destination for a new table containing the data quality job results.

3. In the SQL Editor, click on **+ SQL query**. Paste the following query, and then click **Run**:



Task 3. Create and upload a data quality specification file

Dataplex data quality check requirements are defined using CloudDQ YAML specification files. Once created, the YAML specification file is uploaded to a Cloud Storage bucket that is made accessible to the data quality job.

The YAML file has four keys sections:

- a list of rules to run (either pre-defined or customized rules)
- row filters to select a subset of data for validation
- rule bindings to apply the defined rules to the table(s)
- optional rule dimensions to specify the types of the rules that the YAML file can contain
 In this task, you define a new YAML specification file for data quality checks that identify
 null customer IDs and emails in the specified BigQuery table. After you define the file, you
 upload it to a pre-created Cloud Storage bucket for use in a later task to run the data
 quality job.

Create the data quality specification file

1. In Cloud Shell, run the following command to create a new empty file for the data quality specification:

nano dq-customer-raw-data.yaml

```
student 00 e0f1f299944a@cloudshell:- (qwiklabs-qcp-00-cfaa12938a85)$ gsutil cp dq-customer-raw-data.yaml gs://qwiklabs-gcp-00-cfaa12938a85-bucket
Copying file://dq-customer-raw-data.yaml [Content-Type=application/yaml]...
- [1 files][ 1.0 KiB/ 1.0 KiB]
Operation completed over 1 objects/1.0 KiB.
student_00_e0f1f299944a@cloudshell:- (qwiklabs-gcp-00-cfaa12938a85)$
```

Upload the file to Cloud Storage

• In Cloud Shell, run the following command to upload the file to a Cloud Storage bucket that has been created for this lab:

gsutil cp dq-customer-raw-data.yaml gs://Project ID-bucket

```
student_00_e0f1f299944a@cloudshell:- (qwiklabs-gcp-00-cfaa12938a85)$ gsutil cp dq-customer-raw-data.yaml gs://qwiklabs-gcp-00-cfaa12938a85-bucket Copying file://dq-customer-raw-data.yaml [Content-Type-application/yaml]... - [1 files] [1.0 kib] 1.0 kib] (option completed over 1 objects/1.0 kib] operation completed over 1 objects/1.0 kib. student_00_e0f1f299944a@cloudshell:- (qwiklabs-gcp-00-cfaa12938a85)$
```

Task 4. Define and run a data quality job in Dataplex

The data quality process uses a data quality specification YAML file to run a data quality job and generates data quality metrics that are written to a BigQuery dataset.

In this task, you define and run a data quality job using the data quality specification YAML file uploaded to Cloud Storage in the previous task. When you define the job, you also specify a pre-created BigQuery dataset named **customer_dq_dataset** to store the data quality results.


- 1. In the Google Cloud Console, in the **Navigation menu** (■)> View All Products, navigate to **Analytics** > **Dataplex Universal Catalog**.
- 2. Under Manage lakes, click Process.
- 3. Click +CREATE TASK.
- 4. Under Check Data Quality, click Create task.
- 5. Enter the required information to create a new data quality job:

Property	Value
Dataplex lake	ecommerce-lake
Display name	Customer Data Quality Job
ID	Leave the default value.
Select GCS file	bucket/dq-customer-raw-data.yaml
Select BigQuery dataset	customers_dq_dataset
BigQuery table	dq_results
User service account	Compute Engine default service account

Leave the other default values.

Note that the Compute Engine default service account has been preconfigured for this lab to have the appropriate IAM roles and permissions. For more information, review the Dataplex Universal Catalog documentation titled Create a service account.

- 6. Click Continue.
- 7. For **Start**, select **Immediately**.
- 8. Click Create.



Task 5. Review data quality results in BigQuery

In this task, you review the tables in the **customers_dq_dataset** to identify records that are missing customer ID values or have an invalid values for emails.


- 1. In the Google Cloud Console, in the **Navigation menu** (=), navigate to **BigQuery**.
- 2. In the Explorer pane, expand the arrow next to your project ID to list the contents: _____
- 3. Expand the arrow next to the **customer_dq_dataset** dataset.
- 4. Click on the dq_summary table.
- 5. Click on the **Preview** tab to see the results.

The **dq summary** table provides useful information about the overall data quality including the number of records that were identified to not adhere to the two rules in the data quality specification file.

- 6. Scroll to the last column named failed records query.
- 7. Click on the down arrow in the first row to expand the text and view the entire query for the **VALID_EMAIL** rule results.

Note that the query is quite long and ends with ORDER BY _dq_validation_rule_id.

8. Click on + SQL query. Copy and paste the query into SQL Editor, and click Run.



Learnings & Reflections

- Learned how Dataplex integrates metadata management with data quality.
- Understood how to define reusable and modular rules via YAML.
- Gained insights into integrating Cloud Storage, BigQuery, and Dataplex for automated data validation pipelines.
- Saw how rule dimensions (e.g., completeness, conformance) help categorize data issu

Conclusion

This lab effectively demonstrates the power of **Dataplex** in monitoring and improving data quality within the Google Cloud ecosystem. It enables organizations to create transparent, automated, and scalable validation workflows, reducing the risk of data corruption and increasing trust in data-driven decisions.