Ex No: 6

Date:

# RECOGNIZE A VALID VARIABLE WITH LETTERS AND DIGITS USING LEX AND YACC

#### AIM:

To recognize a valid variable which starts with a letter followed by any number of letters or digits.

## **ALGORITHM:**

- Define lexical rules in variable.l with regex to match valid variables: start with a letter, followed by letters or digits. Tokenize input, distinguishing letters and digits.
- Use lexer (variable.l) to tokenize input into meaningful units like letters and digits.
- Implement grammar rules in parser (variable.y) for recognizing valid variable names using context-free grammar. Incorporate lexer tokens into parsing.
- In parser, implement error handling to detect invalid variable names. Set a flag (e.g., valid) to mark invalid identifiers.
- Check validity post-parsing; if flag remains true, indicate valid identifier. Otherwise, display message for invalid input.

## **PROGRAM:**

## variable.l:

```
% {
  #include "y.tab.h"
% }
%%
[a-zA-Z_][a-zA-Z_0-9]* return letter;
                   return digit;
[0-9]
              return yytext[0];
              return 0;
\n
%%
int yywrap()
return 1;
variable.y:
% {
  #include<stdio.h>
  int valid=1;
% }
```

```
%token digit letter
%%
start: letter s
s: letter s
    | digit s |;
%%
int yyerror()
  printf("\nIts not a identifier!\n");
  valid=0;
  return 0;
int main() {
  printf("\nEnter a name to test for an identifier: ");
  yyparse();
  if(valid) {
     printf("\nIt is a identifier!\n");
  } }
```

## **OUTPUT:**

```
[VinothN210701311@localhost ~]$ vi 311.1
[VinothN210701311@localhost ~]$ vi 311.y
[VinothN210701311@localhost ~]$lex 311.1
[VinothN210701311@localhost ~]$ yacc -d 311.y
[VinothN210701311@localhost ~]$ cc lex.yy.c y.tab.c
[VinothN210701311@localhost ~]$ ./a.out
Enter a name to test for an identifier: a

It is a identifier!
^C
[VinothN210701311@localhost ~]$ ./a.out
Enter a name to test for an identifier: int

Its not a identifier!
^C
[VinothN210701311@localhost ~]$
```

## **RESULT:**