

CSS Reference

- CSS Reference
- CSS Browser Support
- CSS Selectors
- CSS Functions
- CSS Reference Aural
- CSS Web Safe Fonts
- CSS Fallback Fonts
- CSS Animatable
- CSS Units
- CSS PX-EM Converter
- CSS Colors
- CSS Color Values
- CSS Default Values
- CSS Entities

CSS Properties

- accent-color
- align-content
- align-items
- align-self
- all
- animation
- animation-delay
- animation-direction
- animation-duration
- animation-fill-mode
- animation-iteration-count
- animation-name
- animation-play-state
- animation-timing-function
- aspect-ratio
- backdrop-filter
- backface-visibility
- background
- background-attachment
- background-blend-mode
- background-clip
- background-color
- background-image
- background-origin
- background-position
- background-position-x
- background-position-y
- background-repeat
- background-size
- block-size
- border
- border-block
- border-block-color
- border-block-end-color
- border-block-end-style
- border-block-end-width
- border-block-start-color
- border-block-start-style
- border-block-start-width
- border-block-style
- border-block-width
- border-bottom
- border-bottom-color
- border-bottom-left-radius
- border-bottom-right-radius
- border-bottom-style
- border-bottom-width
- border-collapse
- border-color
- border-end-end-radius
- border-end-start-radius
- border-image
- border-image-outset
- border-image-repeat
- border-image-slice
- border-image-source
- border-image-width
- border-inline
- border-inline-color
- border-inline-end-color
- border-inline-end-style
- border-inline-end-width
- border-inline-start-color
- border-inline-start-style
- border-inline-start-width
- border-inline-style
- border-inline-width
- border-left
- border-left-color
- border-left-style
- border-left-width
- border-radius
- border-right
- border-right-color
- border-right-style
- border-right-width
- border-spacing
- border-start-end-radius
- border-start-start-radius
- border-style
- border-top
- border-top-color
- border-top-left-radius
- border-top-right-radius
- border-top-style
- border-top-width
- border-width
- bottom
- box-decoration-break
- box-reflect
- box-shadow
- box-sizing
- break-after
- break-before
- break-inside
- caption-side
- caret-color
- @charset
- clear
- clip
- clip-path
- color
- column-count
- column-fill
- column-gap
- column-rule
- column-rule-color
- column-rule-style
- column-rule-width
- column-span
- column-width
- columns
- content
- counter-increment
- counter-reset
- cursor
- direction
- display
- empty-cells
- filter
- flex
- flex-basis
- flex-direction
- flex-flow
- flex-grow
- flex-shrink
- flex-wrap
- float
- font
- @font-face
- font-family
- font-feature-settings
- font-kerning
- font-size
- font-size-adjust
- font-stretch
- font-style
- font-variant
- font-variant-caps
- font-weight
- gap
- grid
- grid-area
- grid-auto-columns
- grid-auto-flow
- grid-auto-rows
- grid-column
- grid-column-end
- grid-column-gap
- grid-column-start
- grid-gap
- grid-row
- grid-row-end
- grid-row-gap
- grid-row-start
- grid-template
- grid-template-areas
- grid-template-columns
- grid-template-rows
- hanging-punctuation
- height
- hyphens
- image-rendering
- @import
- inline-size
- inset
- inset-block
- inset-block-end
- inset-block-start
- inset-inline
- inset-inline-end
- inset-inline-start
- isolation

Laptops with the power to simplify

HP

HP Dragonfly Pro

SHOP NOW



CSS Selector Reference

◀ Previous

Next ▶

CSS Selectors

In CSS, selectors are patterns used to select the element(s) you want to style.

Use our [CSS Selector Tester](#) to demonstrate the different selectors.

Selector	Example	Example description
<u>.class</u>	.intro	Selects all elements with class="intro"
<u>.class1.class2</u>	.name1.name2	Selects all elements with both <i>name1</i> and <i>name2</i> set within its class attribute
<u>.class1 .class2</u>	.name1 .name2	Selects all elements with <i>name2</i> that is a descendant of an element with <i>name1</i>
<u>#id</u>	#firstname	Selects the element with id="firstname"
<u>*</u>	*	Selects all elements
<u>element</u>	p	Selects all <p> elements
<u>element.class</u>	p.intro	Selects all <p> elements with class="intro"
<u>element.element</u>	div, p	Selects all <div> elements and all <p> elements
<u>element element</u>	div p	Selects all <p> elements inside <div> elements
<u>element>element</u>	div > p	Selects all <p> elements where the parent is a <div> element
<u>element+element</u>	div + p	Selects the first <p> element that is placed immediately after <div> elements
<u>element1~element2</u>	p ~ ul	Selects every element that is preceded by a <p> element
<u>[attribute]</u>	[target]	Selects all elements with a target attribute
<u>[attribute=value]</u>	[target="_blank"]	Selects all elements with target="_blank"
<u>[attribute~=value]</u>	[title~="flower"]	Selects all elements with a title attribute containing the word "flower"
<u>[attribute]=value]</u>	[lang]="en"]	Selects all elements with a lang attribute value equal to "en" or starting with "en-"
<u>[attribute^=value]</u>	a[href^="https"]	Selects every <a> element whose href attribute value begins with "https"
<u>[attribute\$=value]</u>	a[href\$=".pdf"]	Selects every <a> element whose href attribute value ends with ".pdf"
<u>[attribute*=value]</u>	a[href*="w3schools"]	Selects every <a> element whose href attribute value contains the substring "w3schools"
<u>:active</u>	a:active	Selects the active link
<u>::after</u>	p::after	Insert something after the content of each <p> element
<u>::before</u>	p::before	Insert something before the content of each <p> element
<u>:checked</u>	input:checked	Selects every checked <input> element
<u>:default</u>	input:default	Selects the default <input> element
<u>:disabled</u>	input:disabled	Selects every disabled <input> element
<u>:empty</u>	p:empty	Selects every <p> element that has no children (including text nodes)
<u>:enabled</u>	input:enabled	Selects every enabled <input> element
<u>:first-child</u>	p:first-child	Selects every <p> element that is the first child of its parent
<u>::first-letter</u>	p::first-letter	Selects the first letter of every <p> element
<u>::first-line</u>	p::first-line	Selects the first line of every <p> element
<u>:first-of-type</u>	p:first-of-type	Selects every <p> element that is the first <p> element of its parent
<u>:focus</u>	input:focus	Selects the input element which has focus
<u>:fullscreen</u>	:fullscreen	Selects the element that is in full-screen mode
<u>:hover</u>	a:hover	Selects links on mouse over
<u>:in-range</u>	input:in-range	Selects input elements with a value within a specified range
<u>:indeterminate</u>	input:indeterminate	Selects input elements that are in an indeterminate state
<u>:invalid</u>	input:invalid	Selects all input elements with an invalid value
<u>:lang(<i>language</i>)</u>	p:lang(it)	Selects every <p> element with a lang attribute equal to "it" (Italian)
<u>:last-child</u>	p:last-child	Selects every <p> element that is the last child of its parent
<u>:last-of-type</u>	p:last-of-type	Selects every <p> element that is the last <p> element of its parent
<u>:link</u>	a:link	Selects all unvisited links
<u>::marker</u>	::marker	Selects the markers of list items
<u>:not(<i>selector</i>)</u>	:not(p)	Selects every element that is not a <p> element
<u>:nth-child(<i>n</i>)</u>	p:nth-child(2)	Selects every <p> element that is the second child of its parent
<u>:nth-last-child(<i>n</i>)</u>	p:nth-last-child(2)	Selects every <p> element that is the second child of its parent, counting from the last child
<u>:nth-last-of-type(<i>n</i>)</u>	p:nth-last-of-type(2)	Selects every <p> element that is the second <p> element of its parent, counting from the last child
<u>:nth-of-type(<i>n</i>)</u>	p:nth-of-type(2)	Selects every <p> element that is the second <p> element of its parent
<u>:only-of-type</u>	p:only-of-type	Selects every <p> element that is the only <p> element of its parent
<u>:only-child</u>	p:only-child	Selects every <p> element that is the only child of its parent
<u>:optional</u>	input:optional	Selects input elements with no "required" attribute
<u>:out-of-range</u>	input:out-of-range	Selects input elements with a value outside a specified range
<u>::placeholder</u>	input::placeholder	Selects input elements with the "placeholder" attribute specified
<u>:read-only</u>	input:read-only	Selects input elements with the "readonly" attribute specified
<u>:read-write</u>	input:read-write	Selects input elements with the "readonly" attribute NOT specified
<u>:required</u>	input:required	Selects input elements with the "required" attribute specified
<u>:root</u>	:root	Selects the document's root element
<u>::selection</u>	::selection	Selects the portion of an element that is selected by a user
<u>:target</u>	#news:target	Selects the current active #news element (clicked on a URL containing that anchor name)
<u>:valid</u>	input:valid	Selects all input elements with a valid value
<u>:visited</u>	a:visited	Selects all visited links

◀ Previous

Log in to track progress

Next ▶

ADVERTISEMENT

Build your career today!



Get lifelong access to all our courses and certifications

Get Full Access

COLOR PICKER





Join our Mini CSS Bootcamp



★★★★★


"W3Schools Bootcamp is the best investment that I have ever made.

All the material from your catalog is really well explained, and has helped me to gain a great background. "

Student of W3Schools

Read more

ADVERTISEMENT




Laptops with the power to simplify



HP Dragonfly Pro


SHOP NOW

ADVERTISEMENT



BUILD YOUR CAREER. GET FULL ACCESS. SAVE 770\$

Start today



ADVERTISEMENT

Build your career. Get Full Access.

Lifelong access to all W3Schools courses and certifications!

Start today



SAVE 770\$

Top Tutorials

- HTML Tutorial
- CSS Tutorial
- JavaScript Tutorial
- How To Tutorial
- SQL Tutorial
- Python Tutorial
- W3.CSS Tutorial
- Bootstrap Tutorial
- PHP Tutorial
- Java Tutorial
- C++ Tutorial
- jQuery Tutorial

Top References

- HTML Reference
- CSS Reference
- JavaScript Examples
- SQL Reference
- Python Reference
- W3.CSS Reference
- Bootstrap Reference
- PHP Reference
- HTML Colors
- Java Reference
- Angular Reference
- jQuery Reference

Top Examples

- HTML Examples
- CSS Examples
- JavaScript Examples
- How To Examples
- SQL Examples
- Python Examples
- W3.CSS Examples
- Bootstrap Examples
- PHP Examples
- Java Examples
- XML Examples
- jQuery Examples

Get Certified

- HTML Certificate
- CSS Certificate
- JavaScript Certificate
- Front End Certificate
- SQL Certificate
- Python Certificate
- PHP Certificate
- jQuery Certificate
- Java Certificate
- C++ Certificate
- C# Certificate
- XML Certificate

FORUM | ABOUT

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

