

Tutorial 5 - Structures

1. A structure called circle is defined below. The structure consists of the radius of the circle and the (x,y) coordinates of its centre.

```
struct circle {  
    double radius;  
    double x;  
    double y;  
};
```

- (a) Implement the function intersect() that returns 1 if two circles intersect, and 0 otherwise. Two circles intersect when the distance between their centres is less than or equal to the sum of their radii. The function prototype is given below:

```
int intersect(struct circle c1, struct circle c2);
```

- (b) Implement the function contain() that returns 1 if c1 contains c2, i.e. circle c2 is found inside circle c1. Otherwise, the function returns 0. Circle c1 contains circle c2 when the radius of c1 is larger than or equal to the sum of the radius of c2 and the distance between the centres of c1 and c2. The function prototype is given below:

```
int contain(struct circle *c1, struct circle *c2);
```

2. A structure is defined to represent an arithmetic expression:

```
typedef struct {  
    float operand1, operand2;  
    char op; /* operator '+', '-', '*' or '/' */  
} bexpression;
```

- (a) Write a C function that computes the value of an expression and returns the result. For example, the function will return the value of 4/2 if in the structure passed to it, operand1 is 4, operator is '/' and operand2 is 2. The function prototype is given as:

```
float compute1(bexpression expr);
```

- (b) Write another C function that performs the same computation with the following function prototype:

```
float compute2(bexpression *expr);
```

3. Given the following structure definition, write the code for the functions getInput(), mayTakeLeave() and printList() with the following function prototypes:

```
typedef struct {  
    int id; /* staff identifier */  
    int totalLeave; /* the total number of days of leave allowed */
```

```
    int leaveTaken; /* the number of days of leave taken so far */  
} leaveRecord;
```

(a) void getInput(leaveRecord list[], int *n);

Each line of the input has three integers representing one staff identifier, his/her total number of days of leave allowed and his/her number of days of leave taken so far respectively. The function will read the data into the array *list* until end of input and returns the number of records read through *n*.

(b) int mayTakeLeave(leaveRecord list[], int id, int leave, int n);

It returns 1 if a leave application for *leave* days is approved. Staff member with identifier *id* is applying for *leave* days of leave. *n* is the number of staff in *list*. Approval will be given if the leave taken so far plus the number of days applied for is less than or equal to his total number of *leave* days allowed. If approval is not given, it returns 0. It will return -1 if no one in *list* has identifier *id*.

(c) void printList(leaveRecord list[], int n);

It prints the *list* of leave records of each staff. *n* is the number of staff in *list*.