

Tutorial 4 – Character Strings

1. What does the following program print?

```
#include <stdio.h>
#include <string.h>
#define M1 "How are ya, sweetie?"
char M2[40] = "Beat the clock.";
char *M3 = "chat";

int main()
{
    char words[80];
    printf(M1);
    puts(M1);
    puts(M2);
    puts(M2+1);
    gets(words); /* user inputs : win a toy. */
    puts(words);
    scanf("%s", words+6); /* user inputs : snoopy. */
    puts(words);
    words[3] = '\0';
    puts(words);
    while (*M3) puts(M3++);
    puts(--M3);
    puts(--M3);
    M3 = M1;
    puts(M3);
    return 0;
}
```

2. The following unknown function receives a string argument and a character argument, modifies the string argument and returns an integer value. Describe the purpose of the function. Give an example to support your answer.

```
int unknown(char str[ ], char c)
{
    int x, y=0, z=0;

    for (x=0; str[x] != '\0'; x++)
        if (str[x] != c)
            str[y++] = str[x];
        else
            z++;
    str[y] = '\0';
    return z;
}
```

3. Write the function `strncpy()` that copies not more than `n` characters (characters that follow a null character are not copied) from the array pointed to by `s2` to the array pointed to by `s1`. If the array pointed to by `s2` is a string shorter than `n` characters, null characters are appended to the copy in the array pointed to by `s1`, until `n` characters in all have been written. The `strncpy` returns the value of `s1`. The function prototype is:

```
char *strncpy(char * s1, char * s2, int n);
```

4. Write a C function that compares the string pointed to by `s1` to the string pointed to by `s2`. If the string pointed to by `s1` is greater than, equal to, or less than the string pointed to by `s2`, then it returns 1, 0 or -1 respectively. Write the code for the function without using any of the standard C string library functions. The function prototype is given as follows:

```
int stringcmp(char *s1, char *s2);
```