SQL Query

Q1: ID's present in ent_client but not in alert_configs

Query 1

Limit to 1000 rows

```sql
-- Q1: id present in ent_client but not in alert_configs
select id from digitap.ent_client where id not in (select id from infra.alert_configs);
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

id
7556
75081
5144481
5144485
5144486
5144487
5144488
5144489
5144490
5144491
5144492
5144493
5144494
5144495
5144496
5144497
5144498
5144499
5144500
5144501
5144502
5144503
5144504
5144505
5144506

Q2: ID's present in ent_client but not in monitoring_service_configs

Query 1

Limit to 1000 rows

```
-- Q2: id present in ent_client but not in monitoring_service_configs
select id from digitap.ent_client where id not in (select id from infra.monitoring_service_configs);
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

id
7556
75081
5144481
5144485
5144486
5144487
5144488
5144489
5144490
5144491
5144492
5144493
5144494
5144495
5144496
5144497
5144498
5144499
5144500
5144501
5144502
5144503
5144504
5144505
5144506

Q3: ID's present in ent_client and present in monitoring_service_configs but not in alert_configs

Query 1

```
-- Q3: id present in ent_client & present in monitoring_service_configs but not in alert_configs
select ent_client.id from digitap.ent_client where ent_client.id in (select id from infra.monitoring_service_configs)
and ent_client.id not in (select id from infra.alert_configs);
```

Result Grid

id
3
6
7
8
9
10
11
12
13
14
15
16
17
25
26
27