

Frame 2051: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface \Device\NPF_{E61851AA-B655-466B-B636-EFFB20D6FFD5}, id 0
Ethernet II, Src: Intel_4b:2b:7a (a0:29:42:4b:2b:7a), Dst: IETF-VRRP-VRID_01 (00:00:5e:00:01:01)
Internet Protocol Version 4, Src: 10.169.6.39, Dst: 10.151.222.55
Transmission Control Protocol, Src Port: 59113, Dst Port: 12346, Seq: 0, Len: 0
Frame 2052: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface \Device\NPF_{E61851AA-B655-466B-B636-EFFB20D6FFD5}, id 0
Ethernet II, Src: IETF-VRRP-VRID_01 (00:00:5e:00:01:01), Dst: Intel_4b:2b:7a (a0:29:42:4b:2b:7a)
Internet Protocol Version 4, Src: 10.151.222.55, Dst: 10.169.6.39
Transmission Control Protocol, Src Port: 12346, Dst Port: 59113, Seq: 0, Ack: 1, Len: 0
Frame 2053: 54 bytes on wire (432 bits), 54 bytes captured (432 bits) on interface \Device\NPF_{E61851AA-B655-466B-B636-EFFB20D6FFD5}, id 0
Ethernet II, Src: Intel_4b:2b:7a (a0:29:42:4b:2b:7a), Dst: IETF-VRRP-VRID_01 (00:00:5e:00:01:01)
Internet Protocol Version 4, Src: 10.169.6.39, Dst: 10.151.222.55
Transmission Control Protocol, Src Port: 59113, Dst Port: 12346, Seq: 1, Ack: 1, Len: 0
Frame 2113: 61 bytes on wire (488 bits), 61 bytes captured (488 bits) on interface \Device\NPF_{E61851AA-B655-466B-B636-EFFB20D6FFD5}, id 0
Ethernet II, Src: Intel_4b:2b:7a (a0:29:42:4b:2b:7a), Dst: IETF-VRRP-VRID_01 (00:00:5e:00:01:01)
Internet Protocol Version 4, Src: 10.169.6.39, Dst: 10.151.222.55
Transmission Control Protocol, Src Port: 59113, Dst Port: 12346, Seq: 1, Ack: 1, Len: 7
Data (7 bytes)
0000 77 6a 6a 2e 74 78 74 wjj.txt
Frame 2114: 54 bytes on wire (432 bits), 54 bytes captured (432 bits) on interface \Device\NPF_{E61851AA-B655-466B-B636-EFFB20D6FFD5}, id 0
Ethernet II, Src: Intel_4b:2b:7a (a0:29:42:4b:2b:7a), Dst: IETF-VRRP-VRID_01 (00:00:5e:00:01:01)
Internet Protocol Version 4, Src: 10.169.6.39, Dst: 10.151.222.55
Transmission Control Protocol, Src Port: 59113, Dst Port: 12346, Seq: 8, Ack: 1, Len: 0
Frame 2116: 56 bytes on wire (448 bits), 56 bytes captured (448 bits) on interface \Device\NPF_{E61851AA-B655-466B-B636-EFFB20D6FFD5}, id 0
Ethernet II, Src: IETF-VRRP-VRID_01 (00:00:5e:00:01:01), Dst: Intel_4b:2b:7a (a0:29:42:4b:2b:7a)
Internet Protocol Version 4, Src: 10.151.222.55, Dst: 10.169.6.39
Transmission Control Protocol, Src Port: 12346, Dst Port: 59113, Seq: 1, Ack: 9, Len: 0
Frame 2117: 56 bytes on wire (448 bits), 56 bytes captured (448 bits) on interface \Device\NPF_{E61851AA-B655-466B-B636-EFFB20D6FFD5}, id 0
Ethernet II, Src: IETF-VRRP-VRID_01 (00:00:5e:00:01:01), Dst: Intel_4b:2b:7a (a0:29:42:4b:2b:7a)
Internet Protocol Version 4, Src: 10.151.222.55, Dst: 10.169.6.39
Transmission Control Protocol, Src Port: 12346, Dst Port: 59113, Seq: 1, Ack: 9, Len: 0
Frame 2118: 54 bytes on wire (432 bits), 54 bytes captured (432 bits) on interface \Device\NPF_{E61851AA-B655-466B-B636-EFFB20D6FFD5}, id 0
Ethernet II, Src: Intel_4b:2b:7a (a0:29:42:4b:2b:7a), Dst: IETF-VRRP-VRID_01 (00:00:5e:00:01:01)
Internet Protocol Version 4, Src: 10.169.6.39, Dst: 10.151.222.55
Transmission Control Protocol, Src Port: 59113, Dst Port: 12346, Seq: 9, Ack: 2, Len: 0