

CSC411 Assignment 2

Yue Guo

November 9, 2017

1 Gaussian

1.1 P(y)

$$\begin{aligned} P(\mathbf{x} | \mu, \sigma) &= \sum_{k=1}^K P(\mathbf{x} | y = k, \mu, \sigma) P(y = k | \mu, \sigma) \\ &= \sum_{k=1}^K \alpha_k P(\mathbf{x} | y = k, \mu, \sigma) \\ &= \sum_{k=1}^K \alpha_k \left(\prod_{i=1}^D 2\pi\sigma_i \right)^{-\frac{1}{2}} \exp\left\{ -\sum_{i=1}^D \frac{1}{2\sigma_i^2} (x_i - \mu_{ki})^2 \right\} \end{aligned}$$

1.2 visualization

$$\begin{aligned} P(y | \mathbf{x}, \mu, \sigma) &= \frac{P(\mathbf{x}, y=k | \mu, \sigma)}{P(\mathbf{x} | \mu, \sigma)} \\ &= \frac{P(\mathbf{x} | y=k, \mu, \sigma) P(y=k | \mu, \sigma)}{P(\mathbf{x} | \mu, \sigma)} \\ &= \frac{\alpha_k \left(\prod_{i=1}^D 2\pi\sigma_i^2 \right)^{-\frac{1}{2}} \exp\left\{ -\sum_{i=1}^D \frac{1}{2\sigma_i^2} (x_i - \mu_{ki})^2 \right\}}{\sum_{k=1}^K \alpha_k \left(\prod_{i=1}^D 2\pi\sigma_i^2 \right)^{-\frac{1}{2}} \exp\left\{ -\sum_{i=1}^D \frac{1}{2\sigma_i^2} (x_i - \mu_{ki})^2 \right\}} \end{aligned}$$

1.3 visualization

$$\begin{aligned} & -\log P(y^{(1)}, x^{(1)}, \dots, y^{(N)}, x^{(N)} | \theta) \\ &= -\log P(y^{(1)}, x^{(1)} | \theta) - \log P(y^{(2)}, x^{(2)} | \theta) \dots - \log P(y^{(N)}, x^{(N)} | \theta) \\ &= \sum_{k=1}^K -\log[\alpha_k \left(\prod_{i=1}^D 2\pi\sigma_i^2 \right)^{-\frac{1}{2}} \exp\left\{ -\sum_{i=1}^D \frac{1}{2\sigma_i^2} (x_i - \mu_{ki})^2 \right\}] \\ &= \sum_{k=1}^K \sum_{i=1}^D \frac{1}{2\sigma_i^2} (x_i - \mu_{ki})^2 + \sum_{k=1}^K -\log[\alpha_k \left(\prod_{i=1}^D 2\pi\sigma_i^2 \right)^{-\frac{1}{2}}] \\ &= \sum_{k=1}^K \sum_{i=1}^D \frac{1}{2\sigma_i^2} (x_i - \mu_{ki})^2 + \sum_{k=1}^K \frac{1}{2} \log[\alpha_k \left(\prod_{i=1}^D 2\pi\sigma_i^2 \right)] \\ &= \sum_{k=1}^K \sum_{i=1}^D \frac{1}{2\sigma_i^2} (x_i - \mu_{ki})^2 + \sum_{k=1}^K \sum_{i=1}^D \left[\frac{1}{2} \alpha_k \log(2\pi\sigma_i^2) \right] \end{aligned}$$

1.4 visualization

$$\begin{aligned} \frac{\partial}{\partial \mu_{ki}} &= \sum_{i=1}^D \frac{1}{2\sigma_i^2} 2(-x_i + \mu_{ki}) \mathbb{1}(i = k) \\ &= \sum_{i=1}^D \frac{1}{\sigma_i^2} (-x_i + \mu_{ki}) \mathbb{1}(i = k) \end{aligned}$$

Setting $\frac{\partial}{\partial \mu_{ki}} = 0$, we have

$$\begin{aligned} \sum_{i=1}^D \frac{1}{\sigma_i^2} (-x_i + \mu_{ki}) \mathbb{1}(i = k) &= 0 \\ x_i &= \frac{\sum_{i=1}^D \mu_{ki} \mathbb{1}(i=k)}{\sum_{i=1}^D \mathbb{1}(i=k)} \end{aligned}$$

1.5 visualization

$$\begin{aligned} \frac{\partial}{\partial \sigma_i^2} &= \sum_{k=1}^K \sum_{i=1}^D -\frac{1}{2} (x_i - \mu_{ki})^2 \frac{1}{\sigma_i^4} + \frac{1}{2} \sum_{k=1}^K \sum_{i=1}^D \frac{2\pi}{2\pi\sigma_i^2} \\ &= \sum_{k=1}^K \sum_{i=1}^D -\frac{1}{2} (x_i - \mu_{ki})^2 \frac{1}{\sigma_i^4} + \frac{1}{2} \sum_{k=1}^K \sum_{i=1}^D \frac{1}{\sigma_i^2} \\ &= \sum_{i=1}^D \frac{1}{2} \left[-(x_i - \mu_{ki})^2 \frac{1}{\sigma_i^4} + \frac{1}{\sigma_i^2} \right] \mathbb{1}(i = k) \end{aligned}$$

Setting $\frac{\partial}{\partial \sigma_i^2}$ to zero, we have

$$\sum_{i=1}^D \mathbb{1}(i=k)(x_i - \mu_{ki})^2 \frac{1}{\sigma_i^4} = \sum_{i=1}^D \mathbb{1}(i=k) \frac{1}{\sigma_i^2}$$

$$\sum_{i=1}^D \mathbb{1}(i=k)(x_i - \mu_{ki})^2 = \sum_{i=1}^D \mathbb{1}(i=k) \sigma_i^2$$

$$\sigma_i^2 = \frac{\sum_{i=1}^D \mathbb{1}(i=k)(x_i - \mu_{ki})^2}{\sum_{i=1}^D \mathbb{1}(i=k)}$$

2 Handwritten digits

2.1 KNN

1. Plot of digit means




Figure 1:

2.1.1 KNN Euclidean

- (a) K = 1, test accuracy = 0.96875, train accuracy = 1.0
- (b) K = 15, test accuracy = 0.9585, train accuracy = 0.959428571429

2.1.2 Break ties

In my program, I have the array `label_count[0, 10]` in function `def query_knn(self, test_point, k):` that stores the number of neighbours with the digit label corresponding to the index of `label_count` array. I find the maximum number in `label_count`, and the index of the max is the majority vote. If there are multiple, the function `label_count.argmax()` will pick the index that comes first. This is justified in class, we can break ties randomly or assign to the first maximum vote.

2.1.3 K = 1 to 15

K	Training Accuracy	Average Fold	Test Accuracy
1	cell5	0.9644285714285715	0
2	cell8	0.9575714285714285	0

[0.9644285714285715, 0.9575714285714285, 0.9634285714285715, 0.961, 0.9608571428571429, 0.959, 0.957857142857143, 0.9574285714285715, 0.9555714285714286, 0.9528571428571428, 0.9522857142857143, 0.9514285714285714, 0.9504285714285714, 0.95]

2.2 Conditional Gaussian

2.2.1 Plot of log




Figure 2:

2.3 Naives Bayes

2.3.1 Plot of η




Figure 3:




Figure 4: