


Bachelor's Thesis

Flexible User-Friendly Trip Planning Queries

Adviser: Saeed Taghizadeh

Violina Zhekova | May 9, 2019

INSTITUTE FOR PROGRAM STRUCTURES AND DATA ORGANIZATION (IPD), CHAIR PROF. BÖHM



- ◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ || ≡ ↺ 🔍 ↻

-

-

- *Sequenced Route Queries (SRQ)* - finding routes passing through multiple *Points of Interest* (Pols)
- *Advances in Location Based Services (LBS)* and *Geographic Information System (GIS)* applications (e.g. logistics and supply chain management)
- Aim: Designing a language to enable the user to express his query requirements in a flexible manner




- ◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ || ≡ ↺ 🔍 ↻

- ◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ | ≡ ↺ 🔍 ↻

Example

- **Category sequence:** (restaurant, bank, movie theater, restaurant)
Condition: equal restaurants
- **Optimal Sequenced Route (OSR):** (r_1, b_1, mt_1, r_2) , length: 11 (shown with red lines)
- **Optimal route with equal restaurants:** (r_1, b_1, mt_1, r_1) , length: 12 (shown with dashed lines)



- **Problem:** Need for flexibility in route finding queries
- **Solution:** Developing a query language operators to fulfill the essential user's requirements:
 - Relationships among the Pols
 - Order and priority of the Pols
 - Expressing multiple travel variations
- Proposing four essential operators: "equality" operator, "inequality" operator, "or" operator, "order" operator
- Making use of existing approaches (PNE (*Progressive Neighbor Exploration*)) to transform the complex user query

- **Problem:** Need for flexibility in route finding queries
- **Solution:** Developing a query language operators to fulfill the essential user's requirements:
 - Relationships among the Pols
 - Order and priority of the Pols
 - Expressing multiple travel variations
- Proposing four essential operators: "equality" operator, "inequality" operator, "or" operator, "order" operator
- Making use of existing approaches (PNE (*Progressive Neighbor Exploration*)) to transform the complex user query

```

fetch a  $PSR$  from the heap;
switch  $s = size(PSR)$  do
    case  $s == l$  do
         $PSR$  is the optimal route;
        return  $PSR$ ;
    case  $s \neq l$  do
        a)
             $NN(r_{|PSR|}, C_{M_{|PSR|+1}})$ ;
            update  $PSR$  and perform trimming in case it is a candidate
            SR ;
            put  $PSR$  back on the heap ;
        b)
             $kNN(r_{|PSR|-1}, C_{M_{|PSR|}})$ ;
            generate a new  $PSR$  and place it on the heap;

```


Heuristic

Given a sequence of categories $M = (c_1, c_2, \dots, c_l)$ and a PSR $R' = (r_1, r_2, \dots, r_k)$ the **heuristic** for this route is defined as:

$$h(R') = \max_{i \in [k+1, l]} nearestNeighbor(r_k, C_{M_i}) \quad (1)$$

- Informal: The heuristic of a certain PSR is the maximum distance out of the distances to the nearest Pols from the set of categories that are yet to be expanded.

Heuristic

Given a sequence of categories $M = (c_1, c_2, \dots, c_l)$ and a PSR $R' = (r_1, r_2, \dots, r_k)$ the **heuristic** for this route is defined as:

$$h(R') = \max_{i \in [k+1, l]} nearestNeighbor(r_k, C_{M_i}) \quad (1)$$

- Informal: The heuristic of a certain PSR is the maximum distance out of the distances to the nearest Pols from the set of categories that are yet to be expanded.

The **lower bound** of a PSR R' represents the sum of its length and its heuristic:


$$LB(R') = length(R') + h(R') \quad (2)$$

- The proposed algorithm uses a heap, sorted by the lower bound of the routes

Example: Step 1

$M = (r, b, mt, r), EQUAL(0, 3)$


- Optimal route found with PNE: (r_1, b_1, mt_1, r_2)
- Dummy SR: (r_1, b_1, mt_1, r_1) ; Upper Bound $UB = length(dummySR)$



Step	Heap contents (PSR $R : length(R), heuristic(R)$)
1	$(r_1 : 1, 5), (r_2 : 5, 4)$

Example: Step 2


$M = (r, b, mt, r), EQUAL(0, 3)$



Step	Heap contents (PSR R : $length(R)$, $heuristic(R)$)
1	$(r_1 : 1, 5), (r_2 : 5, 4)$
2	$(r_1, b_1 : 4, 3), (r_2 : 5, 4)$

Example: Step 8

$$M = (r, b, mt, r), EQUAL(0, 3)$$




Candidate SR: $(r_1, b_1, mt_1, r_1 : 12, 0)$

Step	Heap contents (PSR $R : length(R), heuristic(R)$)
7	$(r_1, b_1, mt_1 : 7, 5), (r_2, b_1, mt_1 : 11, 4), (r_2, b_2, mt_1 : 11, 4), (r_1, b_2, mt_1 : 11, 5)$
8	$(r_2, b_1, mt_1 : 11, 4), (r_2, b_2, mt_1 : 11, 4), (r_1, b_2, mt_1 : 11, 5)$

Example: Step 9

$M = (r, b, mt, r), EQUAL(0, 3)$



Candidate SR: $(r_2, b_1, mt_1, r_2 : 15, 0)$


Step	Heap contents (PSR $R : length(R), heuristic(R)$)
8	$(r_2, b_1, mt_1 : 11, 4), (r_2, b_2, mt_1 : 11, 4), (r_1, b_2, mt_1 : 11, 5)$
9	$(r_2, b_2, mt_1 : 11, 4), (r_1, b_2, mt_1 : 11, 5)$

- ◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ | ≡ ↺ 🔍 ↻

Example: Step 1

$M = (r, ph, r), UNEQUAL(0, 2)$


- Optimal route found with PNE: (r_1, ph_1, r_1)



Step	Heap contents (PSR R : $length(R)$)
1	$(r_1 : 1)$

Example: Step 2


$M = (r, ph, r), UNEQUAL(0, 2)$



Step	Heap contents (PSR $R : length(R)$)
1	$(r_1 : 1)$
2	$(r_1, ph_1 : 3), (r_2 : 5)$

Example: Step 3


$M = (r, ph, r), UNEQUAL(0, 2)$



Step	Heap contents (PSR $R : length(R)$)
2	$(r_1, ph_1 : 3), (r_2 : 5)$
3	$(r_2 : 5), (r_1, ph_2 : 5), (r_1, ph_1, r_2 : 10)$

Example: Step 5

$M = (r, ph, r), UNEQUAL(0, 2)$




Step	Heap contents (PSR $R : length(R)$)
4	$(r_1, ph_2 : 5), (r_2, ph_2 : 7), (r_1, ph_1, r_2 : 10)$
5	$(r_1, ph_2, r_2 : 7), (r_2, ph_2 : 7), (\cancel{r_1, ph_1, r_2 : 10})$

- **OR sequence:** An OR sequence $OR = (M_1, M_2, \dots, M_m)$ represents the disjunction of category sequences, such as $M_1 = (c_1, c_2, \dots, c_l)$.
- *Input:* A sequence of OR sequences $S = (OR_1, OR_2, \dots, OR_n)$ and a starting point sp in \mathbb{R}^2
- *Output:* Optimal route $R = (r_1, r_2, \dots, r_l)$
- **Proposed approach:** progressively inspects each option M_i from the OR sequences OR_i in $S = (OR_1, OR_2, \dots, OR_n)$, compares them and continues with the best one, based on length, until it reaches a full sequenced route
- **Proposed approach:** runs the PNE algorithm on all possible combinations of the query to find the shortest route out of them

Example: Step 1


$S = (OR_1, OR_2, OR_3), OR_1 = ((b), (ph)), OR_2 = ((mt)), OR_2 = ((r))$



Step	Heap contents (PSR $R : length(r), index(R)$)
1	$(b_1 : 2, 1)$

Example: Step 2


$S = (OR_1, OR_2, OR_3)$, $OR_1 = ((b), (ph))$, $OR_2 = ((mt))$, $OR_3 = ((r))$



Step	Heap contents (PSR R : $length(r)$, $index(R)$)
1	$(b_1 : 2, 1)$
2	$(ph_1 : 3, 1), (b_1, mt_1 : 5, 2)$

Example: Step 6


$S = (OR_1, OR_2, OR_3)$, $OR_1 = ((b), (ph))$, $OR_2 = ((mt))$, $OR_3 = ((r))$



Step	Heap contents (PSR R : $length(r)$, $index(R)$)
5	$(b_1, mt_1 : 5, 2), (ph_1, mt_1 : 6, 2), (ph_2, mt_1 : 7, 2), (b_2, mt_1 : 9, 2)$
6	$(ph_1, mt_1 : 6, 2), (ph_2, mt_1 : 7, 2), (b_1, mt_1, r_2 : 9, 3), (b_2, mt_1 : 9, 2)$

Example: Step 7

$S = (OR_1, OR_2, OR_3)$, $OR_1 = ((b), (ph))$, $OR_2 = ((mt))$, $OR_3 = ((r))$




Step	Heap contents (PSR R : $length(r)$, $index(R)$)
6	$(ph_1, mt_1 : 6, 2)$, $(ph_2, mt_1 : 7, 2)$, $(b_1, mt_1, r_2 : 9, 3)$, $(b_2, mt_1 : 9, 2)$
7	$(ph_2, mt_1 : 7, 2)$, $(b_1, mt_1, r_2 : 9, 3)$, $(b_2, mt_1 : 9, 2)$, $(ph_1, mt_1, r_2 : 10, 3)$
8	$(b_1, mt_1, r_2 : 9, 3)$, $(b_2, mt_1 : 9, 2)$, $(ph_2, mt_1, r_2 : 11, 3)$

- **ORDER sequence:** An order sequence $ORDER = (i_1, i_2, \dots, i_k)$, is a sequence of indices in a category sequence $M_1 = (c_1, c_2, \dots, c_l)$, which indicate that the categories at the given indices should remain in the fixed positions in this category sequence.
- $NOTORDERED = \overline{ORDER}$
- **Input:** A sequence of categories $M = (c_1, c_2, \dots, c_l)$, a starting point sp in \mathbb{R}^2 and an ORDER sequence $ORDER = (i_1, i_2, \dots, i_k)$
- **Output:** Optimal route $R = (r_1, r_2, \dots, r_l)$
- **Proposed approach:** inspects progressively each category option for the indices out of the NOTORDERED sequence, compares them and continues with the best one, based on length, until it reaches a full sequenced route.
- **Proposed approach:** runs the PNE algorithm on all possible permutations of the query to find the shortest route out of them

Example: Step 1


$M = (b, r, ph)$, $ORDER = (1)$



Step	Heap contents (PSR $R : length(r), r.notordered$)
1	$(b_1 : 2, [ph])$

Example: Step 1


$M = (b, r, ph)$, $ORDER = (1)$



Step	Heap contents (PSR $R : length(r), r.notordered$)
1	$(b_1 : 2, [ph])$
2	$(ph_1 : 3, [b]), (b_1, r_2 : 5, [ph])$

Example: Step 6


$M = (b, r, ph)$, $ORDER = (1)$



Step	Heap contents (PSR $R : length(r), r.notordered$)
5	$(ph_1, r_1 : 5, [b]), (b_2, r_2 : 5, [ph]), (ph_2, r_2 : 5, [b]), (b_1, r_2 : 5, [ph])$
6	$(b_2, r_2 : 5, [ph]), (ph_2, r_2 : 5, [b]), (b_1, r_2 : 5, [ph]), (ph_1, r_1, b_1 : 8, [])$

Example: Step 12

$M = (b, r, ph)$, $ORDER = (1)$



Step	Heap contents (PSR $R : length(r), r.notordered$)
10	$(b_2, r_2 : 5, [ph]), (ph_2, r_2, b_2 : 6, []), (b_1, r_1, ph_1 : 7, []), (ph_2, r_1 : 7, [b]), (b_2, r_1 : 9, [ph]), (ph_1, r_2 : 10, [b])$
11	$(ph_2, r_2, b_2 : 6, []), (ph_2, r_1 : 7, [b]), (b_2, r_1 : 9, [ph]), (ph_1, r_2 : 10, [b]), (\cancel{b_2, r_2, ph_1 : 12, []})$

Example

Step	Heap contents (PSR $R : \text{length}(r), r.\text{notordered}$)
1	$(b_1 : 2, [ph])$
2	$(ph_1 : 3, [b]), (b_1, r_2 : 5, [ph])$
3	$(ph_2 : 3, [b]), (ph_1, r_1 : 5, [b]), (b_1, r_2 : 5, [ph])$
4	$(b_2 : 4, [ph]), (ph_2, r_2 : 5, [b]), (ph_1, r_1 : 5, [b]), (b_1, r_2 : 5, [ph])$
5	$(ph_1, r_1 : 5, [b]), (b_2, r_2 : 5, [ph]), (ph_2, r_2 : 5, [b]), (b_1, r_2 : 5, [ph])$
6	$(b_2, r_2 : 5, [ph]), (ph_2, r_2 : 5, [b]), (b_1, r_2 : 5, [ph]), (ph_1, r_1, b_1 : 8, [])$
7	$(b_1, r_2 : 5, [ph]), (b_2, r_2, ph : 5, [ph]), (ph_2, r_2 : 5, [b]), (b_2, r_2, ph_2 : 7, []), \cancel{(ph_1, r_1, b_1 : 8, [])}, (b_2, r_1 : 9, [ph]), (ph_1, r_2 : 10, [b])$
8	$(b_2, r_2 : 5, [ph]), (ph_2, r_2 : 5, [b]), (b_1, r_1 : 5, [ph]), (b_2, r_2, ph_2 : 7, []), \cancel{(b_1, r_2, ph_2 : 7, [])}, (b_2, r_1 : 9, [ph]), (ph_1, r_2 : 10, [b])$
9	$(b_1, r_1 : 5, [ph]), (b_2, r_2 : 5, [ph]), (ph_2, r_2, b_2 : 6, []), \dots$



Inequality



Or



Order












Conclusion



Discussion and Future Work



-  Didier Guzzni, Adam Cheyer, Charles Baur. *Active, a platform for building intelligent software*. IEEE Web Intelligence and Intelligent Agent Technology Workshops, 2006.
-  Alexander Wachtel, Jonas Klamroth, Walter F. Tichy. *A Natural Dialog System Based on Active Ontologies*. Annalen der Physik, 322(10):891–921, 1905.
-  Steven Levy. *An exclusive inside look at how artificial intelligence and machine learning work at Apple*.
<https://www.wired.com/2016/08/an-exclusive-look-at-how-ai>
-  Informationen zum Sicherheitsinhalt von iOS 7.1.2.
<https://support.apple.com/de-de/HT203014>
-  Bernadette Johnson. *How Siri Works*.
<http://electronics.howstuffworks.com/gadgets/high-tech-ga>

-  Stasys Bielinis. *How Siri on iPhone 4S works and why it's a big deal. Apple's AI tech details in 230 pages of patent app.*
[http://www.unwiredview.com/2011/10/12/how-siri-on-iphone-](http://www.unwiredview.com/2011/10/12/how-siri-on-iphone-4s-works-and-why-it-s-a-big-deal-apple-s-ai-tech-details-in-230-pages-of-patent-app/)
-  Johan Schalkwyk, Doug Beeferman, Francoise Beaufays, Bill Byrne, Ciprian Chelba, Mike Cohen, Maryam Garret, Brian Strope. *Google Search by Voice: A case study.*
-  Ciprian Chelba, Dan Bikel, Maria Shugrina, Patrick Nguyen, Shankar Kumar. *Large Scale Language Modeling in Automatic Speech Recognition.*
-  Voice Search
https://www.xovi.de/wiki/Voice_Search



Matthew Lynley. *Google unveils Google Assistant, a virtual assistant that's a big upgrade to Google Now.*

<https://techcrunch.com/2016/05/18/google-unveils-google-a>



Get notifications from Google Now in Chrome

<https://chrome.googleblog.com/2014/02/get-notifications-f>



Use Google Now on tap

<https://support.google.com/websearch/answer/6304517?hl=de>



Mariella Moon. *Google Voice Search can now handle multiple languages with ease.*

<https://www.engadget.com/2014/08/15/google-voice-search-m>



Eric Ravenscraft. *Use Some Google Now Voice Commands Without an Internet Connection.*

<http://lifehacker.com/use-some-google-now-voice-commands->



Meet your Google Assistant

<https://assistant.google.com/>



Joe Belfiore. *Windows Phone 8.1 Update brings Cortana to new markets + new features.*

<https://blogs.windows.com/windowsexperience/2014/07/30/wi>



Mary Jo Foley. *Microsoft gears up for Cortana on Android preview.*

<http://www.zdnet.com/article/microsoft-gears-up-for-cortana>



Brad Sams. *Windows 10: Cortana now syncs reminders.*

<https://www.neowin.net/news/windows-10-cortana-now-syncs->



Virginia Backaitis. *Why Microsoft's Cortana is 14 for 14 Calling World Cup Matches.*

<http://www.cmswire.com/cms/big-data/why-microsofts-cortana>



Tina Sieber. *Here's how to make the most of Cortana, the Windows 10 digital assistant.*

<https://www.digitaltrends.com/computing/get-know-cortana->



Brad Sams. *Cortana Can Now Sync Notifications From Your Android Phone To Your Windows 10 PC.*

<https://www.thurrott.com/windows/windows-10/67251/cortana>







Daniel Rubino. *Hands on with 'Hey Cortana' and the Lumia 930 Denim update*

<https://www.windowscentral.com/hands-on-hey-cortana-video>



Cortana's regions and languages

<https://support.microsoft.com/en-gb/instantanswers/557b5e>

-  R. Sarikaya, P.A. Crook, A. Martin, M. Jeong, J.P. Robichaud, A. Celikyilmaz, Y.B. Kim, A. Rochette, O.Z. Khan, X. Liu, D. Boies, T. Anastasakos, Y. Feizollahi, N.Ramesh, H. Suzuki, R. Holenstein, E. Krawczyk, V. Radostev. *An overview of end-to-end language understanding and dialog management for personal digital assistants.*
-  Chris Hoffman. *15 Things You Can Do With Cortana on Windows 10.*
<https://www.howtogeek.com/225458/15-things-you-can-do-wit>
-  Tom Warren. *1The story of Cortana, Microsoft's Siri killer.*
<https://www.theverge.com/2014/4/2/5570866/cortana-windows>
-  Five Things You Didn't Know About Cortana, Microsoft's Virtual Assistant
<https://www.recode.net/2014/9/22/11631126/five-things-you>



Melissa Riofrio. *Cortana's UI now expresses 18 different emotions. Siri remains detached and aloof*

<http://www.pcworld.com/article/2881902/cortanas-ui-now-ex>



Microsoft takes aim at Alexa with Cortana Skills Kit

<https://www.engadget.com/2017/05/10/stub-microsoft-takes->



Steve Dent. *Die Digitalen Assistenten im Vergleich – Teil 2 unserer Miniserie.*

<http://www.paksafe.de/blog/die-digitalen-assistenten-im-v>







Adrianne Jeffries *Google's featured snippets are worse than fake news.*

<https://theoutline.com/post/1192/google-s-featured-snippe>



Peter Stelzel-Morawietz. *Was taugen Siri, Cortana und Google Now?*

<https://www.pcwelt.de/ratgeber/Spracherkennung-Siri-Corta>

-  Eric Enge *The Great Knowledge Box Showdown: Google Now vs. Siri vs. Cortana.*
<https://www.stonetemple.com/great-knowledge-box-showdown/>
-  Jason Parker. *Google Search vs. Siri: Voice search speed test.*
<https://www.cnet.com/news/google-search-vs-siri-voice-sea>
-  Mehdi Assefi, Guangchi Liu, Mike P. Wittie, Clemente Izurieta.
Department of Computer Science, Montana State University. *An Experimental Evaluation of Apple Siri and Google Speech Recognition.*
-  Britta O'Boyle, Chris Hall. *Siri vs Cortana: Which is the funniest assistant?*
<http://www.pocket-lint.com/news/136238-siri-vs-cortana-wh>