

Translation Sketch

1 Expressions

E translates a Chalice expression into an equivalent SIL expression. Given an scoped identifier i , $\rho(i)$ denotes a globally unique identifier. E.g., $\rho(\text{someField}) = \text{SomeClass}::\text{someField}$

$$E \llbracket e_1 ? e_2 : e_3 \rrbracket_{\text{Ch}} = \llbracket \text{if } E(e_1) \text{ then } E(e_2) \text{ else } E(e_3) \rrbracket_{\text{SIL}} \quad (1)$$

$$E \llbracket e_1 == e_2 \rrbracket_{\text{Ch}} = \llbracket == (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (2)$$

$$E \llbracket e_1 != e_2 \rrbracket_{\text{Ch}} = \llbracket != (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (3)$$

$$E \llbracket e_1 < e_2 \rrbracket_{\text{Ch}} = \llbracket < (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (4)$$

$$E \llbracket e_1 <= e_2 \rrbracket_{\text{Ch}} = \llbracket <= (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (5)$$

$$E \llbracket e_1 > e_2 \rrbracket_{\text{Ch}} = \llbracket > (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (6)$$

$$E \llbracket e_1 >= e_2 \rrbracket_{\text{Ch}} = \llbracket >= (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (7)$$

$$E \llbracket e_1 \text{ in } e_2 \rrbracket_{\text{Ch}} = \llbracket \text{in } (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (8)$$

$$E \llbracket e_1 ! \text{in } e_2 \rrbracket_{\text{Ch}} = E \llbracket ! (e_1 \text{ in } e_2) \rrbracket_{\text{Ch}} \quad (9)$$

$$E \llbracket e_1 + e_2 \rrbracket_{\text{Ch}} = \llbracket + (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (10)$$

$$E \llbracket e_1 - e_2 \rrbracket_{\text{Ch}} = \llbracket - (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (11)$$

$$E \llbracket e_1 * e_2 \rrbracket_{\text{Ch}} = \llbracket * (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (12)$$

$$E \llbracket e_1 / e_2 \rrbracket_{\text{Ch}} = \llbracket / (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (13)$$

$$E \llbracket e_1 \% e_2 \rrbracket_{\text{Ch}} = \llbracket \% (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (14)$$

$$E \llbracket ! e \rrbracket_{\text{Ch}} = \llbracket ! (E(e)) \rrbracket_{\text{SIL}} \quad (15)$$

$$E \llbracket - e \rrbracket_{\text{Ch}} = \llbracket - (E(e)) \rrbracket_{\text{SIL}} \quad (16)$$

$$E \llbracket e_1 [e_2] \rrbracket_{\text{Ch}} = \llbracket \text{at } (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (17)$$

$$E \llbracket e_1 [e_2 \dots] \rrbracket_{\text{Ch}} = \llbracket \text{drop } (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (18)$$

$$E \llbracket e_1 [\dots e_2] \rrbracket_{\text{Ch}} = \llbracket \text{take } (E(e_1), E(e_2)) \rrbracket_{\text{SIL}} \quad (19)$$

$$E \llbracket e_1 . id \rrbracket_{\text{Ch}} = \llbracket E(e_1) . id \rrbracket_{\text{SIL}} \quad \text{Also assert that } e_1 \text{ is not null} \quad (20)$$

$$E \llbracket e_1 . id(e \dots) \rrbracket_{\text{Ch}} = \llbracket \rho(id)(E(e_1), E(e \dots)) \rrbracket_{\text{SIL}} \quad \text{Also assert that } e_1 \text{ is not null} \quad (21)$$

$$E \llbracket \text{true} \rrbracket_{\text{Ch}} = \llbracket \text{true} \rrbracket_{\text{SIL}} \quad (22)$$

$$E \llbracket \text{false} \rrbracket_{\text{Ch}} = \llbracket \text{false} \rrbracket_{\text{SIL}} \quad (23)$$

$$E \llbracket \text{null} \rrbracket_{\text{Ch}} = \llbracket \text{null} \rrbracket_{\text{SIL}} \quad (24)$$

$$E \llbracket \text{this} \rrbracket_{\text{Ch}} = \text{First method argument} \quad (25)$$

$$E \llbracket x \rrbracket_{\text{Ch}} = \llbracket x \rrbracket_{\text{SIL}} \quad \text{where } x \text{ is a numeric literal} \quad (26)$$

2 Statements

S translates Chalice statements into equivalent SIL statements/expressions. τ_1, τ_2, \dots are temporary variables unique to each rule instantiation. Similarly, η_1, η_2, \dots are labels unique to each rule instantiation.

$$S \llbracket \text{assert } e_1 \rrbracket_{\text{Ch}} = \llbracket \text{assert } E(e_1) \rrbracket_{\text{SIL}} \quad (27)$$

$$S \llbracket \text{assume } e_1 \rrbracket_{\text{Ch}} = \llbracket \text{assume } E(e_1) \rrbracket_{\text{SIL}} \quad (28)$$

$$S \llbracket \{s \dots\} \rrbracket_{\text{Ch}} = \llbracket S(s \dots) \rrbracket_{\text{SIL}} \quad (29)$$

Need to flatten nested stmt blocks, since SIL doesn't have local variable scoping.

$$S \llbracket \text{var } id := e_1 \rrbracket_{\text{Ch}} = \llbracket id := E(e_1) \rrbracket_{\text{SIL}} \quad \text{Keep const and ghost attributes} \quad (30)$$

$$S \llbracket \text{call } v \dots := r.m_1(e \dots) \rrbracket_{\text{Ch}} = \llbracket \text{call } v \dots := \rho(m_1)(E(r), E(e \dots)) \rrbracket_{\text{SIL}} \quad (31)$$

$$\begin{aligned} S \llbracket \text{if}(e_1) s_1 \text{ else } s_2 \rrbracket_{\text{Ch}} = & \llbracket \text{if } E(e_1) \text{ then goto } \eta_1 \text{ else } \eta_2 ; \\ & \eta_1 : S(s_1) ; \\ & \text{goto } \eta_3 \\ & \eta_2 : S(s_2) \\ & \eta_3 : \text{nop} \rrbracket_{\text{SIL}} \end{aligned} \quad (32)$$

lockchange for while loops ignored for now.

$$\begin{aligned} S \llbracket \text{while}(c) \text{ invariant } i \dots ; s \rrbracket_{\text{Ch}} = & \llbracket \eta_1 : \tau_1 := E(c) ; \\ & \text{exhale } E(i \dots) ; \\ & \text{if } \tau_1 \text{ then goto } \eta_2 \text{ else } \eta_3 ; \\ & \eta_2 : \text{inhale } E(i \dots) ; \\ & S(s) ; \\ & \text{goto } \eta_1 ; \\ & \eta_3 : \text{inhale } E(i \dots) \rrbracket_{\text{SIL}} \end{aligned} \quad (33)$$

2.1 Predicates

$\sigma(o.p)$ looks up the (permission) expression associated with a predicate p on object o .

$$\begin{aligned} S \llbracket \text{fold } e_1.p_1 \rrbracket_{\text{Ch}} = & \llbracket \text{exhale } \sigma(E(e_1).p_1) ; \\ & \text{inhale acc } (E(e_1).p_1) \rrbracket_{\text{SIL}} \end{aligned} \quad (34)$$

$$\begin{aligned} S \llbracket \text{unfold } e_1.p_1 \rrbracket_{\text{Ch}} = & \llbracket \text{exhale acc } (E(e_1).p_1) ; \\ & \text{inhale } \sigma(E(e_1).p_1) \rrbracket_{\text{SIL}} \end{aligned} \quad (35)$$

2.2 Monitors

$\iota(e)$ denotes the (monitor) invariant of an object e .

$$S \llbracket \text{share } e_1 \rrbracket_{\text{Ch}} = \llbracket \text{exhale } \iota(E(e_1)) \rrbracket_{\text{SIL}} \quad (36)$$

$$S \llbracket \text{unshare } e_1 \rrbracket_{\text{Ch}} = \llbracket \text{exhale } \iota(E(e_1)) \rrbracket_{\text{SIL}} \quad (37)$$