Thermally induced deformation and conjugate heat transfer in a channel with a thermoelastic wall: formulation, reduced-order analysis and finite-element verification

Abstract

Purpose – To formulate, analyse and partly verify a conjugate heat-transfer problem in which a thin polymer strip, heated on its outer face, forms one wall of a laminar slit channel and bows because of through-wall thermal expansion, widening the passage.

Design/methodology/approach – A steady formulation with one consistent set of sign and interface conventions is given. Closed-form thermoelastic results (free curvature, bowing, buckling, beam–column amplification) define a baseline and admissibility guards. A finite-element method and a fixed-point coupling algorithm are specified; the wall is verified with plane-strain eight-node computations, including a restrained, geometrically nonlinear case.

Findings – For water at $\mathrm{Re} = 50$ and a flux of $5\,\mathrm{kW/m^2}$ on a 3 mm PEEK-class strip, the strip bows away from the channel by $0.428\,H_0$ (reduced order) or $0.444\,H_0$ (finite element), the two differing by 3.8 %. Deformation and stress, not buckling, bound the admissible flux. Indicative estimates suggest a roughly halved pressure drop and a higher wall excess temperature, while the return effect of the flow on the bow is small.

Research limitations/implications – No coupled fluid–structure result is reported; the flow-side estimates are reduced-order, the material data are representative; contact, heater and casing are idealised.

Originality/value – Thermally driven wall deformation in forced convection, a verified wall model and a specified, not yet executed, coupled solver.

Keywords Conjugate heat transfer, Thermoelasticity, Fluid–structure interaction, Finite element method, Flexible channel wall, Thermal bending

Paper type Research paper

1. Introduction

Compact heat exchangers, micro-reactors and electronics coolers are increasingly built with polymer walls, which combine low thermal conductivity with a high coefficient of thermal expansion. For the same imposed heat flux, such a wall sustains a through-thickness temperature difference that is far larger than that of a metallic wall of equal thickness, and linear thermoelasticity associates this difference with a free thermal curvature of the wall (Boley and Weiner, 1960, Timoshenko and Goodier, 1970). When the wall is as thick as, or thicker than, the channel is high, the curvature is not a small perturbation of the passage: it modifies the flow cross-section, and heat-transfer predictions that assume a fixed geometry become geometry-dependent in a thermally self-consistent way.

Fluid–structure interaction (FSI) with heat transfer has mostly been studied for deformation driven by the fluid. Soti et al. (2015) computed laminar channel flow past a flexible thin plate and showed that the flow-induced motion passively raises the heat transfer; Alsabery et al. (2019) and Saleh et al. (2025) treated transient natural convection in cavities with flexible walls; Christov et al. (2018) derived the steady relation between flow rate and pressure drop in a deformable shallow channel, again with pressure as the only load. The structure is thermally passive in these studies. Thermally driven structural motion has been

computed for heated flexible cantilevers in a differentially heated cavity (Kumar et al., 2026), a confined natural-convection configuration rather than a forced-convection channel. Conjugate heat transfer in rigid thick-wall channels, finally, has been studied (Rahimimotlagh et al., 2024), but there the wall does not move.

The configuration studied here differs in the mechanism and in the flow class. A finite segment of one wall of a laminar forced-convection slit is a thin thermoelastic strip, heated on its outer face. Conduction across the strip sets up a temperature difference; the associated eigen-curvature, acting on a strip with pinned ends, bows it *away* from the passage; the widened passage changes the near-wall velocity and temperature gradients and therefore the interfacial heat flux, which is one of the boundary data of the conduction problem in the strip. Within the literature examined for this work we did not find a study that combines (i) the thermal eigen-curvature of the wall as the principal deformation mechanism, (ii) a closed steady loop through the conjugate interface, and (iii) a confined forced-convection channel. This positioning is deliberately bounded: the literature search was not exhaustive, and it is not a claim of priority.

The paper makes five contributions, and states clearly what it does not do.

1. A complete steady formulation with one consistent set of sign and interface conventions (Section 2).
2. A reduced-order thermoelastic analysis of the strip in closed form: free curvature, pinned bowing, thermal membrane force and buckling, the beam–column amplification of the bow, and the ratio of thermal to hydraulic deflection (Section 3).
3. A baseline operating point evaluated from first principles, with the heat-flux ceilings imposed by deformation, stress and buckling, and an *indicative* estimate of what the deformation does to the flow (Section 4).
4. A specified finite-element formulation and fixed-point algorithm for the coupled problem, with the treatment of the interface variables made explicit (Section 5.1).
5. A plane-strain Q8 verification of the wall idealisation: a mesh-sensitivity study of the free bow at a fixed sampling height, and an axially restrained, geometrically nonlinear solution of the baseline wall (Section 5.4).

No coupled fluid–structure computation is reported. The coupled solver is specified, not executed; every statement about the flow in Section 4 is a reduced-order estimate and is labelled as such. The paper is organised accordingly: formulation, analysis, baseline, finite element method and verification, and limitations.

2. Problem formulation

2.1 Configuration and assumptions

The configuration is two-dimensional (Figure 1). The fluid reference domain is $\Omega_f^0 = \{-L_e \le X \le L+L_o,\ 0 \le Y \le H_0\}$: a rigid entrance section, a section of length L facing the deformable wall, and a rigid exit section. The only deformable body is the solid strip $\Omega_s^0 = [0,L] \times [H_0, H_0+d]$, of thickness d and unit out-of-plane depth. Its lower face $Y = H_0$ is the conjugate interface Γ_{if}; its upper face $Y = H_0 + d$ is the outer face Γ_h, on which the thermal load is imposed. The strip ends $X = 0$ and $X = L$ are pinned. Rigid, adiabatic casing sections carry the strip at its ends, and the lower channel wall is rigid and adiabatic. The geometry and the operating point are given in Table I.

The following assumptions define the model; each is checked for the baseline in Section 4.

A1 *Plane strain.* The out-of-plane dimension is large compared with H_0 and d and the loading is uniform along it, so the fields are two-dimensional and $\varepsilon_{zz} = 0$ in the solid (Boley and Weiner, 1960, Timoshenko and Goodier, 1970).

A2 *Newtonian, constant-property water* at near-ambient temperature. Laminar, steady flow ($\mathrm{Re}_{D_h} = 50$);




Figure 1. Configuration (schematic, not to scale; the strip thickness and the bow are exaggerated). A thermoelastic strip of length L and thickness d forms part of the upper wall of a slit channel of undeformed height H_0. The outer face Γ_h receives a prescribed heat flux $q'' > 0$ into the strip. With pinned ends the strip bows away from the channel: the interface deflection w is positive away from the channel and the passage widens.

Table I. Geometry and operating point of the baseline (design values).

Quantity	Symbol	Value	Note
Undeformed channel height	H_0	0.50 mm	design input
Hydraulic diameter (slit)	$D_h = 2H_0$	1.0 mm	derived
Deformable (heated) length	L	30 mm	design
Entrance / exit length	L_e, L_o	10 mm, 20 mm	design
Strip thickness	d	3.0 mm	design
Mean inlet velocity	U	0.050 m/s	design
Imposed outer-face heat flux	q''	5.0 kW/m^2	design

viscous dissipation and buoyancy are negligible at the baseline (Section 4).

A3 *Homogeneous, isotropic, linearly thermoelastic solid* of constant E, ν, α, k_s. The values are representative of an unfilled PEEK-class polymer (Table III); they are not frozen against a specific datasheet, and every derived number scales with them.

A4 *Small strains and moderate rotations*, with the wall equation carried to the von Kármán beam–column level of Section 3.4.

A5 *Steady flow and energy, quasi-static solid.* The structural wave-crossing time of the strip, $d\sqrt{\rho_s/E} \approx 1.8\,\mu$s, is many orders of magnitude shorter than the transport times, so inertia is omitted.

A6 *Perfect thermal contact* at Γ_{if}: temperature and normal heat flux are continuous; no contact resistance.

A7 *Ideal pinned ends.* At $X = 0, L$ the vertical displacement vanishes, the mean axial displacement over the end edge vanishes, the applied moment is zero, and the heat flux is zero. This is a pin and not a clamp: a clamp forbids end rotation, and a clamped strip at uniform curvature does not bow at all (Section 3.1).

A8 *Idealised heater.* The heater is represented only by a uniform flux q'' entering the solid through Γ_h. Heater construction, heater–wall contact resistance and heat loss from the outer face are not modelled; all of q'' is assumed to enter the strip.

A9 *Rigid casing as a support, not as a contact.* The casing fixes the end conditions and the reference pressure of the cavity above the strip (equal to the outlet datum). The model contains no contact between the deformed strip and the casing and no casing clearance; the cavity above the strip is assumed to leave room for the computed deflection.

2.2 Governing equations

Fluid. On the deformed fluid domain Ω_f (Section 2.3), steady incompressible flow with constant properties obeys, in the standard form (Bird et al., 1960),

$$\nabla\cdot\boldsymbol{u} = 0, \tag{1}$$

$$\rho\,(\boldsymbol{u}\cdot\nabla)\boldsymbol{u} = -\nabla p + \mu\nabla^2\boldsymbol{u}, \tag{2}$$

$$\rho c_p\,(\boldsymbol{u}\cdot\nabla)T_f = k_f\nabla^2 T_f. \tag{3}$$

Solid. On the reference configuration Ω_s^0 steady conduction (Carslaw and Jaeger, 1947) and linear thermoelastic equilibrium without inertia hold,

$$\nabla\cdot(k_s\nabla T_s) = 0, \tag{4}$$

$$\nabla\cdot\boldsymbol{\sigma} = \mathbf{0}, \qquad \boldsymbol{\sigma} = 2\mu_L\boldsymbol{\varepsilon} + \lambda(\operatorname{tr}\boldsymbol{\varepsilon})\boldsymbol{I} - \beta\theta\boldsymbol{I}, \qquad \boldsymbol{\varepsilon} = \tfrac{1}{2}\left(\nabla\boldsymbol{d} + \nabla\boldsymbol{d}^{\mathsf{T}}\right), \tag{5}$$

with $\theta = T_s - T_{\mathrm{ref}}$, Lamé parameters λ, μ_L and thermoelastic pressure coefficient $\beta = E\alpha/(1-2\nu)$ (Boley and Weiner, 1960). In plane strain the out-of-plane stress is $\sigma_{zz} = \nu(\sigma_{xx}+\sigma_{yy}) - E\alpha\theta$ and is part of the stress state; all stresses reported below are total Cauchy stresses. The deformation-heating source of the transient thermoelastic energy equation vanishes identically in a steady state, so (4) is exact for the steady problem.

Reduced wall equation. For design estimates the strip is treated as an Euler–Bernoulli strip of flexural rigidity per unit depth $D_s = Ed^3/[12(1-\nu^2)]$, the wide-strip value appropriate to plane strain,

$$D_s\,w'''' = p(x), \qquad w(0) = w(L) = w''(0) = w''(L) = 0, \tag{6}$$

where p is the fluid pressure acting on the strip (positive pushes the strip away from the channel). This equation is used for estimates and benchmarks only; the two-dimensional system (4)–(5) is the model.

2.3 Deformed domain

The fluid problem is posed on the domain occupied by the fluid in the converged steady state. Given the solid displacement on Γ_{if}^0, a mesh displacement $\widehat{\boldsymbol{w}}$ is obtained on Ω_f^0 from a pseudo-elastic extension problem with $\widehat{\boldsymbol{w}} = \boldsymbol{d}$ on Γ_{if}^0 and $\widehat{\boldsymbol{w}} = \mathbf{0}$ on rigid boundaries, and $\Omega_f = \{X + \widehat{\boldsymbol{w}}(X)\}$. No time derivative appears, so no mesh velocity or geometric-conservation-law constraint arises in the steady problem (Lesoinne and Farhat, 1996).

2.4 Sign conventions, interface and boundary conditions

A single unit normal $\boldsymbol{n}$, pointing from the fluid into the solid, is used on Γ_{if}. Pressure is positive in compression and stress is positive in tension. The coordinate y points from the fluid into the solid. The deflection w is measured *away from the channel*, $w = +d_2$ with d_2 the displacement in $+y$; the thermal curvature $\kappa_{\mathrm{th}} > 0$ is the curvature that bows the strip away from the channel, and within small slopes $\kappa = -w''$. The heat flux vector is $\boldsymbol{q} = -k\nabla T$, and $q'' > 0$ denotes heat *supplied* to the solid.

On the deformed interface the subsystems exchange kinematics, traction and heat:

$$\boldsymbol{u} = \mathbf{0} \qquad \text{(no slip, steady form of } \boldsymbol{u} = \partial_t\boldsymbol{d}\text{)}, \tag{7}$$

$$\boldsymbol{\sigma}\boldsymbol{n} = (-p\boldsymbol{I} + 2\mu\boldsymbol{D}(\boldsymbol{u}))\,\boldsymbol{n} \qquad \text{(traction continuity)}, \tag{8}$$

$$T_f = T_s \qquad \text{(temperature continuity)}, \tag{9}$$

$$-k_f\nabla T_f\cdot\boldsymbol{n} = -k_s\nabla T_s\cdot\boldsymbol{n} \qquad \text{(normal heat-flux continuity)}, \tag{10}$$

with $\boldsymbol{D}(\boldsymbol{u}) = \frac{1}{2}(\nabla\boldsymbol{u} + \nabla\boldsymbol{u}^{\mathsf{T}})$. The exterior conditions are listed in Table II. Condition B5 makes the sign of the thermal load explicit: with the outward normal $\boldsymbol{n}_{\mathrm{out}} = +\boldsymbol{e}_y$ of the solid on Γ_h, the flux $\boldsymbol{q}\cdot\boldsymbol{n}_{\mathrm{out}} = -k_s\partial_y T_s$

Table II. Boundary conditions. $\boldsymbol{n}_{\text{out}}$ is the outward normal of the solid.

ID	Boundary	Condition
B1	inlet $x = -L_e$	$\boldsymbol{u} = 6U\frac{y}{H_0}\left(1-\frac{y}{H_0}\right)\boldsymbol{e}_x$, $T_f = T_{\text{in}}$
B2	outlet $x = L + L_o$	traction-free (do-nothing) outflow, $\partial_n T_f = 0$
B3	lower wall $y = 0$	$\boldsymbol{u} = \boldsymbol{0}$, $\partial_n T_f = 0$ (rigid, adiabatic)
B4	rigid casing sections	$\boldsymbol{u} = \boldsymbol{0}$, $\partial_n T_f = 0$
B5	outer face Γ_h^0	$+k_s \nabla T_s \cdot \boldsymbol{n}_{\text{out}} = q''$ with $q'' > 0$ heat supplied to the solid
B6	strip ends $X = 0, L$	$d_2 = 0$, $\langle d_1 \rangle = 0$ (edge mean), zero applied moment, $\partial_n T_s = 0$
B7	remaining solid faces	zero traction, zero heat flux
B8	interface Γ_{if}	(7)–(10)

Table III. Material properties used in all calculations.

Property	Symbol	Value	Unit
Water density, viscosity	ρ, μ	1.0×10^3, 1.0×10^{-3}	kg/m^3, Pa s
Water specific heat, conductivity	c_p, k_f	4.18×10^3, 0.60	J/(kg K), W/(m K)
Solid Young's modulus, Poisson ratio	E, ν	3.6×10^9, 0.40	Pa, –
Solid expansion coefficient	α	5.0×10^{-5}	1/K
Solid conductivity	k_s	0.25	W/(m K)
Solid yield stress (guard only)	σ_y	9×10^7	Pa

equals $-q''$ (inward), so $k_s\,\partial_y T_s = +q'' > 0$: the temperature rises towards the outer face, which is therefore the hot face.

2.5 Material data

Table III lists the properties. Water values are standard near-ambient data. The solid values are representative of unfilled PEEK and are datasheet-representative, not grade-specific.

3. Reduced-order thermoelastic analysis of the strip

This section derives the closed-form relations used to size the deformation before any coupled computation. All of them follow from the model of Section 2 under the stated assumptions; the numerical values at the baseline are collected in Section 4.

3.1 Free thermal curvature and the sign chain

Let η be the coordinate across the strip measured from the mid-plane (positive towards the outer face), and let the temperature be linear, $\theta(\eta) = \bar{\theta} + \Gamma\eta$, with $\Gamma = \Delta T_t/d > 0$ by condition B5. For a thin strip with traction-free faces $\sigma_{yy} \simeq 0$, and plane strain gives $\sigma_{xx} = E'[\varepsilon_{xx} - (1+\nu)\alpha\theta]$ with $E' = E/(1-\nu^2)$. With $\varepsilon_{xx} = \varepsilon_0 + \kappa\eta$, a vanishing axial force resultant gives $\varepsilon_0 = (1+\nu)\alpha\bar{\theta}$, and a vanishing moment resultant gives the free thermal eigen-curvature

$$\kappa_{\text{th}} = (1+\nu)\,\alpha\,\frac{\Delta T_t}{d} = (1+\nu)\,\alpha\,\frac{q''}{k_s}, \qquad \Delta T_t = \frac{q''d}{k_s}, \tag{11}$$

where the second form uses one-dimensional steady conduction across the strip (Carslaw and Jaeger, 1947) and is the plane-strain form of the classical result (Boley and Weiner, 1960). Two consequences follow. First, κ_{th} does not depend on d: the through-thickness gradient adjusts to cancel the thickness. Second, a strip clamped at both ends carries the constant restoring moment $D_s\kappa_{\text{th}}$ and does not bow ($w \equiv 0$); the bowing mechanism exists only for pinned ends or for an axially non-uniform $\kappa_{\text{th}}(x)$, which

fixes the support choice A7.

The sign chain is, in order: (i) $q'' > 0$ supplies heat to the outer face (B5); (ii) the temperature therefore rises towards the outer face ($\Gamma > 0$), which is the hot face; (iii) the hot fibres elongate more, so the strip curves with the outer face convex, $\kappa_{\mathrm{th}} > 0$; (iv) with pinned ends this is an arch whose mid-span moves *away* from the channel, $w > 0$; (v) the passage height $H = H_0 + w$ increases. The same chain read backwards shows that a bow *into* the passage would require heating the fluid-facing face, which is a different model (Section 6).

3.2 Pinned bowing at negligible axial force

With $w'' = -\kappa_{\mathrm{th}}$ and $w(0) = w(L) = 0$,

$$w(x) = \frac{\kappa_{\mathrm{th}}}{2} x(L-x), \qquad w_{\max}^{\mathrm{lin}} = \frac{\kappa_{\mathrm{th}} L^2}{8}. \tag{12}$$

This is exact within thin-strip theory when the axial force is negligible, which is the state of a strip free to expand axially.

3.3 Thermal membrane force and buckling

With the axial displacement blocked at both ends the mean axial strain vanishes, and integration across the thickness gives the compressive membrane force per unit depth

$$N_\theta = -\frac{E\, d\, \alpha \bar{\theta}}{1-\nu}, \qquad N_c = |N_\theta|. \tag{13}$$

The pinned–pinned Euler load of the wide strip is $N_{\mathrm{cr}} = \pi^2 D_s / L^2$ (Timoshenko and Gere, 1961). The wide-strip rigidity is the consistent one because plane strain suppresses the anticlastic curvature mode. Setting $N_c = N_{\mathrm{cr}}$ gives the critical mean temperature rise

$$\bar{T}_{\mathrm{cr}} = \frac{\pi^2 d^2}{12\,\alpha(1+\nu)L^2}, \qquad M_b = \frac{\bar{T}_{\mathrm{cr}}}{\bar{\theta}}, \tag{14}$$

where the buckling margin M_b is used as a guard. The mean wall rise is estimated as $\bar{\theta} = \Delta T_t/2 + q''/h + \Delta T_b/2$: half the through-wall drop, the interface excess over the local bulk temperature with the rigid-slit coefficient $h = \mathrm{Nu}_{H1} k_f / D_h$ for one heated wall (Shah and London, 1978), and half the bulk rise $\Delta T_b = q'' L/(\rho U H_0 c_p)$.

3.4 Beam–column bowing at finite membrane force

A pinned strip carrying the compressive force N_c couples its deflection to that force at leading order. Retaining the geometric stiffness of the membrane force and freezing the force at its blocked-state value, the transverse equilibrium of the strip, with total moment $M = D_s(w'' + \kappa_{\mathrm{th}})$ vanishing at the pins, is

$$D_s\, w'''' + N_c\, w'' = 0, \qquad w(0) = w(L) = 0, \quad w''(0) = w''(L) = -\kappa_{\mathrm{th}}. \tag{15}$$

With $\mu^2 = N_c/D_s$ the solution is

$$w(x) = \frac{\kappa_{\mathrm{th}}}{\mu^2}\left[\frac{1-\cos\mu L}{\sin\mu L}\sin\mu x + \cos\mu x - 1\right], \qquad w_{\max} = \frac{\kappa_{\mathrm{th}}}{\mu^2}\left[\sec\frac{\mu L}{2} - 1\right], \tag{16}$$

which reduces to (12) as $\mu L \to 0$ and diverges at $\mu L = \pi$, the Euler threshold (14): the bowing law and the buckling limit are two limits of one relation. The force is not in fact frozen. With both ends blocked, the mean axial strain contains the arc-stretching term $\frac{1}{2}\langle w'^2\rangle$, so the signed force acquires the correction

$$N_\theta(w) = N_\theta + \frac{Ed}{2(1-\nu^2)}\langle w'^2\rangle, \qquad N_c^{\mathrm{sc}} = |N_\theta| - \frac{Ed}{2(1-\nu^2)}\langle w'^2\rangle, \tag{17}$$

which relaxes the compression. Because the family (16) holds for every fixed force, (17) is a scalar fixed-point problem for N_c^{sc}.

Two deflections are therefore defined, and they answer different questions. The *frozen-force* value $w_{\max}$ of (16) with $N_c = |N_\theta|$ is the exact solution of the stated equation (15); because it neglects the relaxation it overestimates the deflection and is a conservative upper bound. The *self-consistent* value solves (16) with N_c^{sc} and is the von Kármán equilibrium of the reduced strip. It is also what the coupled algorithm of Section 5.2 converges to, since it re-evaluates the membrane force at every iteration. The self-consistent value is therefore quoted as the model's best estimate, and the frozen-force value as the upper bound; both are reported. The two differ by 2.3 % at the baseline, 3.0 % and 3.9 % at the heat fluxes of guards G1 and G2 (Section 3.6), and 17 % at $N_c/N_{\mathrm{cr}} = 0.5$, where the frozen-force form should no longer be used.

3.5 Hydraulic loading and the thermal-to-hydraulic ratio

Integrating plane Poiseuille flow (Bird et al., 1960, Shah and London, 1978) gives the slit pressure drop

$$\Delta p = \frac{12\mu U L}{H_0^2}. \tag{18}$$

With the outlet datum $p = 0$ and the casing cavity at the same reference pressure (A9), the gauge pressure on the strip falls linearly from $p(0) = p(L) + \Delta p$ at its upstream end to $p(L) = 12\mu U L_o/H_0^2$ at its downstream end, with mean $\bar{p} = \frac{1}{2}[p(0) + p(L)]$. For pinned ends, a uniform load $\bar{p}$ acting in the same sense as the thermal bow deflects the strip by $w_p = 5\bar{p}L^4/(384 D_s)$ at the linear level (Timoshenko and Goodier, 1970); the mild variation of the load is neglected in this estimate. The ratio of the thermal to the hydraulic deflection of the *same* strip is

$$\Gamma_p = \frac{w_{\mathrm{th}}}{w_p}, \qquad \Gamma_p^{\mathrm{lin}} = \frac{w_{\max}^{\mathrm{lin}}}{w_p} = \frac{48\,\kappa_{\mathrm{th}} D_s}{5\,\bar{p} L^2}, \tag{19}$$

where Γ_p^{lin} uses both deflections at zero membrane force. A second like-for-like form, $\Gamma_p^{N_c}$, computes both deflections with the same compressive force N_c: the thermal deflection from (16) and the pressure deflection from the beam–column equation $D_s w'''' + N_c w'' = \bar{p}$. Both forms compare two responses of one structure in one state and are therefore directly comparable. A ratio that places the thermal deflection *with* the beam–column amplification over a pressure deflection *without* it mixes two states of the structure and is not used. Because κ_{th} is independent of d while $D_s \propto d^3$ and $\bar{p} \propto U H_0^{-2}$, Γ_p grows with wall thickness and falls with velocity and with decreasing channel height.

3.6 Admissibility guards

Five guards bound the regime in which the reduced-order model and the weak form of Section 5.1 are used. (G1) $w_{\max}/H_0 \le 0.5$, so that the deformed fluid mesh keeps positive Jacobians. (G2) $\sigma_{\max} \le 0.2\,\sigma_y$, with $\sigma_{\max}$ the sum of the bending stress $6|M_{\mathrm{mid}}|/d^2$ at mid-span and the membrane stress $E\alpha\bar{\theta}/(1-\nu)$. (G3) $M_b \ge 2$. (G4) $\Gamma_p \ge 5$, the threshold above which the thermal bow is the dominant deformation. (G5) $\mathrm{Re}_{D_h} \le 100$, $\mathrm{Br} < 10^{-2}$ and a Richardson number small enough for the neglect of buoyancy, with $\mathrm{Ri} = g\beta_f \Delta T^* H_0/U^2$ and $\Delta T^* = q'' H_0/k_f$.

4. Baseline results of the reduced-order model

All values in this section are computed by the program `code/hff_model.py` from the inputs of Tables I and III and the relations of Section 3; Table IV collects them. Quantities that depend on the solid properties scale with the datasheet values, which are not frozen (A3).

4.1 Deformation of the passage

The strip bows away from the channel by $w_{\max} = 2.14 \times 10^{-4}$ m, which is $0.428\,H_0$, in the self-consistent state; the frozen-force upper bound is $0.438\,H_0$ (Figure 2a). The passage height at mid-span is $H =$

Table IV. Reduced-order baseline at the design point of Table I. The deflection and passage height are given for the self-consistent state (sc) and, as an upper bound, for the frozen-force state (ff).

Quantity	Expression	Value
Reynolds, Péclet numbers	$2\rho U H_0/\mu$; Re Pr	50; 348 (Pr = 6.97)
Rigid-slit pressure drop	$12\mu UL/H_0^2$ (18)	72 Pa; wall shear 0.6 Pa
Through-wall temperature drop	$\Delta T_t = q''d/k_s$	60 K
Bulk rise; interface excess	ΔT_b; q''/h with $h = 3231\,\mathrm{W/(m^2\,K)}$	1.44 K; 1.55 K
Mean wall temperature rise	$\bar{\theta} = \Delta T_t/2 + q''/h + \Delta T_b/2$	32.3 K
Free thermal curvature	$(1+\nu)\alpha q''/k_s$ (11)	1.4/m
Linear bow	$\kappa_{\mathrm{th}} L^2/8$ (12)	1.57×10^{-4} m $= 0.315\,H_0$
Membrane force; Euler load	N_c (13); $N_{\mathrm{cr}} = \pi^2 D_s/L^2$	2.90×10^4; 1.06×10^5 N m^{-1}; $N_c/N_{\mathrm{cr}} = 0.275$
Critical rise; buckling margin	$\bar{T}_{\mathrm{cr}}$; M_b (14)	117 K; 3.64
Beam–column parameter	$\mu L = L\sqrt{N_c/D_s}$	1.65
Bow, frozen force (ff)	(16)	2.19×10^{-4} m $= 0.438\,H_0$
Bow, self-consistent (sc)	(16), (17)	2.14×10^{-4} m $= 0.428\,H_0$
Mid-span passage height $H_0 + w_{\max}$	derived	$1.428\,H_0$ (sc); $1.4377\,H_0$ = 0.719 mm (ff)
Slope, strains (ff)	$\max\lvert w'\rvert$; $\frac{1}{2}\langle w'^2\rangle$; bending fibre strain	0.028; 1.39×10^{-4}; 9.89×10^{-4}
Stresses (ff)	bending; membrane; sum	4.2 MPa; 9.7 MPa; 13.9 MPa = $0.15\,\sigma_y$
Gauge pressure on the strip	$p(0)$; $p(L)$; $\bar{p}$	120 Pa; 48 Pa; 84 Pa
Hydraulic deflection	$5\bar{p}L^4/(384 D_s)$	9.19×10^{-8} m (zero force); 1.27×10^{-7} m (with N_c)
Thermal-to-hydraulic ratio	Γ_p^{lin}; $\Gamma_p^{N_c}$ (19)	1714; 1726
Buoyancy, dissipation	Ri; Br	1.7×10^{-3}; 1.0×10^{-6}

$H_0 + w_{\max} = 1.428\,H_0$ (sc) or $1.4377\,H_0$ (ff), that is 0.719 mm against the undeformed 0.50 mm. This is a *derived beam-model passage height*, not a prescribed clearance: it is the sum of the design height H_0 and the computed deflection, and nothing in the model constrains it from above (assumption A9). A two-dimensional finite-element solution of the restrained wall (Section 5.4.2) gives $0.444\,H_0$, 3.8 % above the self-consistent value. The beam–column amplification over the linear bow is 1.39, consistent at leading order with the Euler factor $1/(1-N_c/N_{\mathrm{cr}}) = 1.38$. The strains and the slope are small ($\max\lvert w'\rvert = 0.028$, bending fibre strain 9.89×10^{-4}), which supports the small-strain, moderate-rotation level of A4.

4.2 Guards and heat-flux ceilings

The baseline lies inside all five guards of Section 3.6: $w_{\max}/H_0 = 0.438$ (ff) against 0.5; $\sigma_{\max} = 0.15\,\sigma_y$ against 0.2; $M_b = 3.64$ against 2; $\Gamma_p = 1714$ against 5; $\mathrm{Re}_{D_h} = 50$, $\mathrm{Br} = 1.0\times10^{-6}$ and $\mathrm{Ri} = 1.7\times10^{-3}$. All but the last are exceeded in the order deformation, stress, buckling as q'' increases, because κ_{th} and $\bar{\theta}$ both scale with q''. In the frozen-force state G1 is reached at $q'' = 5.5\,\mathrm{kW/m^2}$ ($N_c/N_{\mathrm{cr}} = 0.30$), G2 at 6.0 kW/m^2 ($w_{\max}/H_0 = 0.56$), and the buckling margin $M_b = 2$ at 9.1 kW/m^2, where $w_{\max}/H_0 = 1.16$ would long since be unacceptable. The binding constraints are therefore deformation and stress, with buckling the outer ceiling, and the baseline flux is already 9 % below the first of them.

Buoyancy and viscous dissipation do not enter the baseline: $\mathrm{Ri} = 1.7\times10^{-3}$ and $\mathrm{Br} = 1.0\times10^{-6}$. Stratification can destabilise horizontal flows when it is strong, as studied for a fluid with large property variations by Draskic et al. (2025); that regime is not approached here.




Figure 2. Bowing of the strip (positive away from the channel). (a) Deflection profile at the baseline: linear estimate (12), frozen-force beam–column (16) and self-consistent beam–column (16)–(17). (b) Mid-span deflection against the imposed flux; vertical dotted lines mark the fluxes at which guards G1 ($|w|/H_0 = 0.5$) and G2 (stress cap) are reached. The marker is the baseline.

The stress is dominated by the compressive membrane component, 9.7 MPa, a by-product of the axial constraint that also produces the buckling limit; the bending component is 4.2 MPa.

4.3 Role of the wall material

Because $\kappa_{th} = (1+\nu)\alpha q''/k_s$, the choice of wall material sets the size of the effect. For typical austenitic stainless steel ($k_s \approx 16\,\mathrm{W/(m\,K)}$, $\alpha \approx 1.7\times10^{-5}/\mathrm{K}$, $\nu = 0.30$) at the same flux and geometry, $\kappa_{th} = 6.9\times10^{-3}$ 1/m and $w^{lin}_{max}/H_0 = 1.6\times10^{-3}$: about 203 times smaller than for the polymer, a physically real deformation but irrelevant to the convective field. The combination of low conductivity and high expansion coefficient of the polymer class, not any fluid-side property, selects the design space.

4.4 Indicative consequences for the flow

The deformation is large enough to change the passage substantially, so two flow-side consequences are estimated. Both are reduced-order and indicative only; the coupled computation is required to quantify them. *Hydraulic.* With the flow rate per unit depth UH_0 fixed and the local height $H(x) = H_0 + w(x)$, the lubrication estimate is $\Delta p = 12\mu U H_0 \int_0^L \mathrm{d}x/H^3$, which is 36 Pa, a factor 0.50 of the rigid-slit value (18), a drop of about 50 per cent (Figure 3b). The lubrication parameter $\mathrm{Re}_{H_0} H_0/L = 0.42$ is not small, so the value indicates that the hydraulic effect is of order one rather than giving its magnitude. *Thermal.* With a quasi-developed local coefficient $h(x) = \mathrm{Nu}_{H1} k_f/[2H(x)]$ the mean interface excess q''/h rises from 1.55 K to 1.99 K (a factor 1.29). The thermal entry length is about 17.4 mm, so $L/L_T = 1.7$ and the quasi-developed assumption is not justified; this too is an order-of-magnitude indicator.

Feedback onto the deflection. The larger interface excess raises $\bar{\theta}$ by about 0.45 K out of 32.3 K, which increases w_{max} by only 0.5 %; the hydraulic load changes the deflection by 0.06 % of the thermal bow ($1/\Gamma_p$). At the baseline the effect of the wall on the flow is therefore large, whereas the effect of the flow back on the wall is small, because κ_{th} depends on q'' and on the wall properties only (equation (11)) and the thermal loop enters through $\bar{\theta}$ alone. Whether the closed loop matters elsewhere in the parameter space is a question for the coupled computation, not for this reduced-order model.




Figure 3. Reduced-order consequences of the deformation (indicative). (a) Passage height $H(x)/H_0$ for several imposed fluxes (frozen-force bow). (b) Lubrication estimate of the pressure drop and quasi-developed estimate of the mean interface excess q''/h, both relative to the undeformed passage.

5. Finite-element formulation and verification

This section specifies the finite-element method for the coupled problem of Section 2, states what has and has not been verified, and reports the verification of the wall idealisation. **The coupled fluid–structure–thermal solver is specified here but no result of it is reported.** The only finite-element computations in this paper are those of the wall in Section 5.4.

5.1 Discretisation

Meshes. The fluid and the solid are meshed separately but conformingly: the two meshes share the nodes of Γ_{if}, so that interface data need no interpolation. The fluid mesh follows the deformed interface through the extension problem of Section 2.3.

Fluid. Velocity and pressure use the Taylor–Hood pair, continuous quadratic velocity and continuous linear pressure (P2–P1), which satisfies the discrete inf–sup condition (Hood and Taylor, 1974, Brezzi and Fortin, 1991). On Ω_f the weak form seeks $(\boldsymbol{u}, p)$ with $\boldsymbol{u}$ satisfying B1 and B3–B4 and the interface condition $\boldsymbol{u} = \boldsymbol{0}$ such that, for all admissible $(\boldsymbol{v}, q)$,

$$\int_{\Omega_f} [\rho(\boldsymbol{u}\cdot\nabla\boldsymbol{u})\cdot\boldsymbol{v} + 2\mu\,\boldsymbol{D}(\boldsymbol{u}):\boldsymbol{D}(\boldsymbol{v}) - p\,\nabla\cdot\boldsymbol{v} + q\,\nabla\cdot\boldsymbol{u}]\,\mathrm{d}\Omega = 0, \tag{20}$$

where the do-nothing outflow B2 is the natural condition. The convective term is linearised by Newton iteration.

Energy. Temperature is one continuous quadratic field T on $\Omega_f \cup \Omega_s$ with the conductivity $k = k_f$ or k_s and the velocity $\boldsymbol{u}$ in the fluid and zero in the solid. Because the meshes are conforming, temperature continuity (9) is enforced strongly and the flux continuity (10) is the natural interface condition: there is a *single* interface temperature unknown and no thermal interface iteration. With B5 the weak form is

$$\int_{\Omega_f\cup\Omega_s} [\rho c_p(\boldsymbol{u}\cdot\nabla T)\,\phi + k\nabla T\cdot\nabla\phi]\,\mathrm{d}\Omega + \sum_K \int_K \tau_K\,\rho c_p\,\boldsymbol{u}\cdot\nabla\phi\,\mathscr{R}_K(T)\,\mathrm{d}\Omega = \int_{\Gamma_h} q''\,\phi\,\mathrm{d}\Gamma, \tag{21}$$

with the element residual $\mathscr{R}_K(T) = \rho c_p\,\boldsymbol{u}\cdot\nabla T - k_f\nabla^2 T$. The streamline-upwind/Petrov–Galerkin (SUPG) term (Brooks and Hughes, 1982) is required: the Péclet number is $\mathrm{Pe} = 348$, so that a Galerkin discretisa-

tion without stabilisation is expected to oscillate on any mesh whose streamwise spacing is not of micrometre order. The stabilisation parameter is $\tau_K = \frac{h_K}{2|\boldsymbol{u}|_K}\,(\coth \mathrm{Pe}_K - 1/\mathrm{Pe}_K)$ with $\mathrm{Pe}_K = \rho c_p |\boldsymbol{u}|_K h_K/(2k_f)$ and $\tau_K = 0$ in the solid.

Solid. The displacement is continuous quadratic. To retain the beam–column amplification of Section 3.4 the solid is solved in a total-Lagrangian description with the Green–Lagrange strain $\boldsymbol{E} = \frac{1}{2}(\boldsymbol{F}^{\mathsf{T}}\boldsymbol{F} - \boldsymbol{I})$, the deformation gradient $\boldsymbol{F} = \boldsymbol{I} + \nabla \boldsymbol{d}$, and the St Venant–Kirchhoff law with the in-plane thermal eigenstrain of A1,

$$\boldsymbol{S} = \mathbb{C} : [\boldsymbol{E} - (1+\nu)\alpha\,\theta\,\boldsymbol{I}], \qquad \int_{\Omega_s^0} \boldsymbol{S} : \delta\boldsymbol{E}\,\mathrm{d}\Omega = \int_{\Gamma_{\mathrm{if}}^0} \boldsymbol{t}\cdot\delta\boldsymbol{d}\,\mathrm{d}\Gamma, \tag{22}$$

where, for small strain and rotation, (22) reduces to the linear system (5), and $\theta = T_s - T_{\mathrm{in}}$ is the temperature rise and $\boldsymbol{t}$ is the fluid traction pulled back to the reference interface. The tangent of (22) contains a material part and a geometric part that carries the thermal membrane stress; the latter is what produces the amplification $1/(1 - N_c/N_{\mathrm{cr}})$. A linear solid omits it (Section 5.4.2).

5.2 Coupled fixed-point algorithm

The mechanical coupling is a Dirichlet–Neumann partition: the fluid receives the interface displacement through the mesh extension, and the solid receives the interface traction. With the thermal problem solved as one field, the outer iteration $k = 0, 1, \ldots$ on the deformed geometry Ω^k (Ω^0 undeformed) is:

1. solve the Navier–Stokes problem (20) on Ω_f^k for $(\boldsymbol{u}^k, p^k)$ and form the interface traction $\boldsymbol{t}^k$;
2. solve the energy problem (21) on $\Omega_f^k \cup \Omega_s^k$ for T^k, hence θ^k in the solid;
3. solve (22) with θ^k and $\boldsymbol{t}^k$ for $\boldsymbol{d}^{k+1}$;
4. relax, $\boldsymbol{d}^{k+1} \leftarrow \omega \boldsymbol{d}^{k+1} + (1-\omega)\boldsymbol{d}^k$ with $0 < \omega \le 1$ (Aitken updating is optional), and update the fluid mesh through the extension problem of Section 2.3;
5. stop when $\|\boldsymbol{d}^{k+1} - \boldsymbol{d}^k\| / \|\boldsymbol{d}^{k+1}\|$ and the relative interface heat-flux imbalance are below tolerances.

The guards of Section 3.6 are monitored during the iteration; in particular the mesh-quality guard G1 keeps the extension problem well posed. A partitioned thermal alternative, in which the interface temperature is imposed as a Dirichlet condition on the solid and the flux as a Neumann condition on the fluid, is possible on the same meshes but is not needed here. *No proof of convergence of the fixed point is offered.* The reduced-order estimates of Section 4.4 indicate a weak return coupling at the baseline, which suggests contraction, but this has not been tested.

5.3 Verification hierarchy

Table V lists the verification levels needed before coupled results could be trusted and shows which have been executed. Only the first four concern the wall and the reduced-order model; all levels involving the fluid are planned.

5.4 Verification of the wall idealisation

Two plane-strain computations with eight-node serendipity (Q8) elements, 3×3 Gauss quadrature and a sparse direct solver, are reported. Both are own implementations (`code/q8_strip.py` and `code/q8_nonlinear.py`). The shape functions are checked for partition of unity and for their derivatives against central differences, and the patch test (the exact stress-free thermal-bending field must satisfy the discrete equations) is passed on every mesh with a maximum relative residual of 5×10^{-13}.

5.4.1 Free bow and end supports

With a linear through-thickness temperature of zero mean the beam theory gives the bow $w = \kappa_{\mathrm{th}} L^2/8$ at mid-span (Section 3.1). The finite-element value is sampled at the *fixed* physical point $(L/2, y = d/2)$

Table V. Verification hierarchy. "Done" marks computations reported in this paper.

Level	Test	Reference	Status
V1	Shape functions, patch test (Q8)	exact polynomial field	Done
V2	Closed forms of Section 3 against an independent boundary-value solution	analytic/numerical BVP	Done
V3	Free bow of the wall, end supports, mesh study	$\kappa_{\mathrm{th}} L^2/8$	Done
V4	Restrained nonlinear wall, amplification and membrane force	beam–column	Done
V5	Rigid slit, pressure drop and velocity profile	$12\mu UL/H_0^2$ (Poiseuille)	Planned
V6	Rigid slit, one wall heated, developed Nusselt number	Shah and London (1978)	Planned
V7	Conjugate transfer with a rigid thick wall	Rahimimotlagh et al. (2024)	Planned
V8	Pressure-loaded compliant channel, flow rate–pressure drop	Christov et al. (2018)	Planned
V9	Mesh convergence of the coupled outputs (w, Δp, Nu)	Celik et al. (2008)	Planned
V10	Iteration history and interface energy balance of the fixed point	internal consistency	Planned

Table VI. Free-bow study: mid-span, mid-surface deflection normalised by $\kappa_{\mathrm{th}} L^2/8$. The order p, the extrapolated value and the grid-convergence index (GCI, safety factor 1.25) of the clamp are from the last three axial refinements, $N_x = 48, 96, 192$ (Celik et al., 2008).

N_y	elements ($N_x = 192$)	point pin ($N_x = 192$)	full-edge pin ($N_x = 192$)	clamp ($N_x = 24$)	clamp ($N_x = 192$)	p	clamp, extrap.	GCI (%)
2	384	1.00000	0.99793	−0.0288	−0.0195	1.7	−0.0192	2.0
4	768	1.00000	0.99800	−0.0253	−0.0180	1.3	−0.0175	3.8
8	1536	1.00000	0.99800	−0.0238	−0.0174	1.1	−0.0168	4.2

on every mesh, because a sampling height that changes with the through-thickness refinement is not a property of the mesh. Three end idealisations are compared: an ideal point pin ($u_y = 0$ at the single mid-surface node of each end edge), the pin of the paper realised as $u_y = 0$ on the whole end edge, and a clamp ($u_x = u_y = 0$ on the whole edge). Meshes range from 6×2 to 192×8 elements ($N_x \times N_y$, at most 1536 elements); the results are normalised by $\kappa_{\mathrm{th}} L^2/8$ and are in Table VI and Figure 4.

The ideal point pin returns 1.00000 on every mesh, as it must: the exact field lies in the element space, so this result tests the implementation and not the convergence. The pin of the paper, $u_y = 0$ on the whole edge, gives 0.99800 at 192×4 and 0.99800 at 192×8, a defect of 0.20 %. This is mesh-independent: the value changes by 3×10^{-8} between $N_x = 96$ and 192 at $N_y = 8$ and by 4×10^{-6} between $N_y = 4$ and 8 at $N_x = 192$. The defect is therefore a property of the end condition and not a discretisation error. The clamp bows slightly *towards* the channel. Beam theory gives zero, since a clamp forbids end rotation and a uniform-curvature strip then does not bow; the finite-element value converges slowly to a small negative number (Table VI, extrapolated -0.0168 at $N_y = 8$). The observed order is below two ($p = 1.1$ at $N_y = 8$), so the asymptotic range has not been established and the GCI of 4.2 % is indicative only. The relevant conclusions are that the pin idealisation is reproduced to 0.20 % and that the clamp, which is not used in this paper, suppresses the bow to within -0.0174 of the pinned value, in agreement with beam theory to that level.




Figure 4. Free-bow study against axial refinement N_x for $N_y = 2, 4, 8$ elements through the thickness. (a) Pin realised as $u_y = 0$ on each end edge. (b) Clamp.

Table VII. Restrained wall at the baseline: linear and nonlinear Q8 solutions. w^{lin} is the linear-solid mid-span deflection; $w^{\mathrm{NL}}_{\max}$ the total-Lagrangian one; N_c is the membrane force in the two element columns adjacent to mid-span.

mesh $N_x \times N_y$	elements	$w^{\mathrm{lin}}/(\kappa_{\mathrm{th}} L^2/8)$	$w^{\mathrm{NL}}_{\max}$ (µm)	$w^{\mathrm{NL}}_{\max}/H_0$	N_c at mid-span (kN m^{-1})
24×2	48	0.9979	223.39	0.4468	27.79
48×4	192	0.9980	222.46	0.4449	27.74
96×4	384	0.9980	222.33	0.4447	27.74
96×8	768	0.9980	222.17	0.4443	27.73
192×8	1536	0.9980	222.14	0.4443	27.73

5.4.2 Restrained, geometrically nonlinear wall

The baseline wall is not free: its ends are restrained axially (A7, B6), and the mean temperature rise $\bar{\theta} = 32.3$ K produces the compressive membrane force N_c of Section 3.3. The second computation solves this problem: $\theta(Y) = \bar{\theta} + \Delta T_t (Y/d - \frac{1}{2})$ with the values of Table IV, $u_y = 0$ on the end edges, and a linear constraint that makes the mean axial displacement of each end edge zero, eliminated exactly. The solid is the total-Lagrangian model (22) without fluid load, solved by Newton iteration in four thermal load steps. The analytic tangent agrees with a central finite difference of the residual to 2×10^{-5}, and every step converged in at most 5 iterations to a relative residual of 4×10^{-11}. The same data are solved with the linear solid (material stiffness only) for comparison; Table VII and Figure 5 show the results.

The results are as follows. (i) The linear-solid bow is $0.9980\,\kappa_{\mathrm{th}} L^2/8$, equal to the full-edge pin value of Section 5.4.1: in a linear solid the membrane force does not couple to the bending. (ii) The linear solution carries the membrane force 29.67 kN m^{-1} at mid-span, 2.2 % above the frozen-force beam value of Table IV. (iii) The nonlinear solid bows by 2.221×10^{-4} m ($0.444\,H_0$), an amplification 1.413 over the linear value, compared with 1.39 (frozen force) and 1.36 (self-consistent) in the beam–column model. A linear finite-element solid therefore under-predicts the bow by a factor 1.413, which is why the total-Lagrangian form is specified in Section 5.1. (iv) The membrane force relaxes from 29.67 to 27.73 kN m^{-1}, that is by 6.5 %, against 5.9 % in the beam model: the arc-stretching relaxation of




Figure 5. Restrained baseline wall, finest mesh (192×8). (a) Mid-surface deflection. (b) Compressive membrane force per element column. Beam values are those of Table IV.

Section 3.4 is reproduced in magnitude. (v) The finite-element deflection exceeds the self-consistent beam–column value by 3.8 % and the frozen-force value by 1.5 %. The difference is not explained by the force alone: the beam–column formula evaluated with the finite-element force is still 3.5 % below it, of which a Timoshenko-type shear flexibility of the strip ($\kappa_s = 5/6$) accounts for about 1.2 %. The rest was not isolated; two-dimensional end effects of a strip with $d/L = 0.1$ are a candidate, not a finding. (vi) The nonlinear result changes by 0.014 % between $N_x = 96$ and 192 and by 0.07 % between $N_y = 4$ and 8, so it is mesh-converged at this level.

The reduced-order deflection of Section 4 is therefore a slight under-estimate, by about 3.8 %, of the two-dimensional wall response at the baseline. The guard values and ceiling heat fluxes derived from it are correspondingly a little non-conservative, and the frozen-force values, which are closer to the finite-element result, are the safer of the two reduced-order estimates.

5.5 What has been verified

The reduced-order model of the wall is verified against an independent boundary-value solution (V2) and, in two dimensions, against finite elements for the free bow, the end condition, the membrane force and the nonlinear amplification (V1, V3, V4). The fluid-side estimates of Section 4.4, the coupling algorithm and the formulation of the interface remain unverified until V5–V10 are carried out.

6. Conclusions and limitations

A thin thermoelastic strip heated on its outer face bows *away from the channel*: the through-wall temperature difference sets a free curvature $\kappa_{\mathrm{th}} = (1+\nu)\alpha q''/k_s$ that is independent of the strip thickness, and pinned ends turn it into a bow that widens the passage. At the baseline the reduced-order bow is $0.428\,H_0$ and a two-dimensional geometrically nonlinear finite-element solution of the wall gives $0.444\,H_0$, which is 3.8 % higher; the beam–column amplification of the free bow (1.413 in the finite-element solution) and the relaxation of the membrane force (6.5 % against 5.9 %) are both reproduced in magnitude. The binding limits on the heat flux are deformation and stress, with buckling an outer ceiling. Indicative flow-side estimates, which need the coupled computation for confirmation, point to a hydraulic effect of order one and a notable rise of the wall excess temperature, while the effect of the flow back on the bow is

small at the baseline.

The verification is partial. Only the wall has been verified (levels V1–V4 of Table V); the fluid, the interface formulation and the coupled algorithm are specified and unverified (V5–V10).

Limitations

- **No coupled results.** Every flow-side number is a reduced-order estimate (Section 4.4), and the lubrication and quasi-developed assumptions are not justified at the baseline parameters.
- **Material data** are representative of an unfilled PEEK-class polymer and not frozen against a datasheet; they are constant with temperature, and the strip is linearly thermoelastic (A3).
- **Idealisations.** Perfect thermal contact (A6), ideal pinned ends (A7), an idealised uniform heater (A8), and a casing that is only a support, with no contact with the deformed strip and no clearance (A9). A real mounting would change the end conditions and, with them, the bow (Section 5.4.1).
- **Heated face.** The model heats the outer face. Heating the fluid-facing face would bow the strip into the channel and is a different model, outside this paper.
- **Two dimensions.** Plane strain is assumed; end effects and finite thickness may explain part of the finite-element departure from the beam model; shear flexibility accounts for a small share of it, and most of the 3.8 % has not been attributed.
- **Steady state.** Transient heating, thermal inertia and viscoelasticity of the polymer are not modelled.

Further work

Carry out V5–V10 of Table V; compute the coupled problem and test the contraction of the fixed point; replace the idealised heater and end conditions with a specified mounting and casing contact; and validate against experiment.

A. Nomenclature

Table VIII. Principal symbols (SI units).

Symbol	Meaning	Symbol	Meaning
H_0	undeformed passage height	κ_{th}	free thermal curvature
L, d	strip length and thickness	ν, E	Poisson ratio, Young modulus
L_e, L_o	entrance and outlet lengths	α	thermal expansion coefficient
U	mean inlet velocity	k_s, k_f	solid and fluid conductivity
q''	imposed heat flux (supplied)	D_s	flexural rigidity per unit depth
$\boldsymbol{u}$, p	velocity, pressure	N_c, N_{cr}	compressive membrane force, Euler load
T, θ	temperature, rise above inlet	M_b	buckling margin
$\bar{\theta}$	mean wall temperature rise	$w_{\max}$	maximum deflection (away from channel)
ΔT_t, ΔT_b	through-wall and bulk temperature rise	Γ_p	thermal-to-hydraulic deflection ratio
Re, Pr, Pe	Reynolds, Prandtl, Péclet numbers	Ri, Br	Richardson, Brinkman numbers
$\boldsymbol{d}$, $\boldsymbol{\sigma}$, $\boldsymbol{\varepsilon}$	displacement, stress, strain	$\boldsymbol{F}$, $\boldsymbol{E}$, $\boldsymbol{S}$	deformation gradient, Green–Lagrange strain, second Piola–Kirchhoff stress
Γ_{if}, Γ_h	interface, heated outer face	$\boldsymbol{n}$, $\boldsymbol{n}_{\mathrm{out}}$	interface normal, outward solid normal

References

Alsabery, A. I., Saleh, H., Ghalambaz, M., Chamkha, A. J. and Hashim, I. (2019), "Fluid-structure interaction analysis of transient convection heat transfer in a cavity containing inner solid cylinder and flexible right wall", *International Journal of Numerical Methods for Heat & Fluid Flow*, Vol. 29 No. 10, pp. 3756–3780, doi: 10.1108/HFF-10-2018-0593.

Bird, R. B., Stewart, W. E. and Lightfoot, E. N. (1960), *Transport Phenomena*, John Wiley & Sons, New York, NY.

Boley, B. A. and Weiner, J. H. (1960), *Theory of Thermal Stresses*, John Wiley & Sons, New York, NY.

Brezzi, F. and Fortin, M. (1991), *Mixed and Hybrid Finite Element Methods*, Springer-Verlag, New York, NY, doi: 10.1007/978-1-4612-3172-1.

Brooks, A. N. and Hughes, T. J. R. (1982), "Streamline upwind/Petrov–Galerkin formulations for convection dominated flows with particular emphasis on the incompressible Navier–Stokes equations", *Computer Methods in Applied Mechanics and Engineering*, Vol. 32 No. 1–3, pp. 199–259, doi: 10.1016/0045-7825(82)90071-8.

Carslaw, H. S. and Jaeger, J. C. (1947), *Conduction of Heat in Solids*, Clarendon Press, Oxford.

Celik, I. B., Ghia, U., Roache, P. J., Freitas, C. J., Coleman, H. and Raad, P. E. (2008), "Procedure for estimation and reporting of uncertainty due to discretization in CFD applications", *Journal of Fluids Engineering*, Vol. 130 No. 7, p. 078001, doi: 10.1115/1.2960953.

Christov, I. C., Cognet, V., Shidhore, T. C. and Stone, H. A. (2018), "Flow rate-pressure drop relation for deformable shallow microfluidic channels", *Journal of Fluid Mechanics*, Vol. 841, pp. 267–286, doi: 10.1017/jfm.2018.30.

Draskic, M., Westerweel, J. and Pecnik, R. (2025), "The stability of stratified horizontal flows of carbon dioxide at supercritical pressures", *Journal of Fluid Mechanics*, Vol. 1012, p. A17, doi: 10.1017/jfm.2025.10162.

Hood, P. and Taylor, C. (1974), "Navier–Stokes equations using mixed interpolation", in Oden, J. T., Zienkiewicz, O. C., Gallagher, R. H. and Taylor, C. (Eds), *Finite Element Methods in Flow Problems*, University of Alabama in Huntsville Press, Huntsville, AL, pp. 121–132.

Kumar, V., Assam, A. and Prabhakaran, D. (2026), "Nonlinear thermo-fluid-structure interactions of two interacting flexible cantilever plates in a differentially heated cavity", *Physics of Fluids*, Vol. 38 No. 9, p. 092128, doi: 10.1063/5.0349114.

Lesoinne, M. and Farhat, C. (1996), "Geometric conservation laws for flow problems with moving boundaries and deformable meshes, and their impact on aeroelastic computations", *Computer Methods in Applied Mechanics and Engineering*, Vol. 134 No. 1–2, pp. 71–90, doi: 10.1016/0045-7825(96)01028-6.

Rahimimotlagh, Z., Ahmadian-Elmi, M. and Hajmohammadi, M. R. (2024), "Numerical investigation of conjugate heat transfer in a flattened cross-sectional thick channel", *International Journal of Thermal Sciences*, Vol. 195, p. 108637, doi: 10.1016/j.ijthermalsci.2023.108637.

Saleh, H., Alsabery, A. I., Sheremet, M. A., Ghalambaz, M. and Hashim, I. (2025), "Impact of fluid-structure interaction on unsteady flow within wavy-heated wall cavity", *International Journal of Numerical Methods for Heat & Fluid Flow*, Vol. 35 No. 4, pp. 1484–1511, doi: 10.1108/HFF-01-2025-0045.

Shah, R. K. and London, A. L. (1978), *Laminar Flow Forced Convection in Ducts: A Source Book for Compact Heat Exchanger Analytical Data*, Academic Press, New York, NY.

Soti, A. K., Bhardwaj, R. and Sheridan, J. (2015), "Flow-induced deformation of a flexible thin structure as manifestation of heat transfer enhancement", *International Journal of Heat and Mass Transfer*, Vol. 84, pp. 1070–1081, doi: 10.1016/j.ijheatmasstransfer.2015.01.048.

Timoshenko, S. P. and Gere, J. M. (1961), *Theory of Elastic Stability*, 2nd edition, McGraw-Hill, New York, NY.

Timoshenko, S. P. and Goodier, J. N. (1970), *Theory of Elasticity*, 3rd edition, McGraw-Hill, New York, NY.