

Last updated by | Morgan Mick | Jul 24, 2019 at 9:26 AM GMT+1

The purpose of this class is to manage the entity throughout transformations that are either highly complex or repetitive in nature.

https://anglianwater.visualstudio.com/Data_Services/_wiki/wikis/Data-Services.wiki?pagePath=%2FArchitecture%2FAWBI Platform Architecture Design%2F4.%252D Solution Design%2F4.1 Data Proce... 1/4

https://anglianwater.visualstudio.com/Data_Services/wiki/wikis/Data-Services.wiki?pagePath=%2FArchitecture%2FAWBI Platform Architecture Design%2F4 %252D Solution Design%2F4.1 Data Proce... 2/4

	a databricks global view)											
getCuratedPrimaryKeys	Returns the entity PrimaryKey from AWBISystem - Control.Entity (via a databricks global view)	N/A	entity.getCuratedPrimaryKeys()	Returns the content of PrimaryKey in the AWBISystem table								
getBasePrimaryKeys	Returns a list containing the entity columns marked as PrimaryKey from AWBISystem - Metada.EntityColumns (via a databricks global view)	N/A	entity.getBasePrimaryKeys()	[colOne, colTwo]								
appendMetadata	Returns a the same dataframe passed to the function but with all the standard meta data columns appended	df, preventScd = 0	entity.appendMetadata(myDf, 1)	[colOne, colTwo]								
addSid	Returns a dataframe with the tableSid prepended and populated, required the dataframe to prepend to and the maximum row count in the table	df, maxSid	entity.addSid(myDf, 5987)	<table><tr><td>templateSid</td><td>colOne</td><td>colTwo</td></tr><tr><td>5988</td><td>Test value 1</td><td>Test value 2</td></tr></table>			templateSid	colOne	colTwo	5988	Test value 1	Test value 2
templateSid	colOne	colTwo										
5988	Test value 1	Test value 2										
addHashes	Prepends the Key Hash and Change Hash to a dataframe	df	entity.addHashes(myDf)	<table><tr><td>templateSid</td><td colspan="2">awbiMetadataKeyHash</td></tr><tr><td>5988</td><td colspan="2">df7e70e5021544f4834bbee64a9e3789feb4be81470df629cad6ddb03320a5c</td></tr></table>			templateSid	awbiMetadataKeyHash		5988	df7e70e5021544f4834bbee64a9e3789feb4be81470df629cad6ddb03320a5c	
templateSid	awbiMetadataKeyHash											
5988	df7e70e5021544f4834bbee64a9e3789feb4be81470df629cad6ddb03320a5c											
addDefaultRow	Unions in a default row for a dimension	df	entity.addDefaultRow(myDf)	![image.png](/.attachments/image-ddcada24-20ef-4bc2-86a0-1384e6dd2bcf.png)								
scdUpdates	Prepares the update statement to update existing records in the delta target table	df	entity.scdUpdates(myDf)	N/A								
genScdType2	Generates an order-able set of slowly changing dimension dates (valid from and valid to), also includes	df	entity.genScdType2(myDf)	![image.png](/.attachments/image-8ced74b6-c304-4f0f-8c69-9f4e871bc5f1.png)								

the current indicator field.