Lab Assignment 2:

Performance evaluation of the memory hierarchy of a computer and reverse engineering of the data cache memory

Scheduling: 4 weeks

- Session 1: Activities 1,2,3; 2 hours

- S2: Activity 4 ; 2 hours

- S3: Reverse engineering for the data cache of Nios V/g; 2 hours

- S4: Examn; 1,5 hours

Implementing the Memory Hierarchy Levels of the Basic Computer Structure of the DE0-Nano board

DE0-Nano

Implementation of the memory hierarchy

Activity 1: benchmark

START

Timer and interrupt start

Fibonacci routine

¿end of ITERATIONS?

No

YES

Show internal value of COUNTER variable

```
i AM AT LAB2_PART1 WITH nIOSv/M ... RUNNING ...
tIME: 00000002 33-MS INTERVALS
eND OF PROGRAM
```

Interrupt routine

¿Does timer interrupt have fired?

No

YES

COUNTER += 1

END

Compiling & Linking using Nios V/m + SDRAM


```
C:/altera/12.1sp1/University_Program/NiosII_Computer_Systems/DE0-Nano/DE0-Nano_Basic_Computer_NiosVm_conSDRAM/verilog/so
ftware/niosv/ACpractica2niosv # make
riscv32-unknown-elf-as.exe  lab2_part1_2_3_main.s -alsg -o lab2_part1_2_3_main.s.obj > lab2_part1_2_3_main.s.log
riscv32-unknown-elf-as.exe  excepcionTimer.s -alsg -o excepcionTimer.s.obj > excepcionTimer.s.log
riscv32-unknown-elf-as.exe  escribir_jtag.s -alsg -o escribir_jtag.s.obj > escribir_jtag.s.log
riscv32-unknown-elf-as.exe  contador.s -alsg -o contador.s.obj > contador.s.log
riscv32-unknown-elf-as.exe  DIV.s -alsg -o DIV.s.obj > DIV.s.log
riscv32-unknown-elf-as.exe  BCD.s -alsg -o BCD.s.obj > BCD.s.log
riscv32-unknown-elf-as.exe  lab2_part1_2_3_fibo.s -alsg -o lab2_part1_2_3_fibo.s.obj > lab2_part1_2_3_fibo.s.log
riscv32-unknown-elf-ld.exe  -g -T linker_SDRAM.x  -nostdlib -e _start -u _start --defsym __alt_stack_pointer=0x08001F00
--defsym __alt_stack_base=0x08002000 --defsym __alt_heap_limit=0x8002000 --defsym __alt_heap_start=0x8002000  -o lab2_pa
rt1_2_3_main.elf lab2_part1_2_3_main.s.obj excepcionTimer.s.obj escribir_jtag.s.obj contador.s.obj DIV.s.obj BCD.s.obj l
ab2_part1_2_3_fibo.s.obj
riscv32-unknown-elf-ld.exe: warning: lab2_part1_2_3_main.elf has a LOAD segment with RWX permissions
niosv-stack-report  -p riscv32-unknown-elf- lab2_part1_2_3_main.elf
lab2_part1_2_3_main.elf
 * 1320 B - Program size (code + initialized data).
 * 256 B - Free for stack.
 * 0 B - Free for heap.
riscv32-unknown-elf-objdump  -Sdtx lab2_part1_2_3_main.elf > lab2_part1_2_3_main.elf.objdump
riscv32-unknown-elf-objcopy -O binary lab2_part1_2_3_main.elf lab2_part1_2_3_main.hex
C:/altera/12.1sp1/University_Program/NiosII_Computer_Systems/DE0-Nano/DE0-Nano_Basic_Computer_NiosVm_conSDRAM/verilog/so
ftware/niosv/ACpractica2niosv #
```

Executing using Nios V/m + SDRAM


```
[OpenOCD output] Info : Virtual Tap/SLD node 0x08986E00 found at tap position 0 vtap position 1
[OpenOCD output] Info : datacount=2 progbufsize=8
[OpenOCD output] Info : Examined RISC-V core; found 1 harts
[OpenOCD output] Info :  hart 0: XLEN=32, misa=0x4000b0c3
[OpenOCD output] Info : starting gdb server for tap_020F30DD.0.niosv_0.cpu on 0
[OpenOCD output] Info : Listening on port 49626 for gdb connections
INFO: Found gdb port 49626
[OpenOCD output] Ready for Remote Connections
[OpenOCD output] Info : tcl server disabled
[OpenOCD output] Info : Listening on port 49627 for telnet connections
INFO: Found telnet port 49627
INFO: OpenOCD is ready.
INFO: Sending reset halt to OpenOCD.
INFO: Loading image via GDB. Running "riscv32-unknown-elf-gdb -batch -ex set arch riscv:rv32 -ex set remotetimeout 60 -e
x target extended-remote localhost:49626 -ex load lab2_part1_2_3_main.elf -ex set $mstatus &= ~(0x00000088)".
The target architecture is set to "riscv:rv32".
warning: No executable has been specified and target does not support
determining executable automatically.  Try using the "file" command.
0x09000004 in ?? ()
Loading section .exceptions, size 0x5c lma 0x0
Loading section .text, size 0x38c lma 0x5c
Loading section .rwdata, size 0x140 lma 0x3e8
Start address 0x0000005c, load size 1320
Transfer rate: 4 KB/sec, 440 bytes/write.
[Inferior 1 (Remote target) detached]
INFO: Sending resume to OpenOCD.
```

```
C:/altera/12.1sp1/University_Program/NiosII_Computer_Systems/DE0-Nano/DE0-Nano_Basic_Computer_NiosVm_conSDRAM/verilog/so
ftware/niosv/ACpractica2niosv # juart-terminal.exe
juart-terminal: connected to hardware target using JTAG UART on cable
juart-terminal: "USB-Blaster [USB-0]", device 1, instance 0
juart-terminal: (Use the IDE stop button or Ctrl-C to terminate)


i AM AT LAB2_PART1 WITH nIOSv/M ... RUNNING ...

tIME: 00000008 33-MS INTERVALS

eND OF PROGRAM
```

Executing using Nios V/m + SRAM

```
[OpenOCD output] Info : Listening on port 53290 for telnet connections
INFO: Found telnet port 53290
INFO: OpenOCD is ready.
INFO: Sending reset halt to OpenOCD.
INFO: Loading image via GDB. Running "riscv32-unknown-elf-gdb -batch -ex set arch riscv:rv32 -ex set remotetimeout 60 -e
x target extended-remote localhost:53289 -ex load lab2_part1_2_3_main.elf -ex set $mstatus &= ~(0x00000088)".
The target architecture is set to "riscv:rv32".
warning: No executable has been specified and target does not support
determining executable automatically.  Try using the "file" command.
0x09000004 in ?? ()
Loading section .exceptions, size 0x5c lma 0x8000000
Loading section .text, size 0x3a8 lma 0x800005c
Loading section .rwdata, size 0x140 lma 0x8000404
Start address 0x0800005c, load size 1348
Transfer rate: 4 KB/sec, 449 bytes/write.
[Inferior 1 (Remote target) detached]
INFO: Sending resume to OpenOCD.
C:/altera/12.1sp1/University_Program/NiosII_Computer_Systems/DE0-Nano/DE0-Nano_Basic_Computer_NiosVm_conSDRAM/verilog/so
ftware/niosv/ACpractica2niosv # juart-terminal.exe
juart-terminal: connected to hardware target using JTAG UART on cable
juart-terminal: "USB-Blaster [USB-0]", device 1, instance 0
juart-terminal: (Use the IDE stop button or Ctrl-C to terminate)


i AM AT LAB2_PART1 WITH nIOSv/M ... RUNNING ...

tIME: 00000002 33-MS INTERVALS

eND OF PROGRAM
```

Activity 1: measuring execution time

Soft processor model + memory technology	Execution time	Speed-up
Nios V/m + SDRAM memory (Activity 1)		1X
Nios V/m + on-chip memory (Activity 2)		
Nios V/g + SDRAM memory (Activity 3)		
Nios V/g + on-chip memory (Activity 3)		

Activity 4: discovering data cache microarchitecture

Source code for the main program::
`lab2_part1_2_3_main.s`

```
                ...
                li x14, ITERACIONES        /* initializes the LOOP iteration counter, each iteration executing a Fibonacci loop */
                addi  x17, zero, 0         /* initializes the interval counter of program "x17". */

LOOP:           beq   x14, zero, END       /* execute Fibonacci loop */
                call  FIBONACCI
                addi  x14, x14, -1
                br    LOOP
```

Source code for the routine FIBONACCI:
`lab2_part1_2_3_fibo.s`

```
                ...
                movi  r4, 0
                movi  r5, X
LOOP:  bge     r4, r5, END
                ldb   r0, V(r4)
                addi  r4, r4, P
                br    LOOP
END:
                ...
.data
V:
.skip 65536
                ...
```

Modify source code in the file::
`lab2_part1_2_3_fibo.s`

Activity 4

```
        ...
        movi  r4, 0
        movi  r5, X
LOOP:   bge   r4, r5, END
        ldb   r0, V(r4)
        addi  r4, r4, P
        br    LOOP
END:
        ...
.data
V:
.skip 65536
...
```

X: data size accessed by program,
$$X = P \times E$$

E: number of accesses to main memory

Table. Measures collected after running the benchmark for different data size and data access patterns

P: data access pattern	E: Number of V vector bytes accessed actually					
	128	256	512	1024	2048	4096
P = 1: every one						
P = 2: every two						
P = 4: every four						
P = 8: every eight						

Activity 4

Table. Measures collected after running the benchmark for different data size and data access patterns

P: data access pattern	E: Number of V vector bytes accessed actually					
	128	256	512	1024	2048	4096
P = 1: every one						
P = 2: every two						
P = 4: every four						
P = 8: every eight						

T: execution time

Abrupt change in proportionality:
$\Delta T / \Delta X$

P_2

P_1

ΔT

ΔT

X: data saved in data cache

$X = P \times E$

ΔX ΔX

128   256   512   1024   2048   4096

Method to fill in the table on the left

1) Ejecutar AMP
2) New project

CAMBIA-CACHE:

3) Settings > System Settings > "Custom System" + browse > `<file>.sopcinfo` (System information file)

4) Settings > System Settings > "Custom System" + browse > `<file>.sof` (Quartus II Programming File)

5) Memory Settings > Memory device > `SDRAM`

6) Actions > Download System

CAMBIA-DATOS:

7) Modificar fichero del programa: `lab2_part1_2_3_fibo.s` para establecer **X** y **P**

8) Compile

9) Load

10) Ejecutar el programa y esperar a que salga el tiempo en el terminal de AMP y apuntarlo en la Tabla 3

SEGUIR CAMBIA-DATOS

SEGUIR CAMBIA-CACHE

¿Data cache size?: P=1

```
        ...
        movi r4, 0
        movi r5, X
LOOP:   bge  r4, r5, END
        ldb  r0, V(r4)
        addi r4, r4, P
        br   LOOP
END:
        ...

.data
V:
.skip 65536
        ...
```

Processor address space

Cache

- X **does** fit in the data cache.
- There are only misses in ITERATION=1.
- In ITERATION={2,...,50000} the accesses hit the cache.
- Execution time (T) is proportional to the number of memory accesses (E).

Case Type-1:
NO-overflow
X: data volumes handled by the program; the bytes of the V vector accessed from the program fit in the data cache.

**Case Tyte-2:**
OVERFLOW

Processor address space

Cache

X' > X

- **X' does not** fit in the data cache.
- Many failures in data cache by replacements in all ITERATIONS.
- Execution time does NOT have the same proportion as in lower X.

- **KEY:** find X' for P=1 which means that the execution time does not keep proportion with the number of accesses E that in lower X; the capacity is X'/2

# Execution time **WITHOUT** cache misses after the first LOOP ITERATION

```
        ...
        movi  r4, 0
        movi  r5, X
LOOP:   bge   r4, r5, END
        ldb   r0, V(r4)
        addi  r4, r4, P
        br    LOOP

    END:
        ...

    .data
    V:
    .skip 65536
    ...
```

ITERation

TIME

t_{bge}
t_{lb}
t_{addi}
t_{br}

$t_{ITER} = \sum_i t_i$

$t_{lb} \ (average) = t_{hit}$

$$X \rightarrow 2X$$

$$\sum^{2X} t_{ITER} \approx 2 \times \sum^{X} t_{ITER}$$

HIT
time=t_{ldb}

P   `lb r0,V(X)`

Data Cache

Case Type-1:
NO-cache overflow for all iterations except the first

Double the number of ITERations (2X) should cause the program to take twice as long

Execution time **WITH** cache misses

```
        ...
        movi  r4, 0
        movi  r5, X
LOOP:   bge   r4, r5, END
        ldb   r0, V(r4)
        addi  r4, r4, P
        br    LOOP
END:
        ...
.data
V:
.skip 65536
...
```

ITERation

TIME

$t_{bge'} = t_{bge}$

$t_{lb'} = Pe + t_{lb}$

$t_{addi'} = t_{addi}$

$t_{br'} = t_{br}$

$t'_{ITER} = \sum_{i'} t_{i'} = Pe + \sum_i t_i = Pe + t_{ITER}$

$t_{ldb'} (average) = t_{hit} + MissRate \times Penalization$

$$X \rightarrow 2X$$

$$\sum^{2X} t_{ITER} > 2 \times \sum^X t_{ITER}$$

Double the number of ITERations (2X) should cause the program to take longer than **twice** the time with half the number of ITERations (X).

MISS
time = $Pe + t_{lb}$

P   `lb r0,V(X)`

Data Cache

Miss time = Pe

RAM Memory

¿How do you discover cache size?: P=1

Ratio:
40/20 =
2,0

Ratio :
163/85 =
1,91

Ratio :
320/163
= 1,96

Ratio :
946/320
= 2,96

P	Number of memory accesses					E
Pattern	128	256	512	1024	2048	4096
1	20	40	85	163	320	946
2	20	46	85	163	633	1258
4	27	46	85	476	947	1888
8	24	43	239	480	945	1888

Ratio :
43/24=
1,79

Ratio :
239/43 =
5,56

Ratio :
480/239
= 2,0

SIZE:
2 KiB
(X = P × E)

# ¿ How do you discover block size?

```
        ...
        movi  r4, 0
        movi  r5, X
LOOP:   bge   r4, r5, END
        ldb   r0, V(r4)
        addi  r4, r4, P
        br    LOOP
END:
        ...
.data
V:
.skip 65536
...
```

- Assume the case where the block size is 2 bytes.
- Assume that X is large enough so that the cache memory is always overflowing.

BLOCK:

2 bytes

P = 1

`lb r0,V(0)` `lb r0,V(1)`

Miss	Hit
Miss	Hit
Miss	Hit
Miss	Hit

`ldb r0,V(2)`
`ldb r0,V(4)`
`ldb r0,V(6)`

Some accesses hit in
the cache →
**Execution time
lower than cases
P=2,4**

P = 2

Miss	
Miss	
Miss	
Miss	

All accesses hit in
the cache →
**Execution time
larger tan case
P=1**

P = 4

`lb r0,V(0)`

Miss	
Miss	

`ldb r0,V(4)`

All accesses hit in
the cache →
**Execution time
similar to case
P=2**

¿How do you discover block size?

Look at the same column of accesses and make sure that the cache is overflowing to ensure that at least capacity misses occur

Board
DE0-Nano

BLOCK:

4 B

P			Number of memory accesses			E
Pattern	128	256	512	1024	2048	4096
1	20	40	85	163	320	946
2	20	46	85	163	633	1258
4	27	46	85	476	947	1888
8	24	43	239	480	945	1888

Ratio:
480/476
= 1,0

Ratio:
476/163
= 2,9