

## DBMS Lab Assignment - 02



Name: V. Sai Vipul Mohan



Roll.no: 111801045


---

### 1. Entity Sets and Relationship Sets:


Entity Sets:








Relationship Sets:



Delivery **has** Billing: one-to-one relationship, mandatory participation of Delivery in the relationship and optional participation of Billing in the relationship.(Every Delivery has Billing but not vice versa)



Reservations **has** Billing: one-to-one relationship, mandatory participation of Reservation in the relationship and optional participation of Billing in the relationship.(Every reservations has Billing but not vice versa)




Employee **belongs to** Waiter: one-to-one relationship, optional participation of Employee in the relationship and mandatory participation of Waiter in the relationship.



Waiter **attends** Reservation: one-to-many relationship, mandatory participation of Waiter and Reservation in the relationship. (Single Waiter can attend multiple Reservations)

2. ER Diagram:



3. Use MariaDB
  - a. Create a database Restaurant

```

MariaDB [(none)]> show databases;
+-----+
| Database |
+-----+
| hospital |
| information_schema |
| mysql |
| performance_schema |
| test |
+-----+
5 rows in set (0.004 sec)

MariaDB [(none)]> create database restaurant;
Query OK, 1 row affected (0.001 sec)

MariaDB [(none)]> show databases;
+-----+
| Database |
+-----+
| hospital |
| information_schema |
| mysql |
| performance_schema |
| restaurant |
| test |
+-----+
6 rows in set (0.001 sec)

MariaDB [(none)]> 
```

b. Create all the required tables

```
→ salary float,  
→ date_of_joining datetime,  
→ rating float,  
→ email varchar(50),  
→ address varchar(100));  
ERROR 1046 (3D000): No database selected  
MariaDB [(none)]> use database restaurant;  
ERROR 1049 (42000): Unknown database 'database'  
MariaDB [(none)]> use restaurant;  
Database changed  
MariaDB [restaurant]> create table Employee(  
→ id varchar(255) primary key,  
→ name varchar(50),  
→ position varchar(50),  
→ salary float,  
→ date_of_joining datetime,  
→ rating float,  
→ email varchar(50),  
→ address varchar(100));  
Query OK, 0 rows affected (0.035 sec)  
  
MariaDB [restaurant]> show tables;  
+-----+  
| Tables_in_restaurant |  
+-----+  
| Employee              |  
+-----+  
1 row in set (0.000 sec)  
  
MariaDB [restaurant]> 
```

```

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Employee              |
+-----+
1 row in set (0.000 sec)

MariaDB [restaurant]> create table Reservation(
  -> id varchar(255) primary key,
  -> name varchar(50),
  -> table_number int,
  -> entry_time datetime,
  -> leaving_time datetime,
  -> email varchar(50),
  -> number_of_persons int,
  -> special_status boolean);
Query OK, 0 rows affected (0.027 sec)

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Employee              |
| Reservation           |
+-----+
2 rows in set (0.001 sec)

MariaDB [restaurant]> 
```

```

+-----+
| Tables_in_restaurant |
+-----+
| Employee              |
| Reservation           |
+-----+
2 rows in set (0.001 sec)

MariaDB [restaurant]> create table Billing(
  -> id varchar(255) primary key,
  -> name varchar(50),
  -> table_number int,
  -> waiter_id varchar(255),
  -> delivery_id varchar(255),
  -> mode varchar(20),
  -> bill_amount float,
  -> reservation_id varchar(255));
Query OK, 0 rows affected (0.024 sec)

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Billing                |
| Employee              |
| Reservation           |
+-----+
3 rows in set (0.000 sec)

MariaDB [restaurant]> 
```



```

+-----+
| Billing |
| Employee |
| Reservation |
+-----+
3 rows in set (0.001 sec)

MariaDB [restaurant]> create table Waiter(
  -> id varchar(255) primary key,
  -> name varchar(50),
  -> table_number int,
  -> salary float,
  -> date_of_joining datetime,
  -> rating float,
  -> email varchar(50),
  -> address varchar(100));
Query OK, 0 rows affected (0.035 sec)

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Billing |
| Employee |
| Reservation |
| Waiter |
+-----+
4 rows in set (0.001 sec)

MariaDB [restaurant]> 
```

```

| Employee      |
| Reservation   |
| Waiter        |
+-----+
4 rows in set (0.001 sec)

MariaDB [restaurant]> create table Delivery(
  -> id varchar(255) primary key,
  -> name varchar(50),
  -> mode_of_delivery boolean,
  -> contact_number varchar(20),
  -> amount float,
  -> rating float,
  -> email varchar(50),
  -> company varchar(50));
Query OK, 0 rows affected (0.031 sec)

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Billing                |
| Delivery              |
| Employee              |
| Reservation           |
| Waiter                |
+-----+
5 rows in set (0.001 sec)

MariaDB [restaurant]> 
```

```

| Reservation |
| Waiter      |
| delivery_to_billing |
| employee_to_waiter |
| reservation_to_billing |
+-----+
8 rows in set (0.001 sec)

MariaDB [restaurant]> create table waiter_to_reservation(
  -> waiter_id varchar(255) not null,
  -> reservation_id varchar(255));
Query OK, 0 rows affected (0.031 sec)

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Billing                |
| Delivery              |
| Employee              |
| Reservation           |
| Waiter                |
| delivery_to_billing   |
| employee_to_waiter    |
| reservation_to_billing |
| waiter_to_reservation |
+-----+
9 rows in set (0.001 sec)

MariaDB [restaurant]> 
```

```

MariaDB [restaurant]> drop table delivery_to_billing;
Query OK, 0 rows affected (0.007 sec)

MariaDB [restaurant]> drop table employee_to_waiter;
Query OK, 0 rows affected (0.004 sec)

MariaDB [restaurant]> drop table reservation_to_billing;
Query OK, 0 rows affected (0.006 sec)

MariaDB [restaurant]> create table delivery_to_billing(
  -> delivery_id varchar(255) primary key not null,
  -> billing_id varchar(255));
Query OK, 0 rows affected (0.029 sec)

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Billing                |
| Delivery              |
| Employee              |
| Reservation           |
| Waiter               |
| delivery_to_billing   |
| waiter_to_reservation |
+-----+
7 rows in set (0.001 sec)

MariaDB [restaurant]> 
```

```

| Delivery          |
| Employee          |
| Reservation       |
| Waiter            |
| delivery_to_billing |
| waiter_to_reservation |
+-----+
7 rows in set (0.001 sec)

MariaDB [restaurant]> create table employee_to_waiter(
  -> employee_id varchar(255),
  -> waiter_id varchar(255) primary key not null);
Query OK, 0 rows affected (0.022 sec)

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Billing                |
| Delivery              |
| Employee              |
| Reservation           |
| Waiter                |
| delivery_to_billing   |
| employee_to_waiter    |
| waiter_to_reservation |
+-----+
8 rows in set (0.001 sec)

MariaDB [restaurant]> 
```

```

| Delivery          |
| Employee          |
| Reservation       |
| Waiter           |
| delivery_to_billing |
| employee_to_waiter |
+-----+
7 rows in set (0.001 sec)

MariaDB [restaurant]> create table reservation_to_billing(
  -> reservation_id varchar(255) not null,
  -> billing_id varchar(255));
Query OK, 0 rows affected (0.028 sec)

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Billing                |
| Delivery              |
| Employee              |
| Reservation            |
| Waiter                |
| delivery_to_billing    |
| employee_to_waiter     |
| reservation_to_billing |
+-----+
8 rows in set (0.001 sec)

MariaDB [restaurant]> 
```

c. Show all tables in the database

```

+-----+
| Billing |
| Delivery |
| Employee |
| Reservation |
| Waiter |
| delivery_to_billing |
| employee_to_waiter |
| reservation_to_billing |
| waiter_to_reservation |
+-----+
9 rows in set (0.004 sec)

MariaDB [restaurant]> show tables;

+-----+
| Tables_in_restaurant |
+-----+
| Billing |
| Delivery |
| Employee |
| Reservation |
| Waiter |
| delivery_to_billing |
| employee_to_waiter |
| reservation_to_billing |
| waiter_to_reservation |
+-----+
9 rows in set (0.003 sec)

MariaDB [restaurant]>

```

d. Show structure of the tables created in question 3(b)

```

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Billing                |
| Delivery              |
| Employee              |
| Reservation           |
| Waiter               |
+-----+
5 rows in set (0.001 sec)

MariaDB [restaurant]>
MariaDB [restaurant]>
MariaDB [restaurant]> describe Billing;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id         | varchar(255) | NO   | PRI | NULL    |       |
| name       | varchar(50)  | YES  |     | NULL    |       |
| table_number | int(11)      | YES  |     | NULL    |       |
| waiter_id  | varchar(255) | YES  |     | NULL    |       |
| delivery_id | varchar(255) | YES  |     | NULL    |       |
| mode       | varchar(20)  | YES  |     | NULL    |       |
| bill_amount | float        | YES  |     | NULL    |       |
| reservation_id | varchar(255) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
8 rows in set (0.008 sec)

MariaDB [restaurant]> 
```



```

MariaDB [restaurant]> describe Billing;
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id             | varchar(255)  | NO   | PRI | NULL     |       |
| name           | varchar(50)   | YES  |     | NULL     |       |
| table_number   | int(11)       | YES  |     | NULL     |       |
| waiter_id      | varchar(255)  | YES  |     | NULL     |       |
| delivery_id    | varchar(255)  | YES  |     | NULL     |       |
| mode           | varchar(20)   | YES  |     | NULL     |       |
| bill_amount    | float         | YES  |     | NULL     |       |
| reservation_id | varchar(255)  | YES  |     | NULL     |       |
+-----+-----+-----+-----+-----+-----+
8 rows in set (0.008 sec)

MariaDB [restaurant]> describe delivery;
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id             | varchar(255)  | NO   | PRI | NULL     |       |
| name           | varchar(50)   | YES  |     | NULL     |       |
| mode_of_delivery | tinyint(1)    | YES  |     | NULL     |       |
| contact_number  | varchar(20)   | YES  |     | NULL     |       |
| amount         | float         | YES  |     | NULL     |       |
| rating         | float         | YES  |     | NULL     |       |
| email          | varchar(50)   | YES  |     | NULL     |       |
| company        | varchar(50)   | YES  |     | NULL     |       |
+-----+-----+-----+-----+-----+-----+
8 rows in set (0.009 sec)

```

```

MariaDB [restaurant]> describe delivery;
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id             | varchar(255)  | NO   | PRI | NULL    |       |
| name           | varchar(50)   | YES  |     | NULL    |       |
| mode_of_delivery | tinyint(1)    | YES  |     | NULL    |       |
| contact_number | varchar(20)   | YES  |     | NULL    |       |
| amount         | float         | YES  |     | NULL    |       |
| rating         | float         | YES  |     | NULL    |       |
| email          | varchar(50)   | YES  |     | NULL    |       |
| company        | varchar(50)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
8 rows in set (0.009 sec)

MariaDB [restaurant]> describe Employee;
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id             | varchar(255)  | NO   | PRI | NULL    |       |
| name           | varchar(50)   | YES  |     | NULL    |       |
| position       | varchar(50)   | YES  |     | NULL    |       |
| salary         | float         | YES  |     | NULL    |       |
| date_of_joining | datetime      | YES  |     | NULL    |       |
| rating         | float         | YES  |     | NULL    |       |
| email          | varchar(50)   | YES  |     | NULL    |       |
| address        | varchar(100)  | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
8 rows in set (0.006 sec)

```

```

❯❯❯  ~%1  ..ding/projects (zsh)  %1  mariadb (mariadb)  %2  +
+-----+-----+-----+-----+-----+-----+
| id      | varchar(255) | NO   | PRI | NULL | |
| name    | varchar(50)  | YES  |     | NULL | |
| position | varchar(50)  | YES  |     | NULL | |
| salary  | float        | YES  |     | NULL | |
| date_of_joining | datetime    | YES  |     | NULL | |
| rating  | float        | YES  |     | NULL | |
| email   | varchar(50)  | YES  |     | NULL | |
| address | varchar(100) | YES  |     | NULL | |
+-----+-----+-----+-----+-----+
8 rows in set (0.006 sec)

MariaDB [restaurant]>
MariaDB [restaurant]>
MariaDB [restaurant]> describe Reservation;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id         | varchar(255)  | NO   | PRI | NULL    |       |
| name       | varchar(50)   | YES  |     | NULL    |       |
| table_number | int(11)       | YES  |     | NULL    |       |
| entry_time | datetime      | YES  |     | NULL    |       |
| leaving_time | datetime      | YES  |     | NULL    |       |
| email      | varchar(50)   | YES  |     | NULL    |       |
| number_of_persons | int(11)      | YES  |     | NULL    |       |
| special_status | tinyint(1)    | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+
8 rows in set (0.008 sec)

MariaDB [restaurant]> 
```

```

❯❯❯  ~%1  ..ding/projects (zsh)  %1  mariadb (mariadb)  %2  +
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id             | varchar(255)  | NO   | PRI | NULL    |       |
| name          | varchar(50)   | YES  |     | NULL    |       |
| table_number   | int(11)       | YES  |     | NULL    |       |
| entry_time     | datetime      | YES  |     | NULL    |       |
| leaving_time   | datetime      | YES  |     | NULL    |       |
| email          | varchar(50)   | YES  |     | NULL    |       |
| number_of_persons | int(11)      | YES  |     | NULL    |       |
| special_status | tinyint(1)    | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
8 rows in set (0.008 sec)

MariaDB [restaurant]> describe Waiter;
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id             | varchar(255)  | NO   | PRI | NULL    |       |
| name          | varchar(50)   | YES  |     | NULL    |       |
| table_number   | int(11)       | YES  |     | NULL    |       |
| salary         | float         | YES  |     | NULL    |       |
| date_of_joining | datetime      | YES  |     | NULL    |       |
| rating         | float         | YES  |     | NULL    |       |
| email          | varchar(50)   | YES  |     | NULL    |       |
| address        | varchar(100)  | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
8 rows in set (0.008 sec)

MariaDB [restaurant]> 
```

```

| waiter_to_reservation |
+-----+
9 rows in set (0.004 sec)

MariaDB [restaurant]> show tables;
+-----+
| Tables_in_restaurant |
+-----+
| Billing                |
| Delivery              |
| Employee              |
| Reservation           |
| Waiter                |
| delivery_to_billing   |
| employee_to_waiter    |
| reservation_to_billing|
| waiter_to_reservation |
+-----+
9 rows in set (0.003 sec)

MariaDB [restaurant]> describe delivery_to_billing;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| delivery_id | varchar(255) | NO   | PRI | NULL    |       |
| billing_id  | varchar(255) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.011 sec)

MariaDB [restaurant]> 
```

```

| Delivery
| Employee
| Reservation
| Waiter
| delivery_to_billing
| employee_to_waiter
| reservation_to_billing
| waiter_to_reservation
+-----+
9 rows in set (0.003 sec)

MariaDB [restaurant]> describe delivery_to_billing;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| delivery_id | varchar(255) | NO   | PRI | NULL    |       |
| billing_id  | varchar(255) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.011 sec)

MariaDB [restaurant]> describe employee_to_waiter;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| employee_id | varchar(255) | YES  |     | NULL    |       |
| waiter_id   | varchar(255) | NO   | PRI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.008 sec)

MariaDB [restaurant]> 
```

```
9 rows in set (0.003 sec)

MariaDB [restaurant]> describe delivery_to_billing;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| delivery_id | varchar(255) | NO   | PRI | NULL    |       |
| billing_id  | varchar(255) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.011 sec)

MariaDB [restaurant]> describe employee_to_waiter;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| employee_id | varchar(255) | YES  |     | NULL    |       |
| waiter_id   | varchar(255) | NO   | PRI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.008 sec)

MariaDB [restaurant]> describe reservation_to_billing;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| reservation_id | varchar(255) | NO   | PRI | NULL    |       |
| billing_id     | varchar(255) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.011 sec)

MariaDB [restaurant]> 
```



```
2 rows in set (0.011 sec)

MariaDB [restaurant]> describe employee_to_waiter;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| employee_id | varchar(255) | YES  |     | NULL    |       |
| waiter_id   | varchar(255) | NO   | PRI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.008 sec)

MariaDB [restaurant]> describe reservation_to_billing;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| reservation_id | varchar(255) | NO   | PRI | NULL    |       |
| billing_id     | varchar(255) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.011 sec)

MariaDB [restaurant]> describe waiter_to_reservation;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| waiter_id   | varchar(255) | NO   |     | NULL    |       |
| reservation_id | varchar(255) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.005 sec)

MariaDB [restaurant]> 
```