

TONGXIANG
GO

同翔纺织机械

TONGXIANG
TEXTILE MACHINERY

WOVEN LABEL MACHINE



PICANOL GTMAX-I

GTMAX-I 剑杆织机 GTMAX-I Rapier Loom



· 上海同翔纺织机械有限公司
Shanghai Tongxiang Textile Machinery Co., Ltd



自由飞行式系统 (FF) 特为精细织物设计, 该系统极大程度避免了经纱受损, 适用纬纱品种广, 带植绒底布的走剑板是制造精细长丝经纱的最佳解决方案, 如室内装饰布。

The Free Flight system (FF) is specially designed for weaving delicate fabrics, providing maximum warp friendliness and filling versatility. The covered raceboard is the perfect solution for weaving fine filament warps as found in upholstery fabrics.



选纬器完全模块化, 可以在原有的4通道基础上逐渐增强通道, 直至12个通道。颜色和织花纹由微处理器或大提花机控制。最后, Quick Step模块可互换, 无机械传动, 所以无需保养或润滑。

The weft presenter is fully modular, allowing you to start with e.g. 4-color insertion and to add more channels. The GT-Max is available with up to 12-color insertion. The color and weave pattern are controlled by microprocessor or jacquard. Finally, the Quick Step modules are interchangeable, and there are no mechanical drives, so no maintenance or lubrication is required.



电子控制的卷取 (ETU) 和送经 (ELO) 作为标配安装在GT-Max织机上。二者均由SUMO型马达驱动, 两个马达通过一个集成控制箱进行同步。这种设计保证了织物质量上乘无瑕疵。

The electronically controlled take-up (ETU) and let-off (ELO) are fitted as standard on the GT-Max. Both are driven by SUMO-type motors which are synchronized by the integrated control box. This arrangement guarantees high quality fabric without marks.



油冷的Sumo主马达直接驱动织机, 无需皮带。离合器或刹车盘。高效能的Sumo主马达和主轴及开口机构的直接驱动 (专利) 相结合, 与传统的离合器和刹车盘配置相比, 可节省电能10%以上。由于Sumo马达在织造车间内释放的热量少, 所以空调的使用费用也减少了。

The oil-cooled Sumo main motor drives the weaving machine directly, without belt or clutch and brake. The combination of the highly energy-efficient Sumo motor with the direct drive (patented) of the main shaft and shedding motion results in power savings of more than 10% in comparison with conventional clutch and brake configurations. The energy cost for air conditioning is also reduced as the Sumo motor dissipates less heat in the weaving mill.

主要技术参数 Main Specification

Loom---Picanol	
Model : GTMAX-I Rapier Loom	型号 : GTMAX-I 剑杆织机
Speed : 550rpm(max)	速度 : 550rpm (最大值)
Working width : 1750mm(max)	工作宽度 : 1750 毫米 (最大值)
Repeats : 8 repeats for taffeta (1repeat = 20cm), 16 repeats for Satin (1repeat = 10cm)	循环组数 : 平面8组 (1组 = 20 cm), 缎面16组 (1组 = 10cm)
Control system : Parallel or serial connection Picanol PC Suite Multispeed Optispeed	控制系统 : 并联或串联 必佳乐PC套装 Multispeed Optispeed
Wrap let-off : Load-cell electronically controlled warp let-off system(ELO)	送经 : 荷载传感器电子控制的送经系统 (ELO)
Stop motion : 8 bar electrical 16 mm pitch	停车装置 : 8根电子停经条, 节距30毫米
Take-up : Double pressure roller Electronically controlled take-up system (ETU) Diameter of cloth roll: 580 mm	卷取 : 双压布辊 电子控制在卷取系统 (ETU) 布卷直径580毫米
Weft density : Electronic density adjustment from 6~200 picks/cm	纬密 : 电子密度调整从 6~200 根/厘米
Weft selector : 8 - 12 colors or yarn types (filling presenter with insertion position) [patented]	选纬 : 8-12色或不同纱线规格 (用选纬器定位引纬) [专利]
Weft finding : Automatic pickfinding and closed shed positioning [patented]	寻纬 : 全自动设定找纬和综平时间[专利]
Lubrication : By forced circulation of filtered oil Grouped grease points for manual lubrication	润滑 : 加压循环润滑油过滤润滑, 集中油脂加油点, 便于人工润滑
Warp beam Diameter: 805mm	经轴直径: 805mm
Cloth take-up : PBM Batching motion system for diameters up to 1500 mm	织物卷取 : 大卷装装置, 卷布直径最大可达1500mm
Power : 7.5kw of main motor	功率 : 7.5KW 主电机
Weight : 6500 Kgs (Approx)	重量 : 6500 公斤 (约)
JACQUARD 提花	
Model : Electronic jacquard (SX1344/2688)	型号 : 电子提花 (史陶比尔SX1344/2688)
Hooks : 1048/2688 hooks	针数 : 1048/2688 针
Electronic control : Independent Stäubli JC7 control unit, synchronized with the weaving machine	电子控制 : 独立式史陶比尔JC7控制箱, 与织机同步
Harness : Carbon fiber with spring pull down. Junction is covered by nylon sheaths.	通丝 : 碳纤维丝, 弹簧回综, 覆盖尼龙护套。
Power : 2.5kw (max)	(最大) 功率 : 2.5kw
Weight : Approx.1200 kgs	重量 : Approx.1200 公斤
Weft Feeder 电子储纬器	
Model: Iro Laser G2	型号 : Iro Laser G2
DIMENSION & WEIGHT 尺寸与重量	
整机尺寸/Machine Measurement	5700宽/W x 2200纵/L x 3800高/H mm
Approx 7000kgs (satin) and 6500kgs(taffeta)	缎面机: 7000kgs (satin), 平面机: 6500kgs (taffeta)
Power Supply: 3 phase, 380V, 50HZ, ±10% tolerance	电源/Power Supply 三相, 380伏, 50赫兹, 允许±10%偏差 3 phase, 380V, 50HZ, ±10% tolerance

ITEMA R9500

R9500剑杆织机 R9500 Rapier Loom



· 上海同翔纺织机械有限公司
Shanghai Tongxiang Textile Machinery Co., Ltd



主马达是基于电子驱动及无刷马达技术设计的，可通过触摸屏方便地调节车速。传统的齿轮传动及机械部件因此减少了，相比其前一代产品节约了达20%的能耗。零部件的削减和维护成本的降低更让R9500剑杆织机成为一款增值机型。

简约，可靠，无需维护，无需冷却系统。归功于专用软件，现在无需工具只要在用户界面上输入想要的设定参数即可调整平综高度。

The main drive is based on an electronic drive and brushless motor technology which provides easy touch-screen adjustment for machine speed. Traditional gearing and mechanical parts have been minimized, saving up to 20% in energy cost compared to its predecessors; also providing added value by fewer spare parts and maintenance. Simple, reliable, maintenance free. No cooling system required. Thanks to dedicated software, no tools are required to change harness crossing; simply input the desired setting through the user interface.



全新SK传剑机构的设计可满足高速织造及广泛的品种适应性。当需要引入不同种类纬纱时，SK传剑系统是当今市场上最为先进的导剑系统。超轻，陶瓷镀层，剑头一体化设计，SK传剑系统可提供持续的高速表现和更低的磨损。

其他关键因素有：

- 送纬夹头的位置非常靠近钢筘，在提升织造效率的同时也保障了可靠的品质。
- 接纬夹头内部置有永磁铁，这一开口设计独一无二且享有专利。

The new SK Transfer System is engineered for high speed and versatility. While providing for a wide array of weft yarns, the SK System is the most advanced transfer system on the market today. With an ultralight, ceramic coated, one piece design rapier, the SK System provides consistent, high speed performance and less wear. Other key points:

- The insertion gripper is positioned very close to the reed promoting increased efficiency and dependable quality.
- The receiving gripper features a unique, patented opening system utilizing a permanent magnet integrated within the gripper.



R9500剑杆织机有两种纬纱剪刀可供选择，以适应所有织造需求。

对于简单的纬纱，客户可以选择新设计的纬纱剪刀Rotocut。

对于复杂风格，和/或多种纬纱配置，一种独一无二电子剪刀可应要求供于选择。应用创新技术以及由微电脑芯片操控，可对每色纬纱设定独立的剪纬时间。有了这个精确的工具可有效提高工作效率减少浪费。

The R9500 Weaving machine has a double option for the weft cutter to fit all weaving needs.

For simple wefts, Customers can choose the newly designed Rotocut.

For more complex styles and/or multiple weft configurations, a unique electronic cutter is available upon request. Utilizing innovative technology and controlled by the microprocessor, independent cutting times can set for each weft/color. A precise tool that works to increase efficiency and minimize waste.



可配置4色，8色或12色。

全新设计，最大化地提升多样性和可靠性。无需维护，由微电脑芯片驱动控制，精准协调每个选纬指的动作，幅度轻柔缓和能有效避免相邻纬纱间的干扰。此紧凑的设计使引导的纬纱能极为贴近剪纬位置，从而确保有效控制。

对于挡车工机修工来说，此装置操作简便，可减少剑头及生产品种更换造成的停车时间

Available for configurations for 4, 8 or 12 colors.

Completely re-designed to promote the maximum in versatility and reliability. Maintenance free, driven & controlled by the microprocessor. Fine tuning the stroke of the selected finger promotes a gentle movement and works to eliminate interference with adjacent wefts. Its compact design allows the selected weft to be presented in close proximity to the cutting position insuring firm control.

The device is easily accessible for weaving & maintenance personnel reducing downtime for weft repairs and style changes.

主要技术参数 Main Specification

Loom---Vamatex	
Model : R9500 Rapier Loom	型号 : R9500剑杆织机
Working width : 1900mm(max)	工作宽度 : 1900 毫米 (最大值)
Repeats : 9 repeats for taffeta (1repeat = 20cm), 18 repeats for Satin (1repeat = 10cm)	循环组数 : 平面9组 (1组 = 20 cm), 缎面18组 (1组 = 10cm)
Transfer system : SK Guided rapier "monorail" type hooks. FPA (Free Positive Approach) "Free flying" on a felt covered race.	传剑系统 : 单剑导钩式传剑系统 自由穿梭
Wrap let-off : Electronically controlled	送经 : 电子控制送经
Warp stop motion : Electric or electronic warp stop motion with 6-8 rows.	停经装置 : 普通型或电子型的6列或8列停经架
Take-up : Electronic	卷取 : 电子卷取
Weft density Picks/cm : Standard: 4-84 picks/cm 1-20/8-150 picks/cm on request. Automatic weft density programmable in dobby pattern.	纬密 : 标配 : 4-84纬/厘米 1-20及8-150纬/厘米应要求
Weft Selector: Electronic weft selector 8 or 12 colours.	引纬 : 电子选纬器 : 8色或12色
Weft Finding : Automatic weft pick finding with variable	寻纬 : 可自动寻纬系统
Warp Beam : Single beam. Diameter 800 mm . Upper Beam 800mm ,	经轴 : 单经轴 直径 : 800mm 上经轴 : 800mm
Fabric take up and Cloth roller: Electronic controlled take-up Cloth roller diameter up to 550mm External batching motion	织物卷取 : 织物卷曲和卷布辊 : 电子控制卷曲卷布直径 : 最大550mm
JACQUARD 提花	
Model : Electronic jacquard (Staubli SX2304)	型号 : 电子提花 (史陶比尔SX2304)
Hooks : 2304 hooks	针数 : 2304 针
Controller : By computer	控制器 : 电脑控制
Harness : Carbon fiber with spring pull down. Junction is covered by nylon sheaths.	通丝 : 碳纤维丝, 弹簧回综, 覆盖尼龙护套。
Power : 2.5kw (max)	(最大) 功率 : 2.5kw
Weight : Approx.1200 kgs	重量 : Approx.1200 公斤
Weft Feeder 电子储纬器	
Model: Iro Laser G2	型号 : Iro Laser G2
DIMENSION & WEIGHT 尺寸与重量	
整机尺寸/Machine Measurement Approx 7000kgs (satin) and 6500kgs (taffeta)	5700宽/W x 2200纵/L x 3800高/H mm 缎面机: 7000kgs (satin), 平面机: 6500kgs (taffeta)
Power Supply: 3 phase, 380V, 50HZ, ±10% tolerance	电源/Power Supply 三相, 380伏, 50赫兹, 允许±10%偏差 3 phase, 380V, 50HZ, ±10% tolerance

ITEMA R9000

R9000剑杆织机 R9000 Rapier Loom



· 上海同翔纺织机械有限公司
Shanghai Tongxiang Textile Machinery Co., Ltd



主马达是基于电子驱动及无刷马达技术设计的，可通过触摸屏方便地调节车速。传统的齿轮传动及机械部件因此减少了，相比其前一代产品节约了达20%的能耗。零部件的削减和维护成本的降低更让R9000剑杆织机成为一款增值机型。

简约，可靠，无需维护，无需冷却系统。归功于专用软件，现在无需工具只要在用户界面上输入想要的设定参数即可调整平衡高度。

The main drive is based on an electronic drive and brushless motor technology which provides easy touch-screen adjustment for machine speed. Traditional gearing and mechanical parts have been minimized, saving up to 20% in energy cost compared to its predecessors; also providing added value by fewer spare parts and maintenance. Simple, reliable, maintenance free. No cooling system required. Thanks to dedicated software, no tools are required to change harness crossing; simply input the desired setting through the user interface.

全新SK传剑机构的设计可满足高速织造及广泛的品种适应性。当需要引入不同种类纬纱时，SK传剑系统是当今市场上最为先进的传剑系统。超轻，陶瓷镀层，剑头一体化设计，SK传剑系统可提供持续的高速表现和更低的磨损。

其他关键因素有：

- 送纬夹头的位置非常靠近钢筘，在提升织造效率的同时也保障了可靠的品质。
- 接纬夹头内部置有永磁体，这一开口设计独一无二且享有专利。

The new SK Transfer System is engineered for high speed and versatility. While providing for a wide array of weft yarns, the SK System is the most advanced transfer system on the market today. With an ultralight, ceramic coated, one piece design rapier, the SK System provides consistent, high speed performance and less wear. Other key points:

- The insertion gripper is positioned very close to the reed promoting increased efficiency and dependable quality.
- The receiving gripper features a unique, patented opening system utilizing a permanent magnet integrated within the gripper.

R9000剑杆织机有两种纬纱剪刀可供选择，以适应所有织造需求。

对于简单的纬纱，客户可以选择新设计的纬纱剪刀Rotocut。

对于复杂风格，和/或多种纬纱配置，一种独一无二的电子剪刀可应要求供于选择。应用创新技术以及由微电脑芯片操控，可对每色纬纱设定独立的剪纬时间。有了这个精确的工具可有效提高工作效率减少浪费。

The R9000 Weaving machine has a double option for the weft cutter to fit all weaving needs.

For simple wefts, Customers can choose the newly designed Rotocut.

For more complex styles and/or multiple weft configurations, a unique electronic cutter is available upon request. Utilizing innovative technology and controlled by the microprocessor, independent cutting times can set for each weft/color. A precise tool that works to increase efficiency and minimize waste.

可配置4色，8色或12色。

全新设计，最大化地提升多样性和可靠性。无需维护，由微电脑芯片驱动控制，精准协调每个选纬指的动作，幅度轻柔缓和能有效避免相邻纬纱间的干扰。此紧凑的设计使引导的纬纱能极为贴近剪纬位置，从而确保有效控制。

对于挡车工机修工来说，此装置操作简便，能减少剑头及生产品种更换造成的停车时间

Available for configurations for 4, 8 or 12 colors.

Completely re-designed to promote the maximum in versatility and reliability. Maintenance free, driven & controlled by the microprocessor. Fine tuning the stroke of the selected finger promotes a gentle movement and works to eliminate interference with adjacent wefts. Its compact design allows the selected weft to be presented in close proximity to the cutting position insuring firm control.

The device is easily accessible for weaving & maintenance personnel reducing downtime for weft repairs and style changes.

主要技术参数 Main Specification

Loom---Vamatex	
Model : R9000 Rapier Loom	型号：R9000剑杆织机
Working width : 1900mm(max)	工作宽度：1900 毫米（最大值）
Repeats : 9 repeats for taffeta (1repeat = 20cm), 18 repeats for Satin (1repeat = 10cm)	循环组数：平面9组（1组 = 20 cm），缎面18组（1组 = 10cm）
Transfer system : SK Guided rapier "monorail" type hooks. FPA (Free Positive Approach) "Free flying" on a felt covered race.	传剑系统：单剑导钩式传剑系统 自由穿梭
Wrap let-off : Electronically controlled	送经：电子控制送经
Warp stop motion : Electric or electronic warp stop motion with 6-8 rows.	停经装置：普通型或电子型的6列或8列停经架
Take-up : Electronic	卷取：电子卷取
Weft density Picks/cm : Standard: 4-84 picks/cm 1-20/8-150 picks/cm on request. Automatic weft density programmable in dobby pattern.	纬密：标配：4-84纬/厘米 1-20及8-150纬/厘米应要求
Weft Selector: Electronic weft selector 8 or 12 colours.	引纬：电子选纬器：8色或12色
Weft Finding : Automatic weft pick finding with variable	寻纬：可调自动寻纬系统
Warp Beam : Single beam. Diameter 800 mm . Upper Beam 800mm .	经轴：单经轴 直径：800mm 上经轴：800mm
Fabric take up and Cloth roller: Electronic controlled take-up. Cloth roller diameter up to 550mm External batching motion	织物卷取：织物卷曲和卷布辊： 电子控制卷曲卷布直径：最大550mm
JACQUARD 提花	
Model : Electronic jacquard (BONAS JI2400)	型号：电子提花（博纳斯 JI2400）
Hooks : 2400 hooks	针数：2400 针
Controller : By computer	控制器：电脑控制
Harness : Carbon fiber with spring pull down. Junction is covered by nylon sheaths.	通丝：碳纤维丝，弹簧回综，覆盖尼龙护套。
Power : 2.5kw (max)	（最大）功率：2.5kw
Weight : Approx.1200 kgs	重量：Approx.1200 公斤
Weft Feeder 电子储纬器	
Model: Iro Laser G2	型号：Iro Laser G2
DIMENSION & WEIGHT 尺寸与重量	
整机尺寸/Machine Measurement Approx 7000kgs (satin) and 6500kgs(taffeta)	5700宽/W x 2200纵/L x 3800高/H mm 缎面机: 7000kgs (satin), 平面机: 6500kgs (taffeta)
Power Supply: 3 phase, 380V, 50HZ, ±10% tolerance	电源/Power Supply 三相, 380伏, 50赫兹, 允许±10%偏差 3 phase, 380V, 50HZ, ±10% tolerance