

Python Advanced Assignment 12

1. Does assigning a value to a string's indexed character violate Python's string immutability ?

Ans: String's indexed character cannot to be assigned a New value , as Strings are immutable.

Example:

```
name = "Reinforcement"
print(id(name)) #73472
name[0] = "V" # Raises TypeError
```

2. Does using the += operator to concatenate strings violate Python's string immutability? Why or why not ?

Ans: += operator is used to concatenate strings, it does not violate Python's string immutability Property. Because doing so new creates a new association with data and variable. E.g. str_1="a" and str_1+="b" . effect of this statements to create string ab and reassign it to variable str_1, any string data is not actually modified.

```
In [1]: str_1 = 'a'
print(id(str_1))
str_1 += 'b'
print(id(str_1)) # Does not Modify existing string, Creates a New String Object

2122154235312
2122234490608
```

3. In Python, how many different ways are there to index a character?

Ans: A Character in string can be indexed using string name followed by index number of character in square bracket. **Positive Indexing** i.e. first index is 0 and so on, or **Negative Indexing** i.e. last letter is -1 and so on can be used to index a character

```
In [2]: in_string = "iNeuron Full Stack Data Science"
print(in_string[9],in_string[10],in_string[2]) # Positive Indexing
print(in_string[-1],in_string[-5],in_string[-2]) # Negative Indexing

u l e
e i c
```

4. What is the relationship between indexing and slicing?

Ans: We can access elements of sequence datatypes by using slicing and indexing. Indexing is used to obtaining individual element while slicing for sequence of elements.

```
In [3]: in_string = "iNeuron Full Stack Data Science"
print(in_string[1],in_string[3],in_string[5]) # Indexing
print(in_string[1:15]) # Slicing

N u o
Neuron Full St
```

5. What is an indexed character's exact data type? What is the data form of a slicing-generated substring?

Ans: Indexed characters and sliced substrings have datatype String.

```
In [4]: in_string = "iNeuron Full Stack Data Science"
print(type(in_string[3])) # Indexing -> str
print(type(in_string[1:10])) # Indexing -> str

<class 'str'>
<class 'str'>
```

6. What is the relationship between string and character "types" in Python?

Ans: Object that contains sequence of character datatypes are called String.

7. Identify at least two operators & one method that allow you to combine one or

more smaller strings to create a larger string ?

Ans: `+`, `+=` and `*` allow to combine one or more smaller strings to create a larger string. `<string>.join(<sep>)` method joins element of iterable type like list and tuple to get a combined string.

```
In [5]: in_string = 'iNeuron '  
in_string += 'Full Stack Data Science'  
print(in_string + ' FSDS')  
print('FSDS '*3)  
print(" ".join(['I','N','E','U','R','O','N'])) # List Iterable  
print(" ".join(('I','N','E','U','R','O','N')).lower()) # Tuple Iterable
```

```
iNeuron Full Stack Data Science FSDS  
FSDS FSDS FSDS  
I N E U R O N  
i n e u r o n
```

8. What is the benefit of first checking the target string with in or not in before using the index method to find a substring ?

Ans: Checking the target string with in or not Operators before using the index method to find a substring just helps confirming availability of substring and thus avoid raising of **ValueError**.

Example:

```
in_string = "ineuron"  
in_string.index('x') # Raises ValueError  
in_string.index('u') # 3
```

9. Which operators and built-in string methods produce simple Boolean (true/false) results?

Ans: The String Operators and built-in methods to Produce Simple Boolean (True/False) Results are:

- in
- not
- `<string>.isalpha()`
- `<string>.isalnum()`
- `<string>.isdecimal()`
- `<string>.isdigit()`
- `<string>.islower()`
- `<string>.isnumeric()`
- `<string>.isprintable()`
- `<string>.isspace()`
- `<string>.istitle()`

Loading [MathJax]/jax/output/CommonHTML/fonts/TeX/fontdata.js