

Event Booking Platform - Project Report

Project Title

Event Booking Platform

Project Info

This report includes only core feature/application code from backend configuration and feature modules, plus the frontend source folder.

Why Use My Platform

- Organized backend by feature modules for maintainability.
- Clear frontend source structure for scalable UI development.
- API-first architecture with reusable config and business logic separation.

Folder Structure

```
backend/config
├─ database.js
└─ schema.js
backend/features
├─ booking
│   ├── booking.controller.js
│   └─ booking.router.js
├─ events
│   ├── event.controller.js
│   └─ event.router.js
└─ user
    ├── user.controller.js
    └─ user.router.js
frontend/src
├─ api
│   └─ axios.js
├─ App.css
├─ App.jsx
├─ assets
│   ├── hero.png
│   ├── react.svg
│   └─ vite.svg
├─ context
│   └─ AuthContext.jsx
├─ index.css
├─ main.jsx
├─ Navbar.jsx
└─ pages
    ├── CreateEvent.jsx
    ├── Events.jsx
    └─ Login.jsx
```

- └─ MyBookings.jsx
- └─ MyEvents.jsx
- └─ Profile.jsx
- └─ Signup.jsx
- └─ SingleEvent.jsx

10 directories, 26 files

Selected Code Listing

backend/config/database.js

```
import mongoose from 'mongoose';

export const connectDB = async () => {
  try {
    const mongoURI = process.env.MONGO_URI ||
'mongodb://localhost:27017/eventbooking';

    const conn = await mongoose.connect(mongoURI);

    console.log(`🌿 MongoDB Connected: ${conn.connection.host}`);
    console.log(`📖 Database: ${conn.connection.name}`);

    // Handle connection events
    mongoose.connection.on('error', (err) => {
      console.error('❌ MongoDB connection error:', err);
    });

    mongoose.connection.on('disconnected', () => {
      console.log('🛑 MongoDB disconnected');
    });

    // Graceful shutdown
    process.on('SIGINT', async () => {
      try {
        await mongoose.connection.close();
        console.log('🛑 MongoDB connection closed due to app termination');
        process.exit(0);
      } catch (error) {
        console.error('❌ Error during MongoDB disconnection:', error);
        process.exit(1);
      }
    });

    return conn;
  } catch (error) {
    console.error('❌ Database connection failed:', error.message);
    process.exit(1);
  }
}
```

```

};

export const disconnectDB = async () => {
  try {
    await mongoose.disconnect();
    console.log('🔌 MongoDB disconnected');
  } catch (error) {
    console.error('❌ Error disconnecting from MongoDB:', error);
  }
};

```

backend/config/schema.js

```

import mongoose from 'mongoose';

const { Schema, model } = mongoose;

// User
const userSchema = new Schema({
  name: { type: String, required: true },
  email: { type: String, required: true, unique: true },
  password: { type: String, required: true },
});

// Event
const eventSchema = new Schema({
  title: { type: String, required: true },
  description: { type: String },
  date: { type: Date, required: true },
  location: { type: String, required: true },
  capacity: { type: Number, required: true },
  userID: { type: String, required: true },
});

// Booking
const bookingSchema = new Schema({
  userID: { type: String, required: true },
  eventID: { type: String, required: true },
  seats: { type: Number, default: 1 },
});

export const User = model('User', userSchema);
export const Event = model('Event', eventSchema);
export const Booking = model('Booking', bookingSchema);

```

backend/features/booking/booking.controller.js

```

import { Booking, Event, User } from "../../config/schema.js";

```

```

export const createBooking = async (req, res) => {
  try {
    const booking = await Booking.create(req.body);
    res.status(201).json(booking);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const getBookingById = async (req, res) => {
  try {
    const booking = await Booking.findById(req.params.id);
    if (!booking) return res.status(404).json({ message: 'Booking not found' });
    res.json(booking);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const getBookingsByUser = async (req, res) => {
  try {
    const bookings = await Booking.find({ userID: req.params.userID });
    res.json(bookings);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const getBookingsByEvent = async (req, res) => {
  try {
    const bookings = await Booking.find({ eventID: req.params.eventID });
    res.json(bookings);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const getParticipantsByEvent = async (req, res) => {
  try {
    const { eventID } = req.params;
    const { userID } = req.query;

    const event = await Event.findById(eventID);
    if (!event) return res.status(404).json({ message: 'Event not found' });
    if (!userID || event.userID !== userID) {
      return res.status(403).json({ message: 'Not allowed to view participants for this event' });
    }

    const bookings = await Booking.find({ eventID });
    const participants = await Promise.all(
      bookings.map(async (booking) => {

```

```

        const participant = await User.findById(booking.userID).select('name
email');
        return {
            bookingID: booking._id,
            userID: booking.userID,
            seats: booking.seats,
            name: participant?.name ?? 'Unknown User',
            email: participant?.email ?? 'unknown@email.com',
        };
    })
    );

    res.json(participants);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const deleteBooking = async (req, res) => {
  try {
    const booking = await Booking.findByIdAndDelete(req.params.id);
    if (!booking) return res.status(404).json({ message: 'Booking not found' });
    res.json({ message: 'Booking deleted' });
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

```

backend/features/booking/booking.router.js

```

import express from 'express';
import { createBooking, deleteBooking, getBookingById, getBookingsByEvent,
getBookingsByUser, getParticipantsByEvent } from './booking.controller.js';

const BookingRouter = express.Router();

BookingRouter.post('/', createBooking);
BookingRouter.get('/user/:userID', getBookingsByUser);
BookingRouter.get('/event/:eventID', getBookingsByEvent);
BookingRouter.get('/event/:eventID/participants', getParticipantsByEvent);
BookingRouter.get('/:id', getBookingById);
BookingRouter.delete('/:id', deleteBooking);

export default BookingRouter;

```

backend/features/events/event.controller.js

```
import { Event } from "../../config/schema.js";

export const createEvent = async (req, res) => {
  try {
    const event = await Event.create(req.body);
    res.status(201).json(event);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const getAllEvents = async (req, res) => {
  try {
    const events = await Event.find();
    res.json(events);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const getEventsByUser = async (req, res) => {
  try {
    const events = await Event.find({ userID: req.params.userID });
    res.json(events);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const getEventById = async (req, res) => {
  try {
    const event = await Event.findById(req.params.id);
    if (!event) return res.status(404).json({ message: 'Event not found' });
    res.json(event);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const updateEvent = async (req, res) => {
  try {
    const event = await Event.findByIdAndUpdate(req.params.id, req.body, { new: true });
    if (!event) return res.status(404).json({ message: 'Event not found' });
    res.json(event);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const deleteEvent = async (req, res) => {
```

```

try {
  const event = await Event.findByIdAndDelete(req.params.id);
  if (!event) return res.status(404).json({ message: 'Event not found' });
  res.json({ message: 'Event deleted' });
} catch (err) {
  res.status(500).json({ message: err.message });
}
};

```

backend/features/events/event.router.js

```

import express from 'express';
import { createEvent, deleteEvent, getAllEvents, getEventById, getEventsByUser,
updateEvent } from './event.controller.js';

const EventRouter = express.Router();

EventRouter.post('/', createEvent);
EventRouter.get('/', getAllEvents);
EventRouter.get('/user/:userID', getEventsByUser);
EventRouter.get('/:id', getEventById);
EventRouter.put('/:id', updateEvent);
EventRouter.delete('/:id', deleteEvent);

export default EventRouter;

```

backend/features/user/user.controller.js

```

import bcrypt from 'bcrypt';
import { User } from '../../../config/schema.js';

export const signup = async (req, res) => {
  try {
    const { name, email, password } = req.body;

    const existing = await User.findOne({ email });
    if (existing) return res.status(400).json({ message: 'Email already in use' });

    const hashed = await bcrypt.hash(password, 10);
    const user = await User.create({ name, email, password: hashed });

    res.status(201).json({ message: 'User created', userID: user._id });
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

export const login = async (req, res) => {

```

```

try {
  const { email, password } = req.body;

  const user = await User.findOne({ email });
  if (!user) return res.status(404).json({ message: 'User not found' });

  const match = await bcrypt.compare(password, user.password);
  if (!match) return res.status(401).json({ message: 'Invalid credentials' });

  res.json({ userID: user._id, name: user.name, email: user.email });
} catch (err) {
  res.status(500).json({ message: err.message });
}
};

export const getProfile = async (req, res) => {
  try {
    const user = await User.findById(req.params.id).select('-password');
    if (!user) return res.status(404).json({ message: 'User not found' });

    res.json(user);
  } catch (err) {
    res.status(500).json({ message: err.message });
  }
};

```

backend/features/user/user.router.js

```

import express from 'express';
import { getProfile, login, signup } from './user.controller.js';

const UserRouter = express.Router();

UserRouter.post('/signup', signup);
UserRouter.post('/login', login);
UserRouter.get('/profile/:id', getProfile);

export default UserRouter;

```

frontend/src/api/axios.js

```

import axios from 'axios';

const api = axios.create({
  baseURL: 'http://localhost:5000',
});

export default api;

```


frontend/src/App.css

frontend/src/App.jsx

```
import { BrowserRouter, Routes, Route } from 'react-router-dom';
import { AuthProvider } from '../context/AuthContext'; // ← import this
import Events from './pages/Events';
import SingleEvent from './pages/SingleEvent';
import CreateEvent from './pages/CreateEvent';
import Login from './pages/Login';
import Signup from './pages/Signup';
import Profile from './pages/Profile';
import MyBookings from './pages/MyBookings';
import MyEvents from './pages/MyEvents';
import Navbar from './Navbar';

export default function App() {
  return (
    <BrowserRouter>
      <AuthProvider>          {/* ← must wrap everything */}
        <div className="app-shell">
          <Navbar/>           {/* ← place Navbar here */}
          <Routes>
            <Route path="/events" element={<Events />} />
            <Route path="/events/:id" element={<SingleEvent />} />
            <Route path="/create-event" element={<CreateEvent />} />
            <Route path="/login" element={<Login />} />
            <Route path="/signup" element={<Signup />} />
            <Route path="/profile" element={<Profile />} />
            <Route path="/my-bookings" element={<MyBookings />} />
            <Route path="/my-events" element={<MyEvents />} />
            <Route path="*" element={<Events />} />
          </Routes>
        </div>
      </AuthProvider>
    </BrowserRouter>
  );
}
```

frontend/src/assets/react.svg

```
<svg xmlns="http://www.w3.org/2000/svg" xmlns:xlink="http://www.w3.org/1999/xlink"
aria-hidden="true" role="img" class="iconify iconify--logos" width="35.93"
height="32" preserveAspectRatio="xMidYMid meet" viewBox="0 0 256 228"><path
fill="#00D8FF" d="M210.483 73.824a171.49 171.49 0 0 0-8.24-2.597c.465-1.9.893-3.777
1.273-5.621c6.238-30.281 2.16-54.676-11.769-62.708c-13.355-7.7-35.196.329-57.254
```

19.526a171.23 171.23 0 0 0-6.375 5.848a155.866 155.866 0 0 0-4.241-3.917C100.759
3.829 77.587-4.822 63.673 3.233C50.33 10.957 46.379 33.89 51.995 62.588a170.974
170.974 0 0 0 1.892 8.48c-3.28.932-6.445 1.924-9.474 2.98C17.309 83.498 0 98.307 0
113.668c0 15.865 18.582 31.778 46.812 41.427a145.52 145.52 0 0 0 6.921 2.165a167.467
167.467 0 0 0-2.01 9.138c-5.354 28.2-1.173 50.591 12.134 58.266c13.744 7.926
36.812-.22 59.273-19.855a145.567 145.567 0 0 0 5.342-4.923a168.064 168.064 0 0 0
6.92 6.314c21.758 18.722 43.246 26.282 56.54 18.586c13.731-7.949 18.194-32.003 12.4-
61.268a145.016 145.016 0 0 0-1.535-6.842c1.62-.48 3.21-.974 4.76-1.488c29.348-9.723
48.443-25.443 48.443-41.52c0-15.417-17.868-30.326-45.517-39.844Zm-6.365 70.984c-
1.4.463-2.836.91-4.3 1.345c-3.24-10.257-7.612-21.163-12.963-32.432c5.106-11 9.31-
21.767 12.459-31.957c2.619.758 5.16 1.557 7.61 2.4c23.69 8.156 38.14 20.213 38.14
29.504c0 9.896-15.606 22.743-40.946 31.14Zm-10.514 20.834c2.562 12.94 2.927 24.64
1.23 33.787c-1.524 8.219-4.59 13.698-8.382 15.893c-8.067 4.67-25.32-1.4-43.927-
17.412a156.726 156.726 0 0 1-6.437-5.87c7.214-7.889 14.423-17.06 21.459-
27.246c12.376-1.098 24.068-2.894 34.671-5.345a134.17 134.17 0 0 1 1.386
6.193ZM87.276 214.515c-7.882 2.783-14.16 2.863-17.955.675c-8.075-4.657-11.432-
22.636-6.853-46.752a156.923 156.923 0 0 1 1.869-8.499c10.486 2.32 22.093 3.988
34.498 4.994c7.084 9.967 14.501 19.128 21.976 27.15a134.668 134.668 0 0 1-4.877
4.492c-9.933 8.682-19.886 14.842-28.658 17.94ZM50.35 144.747c-12.483-4.267-22.792-
9.812-29.858-15.863c-6.35-5.437-9.555-10.836-9.555-15.216c0-9.322 13.897-21.212
37.076-29.293c2.813-.98 5.757-1.905 8.812-2.773c3.204 10.42 7.406 21.315 12.477
32.332c-5.137 11.18-9.399 22.249-12.634 32.792a134.718 134.718 0 0 1-6.318-
1.979Zm12.378-84.26c-4.811-24.587-1.616-43.134 6.425-47.789c8.564-4.958 27.502 2.111
47.463 19.835a144.318 144.318 0 0 1 3.841 3.545c-7.438 7.987-14.787 17.08-21.808
26.988c-12.04 1.116-23.565 2.908-34.161 5.309a160.342 160.342 0 0 1-1.76-
7.887Zm110.427 27.268a347.8 347.8 0 0 0-7.785-12.803c8.168 1.033 15.994 2.404 23.343
4.08c-2.206 7.072-4.956 14.465-8.193 22.045a381.151 381.151 0 0 0-7.365-13.322Zm-
45.032-43.861c5.044 5.465 10.096 11.566 15.065 18.186a322.04 322.04 0 0 0-
30.257-.006c4.974-6.559 10.069-12.652 15.192-18.18ZM82.802 87.83a323.167 323.167 0 0
0-7.227 13.238c-3.184-7.553-5.909-14.98-8.134-22.152c7.304-1.634 15.093-2.97 23.209-
3.984a321.524 321.524 0 0 0-7.848 12.897Zm8.081 65.352c-8.385-.936-16.291-2.203-
23.593-3.793c2.26-7.3 5.045-14.885 8.298-22.6a321.187 321.187 0 0 0 7.257
13.246c2.594 4.48 5.28 8.868 8.038 13.147Zm37.542 31.03c-5.184-5.592-10.354-11.779-
15.403-18.433c4.902.192 9.899.29 14.978.29c5.218 0 10.376-.117 15.453-.343c-4.985
6.774-10.018 12.97-15.028 18.486Zm52.198-57.817c3.422 7.8 6.306 15.345 8.596 22.52c-
7.422 1.694-15.436 3.058-23.88 4.071a382.417 382.417 0 0 0 7.859-13.026a347.403
347.403 0 0 0 7.425-13.565Zm-16.898 8.101a358.557 358.557 0 0 1-12.281 19.815a329.4
329.4 0 0 1-23.444.823c-7.967 0-15.716-.248-23.178-.732a310.202 310.202 0 0 1-
12.513-19.846h.001a307.41 307.41 0 0 1-10.923-20.627a310.278 310.278 0 0 1 10.89-
20.637l-.001.001a307.318 307.318 0 0 1 12.413-19.761c7.613-.576 15.42-.876
23.31-.876H128c7.926 0 15.743.303 23.354.883a329.357 329.357 0 0 1 12.335
19.695a358.489 358.489 0 0 1 11.036 20.54a329.472 329.472 0 0 1-11 20.722Zm22.56-
122.124c8.572 4.944 11.906 24.881 6.52 51.026c-.344 1.668-.73 3.367-1.15 5.09c-
10.622-2.452-22.155-4.275-34.23-5.408c-7.034-10.017-14.323-19.124-21.64-
27.008a160.789 160.789 0 0 1 5.888-5.4c18.9-16.447 36.564-22.941 44.612-18.3ZM128
90.808c12.625 0 22.86 10.235 22.86 22.86s-10.235 22.86-22.86-22.86-10.235-
22.86-22.86s10.235-22.86 22.86-22.86Z"></path></svg>

frontend/src/assets/vite.svg

```
<svg xmlns="http://www.w3.org/2000/svg" width="77" height="47" fill="none" aria-  
labelledby="vite-logo-title" viewBox="0 0 77 47"><title id="vite-logo-  
title">Vite</title><style>.parenthesis{fill:#000}@media (prefers-color-scheme:dark)  
{.parenthesis{fill:#fff}}</style><path fill="#9135ff" d="M40.151 45.71c-.663.844-  
2.02.374-2.02-.699V34.708a2.26 2.26 0 0 0-2.262-2.262H24.493c-.92 0-1.457-1.04-.92-  
1.788l7.479-10.471c1.07-1.498 0-3.578-1.842-3.578H15.443c-.92 0-1.456-1.04-.92-  
1.788l9.696-13.576c.213-.297.556-.474.92-.474h28.894c.92 0 1.456 1.04.92 1.788l-7.48  
10.472c-1.07 1.497 0 3.578 1.842 3.578h11.376c.944 0 1.474 1.087.89 1.83L40.153  
45.712z"/><mask id="a" width="48" height="47" x="14" y="0"  
maskUnits="userSpaceOnUse" style="mask-type:alpha"><path fill="#000" d="M40.047  
45.71c-.663.843-2.02.374-2.02-.699V34.708a2.26 2.26 0 0 0-2.262-2.262H24.389c-.92 0-  
1.457-1.04-.92-1.788l7.479-10.472c1.07-1.497 0-3.578-1.842-3.578H15.34c-.92 0-1.456-  
1.04-.92-1.788l9.696-13.575c.213-.297.556-.474.92-.474H53.93c.92 0 1.456 1.04.92  
1.788L47.37 13.03c-1.07 1.498 0 3.578 1.842 3.578h11.376c.944 0 1.474 1.088.89  
1.831L40.049 45.712z"/></mask><g mask="url(#a)"><g filter="url(#b)"><ellipse  
cx="5.508" cy="14.704" fill="#eee6ff" rx="5.508" ry="14.704"  
transform="rotate(269.814 20.96 11.29)scale(-1 1)"/></g><g filter="url(#c)"><ellipse  
cx="10.399" cy="29.851" fill="#eee6ff" rx="10.399" ry="29.851"  
transform="rotate(89.814 -16.902 -8.275)scale(1 -1)"/></g><g filter="url(#d)">  
<ellipse cx="5.508" cy="30.487" fill="#8900ff" rx="5.508" ry="30.487"  
transform="rotate(89.814 -19.197 -7.127)scale(1 -1)"/></g><g filter="url(#e)">  
<ellipse cx="5.508" cy="30.599" fill="#8900ff" rx="5.508" ry="30.599"  
transform="rotate(89.814 -25.928 4.177)scale(1 -1)"/></g><g filter="url(#f)">  
<ellipse cx="5.508" cy="30.599" fill="#8900ff" rx="5.508" ry="30.599"  
transform="rotate(89.814 -25.738 5.52)scale(1 -1)"/></g><g filter="url(#g)"><ellipse  
cx="14.072" cy="22.078" fill="#eee6ff" rx="14.072" ry="22.078"  
transform="rotate(93.35 31.245 55.578)scale(-1 1)"/></g><g filter="url(#h)"><ellipse  
cx="3.47" cy="21.501" fill="#8900ff" rx="3.47" ry="21.501" transform="rotate(89.009  
35.419 55.202)scale(-1 1)"/></g><g filter="url(#i)"><ellipse cx="3.47" cy="21.501"  
fill="#8900ff" rx="3.47" ry="21.501" transform="rotate(89.009 35.419 55.202)scale(-1  
1)"/></g><g filter="url(#j)"><ellipse cx="14.592" cy="9.743" fill="#8900ff"  
rx="4.407" ry="29.108" transform="rotate(39.51 14.592 9.743)"/></g><g  
filter="url(#k)"><ellipse cx="61.728" cy="-5.321" fill="#8900ff" rx="4.407"  
ry="29.108" transform="rotate(37.892 61.728 -5.32)"/></g><g filter="url(#l)">  
<ellipse cx="55.618" cy="7.104" fill="#00c2ff" rx="5.971" ry="9.665"  
transform="rotate(37.892 55.618 7.104)"/></g><g filter="url(#m)"><ellipse  
cx="12.326" cy="39.103" fill="#8900ff" rx="4.407" ry="29.108"  
transform="rotate(37.892 12.326 39.103)"/></g><g filter="url(#n)"><ellipse  
cx="12.326" cy="39.103" fill="#8900ff" rx="4.407" ry="29.108"  
transform="rotate(37.892 12.326 39.103)"/></g><g filter="url(#o)"><ellipse  
cx="49.857" cy="30.678" fill="#8900ff" rx="4.407" ry="29.108"  
transform="rotate(37.892 49.857 30.678)"/></g><g filter="url(#p)"><ellipse  
cx="52.623" cy="33.171" fill="#00c2ff" rx="5.971" ry="15.297"  
transform="rotate(37.892 52.623 33.17)"/></g></g><path d="M6.919 0c-9.198 13.166-  
9.252 33.575 0 46.789h6.215c-9.25-13.214-9.196-33.623 0-46.789zm6.215 0h-  
6.215c9.198 13.166 9.252 33.575 0 46.789h6.215c9.25-13.214 9.196-33.623 0-46.789"  
class="parenthesis"/><defs><filter id="b" width="60.045" height="41.654" x="-5.564"  
y="16.92" color-interpolation-filters="sRGB" filterUnits="userSpaceOnUse"><feFlood  
flood-opacity="0" result="BackgroundImageFix"/><feBlend in="SourceGraphic"  
in2="BackgroundImageFix" result="shape"/><feGaussianBlur  
result="effect1_foregroundBlur_2002_17286" stdDeviation="7.659"/></filter><filter
```

```
id="c" width="90.34" height="51.437" x="-40.407" y="-6.762" color-interpolation-
filters="sRGB" filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="7.659"/></filter><filter id="d" width="79.355" height="29.4"
x="-35.435" y="2.801" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="e" width="79.579" height="29.4"
x="-30.84" y="20.8" color-interpolation-filters="sRGB" filterUnits="userSpaceOnUse">
<feFlood flood-opacity="0" result="BackgroundImageFix"/><feBlend in="SourceGraphic"
in2="BackgroundImageFix" result="shape"/><feGaussianBlur
result="effect1_foregroundBlur_2002_17286" stdDeviation="4.596"/></filter><filter
id="f" width="79.579" height="29.4" x="-29.307" y="21.949" color-interpolation-
filters="sRGB" filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="g" width="74.749" height="58.852"
x="29.961" y="-17.13" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="7.659"/></filter><filter id="h" width="61.377" height="25.362"
x="37.754" y="3.055" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="i" width="61.377" height="25.362"
x="37.754" y="3.055" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="j" width="56.045" height="63.649"
x="-13.43" y="-22.082" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="k" width="54.814" height="64.646"
x="34.321" y="-37.644" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="l" width="33.541" height="35.313"
x="38.847" y="-10.552" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="m" width="54.814" height="64.646"
x="-15.081" y="6.78" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
```

```

result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="n" width="54.814" height="64.646"
x="-15.081" y="6.78" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="o" width="54.814" height="64.646"
x="22.45" y="-1.645" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter><filter id="p" width="39.409" height="43.623"
x="32.919" y="11.36" color-interpolation-filters="sRGB"
filterUnits="userSpaceOnUse"><feFlood flood-opacity="0"
result="BackgroundImageFix"/><feBlend in="SourceGraphic" in2="BackgroundImageFix"
result="shape"/><feGaussianBlur result="effect1_foregroundBlur_2002_17286"
stdDeviation="4.596"/></filter></defs></svg>

```

frontend/src/context/AuthContext.jsx

```

import { createContext, useContext, useState } from 'react';

const AuthContext = createContext(null);

export function AuthProvider({ children }) {
  const [user, setUser] = useState(() => {
    const stored = localStorage.getItem('user');
    return stored ? JSON.parse(stored) : null;
  });

  const login = (userData) => {
    setUser(userData);
    localStorage.setItem('user', JSON.stringify(userData));
  };

  const logout = () => {
    setUser(null);
    localStorage.removeItem('user');
  };

  return (
    <AuthContext.Provider value={{ user, login, logout }}>
      {children}
    </AuthContext.Provider>
  );
}

export function useAuth() {
  const ctx = useContext(AuthContext);
  if (!ctx) throw new Error('useAuth must be used inside <AuthProvider>');
}

```

```
    return ctx;
}
```

frontend/src/index.css

```
@import "tailwindcss";

@theme {
  --color-brand-50: #eef4ff;
  --color-brand-100: #d9e6ff;
  --color-brand-200: #b8d0ff;
  --color-brand-300: #8eb0ff;
  --color-brand-400: #5f89ff;
  --color-brand-500: #3f65f2;
  --color-brand-600: #304fd0;
  --color-brand-700: #273fa7;
  --color-brand-800: #223785;
  --color-brand-900: #1f316c;

  --color-accent-400: #16d1c1;
  --color-accent-500: #0db8aa;
  --color-accent-600: #0a968a;
}

@layer base {
  body {
    min-height: 100vh;
    color: #e5e7eb;
    background:
      radial-gradient(circle at 5% 0%, rgba(63, 101, 242, 0.24), transparent 36%),
      radial-gradient(circle at 95% 0%, rgba(22, 209, 193, 0.16), transparent 34%),
      linear-gradient(180deg, #060a16 0%, #0a1021 45%, #091021 100%);
  }
}

@layer components {
  .app-shell {
    @apply min-h-screen;
  }

  .page-shell {
    @apply relative px-4 py-10 sm:px-6 lg:px-10;
  }

  .page-shell::before {
    content: "";
    @apply pointer-events-none absolute inset-x-0 top-0 -z-10 h-72;
    background: linear-gradient(180deg, rgba(63, 101, 242, 0.14), rgba(63, 101, 242, 0));
  }
}
```

```
.content-wrap {
  @apply mx-auto w-full max-w-6xl;
}

.glass-card {
  @apply rounded-3xl border border-white/10 bg-white/5 shadow-2xl shadow-black/30
  backdrop-blur-xl;
}

.surface-card {
  @apply rounded-2xl border border-slate-700/70 bg-slate-900/70;
}

.input-modern {
  @apply w-full rounded-xl border border-slate-600 bg-slate-950/80 px-4 py-3 text-
  sm text-white outline-none transition-all placeholder:text-slate-500 focus:border-
  brand-400 focus:ring-2 focus:ring-brand-500/25;
}

.btn-primary {
  @apply inline-flex items-center justify-center rounded-xl bg-gradient-to-r from-
  brand-500 to-accent-500 px-4 py-2.5 text-sm font-semibold text-white shadow-lg
  shadow-black/40 transition-all hover:from-brand-400 hover:to-accent-400;
}

.btn-secondary {
  @apply inline-flex items-center justify-center rounded-xl border border-slate-
  700 bg-slate-900/70 px-4 py-2.5 text-sm font-semibold text-slate-200 transition-all
  hover:border-slate-500 hover:bg-slate-800;
}

.badge-soft {
  @apply inline-flex items-center rounded-full border border-brand-400/30 bg-
  brand-500/10 px-3 py-1 text-xs font-semibold uppercase tracking-wider text-brand-
  200;
}

.celebrate-burst {
  position: relative;
  width: 16rem;
  height: 16rem;
  animation: fade-burst 900ms ease-out forwards;
}

.celebrate-dot {
  --distance: 84px;
  position: absolute;
  top: 50%;
  left: 50%;
  width: 0.75rem;
  height: 0.75rem;
  border-radius: 9999px;
```

```

    background: radial-gradient(circle, #ffffff 0%, #7ff5e9 45%, #3f65f2 100%);
    transform: rotate(var(--angle)) translateY(0);
    opacity: 0;
    animation: dot-burst 900ms ease-out forwards;
  }
}

@keyframes dot-burst {
  0% {
    transform: rotate(var(--angle)) translateY(0) scale(0.2);
    opacity: 0;
  }
  15% {
    opacity: 1;
  }
  100% {
    transform: rotate(var(--angle)) translateY(calc(-1 * var(--distance))) scale(1);
    opacity: 0;
  }
}

@keyframes fade-burst {
  0% {
    opacity: 1;
  }
  100% {
    opacity: 0;
  }
}

.cancel-modal {
  animation: cancel-modal-in 220ms ease-out;
}

@keyframes cancel-modal-in {
  0% {
    transform: translateY(10px) scale(0.97);
    opacity: 0;
  }
  100% {
    transform: translateY(0) scale(1);
    opacity: 1;
  }
}

```

frontend/src/main.jsx

```

import { StrictMode } from 'react'
import { createRoot } from 'react-dom/client'
import './index.css'
import App from './App.jsx'

```



```

createRoot(document.getElementById('root')).render(
  <StrictMode>
    <App />
  </StrictMode>,
)

```

frontend/src/Navbar.jsx

```

import { useNavigate, useLocation } from 'react-router-dom';
import { useAuth } from '../context/AuthContext';

export default function Navbar() {
  const { user, logout } = useAuth();
  const navigate = useNavigate();
  const location = useLocation();

  const handleLogout = () => {
    logout();
    navigate('/login');
  };

  const isActive = (path) => {
    if (path === '/events') {
      return location.pathname === '/events' ||
location.pathname.startsWith('/events/');
    }
    return location.pathname === path;
  };

  const navLink = (path, label) => (
    <button
      onClick={() => navigate(path)}
      className={`rounded-lg px-3 py-1.5 text-sm font-semibold transition-all ${
        isActive(path)
          ? 'bg-brand-500/20 text-brand-100'
          : 'text-slate-300 hover:bg-slate-800/80 hover:text-white'
        }`}
    >
      {label}
    </button>
  );

  // Hide navbar on auth pages
  const hideOn = ['/login', '/signup'];
  if (hideOn.includes(location.pathname)) return null;

  return (
    <nav className="sticky top-0 z-50 px-3 pt-3 sm:px-4">
      <div className="content-wrap glass-card">
        <div className="flex h-16 items-center justify-between gap-3 px-4 sm:px-6">

```

```

<button
  onClick={() => navigate('/events')}
  className="flex shrink-0 items-center gap-2.5"
>
  <div className="flex h-9 w-9 items-center justify-center rounded-xl bg-
gradient-to-br from-brand-500 to-accent-500 text-base shadow-lg shadow-black/40">
    *
  </div>
  <div className="hidden text-left sm:block">
    <p className="text-[11px] font-medium uppercase tracking-[0.2em] text-
slate-400">Event Platform</p>
    <p className="text-lg font-bold text-white">Evently</p>
  </div>
</button>

{user && (
  <div className="hidden items-center gap-1 md:flex">
    {navLink('/events', 'Events')}
    {navLink('/create-event', 'Create Event')}
    {navLink('/my-events', 'My Events')}
    {navLink('/my-bookings', 'My Bookings')}
  </div>
)}

<div className="flex items-center gap-2">
  {user ? (
    <>
      <button
        onClick={() => navigate('/profile')}
        className={`flex items-center gap-2 rounded-xl border px-2.5 py-
1.5 transition-all ${
          isActive('/profile')
            ? 'border-brand-300/50 bg-brand-500/15'
            : 'border-transparent hover:border-slate-600 hover:bg-slate-
800/70'
        }}
      >
        <div className="flex h-8 w-8 items-center justify-center rounded-
lg bg-gradient-to-br from-brand-500 to-accent-500 text-xs font-bold text-white">
          {user?.name?.[0]?.toUpperCase() ?? user?.email?.
[0]?.toUpperCase()}
        </div>
        <span className="hidden text-sm font-semibold text-slate-200
sm:block">
          {user?.name?.split(' ')[0] ?? 'Profile'}
        </span>
      </button>
      <button
        onClick={handleLogout}
        className="rounded-xl border border-slate-700 px-3 py-1.5 text-sm
font-semibold text-slate-300 transition-all hover:border-red-400/40 hover:bg-red-
500/10 hover:text-red-300"

```

```

      >
        Sign out
      </button>
    </>
  ) : (
    <div className="flex items-center gap-2">
      <button
        onClick={() => navigate('/login')}
        className="btn-secondary py-2"
      >
        Login
      </button>
      <button
        onClick={() => navigate('/signup')}
        className="btn-primary py-2"
      >
        Sign Up
      </button>
    </div>
  )}
</div>
</div>

{user && (
  <div className="flex items-center justify-around border-t border-white/10
px-2 py-2 md:hidden">
    {[
      { path: '/events', icon: '📅', label: 'Events' },
      { path: '/create-event', icon: '✚', label: 'Create' },
      { path: '/my-events', icon: '📋', label: 'Mine' },
      { path: '/my-bookings', icon: '📅', label: 'Bookings' },
      { path: '/profile', icon: '👤', label: 'Profile' },
    ].map(({ path, icon, label }) => (
      <button
        key={path}
        onClick={() => navigate(path)}
        className={`flex min-w-16 flex-col items-center gap-1 rounded-lg px-
3 py-1.5 transition-all ${
          isActive(path)
            ? 'bg-brand-500/20 text-brand-200'
            : 'text-slate-400 hover:bg-slate-800/70 hover:text-slate-200'
        }`}
      >
        <span className="text-sm">{icon}</span>
        <span className="text-[11px] font-medium">{label}</span>
      </button>
    ))}
  </div>
)}
</div>
</nav>

```

```
);  
}
```

frontend/src/pages/CreateEvent.jsx

```
import { useForm } from 'react-hook-form';  
import { useNavigate } from 'react-router-dom';  
import api from '../api/axios';  
import { useAuth } from '../context/AuthContext';  
import { useEffect } from 'react';  
  
export default function CreateEvent() {  
  const { register, handleSubmit, formState: { errors, isSubmitting } } = useForm();  
  const { user } = useAuth();  
  const navigate = useNavigate();  
  
  useEffect(() => {  
    if (!user) navigate('/login');  
  }, []);  
  
  const onSubmit = async (data) => {  
    try {  
      await api.post('/event', { ...data, userID: user.userID });  
      navigate('/events');  
    } catch (err) {  
      alert(err.response?.data?.message || 'Failed to create event');  
    }  
  };  
  
  const inputClass = "input-modern";  
  
  return (  
    <div className="page-shell">  
      <div className="mx-auto w-full max-w-3xl">  
        <div className="mb-6 text-center">  
          <span className="badge-soft mb-3">Host Experience</span>  
          <h2 className="text-3xl font-bold text-white sm:text-4xl">Create a New  
Event</h2>  
          <p className="mt-2 text-sm text-slate-300">Publish your event and start  
collecting bookings in minutes.</p>  
        </div>  
  
        <form onSubmit={handleSubmit(onSubmit)} className="glass-card flex flex-col  
gap-5 p-6 sm:p-8">  
  
          <div className="flex flex-col gap-1.5">  
            <label className="text-xs font-semibold uppercase tracking-wider text-  
slate-300">Title</label>  
            <input {...register('title', { required: 'Title is required' })}  
placeholder="Give your event a name" className={inputClass} />  
            {errors.title && <span className="text-red-400 text-xs">
```

```

{errors.title.message}</span>}
    </div>

    <div className="flex flex-col gap-1.5">
      <label className="text-xs font-semibold uppercase tracking-wider text-slate-300">Description</label>
      <input {...register('description')} placeholder="What's this event about?" className={inputClass} />
    </div>

    <div className="grid grid-cols-1 gap-4 sm:grid-cols-2">
      <div className="flex flex-col gap-1.5">
        <label className="text-xs font-semibold uppercase tracking-wider text-slate-300">Date</label>
        <input type="date" {...register('date', { required: 'Date is required' })} className={inputClass} />
        {errors.date && <span className="text-red-400 text-xs">
{errors.date.message}</span>}
      </div>
      <div className="flex flex-col gap-1.5">
        <label className="text-xs font-semibold uppercase tracking-wider text-slate-300">Capacity</label>
        <input type="number" {...register('capacity', { required: 'Required', min: 1 })} placeholder="100" className={inputClass} />
        {errors.capacity && <span className="text-red-400 text-xs">
{errors.capacity.message}</span>}
      </div>
    </div>

    <div className="flex flex-col gap-1.5">
      <label className="text-xs font-semibold uppercase tracking-wider text-slate-300">Location</label>
      <input {...register('location', { required: 'Location is required' })} placeholder="City, Venue" className={inputClass} />
      {errors.location && <span className="text-red-400 text-xs">
{errors.location.message}</span>}
    </div>

    <button
      type="submit"
      disabled={isSubmitting}
      className="btn-primary mt-2 w-full disabled:cursor-not-allowed disabled:opacity-50"
      >
      {isSubmitting ? 'Publishing...' : 'Publish Event'}
    </button>
  </form>
</div>
</div>
);
}

```

frontend/src/pages/Events.jsx

```
import { useEffect, useState } from 'react';
import { useNavigate } from 'react-router-dom';
import api from '../api/axios';
import { useAuth } from '../context/AuthContext';

export default function Events() {
  const [events, setEvents] = useState([]);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState('');
  const { user } = useAuth();
  const navigate = useNavigate();

  useEffect(() => {
    api.get('/event')
      .then(res => setEvents(res.data))
      .catch((err) => setError(err.response?.data?.message || 'Failed to load events'))
      .finally(() => setLoading(false));
  }, []);

  if (loading) return (
    <div className="min-h-screen flex items-center justify-center">
      <div className="flex flex-col items-center gap-3">
        <div className="h-9 w-9 rounded-full border-2 border-brand-400 border-t-transparent animate-spin"></div>
        <span className="text-sm text-slate-400">Loading events...</span>
      </div>
    </div>
  );

  return (
    <div className="page-shell">
      <div className="content-wrap space-y-8">
        <div className="glass-card flex flex-col gap-6 p-6 sm:p-8 lg:flex-row lg:items-end lg:justify-between">
          <div>
            <span className="badge-soft mb-3">Discover Curated Experiences</span>
            <h1 className="text-3xl font-bold tracking-tight text-white sm:text-4xl">Live Events</h1>
            <p className="mt-2 max-w-2xl text-sm text-slate-300 sm:text-base">
              Explore upcoming events, reserve your spot instantly, and keep all your bookings organized in one place.
            </p>
          </div>
          <div className="flex flex-wrap gap-2">
            {user && (
              <>
                <button onClick={() => navigate('/create-event')} className="btn-primary">

```

```

        + Create Event
      </button>
      <button onClick={() => navigate('/profile')} className="btn-
secondary">
        Profile
      </button>
    </>
  )}
  {!user && (
    <button onClick={() => navigate('/login')} className="btn-secondary">
      Login
    </button>
  )}
</div>
</div>

{error && (
  <div className="rounded-xl border border-red-400/40 bg-red-500/10 px-4 py-
3 text-sm text-red-200">
    {error}
  </div>
)}

{!error && events.length === 0 && (
  <div className="glass-card mt-10 px-6 py-14 text-center">
    <p className="mb-4 text-5xl">🐼</p>
    <p className="text-slate-300">No events yet. Be the first to create one!
</p>
  </div>
)}

<div className="grid grid-cols-1 gap-5 sm:grid-cols-2 lg:grid-cols-3">
  {events.map(event => (
    <div key={event._id} className="group surface-card flex flex-col gap-4
p-5 transition-all hover:-translate-y-1 hover:border-brand-300/60 hover:bg-slate-
900">
      <div className="flex items-start justify-between gap-2">
        <h3 className="text-base font-semibold leading-snug text-white
transition-colors group-hover:text-brand-200">{event.title}</h3>
        <span className="shrink-0 rounded-lg border border-brand-300/35 bg-
brand-500/10 px-2.5 py-1 text-xs font-semibold text-brand-100">
          {new Date(event.date).toLocaleDateString('en-US', { month:
'short', day: 'numeric' })}
        </span>
      </div>
      <div>
        {event.description && (
          <p className="flex-1 text-sm leading-relaxed text-slate-300">
{event.description}</p>
        )}
        <div className="flex gap-3 text-xs">
          <span className="rounded-lg border border-slate-700 bg-slate-800/70
px-2.5 py-1 text-slate-300">📍 {event.location}</span>

```

```

        <span className="rounded-lg border border-slate-700 bg-slate-800/70
px-2.5 py-1 text-slate-300">👤 {event.capacity}</span>
      </div>
      <button
        onClick={() => navigate(`/events/${event._id}`)}
        className="btn-primary mt-auto w-full"
      >
        View Details
      </button>
    </div>
  )}
</div>
</div>
</div>
);
}

```

frontend/src/pages/Login.jsx

```

import { useForm } from 'react-hook-form';
import { useNavigate, Link } from 'react-router-dom';
import api from '../api/axios';
import { useAuth } from '../context/AuthContext';

export default function Login() {
  const { register, handleSubmit, formState: { errors, isSubmitting } } = useForm();
  const { login } = useAuth();
  const navigate = useNavigate();

  const onSubmit = async (data) => {
    try {
      const res = await api.post('/user/login', data);
      login(res.data);
      navigate('/events');
    } catch (err) {
      alert(err.response?.data?.message || 'Login failed');
    }
  };

  const inputClass = "input-modern";

  return (
    <div className="page-shell flex items-center justify-center">
      <div className="w-full max-w-md">
        <div className="text-center mb-8">
          <div className="mb-4 inline-flex h-14 w-14 items-center justify-center
rounded-2xl bg-gradient-to-br from-brand-500 to-accent-500 text-2xl shadow-lg
shadow-black/40">+</div>
          <h2 className="text-3xl font-bold text-white">Welcome Back</h2>
          <p className="mt-1 text-sm text-slate-300">Sign in to manage your events
and bookings.</p>

```



```

    </div>

    <form onSubmit={handleSubmit(onSubmit)} className="glass-card flex flex-col
gap-5 p-7">
      <div className="flex flex-col gap-1.5">
        <label className="text-xs font-semibold uppercase tracking-wider text-
slate-300">Email</label>
        <input type="email" {...register('email', { required: 'Email is
required' })} placeholder="john@example.com" className={inputClass} />
        {errors.email && <span className="text-red-400 text-xs">
{errors.email.message}</span>}
      </div>

      <div className="flex flex-col gap-1.5">
        <label className="text-xs font-semibold uppercase tracking-wider text-
slate-300">Password</label>
        <input type="password" {...register('password', { required: 'Password is
required' })} placeholder="....." className={inputClass} />
        {errors.password && <span className="text-red-400 text-xs">
{errors.password.message}</span>}
      </div>

      <button
        type="submit"
        disabled={isSubmitting}
        className="btn-primary mt-1 w-full disabled:cursor-not-allowed
disabled:opacity-50"
      >
        {isSubmitting ? 'Signing in...' : 'Sign In'}
      </button>

      <p className="text-center text-sm text-slate-300">
        No account? <Link to="/signup" className="font-semibold text-brand-200
transition-colors hover:text-brand-100">Sign Up</Link>
      </p>
    </form>
  </div>
</div>
);
}

```

frontend/src/pages/MyBookings.jsx

```

import { useEffect, useState } from 'react';
import { useNavigate } from 'react-router-dom';
import api from '../api/axios';
import { useAuth } from '../context/AuthContext';

export default function MyBookings() {
  const { user } = useAuth();
  const navigate = useNavigate();

```

```

const [bookings, setBookings] = useState([]);
const [loading, setLoading] = useState(true);
const [cancelTarget, setCancelTarget] = useState(null);
const [isCancelling, setIsCancelling] = useState(false);

useEffect(() => {
  if (!user) return navigate('/login');
  api.get(`/booking/user/${user.userID}`)
    .then(res => setBookings(res.data))
    .catch(() => alert('Failed to load bookings'))
    .finally(() => setLoading(false));
}, []);

const handleCancel = async () => {
  if (!cancelTarget) return;
  try {
    setIsCancelling(true);
    await api.delete(`/booking/${cancelTarget._id}`);
    setBookings(prev => prev.filter(b => b._id !== cancelTarget._id));
    setCancelTarget(null);
  } catch {
    alert('Failed to cancel booking');
  } finally {
    setIsCancelling(false);
  }
};

if (loading) return (
  <div className="min-h-screen flex items-center justify-center">
    <div className="flex flex-col items-center gap-3">
      <div className="h-9 w-9 rounded-full border-2 border-brand-400 border-t-transparent animate-spin"></div>
      <span className="text-sm text-slate-400">Loading your bookings...</span>
    </div>
  </div>
);

return (
  <div className="page-shell">
    <div className="mx-auto w-full max-w-3xl">
      <div className="glass-card mb-8 flex flex-col gap-4 p-6 sm:flex-row sm:items-end sm:justify-between">
        <div>
          <span className="badge-soft mb-2">Your Reservations</span>
          <h1 className="text-3xl font-bold text-white">My Bookings</h1>
        </div>
        <button onClick={() => navigate('/events')} className="btn-secondary">
          ← Back to Events
        </button>
      </div>

      {bookings.length === 0 && (

```

```

    <div className="glass-card mt-20 px-6 py-14 text-center">
      <p className="mb-4 text-5xl">🎫</p>
      <p className="text-slate-300">No bookings yet. Go grab some tickets!</p>
      <button onClick={() => navigate('/events')} className="mt-4 text-sm
font-semibold text-brand-200 transition-colors hover:text-brand-100">Browse Events
    </button>
  </div>
)}

<div className="flex flex-col gap-3">
  {bookings.map(b => (
    <div key={b._id} className="surface-card flex items-center justify-
between gap-4 px-5 py-4 transition-all hover:border-brand-300/45">
      <div className="flex items-center gap-4">
        <div className="flex h-10 w-10 items-center justify-center rounded-
xl border border-brand-300/35 bg-brand-500/15 text-lg">📅</div>
        <div className="flex flex-col gap-0.5">
          <span className="text-sm font-semibold text-slate-100">
            Event <code className="font-mono text-xs text-brand-200">
{b.eventID}</code>
          </span>
          <span className="text-xs text-slate-400">{b.seats} seat{b.seats >
1 ? 's' : ''} booked</span>
        </div>
      </div>
      <button
        onClick={() => setCancelTarget(b)}
        className="rounded-xl border border-red-500/35 bg-red-500/10 px-3.5
py-2 text-xs font-semibold text-red-300 transition-all hover:bg-red-500/20"
      >
        Cancel
      </button>
    </div>
  )})
</div>
</div>

{cancelTarget && (
  <div className="fixed inset-0 z-50 flex items-center justify-center bg-
slate-950/70 p-4 backdrop-blur-sm">
    <div className="cancel-modal glass-card w-full max-w-md p-6">
      <div className="mb-3 inline-flex h-11 w-11 items-center justify-center
rounded-xl border border-red-400/35 bg-red-500/15 text-xl">
        ⚠️
      </div>
      <h2 className="text-xl font-semibold text-white">Cancel Booking?</h2>
      <p className="mt-2 text-sm text-slate-300">
        This will remove your ticket for event
        {''}
        <span className="font-mono text-brand-200">{cancelTarget.eventID}
      </span>
    </div>
  </div>
)

```

```

    </p>
    <div className="mt-6 flex items-center justify-end gap-2">
      <button
        onClick={() => setCancelTarget(null)}
        className="btn-secondary"
        disabled={isCancelling}
      >
        Keep Booking
      </button>
      <button
        onClick={handleCancel}
        disabled={isCancelling}
        className="rounded-xl border border-red-500/35 bg-red-500/15 px-4
py-2.5 text-sm font-semibold text-red-200 transition-all hover:bg-red-500/25
disabled:cursor-not-allowed disabled:opacity-50"
      >
        {isCancelling ? 'Cancelling...' : 'Yes, Cancel'}
      </button>
    </div>
  </div>
</div>
  )}
</div>
);
}

```

frontend/src/pages/MyEvents.jsx

```

import { useEffect, useState } from 'react';
import { useNavigate } from 'react-router-dom';
import api from '../api/axios';
import { useAuth } from '../context/AuthContext';

export default function MyEvents() {
  const { user } = useAuth();
  const navigate = useNavigate();
  const [events, setEvents] = useState([]);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState('');
  const [participantsByEvent, setParticipantsByEvent] = useState({});
  const [expanded, setExpanded] = useState({});
  const [loadingParticipants, setLoadingParticipants] = useState({});

  useEffect(() => {
    if (!user) {
      navigate('/login');
      return;
    }

    api.get(`/event/user/${user.userID}`)
      .then((res) => setEvents(res.data))

```

```

        .catch((err) => setError(err.response?.data?.message || 'Failed to load your
events'))
        .finally(() => setLoading(false));
    }, [navigate, user]);

const loadParticipants = async (eventID) => {
    if (participantsByEvent[eventID]) return;
    try {
        setLoadingParticipants((prev) => ({ ...prev, [eventID]: true }));
        const res = await api.get(`/booking/event/${eventID}/participants`, {
            params: { userID: user.userID },
        });
        setParticipantsByEvent((prev) => ({ ...prev, [eventID]: res.data }));
    } catch (err) {
        setParticipantsByEvent((prev) => ({
            ...prev,
            [eventID]: { error: err.response?.data?.message || 'Failed to load
participants' },
        }));
    } finally {
        setLoadingParticipants((prev) => ({ ...prev, [eventID]: false }));
    }
};

const toggleParticipants = async (eventID) => {
    const nextOpen = !expanded[eventID];
    setExpanded((prev) => ({ ...prev, [eventID]: nextOpen }));
    if (nextOpen) {
        await loadParticipants(eventID);
    }
};

if (loading) {
    return (
        <div className="min-h-screen flex items-center justify-center">
            <div className="flex flex-col items-center gap-3">
                <div className="h-9 w-9 rounded-full border-2 border-brand-400 border-t-
transparent animate-spin"></div>
                <span className="text-sm text-slate-400">Loading your events...</span>
            </div>
        );
}

return (
    <div className="page-shell">
        <div className="content-wrap">
            <div className="glass-card mb-8 flex flex-col gap-4 p-6 sm:flex-row
sm:items-end sm:justify-between">
                <div>
                    <span className="badge-soft mb-2">Event Owner Dashboard</span>
                    <h1 className="text-3xl font-bold text-white">My Events</h1>

```

```

    <p className="mt-2 text-sm text-slate-300">View all events you created
and see their participants.</p>
  </div>
  <button onClick={() => navigate('/create-event')} className="btn-primary">
    + Create Event
  </button>
</div>

{error && (
  <div className="mb-4 rounded-xl border border-red-400/40 bg-red-500/10 px-
4 py-3 text-sm text-red-200">
    {error}
  </div>
)}

{!error && events.length === 0 && (
  <div className="glass-card px-6 py-14 text-center">
    <p className="mb-4 text-5xl">17</p>
    <p className="text-slate-300">You have not created any events yet.</p>
    <button onClick={() => navigate('/create-event')} className="btn-
secondary mt-4">
      Create your first event
    </button>
  </div>
)}

<div className="space-y-4">
  {events.map((event) => {
    const participantData = participantsByEvent[event._id];
    const isOpen = expanded[event._id];
    const isLoadingParticipants = loadingParticipants[event._id];
    const participants = Array.isArray(participantData) ? participantData :
[];

    const participantError = participantData?.error;

    return (
      <div key={event._id} className="surface-card overflow-hidden">
        <div className="flex flex-col gap-4 p-5 sm:flex-row sm:items-center
sm:justify-between">
          <div>
            <h2 className="text-lg font-semibold text-white">{event.title}
</h2>

            <p className="mt-1 text-sm text-slate-300">
              {new Date(event.date).toLocaleDateString()} · {event.location}
            </p>
            <p className="mt-1 text-xs text-slate-400">Capacity:
{event.capacity}</p>
          </div>
          <div className="flex flex-wrap gap-2">
            <button
              onClick={() => navigate(`/events/${event._id}`)}
              className="btn-secondary"

```

```

    >
      Open Event
    </button>
    <button
      onClick={() => toggleParticipants(event._id)}
      className="btn-primary"
    >
      {isOpen ? 'Hide Participants' : 'View Participants'}
    </button>
  </div>
</div>

{isOpen && (
  <div className="border-t border-slate-700/70 bg-slate-900/50 p-5">
    {isLoadingParticipants && (
      <p className="text-sm text-slate-400">Loading participants...
</p>

    )}

    {!isLoadingParticipants && participantError && (
      <div className="rounded-xl border border-red-400/40 bg-red-
500/10 px-4 py-3 text-sm text-red-200">
        {participantError}
      </div>
    )}

    {!isLoadingParticipants && !participantError &&
participants.length === 0 && (
      <p className="text-sm text-slate-400">No participants yet.</p>
    )}

    {!isLoadingParticipants && !participantError &&
participants.length > 0 && (
      <div className="overflow-x-auto">
        <table className="w-full text-left text-sm">
          <thead>
            <tr className="text-slate-400">
              <th className="pb-2 font-medium">Name</th>
              <th className="pb-2 font-medium">Email</th>
              <th className="pb-2 font-medium">Seats</th>
            </tr>
          </thead>
          <tbody>
            {participants.map((participant) => (
              <tr key={participant.bookingID} className="border-t
border-slate-700/50 text-slate-200">
                <td className="py-2">{participant.name}</td>
                <td className="py-2">{participant.email}</td>
                <td className="py-2">{participant.seats}</td>
              </tr>
            ))}
          </tbody>
        </table>
      </div>
    )}
  )}

```

```

        </table>
      </div>
    )}
  </div>
  )}
</div>
);
}}
</div>
</div>
</div>
);
}

```

frontend/src/pages/Profile.jsx

```

import { useEffect, useState } from 'react';
import { useAuth } from '../context/AuthContext';
import { useNavigate } from 'react-router-dom';
import api from '../api/axios';

export default function Profile() {
  const { user, logout } = useAuth();
  const navigate = useNavigate();
  const [profile, setProfile] = useState(null);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    if (!user) return navigate('/login');
    api.get(`/user/profile/${user.userID}`)
      .then(res => setProfile(res.data))
      .catch(() => alert('Failed to load profile'))
      .finally(() => setLoading(false));
  }, []);

  const handleLogout = () => {
    logout();
    navigate('/login');
  };

  if (loading) return (
    <div className="min-h-screen flex items-center justify-center">
      <div className="h-9 w-9 rounded-full border-2 border-brand-400 border-t-transparent animate-spin"></div>
    </div>
  );

  return (
    <div className="page-shell flex items-center justify-center">
      <div className="w-full max-w-md">
        <div className="glass-card flex flex-col items-center gap-5 p-8 text-

```



```

center">
  <div className="relative">
    <div className="flex h-20 w-20 items-center justify-center rounded-2xl
bg-gradient-to-br from-brand-500 to-accent-500 text-3xl font-extrabold text-white
shadow-lg shadow-black/40">
      {profile?.name?.[0]?.toUpperCase()}
    </div>
    <div className="absolute -bottom-1 -right-1 h-5 w-5 rounded-full border-
2 border-slate-900 bg-emerald-400"></div>
  </div>

  <div>
    <h2 className="text-2xl font-bold text-white">{profile?.name}</h2>
    <p className="mt-0.5 text-sm text-slate-300">{profile?.email}</p>
    <p className="mt-2 rounded-lg border border-slate-700 bg-slate-900/70
px-3 py-1 font-mono text-xs text-slate-400">{profile?._id}</p>
  </div>

  <div className="mt-1 flex w-full flex-col gap-2.5">
    <button onClick={() => navigate('/events')} className="btn-primary w-
full">
      Browse Events
    </button>
    <button onClick={() => navigate('/my-events')} className="btn-secondary
w-full">
      My Events
    </button>
    <button onClick={() => navigate('/my-bookings')} className="btn-
secondary w-full">
      My Bookings
    </button>
    <button onClick={handleLogout} className="w-full rounded-xl border
border-red-500/35 bg-red-500/10 py-3 text-sm font-semibold text-red-300 transition-
all hover:bg-red-500/20">
      Sign Out
    </button>
  </div>
</div>
</div>
</div>
);
}

```

frontend/src/pages/Signup.jsx

```

import { useForm } from 'react-hook-form';
import { useNavigate, Link } from 'react-router-dom';
import api from '../api/axios';

export default function Signup() {
  const { register, handleSubmit, formState: { errors, isSubmitting } } = useForm();

```

```

const navigate = useNavigate();

const onSubmit = async (data) => {
  try {
    await api.post('/user/signup', data);
    navigate('/login');
  } catch (err) {
    alert(err.response?.data?.message || 'Signup failed');
  }
};

const inputClass = "input-modern";

return (
  <div className="page-shell flex items-center justify-center">
    <div className="w-full max-w-md">
      <div className="text-center mb-8">
        <div className="mb-4 inline-flex h-14 w-14 items-center justify-center rounded-2xl bg-gradient-to-br from-accent-500 to-brand-500 text-2xl shadow-lg shadow-black/40">
          <h2 className="text-3xl font-bold text-white">Create Account</h2>
          <p className="mt-1 text-sm text-slate-300">Join Evently and start booking in seconds.</p>
        </div>
      </div>

      <form onSubmit={handleSubmit(onSubmit)} className="glass-card flex flex-col gap-5 p-7">
        <div className="flex flex-col gap-1.5">
          <label className="text-xs font-semibold uppercase tracking-wider text-slate-300">Name</label>
          <input {...register('name', { required: 'Name is required' })} placeholder="John Doe" className={inputClass} />
          {errors.name && <span className="text-red-400 text-xs">{errors.name.message}</span>}
        </div>

        <div className="flex flex-col gap-1.5">
          <label className="text-xs font-semibold uppercase tracking-wider text-slate-300">Email</label>
          <input type="email" {...register('email', { required: 'Email is required' })} placeholder="john@example.com" className={inputClass} />
          {errors.email && <span className="text-red-400 text-xs">{errors.email.message}</span>}
        </div>

        <div className="flex flex-col gap-1.5">
          <label className="text-xs font-semibold uppercase tracking-wider text-slate-300">Password</label>
          <input type="password" {...register('password', { required: 'Password is required', minLength: { value: 6, message: 'Min 6 characters' } })} placeholder="••••••••" className={inputClass} />
          {errors.password && <span className="text-red-400 text-xs">

```

```

{errors.password.message}</span>}
    </div>

    <button
      type="submit"
      disabled={isSubmitting}
      className="btn-primary mt-1 w-full disabled:cursor-not-allowed
disabled:opacity-50"
    >
      {isSubmitting ? 'Creating account...' : 'Create Account'}
    </button>

    <p className="text-center text-sm text-slate-300">
      Already have an account? <Link to="/login" className="font-semibold
text-brand-200 transition-colors hover:text-brand-100">Login</Link>
    </p>
  </form>
</div>
</div>
);
}

```

frontend/src/pages/SingleEvent.jsx

```

import { useEffect, useState } from 'react';
import { useNavigate, useParams } from 'react-router-dom';
import api from '../api/axios';
import { useAuth } from '../context/AuthContext';

export default function SingleEvent() {
  const { id } = useParams();
  const navigate = useNavigate();
  const { user } = useAuth();

  const [event, setEvent] = useState(null);
  const [loading, setLoading] = useState(true);
  const [bookingSeats, setBookingSeats] = useState(1);
  const [bookingState, setBookingState] = useState({
    status: 'idle',
    message: '',
  });

  useEffect(() => {
    api.get(`/event/${id}`)
      .then((res) => setEvent(res.data))
      .catch((err) => {
        setBookingState({
          status: 'error',
          message: err.response?.data?.message || 'Failed to load event',
        });
      });
  });
}

```

```

        .finally(() => setLoading(false));
    }, [id]);

    useEffect(() => {
        if (bookingState.status !== 'success' && bookingState.status !== 'error')
        return;

        const timer = setTimeout(() => {
            setBookingState((prev) => ({ ...prev, status: 'idle', message: '' }));
        }, 3500);

        return () => clearTimeout(timer);
    }, [bookingState.status]);

    const handleBookTicket = async () => {
        if (!user) {
            navigate('/login');
            return;
        }

        try {
            setBookingState({ status: 'submitting', message: '' });
            await api.post('/booking', {
                userID: user.userID,
                eventID: event._id,
                seats: Number(bookingSeats) || 1,
            });
            setBookingState({
                status: 'success',
                message: 'Booking confirmed! Your ticket is now reserved.',
            });
        } catch (err) {
            setBookingState({
                status: 'error',
                message: err.response?.data?.message || 'Booking failed. Please try again.',
            });
        }
    };

    if (loading) {
        return (
            <div className="min-h-screen flex items-center justify-center">
                <div className="flex flex-col items-center gap-3">
                    <div className="h-9 w-9 rounded-full border-2 border-brand-400 border-t-transparent animate-spin"></div>
                    <span className="text-sm text-slate-400">Loading event details...</span>
                </div>
            </div>
        );
    }

    if (!event) {

```

```

return (
  <div className="page-shell">
    <div className="content-wrap">
      <div className="glass-card px-6 py-14 text-center">
        <h1 className="text-2xl font-bold text-white">Event not found</h1>
        <p className="mt-2 text-slate-300">The event might have been removed or
the link is invalid.</p>
        <button onClick={() => navigate('/events')} className="btn-secondary mt-
5">
          Back to Events
        </button>
      </div>
    </div>
  </div>
);
}

return (
  <div className="page-shell relative overflow-hidden">
    {bookingState.status === 'success' && (
      <div className="pointer-events-none absolute inset-0 z-10 flex items-center
justify-center">
        <div className="celebrate-burst">
          {Array.from({ length: 16 }).map((_, index) => (
            <span
              key={index}
              className="celebrate-dot"
              style={{ '--angle': `${index * 22.5}deg` }}
            />
          ))}
        </div>
      </div>
    )}

    <div className="content-wrap">
      <div className="glass-card overflow-hidden">
        <div className="border-b border-white/10 px-6 py-6 sm:px-8">
          <button onClick={() => navigate('/events')} className="btn-secondary mb-
5">
            ← All Events
          </button>
          <div className="flex flex-col gap-3 lg:flex-row lg:items-end lg:justify-
between">
            <div>
              <span className="badge-soft mb-3">Single Event</span>
              <h1 className="text-3xl font-bold text-white sm:text-4xl">
{event.title}</h1>
              {event.description && <p className="mt-3 max-w-2xl text-slate-300">
{event.description}</p>}
            </div>
            <div className="rounded-2xl border border-brand-300/30 bg-brand-500/10
px-4 py-3 text-sm text-brand-100">

```

```

        {new Date(event.date).toLocaleDateString('en-US', {
            weekday: 'short',
            month: 'long',
            day: 'numeric',
            year: 'numeric',
        })}
    </div>
</div>
</div>

<div className="grid gap-6 px-6 py-6 sm:px-8 lg:grid-cols-[1fr_320px]">
    <div className="surface-card p-5">
        <h2 className="text-lg font-semibold text-white">Event Details</h2>
        <div className="mt-4 grid gap-3 sm:grid-cols-2">
            <div className="rounded-xl border border-slate-700 bg-slate-900/70
p-4">
                <p className="text-xs uppercase tracking-wider text-slate-
400">Location</p>
                <p className="mt-1 text-sm font-medium text-white">
{event.location}</p>
            </div>
            <div className="rounded-xl border border-slate-700 bg-slate-900/70
p-4">
                <p className="text-xs uppercase tracking-wider text-slate-
400">Capacity</p>
                <p className="mt-1 text-sm font-medium text-white">
{event.capacity} seats</p>
            </div>
            <div className="rounded-xl border border-slate-700 bg-slate-900/70
p-4 sm:col-span-2">
                <p className="text-xs uppercase tracking-wider text-slate-
400">Event ID</p>
                <p className="mt-1 break-all font-mono text-xs text-brand-200">
{event._id}</p>
            </div>
        </div>
    </div>

    <div className="surface-card p-5">
        <h2 className="text-lg font-semibold text-white">Book Tickets</h2>
        <p className="mt-2 text-sm text-slate-300">Reserve your spot for this
event in one click.</p>

        <label className="mt-4 block text-xs font-semibold uppercase tracking-
wider text-slate-300">
            Number of Seats
        </label>
        <input
            type="number"
            min="1"
            max={event.capacity || 1000}
            value={bookingSeats}

```

```

        onChange={e => setBookingSeats(e.target.value)}
        className="input-modern mt-2"
      />

      <button
        onClick={handleBookTicket}
        disabled={bookingState.status === 'submitting'}
        className="btn-primary mt-4 w-full disabled:cursor-not-allowed
disabled:opacity-50"
      >
        {bookingState.status === 'submitting' ? 'Booking...' : 'Book
Tickets'}
      </button>

      {bookingState.message && (
        <div
          className={`mt-4 rounded-xl border px-3 py-2 text-sm ${
            bookingState.status === 'success'
              ? 'border-emerald-400/40 bg-emerald-500/10 text-emerald-200'
              : 'border-red-400/40 bg-red-500/10 text-red-200'
            }`}
        >
          {bookingState.message}
        </div>
      )}
    </div>
  </div>
</div>
</div>
</div>
);
}

```