



AMERICAN UNIVERSITY
OF PHNOM PENH
STUDY LOCALLY. LIVE GLOBALLY.


Transformers

Rina BUOY


[Source](#)

Fine-tuning

Transfer Learning



Transfer Learning



Model Zoos

TORCHVISION.MODELS

The models subpackage contains definitions of models for addressing different tasks, including: image classification, pixelwise semantic segmentation, object detection, instance segmentation, person keypoint detection and video classification.

Classification

The models subpackage contains definitions for the following model architectures for image classification:

- AlexNet
- VGG
- ResNet
- SqueezeNet
- DenseNet
- Inception v3
- GoogLeNet
- ShuffleNet v2
- MobileNet v2
- ResNeXt
- Wide ResNet
- MNASNet



Computer Vision


| Model | Description | Reference |
|----------------------------|---|----------------------------------|
| MNIST | A basic model to classify digits from the MNIST dataset | Link |
| ResNet | A deep residual network for image recognition | arXiv:1512.03385 |
| RetinaNet | A fast and powerful object detector | arXiv:1708.02002 |
| Mask R-CNN | An object detection and instance segmentation model | arXiv:1703.06870 |

<https://github.com/tensorflow/models/tree/master/official>


Transformers

Transformers

- Ground-breaking architecture that set SOTA on first translation and later all other NLP and CV tasks.
- Attention is all you need (2017)



Encoder-Decoder Transformers




<https://blog.gopenai.com/the-transformer-architecture-a-comprehensive-exploration-with-examples-b8c55b0e72e0>



Large Language Models

GPT / GPT-2 (2019)

- Generative Pre-trained Transformer
- Decoder-only (uses masked self-attention)
- Trained on 8M web pages, largest model is 1.5B




Masked Self-Attention



https://cdn.openai.com/better-language-models/language_models_are_unsupervised_multitask_learners.pdf

BERT (2019)



- *Bidirectional* Encoder Representations from Transformers
- Encoder-only (no attention masking)
- 110M params
- 15% of all words masked out



<https://docs.google.com/presentation/d/1flhGikFPnb7G5kr58OvYC3GN4io7MznnM0aAgadvJfc>

T5: Text-to-Text Transfer Transformer (2020)


- Input and output are both text strings
- Encoder-Decoder architecture
- Trained on C4 (Colossal Clean Crawled Corpus) - 100x larger than Wikipedia
- 11B parameters, open source!



<https://ai.ooalebloa.com/2020/02/exploring-transfer-learning-with-t5.html>

GPT-3 (2020)

- Just like GPT/GPT-2, but 100x larger (175B params)
- Exhibits unprecedented few-shot and zero-shot learning
- Not yet overfitting!
- Available via API



Zero-shot

The model predicts the answer given only a natural language description of the task. No gradient updates are performed.

```
1 Translate English to French:  ← task description
2 cheese => .....           ← prompt
```

One-shot

In addition to the task description, the model sees a single example of the task. No gradient updates are performed.

```
1 Translate English to French:  ← task description
2 sea otter => loutre de mer    ← example
3 cheese => .....             ← prompt
```

Few-shot

In addition to the task description, the model sees a few examples of the task. No gradient updates are performed.

```
1 Translate English to French:  ← task description
2 sea otter => loutre de mer    ← examples
3 peppermint => menthe poivrée ← 
4 plush girafe => girafe peluche ← 
5 cheese => .....             ← prompt
```

Instruct-GPT (2022)

- Had humans rank different GPT-3 outputs, and used RL to fine-tune the model
- **Much** better at following instructions
- `text-davinci-002` in the API
 - Unclear how big the model is. Could be ~10x smaller than 175B?

PROMPT *Explain the moon landing to a 6 year old in a few sentences.*

COMPLETION GPT-3

Explain the theory of gravity to a 6 year old.

Explain the theory of relativity to a 6 year old in a few sentences.


Explain the big bang theory to a 6 year old.

Explain evolution to a 6 year old.

InstructGPT

People went to the moon, and they took pictures of what they saw, and sent them back to the earth so we could all see them.

3.



Chinchilla (2022)

- Trained over 400 LM's from 70M to 16B params on 5B to 500B tokens
- Derived formulas for optimal model and training set size given a fixed compute budget
- Found that most LLMs are "undertrained"
- Trained Chinchilla (70B) vs Gopher (280B) at the same compute budget, by using 4x fewer params and 4x more data


| Model | Size (# Parameters) | Training Tokens |
|----------------------------------|---------------------|-----------------|
| LaMDA (Thoppilan et al., 2022) | 137 Billion | 168 Billion |
| GPT-3 (Brown et al., 2020) | 175 Billion | 300 Billion |
| Jurassic (Lieber et al., 2021) | 178 Billion | 300 Billion |
| Gopher (Rae et al., 2021) | 280 Billion | 300 Billion |
| MT-NLG 530B (Smith et al., 2022) | 530 Billion | 270 Billion |
| Chinchilla | 70 Billion | 1.4 Trillion |






Training Compute-Optimal Large Language Models

Jordan Hoffmann*, Sebastian Borgeaud*, Arthur Mensch*, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, Tom Hennigan, Eric Noland, Katie Millican, George van den Driessche, Bogdan Damoc, Aurelia Guy, Simon Osindero, Karen Simonyan, Erich Elsen, Jack W. Rae, Oriol Vinyals and Laurent Sifre*

*Equal contributions



Scaling Law



LLM Vendors

LLM Vendor: OpenAI

- Four model sizes
 - Most GPT-3 results you've seen are from Davinci
 - Probably 350M, 1.3B, 6.7B, and 175B
<https://blog.eleuther.ai/gpt3-model-sizes/>
 - 1000 tokens ~= 750 words
 - I have ~800 tweets, about 40K words, so it would cost ~\$1 to process all my tweets
- Ability to fine-tune models (for extra cost)
- Quota is pretty small to start, over time can raise
- Apply for review before going into production

| Base models | |
|--------------------------------------|----------------------|
| Ada <small>Fastest</small> | \$0.0004 / 1K tokens |
| Babbage | \$0.0005 / 1K tokens |
| Curie | \$0.0020 / 1K tokens |
| Davinci <small>Most powerful</small> | \$0.0200 / 1K tokens |

Cohere.ai

Cohere.ai

Generate

Embed

Classify

Presets

Example Presets

Content Creation

Blog Posts

Email Copy

Hashtag Generator

Product Descriptions

Summarization

Chat Summarization

Article Summarization

Paraphrasing

Spelling & Grammar Check

Correct Errors in Voice to Text Trans...

Information Extraction

Extract Entities from Legal Agreeeme...

Extract Entities from Invoices

Summarize this dialogue:

Customer: Please connect me with a support agent.

AI: Hi there, how can I assist you today?

Customer: I forgot my password and lost access to the email affiliated to my account. Can you please help me?

AI: Yes of course. First I'll need to confirm your identity and then I can connect you with one of our support agents.

TLDR: A customer lost access to their account.

Summarize this dialogue:

AI: Hi there, how can I assist you today?

Customer: I want to book a product demo.

AI: Sounds great. What country are you located in?

Customer: I'll connect you with a support agent who can get something scheduled for you.

TLDR: A customer wants to book a product demo.

Summarize this dialogue:

AI: Hi there, how can I assist you today?

Customer: I want to get more information about your pricing.

AI: I can pull this for you, just a moment.

TLDR:

Clear all

Save

Generate

Generate

Embed

Price per 1 million characters

Imagine a large language model that can be used to write or summarize copy for just about any other application you can think of. That's Generate.

| Model Size | Baseline Model | Finetuned Model* |
|------------|----------------|------------------|
| Large | \$12.00 | Coming Soon |
| Medium | \$1.35 | \$2.70 |
| Small | \$0.25 | \$0.50 |

*It's free to finetune a model, so we'll only charge you when you make calls to it.

Price per 1 million characters

Picture tasking AI to read every single Reddit post about your company, then plot it into an easy-to-understand graph. You can do that, and more, with Embed.

| Model Size | Baseline Model | Finetuned Model* |
|------------|----------------|------------------|
| Large | \$80.00 | Coming Soon |
| Medium | \$20.00 | \$40.00 |
| Small | \$2.00 | \$4.00 |

*It's free to finetune a model, so we'll only charge you when you make calls to it.

https://cohere.ai/pricing

Export code

Share

Parameters

Model

large-20220720 (large)

Number of Tokens

20

Temperature

0.6

Stop Sequences

top-k

0

top-p

1

Frequency penalty

0

AI21

AI21

AI21studio

PlaygroundModelsDatasetsDocsCommunityPricing

Completion

Choose Preset

Generate code

Model

j1-grande (17B)

Max completion length

235

12048

Temperature

0.15

01


Generate code

Q: Write a Python program that calculates the sum of all positive integers smaller than 8.
A: sum(x for x in range(8))
Q: Write a Python program that fetches the current weather in Madrid, Spain.
A: import urllib2
url = "http://www.meteo.es/es/noticias/actualidad/"
response = urllib2.urlopen(url)
html = response.read()
print html
Q:

How was the completion?

| | Prompt Input text | Completion Generated text, per 1K tokens | Request Each time you call the API |
|------------------------------|----------------------|---|---------------------------------------|
| J-1 Large 7.5B parameters | Free | \$0.03 | \$0.0003 |
| J-1 Grande 17B parameters | Free | \$0.08 | \$0.0008 |
| J-1 Jumbo 180B parameters | Free | \$0.25 | \$0.005 |

Open-source LLMs



Prompt Engineering

Alien Technology

- The most recent version of GPT-3 (text-davinci-002, based on InstructGPT) is alien technology
- People are finding out how it works by playing with it
- Here we cover some notable examples
- Play around and you're likely to discover something new!



Prompt Engineering

- GPT-3 is surprisingly bad at reversing words due to **tokenization**:
- It doesn't see letters and words as humans do.
- Instead, it sees “tokens,” which are chunks of characters.
- Furthermore, it gets confused with long-ish sequences.
- Finally, it has trouble merging characters.
- For it to work, you have to teach GPT-3 the algorithm to use to get around its limitations.

Prompt Engineering

Reverse the words below:

Word: alphabet

Reasoning:




- Add spaces between letters: a l p h a b e t
- Add numbers: 1:a 2:l 3:p 4:h 5:a 6:b 7:e 8:t
- Reverse numbers and letters: 8:t 7:e 6:b 5:a 4:h 3:p 2:l 1:a
- Remove numbers: t e b a h p l a
- Merge the letters in groups of two: te ba hp la, teba hpla, tebahpla
- Final result: tebahpla

Word: encyclopedia


Reasoning:

- Add spaces between letters: e n c y c l o p e d i a
- Add numbers: 1:e 2:n 3:c 4:y 5:c 6:l 7:o 8:p 9:e 10:d 11:i 12:a
- Reverse numbers and letters: 12:a 11:i 10:d 9:e 8:p 7:o 6:l 5:c 4:y 3:c 2:n 1:e
- Remove numbers: a i d e p o l c y c n e
- Merge the letters in groups of two: ai de po lc yc ne, aide polc ycne, aidepolcycne
- Final result: aidepolcycne


Mode


Engine

text-davinci-002 

Temperature 0




Maximum length 256




Stop sequences

Enter sequence and press Tab


Top P 1







Frequency penalty 0



Presence penalty 0



Submit

309

Let's think step by step

- Simply adding "Let's think step by step." Increases the accuracy on MultiArithm from 17% to 78%, and on GSM8K from 10% to 40%.
- That's it! 🍷

Question: Alice has 44 apples, and Bob has 20 apples. Alice gives Bob half of her apples. Then, Bob gives Alice 5 apples. How many apples does Alice now have?

Answer: Alice has 31 apples.

Question: Alice has 44 apples, and Bob has 20 apples. Alice gives Bob half of her apples. Then, Bob gives Alice 5 apples. How many apples does Alice now have?

Answer: Let's think step by step.

Alice has 44 apples.

Bob has 20 apples.

Alice gives Bob half of her apples. This means that Alice now has 22 apples.

Bob gives Alice 5 apples. This means that Alice now has 27 apples.

ChatGPT Prompt Engineering for Developers


- <https://www.deeplearning.ai/short-courses/chatgpt-prompt-engineering-for-developers/>



Code

Deepmind Alphacode (2022)

- Pre-trained on Github (715GB) + CodeContests
- Encoder-only 41B model, with filtering
- Top 54% (above average) in Codeforces competitions!



<https://www.deepmind.com/blog/competitive-programming-with-alphacode>

Generating Code

- OpenAI GPT-3 is pretty good at generating code
 - Fine-tuned Codex (in beta) models can be even better

Github Copilot

Github Copilot



Visual Studio Code

max_sum_slice.py

```
1 def max_sum_slice(xs):
2     max_ending = max_so_far = 0
3     for x in xs:
4         max_ending = max(0, max_ending + x)
5         max_so_far = max(max_so_far, max_ending)
6     return max_so_far
```

Previous Next Accept

- Unobtrusive Codex-powered completions in your code editor
- Try it!

[@sergeykarayev](#)



Semantic Search


Semantic Search

- Text (words, sentences, paragraphs, etc) can be embedded with LLMs
- Query (word, sentence, paragraph, etc) can be embedded in the same way
- Cosine similarity between the embedding vectors is good proxy for semantic overlap


Semantic Search Implementation

- The challenge is the computation required. Dense float vectors of even 512 dimensions don't scale past ~10K.
- Libraries like FAISS and ScaNN make such searching feasible
- Great read from Google

Segmenting the search space




Hierarchical Navigable Small World (average path length $\log\log N$)



Vector Search Open-source

- DeepSet Haystack Python library is a high-level
- Another interesting Python open-source: Jina.ai



Initialising a new DocumentStore within Haystack is straightforward.

Elasticsearch

Open Distro for Elasticsearch

OpenSearch

Milvus

FAISS

In Memory

SQL

Weaviate

Pinecone

Vector Search Vendors

- Pinecone is PaaS for vector search that supports filtering and live updates
- Other solutions to check out: Weaviate, Milvus, Qdrant, Google Vector AI Matching Engine

Going Cross-Modal


CLIP: Contrastive Language-Image Pre-Training

CLIP

Learning Transferable Visual Models From Natural Language Supervision

Alec Radford^{*1} Jong Wook Kim^{*1} Chris Hallacy¹ Aditya Ramesh¹ Gabriel Goh¹ Sandhini Agarwal¹
Girish Sastry¹ Amanda Askell¹ Pamela Mishkin¹ Jack Clark¹ Gretchen Krueger¹ Ilya Sutskever¹

- 400M image-text pairs crawled from the Internet
- Transformer to encode text, ResNet or Visual Transformer to encode image
- Contrastive training: maximize cosine similarity of correct image-text pairs (32K pairs per batch)



```
# image_encoder - ResNet or Vision Transformer
# text_encoder - CBOW or Text Transformer
# I[n, h, w, c] - minibatch of aligned images
# T[n, l] - minibatch of aligned texts
# W_i[d_i, d_e] - learned proj of image to embed
# W_t[d_t, d_e] - learned proj of text to embed
# t - learned temperature parameter

# extract feature representations of each modality
I_f = image_encoder(I) #[n, d_i]
T_f = text_encoder(T) #[n, d_t]

# joint multimodal embedding [n, d_e]
I_e = l2_normalize(np.dot(I_f, W_i), axis=1)
T_e = l2_normalize(np.dot(T_f, W_t), axis=1)

# scaled pairwise cosine similarities [n, n]
logits = np.dot(I_e, T_e.T) * np.exp(t)

# symmetric loss function
labels = np.arange(n)
loss_i = cross_entropy_loss(logits, labels, axis=0)
loss_t = cross_entropy_loss(logits, labels, axis=1)
loss = (loss_i + loss_t)/2
```


CLIP Open-source

- OpenAI released all trained CLIP models
- OpenCLIP re-trained them on LAION, and published even bigger ones
- Note that CLIP is image → embedding and text → embedding, not image → text or text → image!

We have trained:

- ViT-B/32 on LAION-400M with an accuracy of 62.9%, comparable to OpenAI's 63.2%, zero-shot top-1 on ImageNet1k
- ViT-B/32 on LAION-2B with an accuracy of 66.6%.
- ViT-B/16 on LAION-400M achieving an accuracy of 67.1%, lower than OpenAI's 68.3% (as measured here, 68.6% in paper)
- ViT-B/16+ 240x240 (~50% more FLOPS than B/16 224x224) on LAION-400M achieving an accuracy of 69.2%
- ViT-L/14 on LAION-400M with an accuracy of 72.77%, vs OpenAI's 75.5% (as measured here, 75.3% in paper)
- ViT-L/14 on LAION-2B with an accuracy of 75.3%, vs OpenAI's 75.5% (as measured here, 75.3% in paper)
- ViT-H/14 on LAION-2B with an accuracy of 78.0. The best in1k zero-shot for released, open-source weights thus far.
- ViT-g/14 on LAION-2B with an accuracy of 76.6. This was trained on reduced schedule, same samples seen as 400M models.

https://github.com/mlfoundations/open_clip

```
model, preprocess = clip.load("ViT-B/32", device=device)

image = preprocess(Image.open("CLIP.png")).unsqueeze(0).to(device)
text = clip.tokenize(["a diagram", "a dog", "a cat"]).to(device)

with torch.no_grad():
    image_features = model.encode_image(image)
    text_features = model.encode_text(text)

    logits_per_image, logits_per_text = model(image, text)
    probs = logits_per_image.softmax(dim=-1).cpu().numpy()

print("Label probs:", probs) # prints: [[0.9927937  0.00421068  0.00299572]]
```

<https://github.com/openai/CLIP>

Cross-modal search

- Since CLIP embeds images and text into a shared space, can search images by text and vice versa...

Backend url:
<https://rom1504.github.io/clip-retrieval>

Index:
knn08

smug face

Clip retrieval works by converting the text query to a CLIP embedding, then using that embedding to query a knn index of clip image embeddings

Display captions ☒
Display full captions ☐
Display similarities ☐
Safe mode ☒
Remove violence ☒
Hide duplicate urls ☒
Hide (near) duplicate images ☒
Enable aesthetic scoring ☐
Aesthetic score
Aesthetic weight
Search over
Search with multilingual clip ☐

Funny dog face meme - photo#29

Asakusa Midori - Eizouken ni wa Te wo Dasu na! I L...

Yukinoshita Haruno (雪ノ下 陽乃) dislikes when Yukinosh...

shizuka

フェネックちゃん(へ

"The feeling when your program finally works"

Photos by bruce mars, LOGAN WEAVER, Vasyi Skunziak on Unsplash.

<https://rom1504.github.io/clip-retrieval>

<https://github.com/haltakov/natural-language-image-search>

@sergevkaraev

Building Multimodal Search

- <https://www.deeplearning.ai/short-courses/building-multimodal-search-and-rag/>

Explore CoursesAI Newsletter ▾

SHORT COURSE

Building Multimodal Search and RAG

Enroll for Free

IN COLLABORATION WITH


 **Weaviate**

CLIP Image Captioning (image \rightarrow text)

- One way is ClipCap: train a network to go from CLIP image embedding to a sequence of "word" embeddings that a LLM like GPT-2 can continue
- Training data is (image, caption) pairs, mapping network is a transformer; CLIP and GPT-2 are frozen


ClipCap: CLIP Prefix for Image Captioning

Ron Mokady* Amir Hertz* Amit H. Bermano
The Blavatnik School of Computer Science, Tel Aviv University



CLIP Image Generation (text → image)

- unCLIP (DALL-E 2)
 - CLIP: text encoder + image encoder
 - *Prior*: mapping from text embedding to image embedding
 - *Decoder*: mapping from image embedding to image
- Unclear training data



Hierarchical Text-Conditional Image Generation with CLIP Latents

Aditya Ramesh*
OpenAI
aramesh@openai.com

Prafulla Dhariwal*
OpenAI
prafulla@openai.com

Alex Nichol*
OpenAI
alex@openai.com

Casey Chu*
OpenAI
casey@openai.com

Mark Chen
OpenAI
mark@openai.com

More ???