

WARNER BROS. DISCOVERY

Software Engineering Interview

7-Day DSA Complete Reference Manual

40 Solved LeetCode Problems in Swift 6 with Line-by-Line Logic, Xcode Syntax Highlighting & Clickable Problem URLs

Target Role: Software Engineer (iOS / Core Swift)	Curriculum Length: 7 Days
Total Solved Programs: 40 Complete Solutions	Language: Swift 6
Playground Artifact: WBD_7Day_DSAPrep.playground	LeetCode Links: 100% Clickable URLs Included

Curriculum Strategy & Priority Blueprint

This master reference manual contains full Swift 6 implementations and detailed algorithmic logic for all 40 core coding interview problems. Each section provides: (1) **Algorithmic Intuition & Logic**, (2) **Swift Implementation formatted in Xcode Light Theme**, (3) **Formal Time & Space Complexity Analyses**, and (4) **Clickable LeetCode Problem URLs**.

Priority Tier	Core Topics	Target Mastery
Tier 1 (Critical █████)	Arrays & Hashing, Sliding Window, Trees & BST	15-20 min O(N) execution
Tier 2 (High ████)	Linked Lists, Binary Search, Graphs, Stack	20 min pattern recognition
Tier 3 (Medium ███)	Heap / Priority Queue, Dynamic Programming	1D DP & Top K patterns

Day 1: Arrays & Hashing

1. Two Sum (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Use a Hash Map mapping element values to their indices. For each number, compute complement = target - num. If complement exists in map, return indices immediately. Otherwise, store current num in map.

```
class TwoSum {
    static func solve(_ nums: [Int], _ target: Int) -> [Int] {
        var map = [Int: Int]()
        for (i, num) in nums.enumerated() {
            let complement = target - num
            if let complementIndex = map[complement] {
                return [complementIndex, i]
            }
            map[num] = i
        }
        return []
    }
}
```

Time Complexity: $O(N)$ - Single pass over array of length N

Space Complexity: $O(N)$ - Hash map storing up to N entries

2. Contains Duplicate (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Use a Hash Set to track visited elements. As we iterate through the array, check if current element is already present in the set. If yes, duplicate exists. Otherwise, insert element into set.

```
class ContainsDuplicate {
    static func solve(_ nums: [Int]) -> Bool {
        var seen = Set<Int>()
        for num in nums {
            if seen.contains(num) { return true }
            seen.insert(num)
        }
        return false
    }
}
```

Time Complexity: $O(N)$ - Single pass over N elements

Space Complexity: $O(N)$ - Space for Set storing unique values

3. Best Time to Buy and Sell Stock (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Maintain a running minimum purchase price `minPrice`. Iterate through stock prices: compute potential profit price - `minPrice` and update global `maxProfit`. Update `minPrice` whenever a lower price is found.

```
class BuySellStock {
    static func solve(_ prices: [Int]) -> Int {
        var minPrice = Int.max, maxProfit = 0
        for price in prices {
            minPrice = min(minPrice, price)
            maxProfit = max(maxProfit, price - minPrice)
        }
        return maxProfit
    }
}
```

Time Complexity: O(N) - Single linear pass

Space Complexity: O(1) - Constant auxiliary space

4. Maximum Subarray (Medium - Kadane's Algorithm) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Kadane's algorithm: At each element, decide whether to append element to existing running subarray sum (`currentSum + num`) or start a fresh subarray from `num`. Track global maximum `maxSoFar` across all steps.

```
class MaxSubarray {
    static func solve(_ nums: [Int]) -> Int {
        guard !nums.isEmpty else { return 0 }
        var maxSoFar = nums[0], currentSum = nums[0]
        for num in nums.dropFirst() {
            currentSum = max(num, currentSum + num)
            maxSoFar = max(maxSoFar, currentSum)
        }
        return maxSoFar
    }
}
```

Time Complexity: O(N) - Linear pass through array

Space Complexity: O(1) - Constant memory variables

5. Longest Substring Without Repeating Characters (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Sliding window with two pointers `left` and `right`. Maintain a hash map of character -> last seen index. When a duplicate character is encountered inside window (`lastSeen >= left`), jump left past `lastSeen`.

```
class LongestSubstringWithoutRepeating {
    static func solve(_ s: String) -> Int {
        let chars = Array(s)
        var map = [Character: Int](), left = 0, maxLen = 0
        for (right, char) in chars.enumerated() {
            if let lastPos = map[char], lastPos >= left {
                left = lastPos + 1
            }
            map[char] = right
            maxLen = max(maxLen, right - left + 1)
        }
        return maxLen
    }
}
```

Time Complexity: O(N) - Linear sweep of string length N

Space Complexity: O(min(N, M)) - Space for character map

6. Product of Array Except Self (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Two prefix passes without division. Pass 1: compute prefix products from left to right into result array. Pass 2: compute suffix products from right to left while multiplying directly into result array.

```
class ProductExceptSelf {
    static func solve(_ nums: [Int]) -> [Int] {
        let n = nums.count
        var result = Array(repeating: 1, count: n)
        var leftProd = 1
        for i in 0..
```

Time Complexity: $O(N)$ - Two linear passes

Space Complexity: $O(1)$ - Output array does not count as extra space

Day 2: Strings, Linked Lists & Stack

7. Valid Anagram (Easy) [■ Open LeetCode Problem](#)

Logic & Intuition: Count character occurrences in string *s* using a hash map or frequency array. Decrement counts while iterating through string *t*. Return false if count drops below 0 or lengths differ.

```
class ValidAnagram {
    static func solve(_ s: String, _ t: String) -> Bool {
        guard s.count == t.count else { return false }
        var counts = [Character: Int]()
        for char in s { counts[char, default: 0] += 1 }
        for char in t {
            guard let count = counts[char], count > 0 else { return false }
            counts[char] = count - 1
        }
        return true
    }
}
```

Time Complexity: O(N) - Linear pass over both strings

Space Complexity: O(1) - Fixed 26-letter frequency table

8. Valid Parentheses (Easy) [■ Open LeetCode Problem](#)

Logic & Intuition: Push opening brackets onto stack. For closing brackets, check if stack is non-empty and matching opening bracket is at stack top. If valid, pop top; otherwise return false. Check stack is empty at end.

```
class ValidParentheses {
    static func solve(_ s: String) -> Bool {
        var stack = [Character]()
        let map: [Character: Character] = [")": "(", "]"": "[", "}": "{"]
        for char in s {
            if let expected = map[char] {
                if stack.isEmpty || stack.removeLast() != expected { return false }
            } else {
                stack.append(char)
            }
        }
        return stack.isEmpty
    }
}
```

Time Complexity: O(N) - Single pass over string length N

Space Complexity: O(N) - Stack storing up to N brackets

9. Reverse Linked List (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Iterative 3-pointer strategy: maintain *prev* (starts *nil*) and *curr* (starts *head*). Save *nextTemp* = *curr.next*, set *curr.next* = *prev*, then advance *prev* = *curr* and *curr* = *nextTemp*. Return *prev*.

```
class ReverseLinkedList {
    static func solve(_ head: ListNode?) -> ListNode? {
        var prev: ListNode? = nil, curr = head
        while curr != nil {
            let nextTemp = curr?.next
            curr?.next = prev
            prev = curr
            curr = nextTemp
        }
        return prev
    }
}
```

Time Complexity: $O(N)$ - Single pass over linked list nodes **Space Complexity:** $O(1)$ - Constant auxiliary pointer space

10. Merge Two Sorted Lists (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Use dummy head node with pointer *tail*. Compare values *p1.val* vs *p2.val*, attach smaller node to *tail.next*, and advance that list pointer. Attach remaining non-*nil* list at end.

```
class MergeTwoLists {
    static func solve(_ l1: ListNode?, _ l2: ListNode?) -> ListNode? {
        let dummy = ListNode(0)
        var tail = dummy, p1 = l1, p2 = l2
        while let n1 = p1, let n2 = p2 {
            if n1.val <= n2.val { tail.next = n1; p1 = n1.next }
            else { tail.next = n2; p2 = n2.next }
            tail = tail.next!
        }
        tail.next = p1 ?? p2
        return dummy.next
    }
}
```

Time Complexity: $O(N + M)$ - Proportional to nodes in both lists

Space Complexity: $O(1)$ - Constant extra pointers

11. Linked List Cycle (Easy - Floyd's Tortoise and Hare) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Fast & Slow pointer pattern. Advance slow pointer by 1 step and fast pointer by 2 steps. If a cycle exists, fast will eventually meet slow (slow === fast). If fast hits nil, no cycle exists.

```
class LinkedListCycle {
    static func hasCycle(_ head: ListNode?) -> Bool {
        var slow = head, fast = head
        while fast != nil && fast?.next != nil {
            slow = slow?.next
            fast = fast?.next?.next
            if slow === fast { return true }
        }
        return false
    }
}
```

Time Complexity: O(N) - Fast pointer travels at most 2N steps

Space Complexity: O(1) - Two extra pointers

12. Remove Nth Node From End of List (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Two pointers first and second initialized at dummy node. Advance first by $n + 1$ steps to create a gap of n nodes between them. Move both pointers together until first reaches nil. Unlink node.

```
class RemoveNthFromEnd {
    static func solve(_ head: ListNode?, _ n: Int) -> ListNode? {
        let dummy = ListNode(0, head)
        var first: ListNode? = dummy, second: ListNode? = dummy
        for _ in 0...n { first = first?.next }
        while first != nil {
            first = first?.next
            second = second?.next
        }
        second?.next = second?.next?.next
        return dummy.next
    }
}
```

Time Complexity: O(N) - Single pass over list

Space Complexity: O(1) - Constant pointer space

13. Min Stack (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Maintain two parallel stacks: *mainStack* for storing values, and *minStack* for storing the minimum value present up to that depth. On push, push $\min(\text{val}, \text{minStack.last})$ onto *minStack*.

```
class MinStack {
    private var mainStack = [Int](), minStack = [Int]()
    func push(_ val: Int) {
        mainStack.append(val)
        let curMin = minStack.last ?? Int.max
        minStack.append(min(val, curMin))
    }
    func pop() { _ = mainStack.popLast(); _ = minStack.popLast() }
    func top() -> Int { return mainStack.last ?? -1 }
    func getMin() -> Int { return minStack.last ?? -1 }
}
```

Time Complexity: $O(1)$ - Constant time for push, pop, top, getMin

Space Complexity: $O(N)$ - Dual stacks storing N values

Day 3: Binary Search, Sorting & Intervals

14. Binary Search (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Maintain left and right pointers. Calculate $mid = left + (right - left) / 2$ to avoid integer overflow. Compare $nums[mid]$ with target to halve search range at each step.

```
class BinarySearch {
    static func solve(_ nums: [Int], _ target: Int) -> Int {
        var left = 0, right = nums.count - 1
        while left <= right {
            let mid = left + (right - left) / 2
            if nums[mid] == target { return mid }
            else if nums[mid] < target { left = mid + 1 }
            else { right = mid - 1 }
        }
        return -1
    }
}
```

Time Complexity: $O(\log N)$ - Halves search space per step **Space Complexity:** $O(1)$ - Iterative search

15. Search in Rotated Sorted Array (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Binary search on rotated array: At mid, check if left half $nums[left...mid]$ is sorted ($nums[left] \leq nums[mid]$). If yes, check if target lies in left range; else search right half.

```
class SearchRotated {
    static func solve(_ nums: [Int], _ target: Int) -> Int {
        var left = 0, right = nums.count - 1
        while left <= right {
            let mid = left + (right - left) / 2
            if nums[mid] == target { return mid }
            if nums[left] <= nums[mid] {
                if nums[left] <= target && target < nums[mid] { right = mid - 1 }
                else { left = mid + 1 }
            } else {
                if nums[mid] < target && target <= nums[right] { left = mid + 1 }
                else { right = mid - 1 }
            }
        }
        return -1
    }
}
```

Time Complexity: $O(\log N)$ - Modified binary search **Space Complexity:** $O(1)$ - Constant variables

16. Find Minimum in Rotated Sorted Array (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Compare `nums[mid]` with right boundary `nums[right]`. If `nums[mid] > nums[right]`, minimum lies strictly in right half (`left = mid + 1`). Otherwise minimum is at `mid` or in left half (`right = mid`).

```
class FindMinRotated {
    static func solve(_ nums: [Int]) -> Int {
        var left = 0, right = nums.count - 1
        while left < right {
            let mid = left + (right - left) / 2
            if nums[mid] > nums[right] { left = mid + 1 }
            else { right = mid }
        }
        return nums[left]
    }
}
```

Time Complexity: $O(\log N)$ - Logarithmic search

Space Complexity: $O(1)$ - Constant extra space

17. Koko Eating Bananas (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Binary search on eating speed k in range $1 \dots \text{maxPile}$. For candidate speed k , compute total hours spent using ceiling division $(\text{pile} + k - 1) / k$. If $\text{hours} \leq h$, try smaller speed.

```
class KokoEatingBananas {
    static func minEatingSpeed(_ piles: [Int], _ h: Int) -> Int {
        var left = 1, right = piles.max() ?? 1, result = right
        while left <= right {
            let k = left + (right - left) / 2
            var hours = 0
            for pile in piles { hours += (pile + k - 1) / k }
            if hours <= h { result = k; right = k - 1 }
            else { left = k + 1 }
        }
        return result
    }
}
```

Time Complexity: $O(N \log(\text{MaxPile}))$ - N piles * binary search on max pile

Space Complexity: $O(1)$ - Constant auxiliary space

18. Merge Intervals (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Sort intervals by start times $start_i$. Maintain `currentInterval`. Iterate sorted list: if $next.start \leq current.end$, merge by setting $current.end = \max(current.end, next.end)$. Else push current and update.

```
class MergeIntervals {
    static func solve(_ intervals: [[Int]]) -> [[Int]] {
        guard intervals.count > 1 else { return intervals }
        let sorted = intervals.sorted { $0[0] < $1[0] }
        var res = [[Int]](), curr = sorted[0]
        for next in sorted.dropFirst() {
            if next[0] <= curr[1] { curr[1] = max(curr[1], next[1]) }
            else { res.append(curr); curr = next }
        }
        res.append(curr)
        return res
    }
}
```

Time Complexity: $O(N \log N)$ - Sorting intervals takes $N \log N$

Space Complexity: $O(N)$ - Storage for merged result

19. Insert Interval (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: 3 Phase processing: (1) Add all intervals ending before $newInterval.start$. (2) Merge all overlapping intervals with $newInterval$ by expanding bounds. (3) Add all remaining intervals starting after.

```
class InsertInterval {
    static func solve(_ intervals: [[Int]], _ newInterval: [Int]) -> [[Int]] {
        var res = [[Int]](), newInt = newInterval, i = 0, n = intervals.count
        while i < n && intervals[i][1] < newInt[0] { res.append(intervals[i]); i += 1 }
        while i < n && intervals[i][0] <= newInt[1] {
            newInt[0] = min(newInt[0], intervals[i][0])
            newInt[1] = max(newInt[1], intervals[i][1])
            i += 1
        }
        res.append(newInt)
        while i < n { res.append(intervals[i]); i += 1 }
        return res
    }
}
```

Time Complexity: $O(N)$ - Single linear pass over sorted intervals

Space Complexity: $O(N)$ - Output array space

20. Non-Overlapping Intervals (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Greedy choice: Sort intervals by end times end_i . Maintain $lastEnd$. When an overlapping interval is found ($interval.start < lastEnd$), increment removal count. Otherwise update $lastEnd = interval.end$.

```
class NonOverlappingIntervals {
    static func eraseOverlapIntervals(_ intervals: [[Int]]) -> Int {
        guard !intervals.isEmpty else { return 0 }
        let sorted = intervals.sorted { $0[1] < $1[1] }
        var removals = 0, lastEnd = sorted[0][1]
        for interval in sorted.dropFirst() {
            if interval[0] < lastEnd { removals += 1 }
            else { lastEnd = interval[1] }
        }
        return removals
    }
}
```

Time Complexity: $O(N \log N)$ - Sorting intervals

Space Complexity: $O(1)$ - Constant variables

Day 4: Trees & Binary Search Trees

21. Maximum Depth of Binary Tree (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Recursion base case: nil node has depth 0. For non-nil node, depth is $1 + \max(\text{depth}(\text{left}), \text{depth}(\text{right}))$. Postorder DFS traversal.

```
class MaxDepthBinaryTree {
    static func maxDepth(_ root: TreeNode?) -> Int {
        guard let root = root else { return 0 }
        return 1 + max(maxDepth(root.left), maxDepth(root.right))
    }
}
```

Time Complexity: $O(N)$ - Visits each tree node once

Space Complexity: $O(H)$ - Recursion call stack proportional to height H

22. Invert Binary Tree (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Recursively swap left and right children: save `root.left`, set `root.left = invertTree(root.right)` and `root.right = invertTree(temp)`. Return `root`.

```
class InvertBinaryTree {
    static func invertTree(_ root: TreeNode?) -> TreeNode? {
        guard let root = root else { return nil }
        let temp = root.left
        root.left = invertTree(root.right)
        root.right = invertTree(temp)
        return root
    }
}
```

Time Complexity: $O(N)$ - Visits all nodes

Space Complexity: $O(H)$ - Call stack space

23. Binary Tree Level Order Traversal (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: BFS Queue traversal. Process level by level: snapshot current queue.count, dequeue nodes of current level into level array, and enqueue non-nil left and right children.

```
class LevelOrderTraversal {
    static func solve(_ root: TreeNode?) -> [[Int]] {
        guard let root = root else { return [] }
        var res = [[Int]](), queue = [root]
        while !queue.isEmpty {
            let levelSize = queue.count
            var level = [Int]()
            for _ in 0..

```

Time Complexity: $O(N)$ - Dequeues every node once

Space Complexity: $O(N)$ - Queue holds max nodes at tree level

24. Diameter of Binary Tree (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: At each node, the longest path passing through it is leftDepth + rightDepth. Maintain a global maxDiameter. Recursive depth helper returns $1 + \max(\text{leftDepth}, \text{rightDepth})$.

```
class DiameterBinaryTree {
    static func diameterOfBinaryTree(_ root: TreeNode?) -> Int {
        var maxDia = 0
        func depth(_ node: TreeNode?) -> Int {
            guard let node = node else { return 0 }
            let l = depth(node.left), r = depth(node.right)
            maxDia = max(maxDia, l + r)
            return 1 + max(l, r)
        }
        _ = depth(root)
        return maxDia
    }
}
```

Time Complexity: $O(N)$ - Single pass over tree

Space Complexity: $O(H)$ - Recursion depth H

25. Validate Binary Search Tree (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Recursive bound validation: pass minVal and maxVal down recursive calls. Left child must satisfy val < parent.val, right child must satisfy val > parent.val.

```
class ValidateBST {
    static func isValidBST(_ root: TreeNode?) -> Bool { return helper(root, nil, nil) }
    private static func helper(_ node: TreeNode?, _ min: Int?, _ max: Int?) -> Bool {
        guard let node = node else { return true }
        if let min = min, node.val <= min { return false }
        if let max = max, node.val >= max { return false }
        return helper(node.left, min, node.val) && helper(node.right, node.val, max)
    }
}
```

Time Complexity: O(N) - Visits each node once

Space Complexity: O(H) - Call stack depth H

26. Lowest Common Ancestor (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Recursive bottom-up search: if root is nil, p, or q, return root. Recurse left and right subtrees. If both left and right return non-nil, root is the LCA. Otherwise return non-nil branch.

```
class LowestCommonAncestor {
    static func solve(_ root: TreeNode?, _ p: TreeNode?, _ q: TreeNode?) -> TreeNode? {
        if root == nil || root === p || root === q { return root }
        let left = solve(root?.left, p, q), right = solve(root?.right, p, q)
        if left != nil && right != nil { return root }
        return left != nil ? left : right
    }
}
```

Time Complexity: O(N) - Worst case visits all nodes

Space Complexity: O(H) - Call stack depth

27. Kth Smallest Element in a BST (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Iterative Inorder traversal (Left -> Node -> Right) using a stack. Nodes are popped in strictly ascending order. Increment counter on pop; when counter == k, return node value.

```
class KthSmallestBST {
    static func kthSmallest(_ root: TreeNode?, _ k: Int) -> Int {
        var stack = [TreeNode](), curr = root, count = 0
        while curr != nil || !stack.isEmpty {
            while let node = curr { stack.append(node); curr = node.left }
            let node = stack.removeLast()
            count += 1
            if count == k { return node.val }
            curr = node.right
        }
        return -1
    }
}
```

Time Complexity: O(H + K) - Traverses to left leaf and pops K nodes

Space Complexity: O(H) - Stack depth H

Day 5: Graphs

28. Number of Islands (Medium) [Open LeetCode Problem](#)

Logic & Intuition: Iterate 2D grid cell by cell. When a land cell '1' is found, increment island counter and launch DFS to sink all connected land cells by mutating them to '0'.

```
class NumberOfIslands {
    static func numIslands(_ grid: [[Character]]) -> Int {
        guard !grid.isEmpty else { return 0 }
        var g = grid, rows = g.count, cols = g[0].count, count = 0
        for r in 0..

```

Time Complexity: $O(M * N)$ - Every grid cell visited at most a constant number of times

Space Complexity: $O(M * N)$ - Worst case recursion depth for all land cells

29. Clone Graph (Medium) [Open LeetCode Problem](#)

Logic & Intuition: Deep copy undirected graph using DFS and a visited dictionary mapping original node value -> cloned Node. For each neighbor of current node, attach recursively cloned neighbor.

```
class CloneGraph {
    static func clone(_ node: Node?) -> Node? {
        guard let node = node else { return nil }
        var visited = [Int: Node]()
        func dfs(_ curr: Node) -> Node {
            if let cloned = visited[curr.val] { return cloned }
            let copy = Node(curr.val)
            visited[curr.val] = copy
            for n in curr.neighbors { copy.neighbors.append(dfs(n)) }
            return copy
        }
        return dfs(node)
    }
}
```

Time Complexity: $O(V + E)$ - Visits all vertices V and edges E

Space Complexity: $O(V)$ - Visited dictionary storing V nodes

30. Course Schedule (Medium - Topological Sort) [■ Open LeetCode Problem](#)

Logic & Intuition: Kahn's Algorithm BFS: Build adjacency list and in-degree count for each course. Enqueue all courses with in-degree 0. Dequeue course, increment processed count, and decrement in-degree of neighbors.

```
class CourseSchedule {
    static func canFinish(_ numCourses: Int, _ pre: [[Int]]) -> Bool {
        var inDeg = Array(repeating: 0, count: numCourses), adj = [Int: [Int]]()
        for p in pre { adj[p[1], default: []].append(p[0]); inDeg[p[0]] += 1 }
        var q = (0..

```

Time Complexity: $O(V + E)$ - Processing nodes and edges **Space Complexity:** $O(V + E)$ - Adjacency list and in-degree table

31. Rotting Oranges (Medium - Multi-Source BFS) [■ Open LeetCode Problem](#)

Logic & Intuition: Multi-Source BFS: Enqueue all rotten oranges 2 initially and count fresh oranges 1. Process queue level by level (1 minute step). Rot adjacent fresh oranges and enqueue them.

```
class RottingOranges {
    static func orangesRotting(_ grid: [[Int]]) -> Int {
        var g = grid, R = g.count, C = g[0].count, q = [(Int, Int)](), fresh = 0
        for r in 0..

```

Time Complexity: $O(M * N)$ - Every cell visited in BFS **Space Complexity:** $O(M * N)$ - Queue space for grid cells

32. Pacific Atlantic Water Flow (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Reverse ocean border DFS: Start DFS from Pacific borders (top/left) and Atlantic borders (bottom/right). Water flows uphill (nextHeight >= currHeight). Result cells are reachable by both oceans.

```
class PacificAtlantic {
    static func solve(_ heights: [[Int]]) -> [[Int]] {
        guard !heights.isEmpty else { return [] }
        let R = heights.count, C = heights[0].count
        var pac = Array(repeating: Array(repeating: false, count: C), count: R)
        var atl = Array(repeating: Array(repeating: false, count: C), count: R)
        func dfs(_ r: Int, _ c: Int, _ vis: inout [[Bool]], _ prev: Int) {
            if r < 0 || c < 0 || r >= R || c >= C || vis[r][c] || heights[r][c] < prev { return }
            vis[r][c] = true
            dfs(r+1, c, &vis, heights[r][c]); dfs(r-1, c, &vis, heights[r][c])
            dfs(r, c+1, &vis, heights[r][c]); dfs(r, c-1, &vis, heights[r][c])
        }
        for c in 0..

```

Time Complexity: $O(M * N)$ - DFS from ocean borders

Space Complexity: $O(M * N)$ - Matrix for ocean visited flags

33. Graph Valid Tree (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: A graph of n nodes is a valid tree iff: (1) edges.count == $n - 1$, and (2) it is fully connected with no cycles (DFS starting from node 0 visits all n nodes without visiting parent).

```
class GraphValidTree {
    static func validTree(_ n: Int, _ edges: [[Int]]) -> Bool {
        if edges.count != n - 1 { return false }
        var adj = [Int: [Int]]()
        for e in edges {
            adj[e[0], default: []].append(e[1]); adj[e[1], default: []].append(e[0])
        }
        var visited = Set<Int>()
        func dfs(_ curr: Int, _ parent: Int) -> Bool {
            if visited.contains(curr) { return false }
            visited.insert(curr)
            for neighbor in adj[curr] ?? [] {
                if neighbor == parent { continue }
                if !dfs(neighbor, curr) { return false }
            }
            return true
        }
        return dfs(0, -1) && visited.count == n
    }
}
```

Time Complexity: $O(V + E)$ - DFS graph traversal

Space Complexity: $O(V + E)$ - Adjacency list + visited set

Day 6: Dynamic Programming & Heap

34. Climbing Stairs (Easy) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Fibonacci DP transition: $dp[i] = dp[i-1] + dp[i-2]$. Space optimized to two rolling variables first and second representing previous step combinations.

```
class ClimbingStairs {
    static func climbStairs(_ n: Int) -> Int {
        if n <= 2 { return n }
        var first = 1, second = 2
        for _ in 3...n {
            let third = first + second
            first = second; second = third
        }
        return second
    }
}
```

Time Complexity: $O(N)$ - Linear iteration up to stair N

Space Complexity: $O(1)$ - Constant variables

35. House Robber (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: 1D DP state: At house i , max stolen money is $\max(\text{prev1}, \text{prev2} + \text{num})$. Maintain prev1 (max up to $i-1$) and prev2 (max up to $i-2$) across iteration.

```
class HouseRobber {
    static func rob(_ nums: [Int]) -> Int {
        var prev1 = 0, prev2 = 0
        for num in nums {
            let current = max(prev1, prev2 + num)
            prev2 = prev1; prev1 = current
        }
        return prev1
    }
}
```

Time Complexity: $O(N)$ - Single pass over houses

Space Complexity: $O(1)$ - Rolling variables

36. Coin Change (Medium) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Unbounded knapsack bottom-up DP table dp of size $amount + 1$ initialized to $amount + 1$. Base case $dp[0] = 0$. For i in $1 \dots amount$, $dp[i] = \min(dp[i], dp[i - coin] + 1)$.

```
class CoinChange {
    static func solve(_ coins: [Int], _ amount: Int) -> Int {
        guard amount > 0 else { return 0 }
        var dp = Array(repeating: amount + 1, count: amount + 1)
        dp[0] = 0
        for i in 1...amount {
            for coin in coins {
                if i - coin >= 0 { dp[i] = min(dp[i], dp[i - coin] + 1) }
            }
        }
        return dp[amount] > amount ? -1 : dp[amount]
    }
}
```

Time Complexity: $O(\text{Amount} * \text{Coins.count})$ - Inner loop over coin types

Space Complexity: $O(\text{Amount})$ - 1D DP table array

37. Longest Increasing Subsequence (Medium - Patience Sorting) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Maintain tails array storing smallest tail value of all increasing subsequences of length $i+1$. Binary search position of num in tails: replace element or append.

```
class LongestIncreasingSubsequence {
    static func lengthOfLIS(_ nums: [Int]) -> Int {
        var tails = [Int]()
        for num in nums {
            var left = 0, right = tails.count
            while left < right {
                let mid = left + (right - left) / 2
                if tails[mid] < num { left = mid + 1 }
                else { right = mid }
            }
            if left == tails.count { tails.append(num) }
            else { tails[left] = num }
        }
        return tails.count
    }
}
```

Time Complexity: $O(N \log N)$ - Binary search inside linear loop

Space Complexity: $O(N)$ - Space for tails array

38. Word Break (Medium) [Open LeetCode Problem](#)

Logic & Intuition: Boolean DP table $dp[i]$ representing if string prefix $s[0..<i]$ can be segmented. Base case $dp[0] = \text{true}$. For j from 0 to $i-1$, if $dp[j] \ \&\& \ \text{wordSet.contains}(s[j..<i])$, set $dp[i] = \text{true}$.

```
class WordBreak {
    static func solve(_ s: String, _ wordDict: [String]) -> Bool {
        let dict = Set(wordDict), n = s.count, chars = Array(s)
        var dp = Array(repeating: false, count: n + 1)
        dp[0] = true
        for i in 1...n {
            for j in 0.. {
                if dp[j] && dict.contains(String(chars[j..

```

Time Complexity: $O(N^2 * L)$ - Substring slice and set check

Space Complexity: $O(N + D)$ - DP array and dictionary hash set

39. Kth Largest Element in an Array (Medium - QuickSelect) [Open LeetCode Problem](#)

Logic & Intuition: QuickSelect algorithm: Partition array around pivot element. If pivot index equals target rank (count - k), return pivot value. Otherwise recurse into left or right partition.

```
class KthLargestElement {
    static func findKthLargest(_ nums: [Int], _ k: Int) -> Int {
        var copy = nums, target = copy.count - k
        func quickSelect(_ l: Int, _ r: Int) -> Int {
            if l == r { return copy[l] }
            let p = partition(&copy, l, r)
            if p == target { return copy[p] }
            else if p < target { return quickSelect(p + 1, r) }
            else { return quickSelect(l, p - 1) }
        }
        return quickSelect(0, copy.count - 1)
    }
    private static func partition(_ nums: inout [Int], _ l: Int, _ r: Int) -> Int {
        let pivot = nums[r]; var i = l
        for j in l..r {
            if nums[j] <= pivot { nums.swapAt(i, j); i += 1 }
        }
        nums.swapAt(i, r)
        return i
    }
}
```

Time Complexity: $O(N)$ Average, $O(N^2)$ Worst Case - QuickSelect expected time

Space Complexity: $O(1)$ - In-place partition

40. Top K Frequent Elements (Medium - Bucket Sort) [\[■ Open LeetCode Problem\]](#)

Logic & Intuition: Count frequency of each number into hash map. Create bucket array buckets where index represents frequency count. Iterate buckets backwards from highest frequency to collect top k elements.

```
class TopKFrequent {
    static func solve(_ nums: [Int], _ k: Int) -> [Int] {
        var counts = [Int: Int]()
        for num in nums { counts[num, default: 0] += 1 }
        var buckets = Array(repeating: [Int](), count: nums.count + 1)
        for (num, freq) in counts { buckets[freq].append(num) }
        var res = [Int]()
        for i in (0..nums.count).reversed() {
            for num in buckets[i] {
                res.append(num); if res.count == k { return res }
            }
        }
        return res
    }
}
```

Time Complexity: $O(N)$ - Bucket sort linear sweep

Space Complexity: $O(N)$ - Hash map and bucket storage

Day 7: Mock Interview & Final Revision Guide

Day 7 is dedicated to consolidating all learned patterns and performing timed mock interview simulations. Do not learn new topics on Day 7. Focus on clean communication, Big-O mastery, and edge-case validation.

■ 7-Step Interview Response Framework

1. **Clarify Requirements:** Confirm array length, range of integers, duplicates, nulls, and expected return types.
2. **State Naive / Brute Force Solution:** State the naive approach and analyze its Time & Space complexity out loud.
3. **Identify Optimal Pattern:** Transition to the optimal pattern (e.g. Hash Map, Two Pointers, BFS, DP).
4. **Discuss Time vs Space Trade-offs:** Explain why spending memory improves time (e.g. $O(N)$ space map reduces time to $O(N)$).
5. **Write Clean Swift Code:** Write idiomatic Swift with type inference, clean optionals, and guard statements.
6. **Dry Run with Sample Inputs:** Walk through your code line-by-line using a short test array.
7. **Test Edge Cases:** Test empty input, single element, negative numbers, duplicates, and max boundaries.

■ Master Data Structure Complexity Reference Table

Data Structure / Algorithm	Access	Search	Insertion / Deletion	Space Complexity
Array / Contiguous Buffer	$O(1)$	$O(N)$	$O(N)$	$O(N)$
Hash Map / Set	N/A	$O(1)$ Avg	$O(1)$ Avg	$O(N)$
Singly Linked List	$O(N)$	$O(N)$	$O(1)$ at Head	$O(N)$
Binary Search Tree (BST)	$O(H)$	$O(H)$	$O(H)$	$O(N)$
Min / Max Heap	$O(1)$ Top	$O(N)$	$O(\log N)$ Push/Pop	$O(N)$
Graph BFS / DFS	N/A	$O(V + E)$	$O(V + E)$	$O(V + E)$
Binary Search	N/A	$O(\log N)$	N/A	$O(1)$ Iterative

■ Final Checklist Before Interview

- ✓■ Ensure 100% test assertions pass in `WBD_7Day_DSAPrep.playground`.
- ✓■ Memorize binary search templates (`left <= right` vs `left < right`).
- ✓■ Practice speaking out loud while coding in Swift.
- ✓■ Stay calm, communicate clearly, and enjoy the problem-solving process!