



Computer Engineering Department

Course name: Web Technologies

Course code: 2CP08

Faculty: Prof Kirtikumar Sharma

ID: 23CP029

Name: Viral Vipulkumar Bhoi

Topic: Report of LAB - 4

LAB 3: Cascading Style Sheets (CSS): Create Mypage.html using an external style sheet. Adding CSS: External, Internal and Inline

TABLE OF CONTENT:

4.1 Cascading Style Sheets (CSS).....	3
4.2 HTML code for Mypage	4
4.3 CSS code for Mypage	7
4.4 Output	9
4.5 Q1	10
4.6 Q2	11

4.1 CSS And html Tags ::

1. ID:

- The id attribute is used in HTML to assign a unique identifier to an element
- Same id cannot be given to more than one element.

2. Class:

- a **class** is an attribute used to group multiple elements.

3. <link>:

- It is used to define a relationship between the current document and an external resource.

4. CSS:

- CSS (cascading stylesheet) used to define overall looks of webpage, three ways to include : inline, internal and external.

5. CSS block:

- selector { property: value; }.

6. Select by element name:

- Ele_name { property: value; }.

7. Select by element id:

- #id_name { property: value; }.

8. Select by element class:

- .id_name { property: value; }.

9. Pseudo class:

- A **pseudo-class** targets elements based on their state or behaviour.
- selector:pseudo-class { property: value; }
- e.g. hover , nth-child, first-child, last-child etc.

10. Pseudo element:

- A **pseudo-element** allows you to style specific parts of an element.
- selector::pseudo-element { property: value; }
- e.g. before, after, first-letter, etc.

11. <Style>:

- Used for internal CSS. Defined inside head tag.

4.2 HTML code for Mypage:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title> Mypage </title>
```

```
    <link rel="stylesheet" href="style.css">
```

```
  </head>
```

```
  <body>
```

```
    <h1> working with css </h1>
```

```
    <p> this is a random paragraph. this is a random paragraph. this is a random paragraph. this is a random paragraph. this is a random paragraph. this is a random paragraph. </p>
```

```
  <table>
```

```
    <tr>
```

```
      <th> roll no. </th>
```

```
      <th> sub-1 </th>
```

```
      <th> sub-2 </th>
```

```
    </tr>
```

```
    <tr>
```

```
      <td> 1001 </td>
```

```
      <td> 45 </td>
```

```
      <td> 38 </td>
```

```
    </tr>
```

```
    <tr>
```

```
      <td> 1002 </td>
```

```
      <td> 35 </td>
```

```
      <td> 39 </td>
```

```
    </tr>
```

```
  </tr>
```

```
<td> 1003 </td>

<td> 40 </td>

<td> 40 </td>

</tr>

<tr>

<td> 1004 </td>

<td> 49 </td>

<td> 32 </td>

</tr>

<tr>

<td> 1005 </td>

<td> 30 </td>

<td> 32 </td>

</tr>

</table>
```

```
<h2> Example of list </h2>
```

```
<ul>

<li> item-1 </li>

<li> item-2 </li>

<li> item-3 </li>

<li> item-4 </li>

<li> item-5 </li>

</ul>
```

```
<div class = "style">
```

This text is styled with some of the text formatting properties. The heading uses the text-align, text-transform, and color properties. The paragraph is indented, aligned, and the space between characters is specified. The underline is removed from this colored "Try it Yourself" link.

```
</div>
```

```
<h3>
```

```
<a href="https://www.google.com"> Google </a>
```

```
<a href="https://www.Youtube.com"> Youtube </a>
```

```
<a href="https://www.linkedin.com"> LinkedIn </a>
```

```
<a href="https://www.leetcode.com"> LeetCode </a>
```

```
<a href="https://www.w3schools.com"> W3schools </a>
```

```
</body>
```

```
</html>
```

4.3 CSS code for Mypage:

```
body{
    background-color : red;
}
h1, h2, h3, h4, h5, h6{
    font-size: 150%;
}
p{
    font-weight : bold;
    font-family : Arial;
}
.style{
    text-transform: capitalize;
    text-decoration-line: underline;
    text-indent: 1cm;
}
ul{
    list-style-type: circle;
}
li{
    border-top: 2px solid black;
    border-right: 2px solid black;
    margin: 1cm;
    font-size : 22px;
}
a{
    padding : 15px;
    text-decoration : none;
}
a:visited {
```

```
        color: white;
    }
    a:hover{
        color : green;
        background-color : yellow;
    }
    a:active {
        color: green;
    }
    table{
        width : 80%;
        border-collapse: collapse;
        text-align:center;
        font-family : Verdana;
        margin: auto;
        border: 4px solid black;
    }
    td,th{
        border-bottom: 1px solid #000;
        padding: 7px;
    }
    th{
        background-color:DodgerBlue;
    }
    tr:nth-child(even) {
        background-color: hsl(185, 57%, 91%);
    }
    tr:nth-child(odd) {
        background-color: #fff;
    }
}
```


4.4 Output:

working with css

this is a random paragraph, this is a random paragraph, this is a random paragraph, this is a random paragraph, this is a random paragraph.

roll no.	sub-1	sub-2
1001	45	38
1002	35	39
1003	40	40
1004	49	32
1005	30	32

Example of list

- item-1
- item-2
- item-3
- item-4
- item-5

This Text Is Styled With Some Of The Text Formatting Properties. The Heading Uses The Text-Align, Text-Transform, And Color Properties. The Paragraph Is Indented, Aligned, And The Space Between Characters Is Specified. The Underline Is Removed From This Colored "Try It Yourself" Link.

[Google](#) [Youtube](#) [LinkedIn](#) [LeetCode](#) [W3schools](#)

4.5 Q1:

23CP029

Q-1 Compare class and ID selectors in CSS with proper example.

⇒ class selector :-

- used to style multiple elements with same style with given class.
- define in following manner in CSS

Let `<p class="para"> This is a paragraph </p>`

then CSS for it is

• para {
 font-size : large;
}

⇒ ID selector :-

- used to style single unique element with ID.
- defines with (#) in CSS

e.d. `<div id="box"> This is box </div>`

CSS :-

#box {
 background-color : blue;
}

Q-2 what are different type of cascading style sheets & Elaborate with example

4.6 Q2:

23CP029

Page No.:
Date:

① Inline CSS:

→ Applied directly to HTML element using style attribute.

e.g. `<P style="color: red;"> inline css </P>`

② Internal CSS :-

→ Defined within a `<style>` tag inside `<head>`.

e.g.

```
<head>
  <style>
    h1 {
      color: red;
    }
  </style>
</head>
```

③ External CSS :-

→ Defined in a separate CSS file & linked with HTML.

e.g. `<link rel="stylesheet" href="style.css">`

