# Every command

## Cuevik Start

| Command | What it does | Approved by | Branch → PR to | Writes |
|---|---|---|---|---|
| `/cuevik-start:00-bootstrap` | Connects or creates the GitHub repo and project board, then lands the governance baseline in a reviewed PR. | Architect | `init/00-bootstrap` → `main` | `CONTRIBUTING.md`, `.cuevik/config.json`, `.cuevik/lineage.json`, `.markdownlint.json` |
| `/cuevik-start:01-product-concept` | Drafts the product concept with you: what it is, who it is for and why it exists. | Product Owner | `init/01-product-concept` → `main` | `docs/PRODUCT.md` |
| `/cuevik-start:02-product-requirements` | Turns the concept into numbered, testable requirements (the PRD). | Product Owner | `init/02-product-requirements` → `main` | `docs/PRD.md` |
| `/cuevik-start:03-architecture` | Designs the system: components, data, integrations and the decisions behind them. | Architect, Product Owner | `init/03-architecture` → `main` | `docs/ARCHITECTURE.md` |
| `/cuevik-start:04-tech-stack` | Locks the approved technologies and the build, test and lint commands. | Architect | `init/04-tech-stack` → `main` | `docs/TECH-STACK.md`, `CONTRIBUTING.md` |
| `/cuevik-start:05-ai-tool-guide` | Sets the rules for AI coding assistants and generates the files each one reads. | Architect | `init/05-ai-tool-guide` → `main` | `docs/AI-TOOL-GUIDE.md`, `CLAUDE.md`, `.github/copilot-instructions.md` |
| `/cuevik-start:06-readme` | Replaces the boilerplate README with the project's real entry point. | Architect | `init/06-readme` → `main` | `README.md` |
| `/cuevik-start:07-backlog` | Derives epics and stories from the product docs and files them as GitHub issues. | Product Owner | `init/07-backlog` → `main` | `docs/BACKLOG.md` |

| Command | What it does | Approved by | Branch → PR to | Writes |
|---|---|---|---|---|
| `/cuevik-start:08-finalize` | Removes the initiation-only rules from CONTRIBUTING.md and hands over the permanent ones. | Architect | `init/08-finalize` → `main` | `CONTRIBUTING.md` |
| `/cuevik-start:status` | Shows how far initiation has got, from what is merged on GitHub. Read-only. | Read the report | — | Nothing (report only) |
| `/cuevik-start:cleanup` | Deletes local `init/*` branches whose PR is merged, after listing them for your confirmation. | Confirm the list | — | Deletes merged local `init/*` branches |

## Cuevik Ship

| Command | What it does | Approved by | Branch → PR to | Writes |
|---|---|---|---|---|
| `/cuevik-ship:01-brainstorm` | Takes an idea or an existing issue, checks it is not a duplicate, and explores it until you can approve or reject it. | Approve or reject, then merge | `ship/<n>-<slug>/01-brainstorm` → `ship/<n>-<slug>/issue` | GitHub issue and brainstorming folder |
| `/cuevik-ship:02-audit-prd` | Checks the approved idea against the product docs and ratifies it into new or changed requirements. | Review and merge | `ship/<n>-<slug>/02-audit-prd` (cut from `main`) → `main` | `PRODUCT.md` and `PRD.md` changes |
| `/cuevik-ship:03-create-backlog` | Files the requirements as an epic and stories on GitHub, splitting the idea when it covers several. | Approve the list | — | GitHub issues: epic and stories |
| `/cuevik-ship:04-plan-intent` | States the problem and scope, before any solution, in the issue's own work folder. | Review and merge | `ship/<n>-<slug>/04-plan-intent` → `ship/<n>-<slug>/issue` | `intent.md` in the work folder |
| `/cuevik-ship:05-design-spec` | Writes the spec: behaviour, data, rules and tests. | Review and merge | `ship/<n>-<slug>/05-design-spec` → `ship/<n>-<slug>/issue` | `spec.md` in the work folder |

| Command | What it does | Approved by | Branch → PR to | Writes |
|---|---|---|---|---|
| `/cuevik-ship:06-build-plan` | Turns the spec into a dependency-ordered task list that a fresh session can execute. | Review and merge | `ship/<n>-<slug>/06-build-plan` → `ship/<n>-<slug>/issue` | `plan.md` in the work folder |
| `/cuevik-ship:07-execute-plan` | Builds the plan on a code branch and opens the code PR to `main`. | Review and merge the code PR | `ship/<n>-<slug>/07-execute-plan` (cut from `main`) → `main` | The code |
| `/cuevik-ship:cleanup` | Removes the issue's worktree and local branches and archives the remote branch as a tag, after listing them for your confirmation. | Confirm the list | — | Worktree, local branches, archive tag |

## Cuevik Docs

| Command | What it does | Approved by | Branch → PR to | Writes |
|---|---|---|---|---|
| `/cuevik-docs:audit` | Reads your docs once and reports gaps (Align), contradictions (Drift) and duplication (Absorb). | Read the report | — | A findings report |
| `/cuevik-docs:update` | Updates one source-of-truth document through a reviewed PR, using its owner and reviewers from the lineage, and flags downstream documents. | Review and merge | `docs/update/<doc>` → `main` | The document, via PR |