Cuevik Plugins — Walkthrough

Plugins cuevik-start 0.1, cuevik-ship 0.1, cuevik-docs 0.1 | **Marketplace** cuevik-plugins | **Author** Viral Parikh

Claude drafts each step, you approve it. This guide covers all three plugins: how to install them, how every step works, and what each command does, from an empty repo to a merged code PR.

Contents

1. What you get
2. Install and prerequisites
3. How it works
4. The flow by actor
5. cuevik-start: set up a project
6. cuevik-ship: deliver one issue at a time
7. cuevik-docs: keep the documents true
8. Command reference
9. Who owns which document
10. Troubleshooting
11. Known limits

Version history

1 What you get

Three plugins with one rule: every document and change reaches `main` through a reviewed PR, and the next step will not run until the previous PR is merged.

Plugin	Use it to	Commands
`cuevik-start`	Start a project the governed way	`00` – `08`, `status`, `cleanup`
`cuevik-ship`	Deliver one issue at a time, from idea to code PR	`01` – `07`, `cleanup`
`cuevik-docs`	Audit and update source-of-truth documents	`audit`, `update`

Each command carries a tag. **Available** means you can install and run it today. **Planned** means it is described here from the design and is not installable yet. The tags are generated from the plugins, so they change as commands are built.

2 Install and prerequisites

Before you install:

- **GitHub CLI** (`gh`), signed in with the `project` scope: `gh auth login`, then `gh auth refresh -s project`.
- A local Claude Code session. Cloud sessions cannot reach GitHub Projects.
- Read access to the marketplace repository, which is private for now.
- Admin rights on the project's repo. `00-bootstrap` changes a repo setting and links a board.
- GitHub as your host. It is the only one supported.

Install, in Claude Code:

```
/plugin marketplace add viralparikh-dev/cuevik-plugins
/plugin install cuevik-start@cuevik-plugins
/plugin install cuevik-ship@cuevik-plugins
```

`cuevik-docs` installs automatically: both other plugins depend on it.

Run commands in your project folder (the repo root), in a new Claude Code session. Steps run only when you type them; Claude never starts one on its own.

3 How it works

- **One step, one session.** Run one step per session. Ask for a second step in the same session and it tells you to start a new one.
- **One PR per step.** A step works on its own branch (`init/<name>` in `cuevik-start`), commits there, and opens a PR to `main` once you approve. It never commits to `main` .
- **Merged means final.** A document counts only when its PR is merged. The next step refuses to run until the previous PR is merged. An open PR does not count.
- **Nothing happens without a yes.** Before it creates a branch, writes files, files issues or pushes, a step shows a checklist of what it verified and waits for your explicit `yes` .
- **One question at a time, fixed structure.** Claude interviews you for each section with pick-or-type questions, offers only drafts it can trace to an earlier document or answer, never assumes an answer, and fills a template, so every project gets the same sections in the same order, with no placeholders left.
- **Owners and reviewers.** Every document has an owner role and reviewer roles. Claude acts as the owner while it drafts, and each reviewer applies their own checklist at PR review. These are roles, not GitHub accounts.
- **Solo is fine.** GitHub does not let you approve your own PR, so when one person holds every role, the self-review checklist in `CONTRIBUTING.md` is the approval. Wait a few hours (ideally a day), check every required section is covered and no upstream document changed on `main` , then merge. Change hats on purpose.
- **Finished means finished.** Re-running a finished step stops and sends you to `/cuevik-docs:update <document>` .

What happens inside a step


1. You start the command in a fresh session, in the project folder.
2. It checks the ground: clean working tree, `main` up to date, the previous step's PR merged, upstream documents on `main` , and this step's output not already final.
3. It shows the checklist, waits for your `yes` , then creates the step's branch from `main` .
4. It interviews you, drafts, and revises until you approve, then commits on the branch.
5. On your approval it pushes and opens the PR, with a summary and the reviewer checklist.
6. You review and merge on GitHub, then start the next step in a new session.

4 The flow by actor

Who acts at each step, one diagram per plugin. They are also the three pages of `Cuevik-Plugins_WalkthroughByActor.pdf`.


cuevik-start

Lanes are the document owners from the project's lineage. Every command is `/cuevik-start:<name>`.




cuevik-ship

You approve and merge, Claude runs each command in its own session, and GitHub holds the issue, branches and PRs. Every command is `/cuevik-ship:<name>`.



cuevik-docs

Same lanes as `cuevik-ship`. Every command is `/cuevik-docs:<name>`.



5 cuevik-start: set up a project

Nine steps, run in order, one session and one PR each. Each step reads the documents before it from `main`, so the order matters. Every command is `/cuevik-start:<name>` and runs on branch `init/<name>`. The line under each heading is generated from the plugin's own step registry and lineage.

Two small files describe the project to the plugins; `00-bootstrap` writes and commits both. `.cuevik/config.json` holds the project board's ids, so steps can add issues and move cards. `.cuevik/lineage.json` holds who owns and reviews each document and what it is built from. Everything else is your documents: the plugins never copy their own files into your repo.

00-bootstrap

Status: Available · **Owner:** Architect · **Reviewers:** Architect · **Reads:** — · **Writes:** `CONTRIBUTING.md`, `.cuevik/config.json`, `.cuevik/lineage.json`, `.markdownlint.json` · **Then:** `/cuevik-start:01-product-concept`

Connects or creates the GitHub repo and project board, then lands the governance baseline. Run it first, in the project folder. It is the only step that creates things outside your repo, so it shows its checks, lists every change with its commands, and asks once to make them all.

- **Repo.** Connects the folder to a GitHub repo, or creates one. It asks for the owner and name, and for the visibility of a new repo (private is suggested). In an empty folder it clones an existing repo. It stops if the folder has files but no repo (it never commits your files for you), if the folder sits inside another repo, or if `origin` is not on GitHub.
- **Board.** Asks who owns the project board (the repo's owner by default), lists that owner's open boards, and lets you pick one or create a new one. A new board starts from one of three choices: the Cuevik template (recommended), your own template (pick one of your boards or paste its link), or a blank board. If the template cannot be read, it asks again. A blank board gets only GitHub's default Status options (`Todo`, `In Progress`, `Done`). The board needs a single-select field named `Status`.
- **Remote changes.** Approved together with one yes: create the board, link it to the repo, turn on auto-delete for merged PR branches, so GitHub removes each PR's branch when it merges, and file the initiation issues. Then it checks the board's seven workflows are on and walks you through turning on

any that are off (GitHub offers no way to do this for you), including `Auto-add to project` with this repo in its filter.

- **Initiation issues.** An `Epic: Project Initiation` epic and one story per later step, such as `INIT-01: Product Concept`, labelled `initiation`, assigned to you, added to the board as sub-issues of the epic, with Priority, Size and Efforts (hours) set when the board has those fields. On a board with no sprints yet, it creates `Sprint-00` and puts them all in it. Each step's PR closes its story when it merges, and the last step closes the epic, so the board shows how far setup has got. They never carry the `epic` or `story` labels, so the real backlog never picks them up.
- **The PR.** Opens `init/00-bootstrap` with `CONTRIBUTING.md`, `.cuevik/config.json`, `.cuevik/lineage.json` and `.markdownlint.json`. An existing `.markdownlint.json` is kept. An existing `CONTRIBUTING.md` keeps its text: the governance text is inserted after its first heading and you see the diff first. If the repo has no commit yet, it first makes one empty commit, `chore: initialize repository`, on `main` and pushes it. That is the only commit bootstrap makes on `main`.
- **The governance text** covers the review flow, Conventional Commits and the rule never to push to `main`. It also carries the initiation-only branching table and the self-review checklist, which `08-finalize` removes.
- **It stops, and says what to fix,** if `gh` is not signed in, the default branch is not `main`, you lack admin rights on the repo, the repo is already bootstrapped, or a `00-bootstrap` PR is already open.

Review the PR:

- `CONTRIBUTING.md` holds the governance text verbatim, with both `INITIATION-ONLY` markers. If it already existed, your text is unchanged.
- No stack-specific commands in `CONTRIBUTING.md`.
- `.cuevik/config.json` names the board linked to this repo, with ids read from GitHub, and the initiation issue numbers.
- `.cuevik/lineage.json` matches the plugin's default lineage.
- Auto-delete is on: `gh repo view --json deleteBranchOnMerge` returns `true`.
- No plugin files (runner, registry, templates, roles) in the diff.

Not yet tested: linking a user-owned board to an organisation-owned repo.

01-product-concept

Status: Available · **Owner:** Product Owner · **Reviewers:** Product Owner · **Reads:** — · **Writes:** `docs/PRODUCT.md` · **Then:** `/cuevik-start:02-product-requirements`

Defines what the product is, who it is for and why it exists. Claude interviews you as the Product Owner and pushes back: every feature must answer *what user problem does this solve?*, and nothing technical belongs here. The result is `docs/PRODUCT.md` with six sections: Overview, Target Users, Features, Scope (In / Out), Success Criteria, Anti-Patterns.

02-product-requirements

Status: Planned · **Owner:** Product Owner · **Reviewers:** Product Owner · **Reads:** `docs/PRODUCT.md` · **Writes:** `docs/PRD.md` · **Then:** `/cuevik-start:03-architecture`

Turns the concept into numbered, testable requirements. The result is `docs/PRD.md` with twelve sections: Overview, Target Users, Problem Statements, Features / Capabilities, User Stories, Functional Requirements, Non-Functional Requirements, Acceptance Criteria, Out of Scope (This Release), Dependencies & Assumptions, Constraints (Non-Architectural), Risks & Edge Cases.

The Product Owner blocks the PR if:

- acceptance criteria are vague ("works correctly", "performs well")
- a feature has no user story
- a requirement does not trace back to `docs/PRODUCT.md`
- implementation, architecture or stack details appear
- out-of-scope items are implied instead of listed
- requirements lack unique IDs

03-architecture

Status: Planned · **Owner:** Architect · **Reviewers:** Architect, Product Owner · **Reads:** `docs/PRD.md` · **Writes:** `docs/ARCHITECTURE.md` · **Then:** `/cuevik-start:04-tech-stack`

Designs the system from the requirements. The result is `docs/ARCHITECTURE.md` with eight sections: System Architecture, Data Design, Data Flow & Interactions, Key Design Decisions, Implementation Conventions, Integration Points, Security Posture & Data Classification, Non-Functional Approach.

Every significant decision is written as **Context, Decision, Alternatives rejected, Trade-offs**. The Product Owner co-reviews the scope only. If the architecture contradicts or widens the scope in the PRD, they block the PR with a written scope conflict. Resolving it takes a PRD update through its own PR first, then the architecture is revised.

04-tech-stack

Status: Planned · **Owner:** Architect · **Reviewers:** Architect · **Reads:** `docs/PRD.md`, `docs/ARCHITECTURE.md` · **Writes:** `docs/TECH-STACK.md`, `CONTRIBUTING.md` · **Then:** `/cuevik-start:05-ai-tool-guide`

Locks the approved technologies and the trade-offs behind them. The result is `docs/TECH-STACK.md` with six sections: Languages & Frameworks, Datastores, Cloud & Infrastructure Services, Key Libraries / Tools, Selection Trade-offs, Versions & Constraints.

It then appends a tooling layer (build, test and lint commands) to `CONTRIBUTING.md`, using only technologies approved in `TECH-STACK.md` and leaving the governance layer from `00-bootstrap` untouched. The Architect blocks the PR if a technology choice has no justification against the alternatives.

05-ai-tool-guide

Status: Planned · **Owner:** Architect · **Reviewers:** Architect · **Reads:** `docs/ARCHITECTURE.md`, `docs/TECH-STACK.md` · **Writes:** `docs/AI-TOOL-GUIDE.md`, `CLAUDE.md`, `.github/copilot-instructions.md` · **Then:** `/cuevik-start:06-readme`

Sets the rules AI coding assistants follow on this project. It asks which AI tools the team uses, then writes `docs/AI-TOOL-GUIDE.md` and only the adapter files for those tools (`CLAUDE.md`, `.github/copilot-instructions.md`). The shared rules live in the guide; each adapter holds only tool-specific settings.

The guide has ten sections: Project Context, Coding Conventions, Scope Boundaries, Banned Patterns, Testing Rules, Documentation Rules, Decision Escalation, Agent Behavior Rules, Off-Limits Boundaries, Workflow Conventions.

06-readme

Status: Planned · **Owner:** Architect · **Reviewers:** Architect · **Reads:** `docs/PRODUCT.md`, `docs/PRD.md`, `docs/ARCHITECTURE.md`, `docs/TECH-STACK.md`, `docs/AI-TOOL-GUIDE.md` · **Writes:** `README.md` · **Then:** `/cuevik-start:07-backlog`

Replaces the repo's boilerplate README with the project's real entry point, built from the documents before it: Project Overview, Key Concepts, Prerequisites, Environment Setup, Install & Run, Run Tests, Project Structure, Further Reading. Leftover placeholder text is removed, and every command in the README is run before it is committed.

07-backlog

Status: Planned · **Owner:** Product Owner · **Reviewers:** Product Owner · **Reads:** `docs/PRODUCT.md`, `docs/PRD.md`, `docs/ARCHITECTURE.md`, `docs/TECH-STACK.md`, `docs/AI-TOOL-GUIDE.md`, `README.md` · **Writes:** `docs/BACKLOG.md` · **Then:** `/cuevik-start:08-finalize`

Derives epics and stories from the product concept and the PRD, shows them, and writes nothing until you approve. It then creates the GitHub issues one at a time, labelled `epic`, `story` and `priority:*`, and records the initial backlog in `docs/BACKLOG.md`: Summary, Epics, Stories, Out-of-Scope Notes.

After setup, GitHub is the backlog. `docs/BACKLOG.md` is a snapshot and stays frozen.

08-finalize

Status: Planned · **Owner:** Architect · **Reviewers:** Architect · **Reads:** `docs/TECH-STACK.md` · **Writes:** `CONTRIBUTING.md` · **Then:** `/cuevik-start:cleanup`

Ends initiation. It reads `CONTRIBUTING.md` from `main`, removes the fenced `INITIATION-ONLY` block (the branching table and the self-review checklist), keeps the permanent governance and the tooling layer exactly as they are, and puts a short development-phase stub where the block was. It does not write a full development policy: the team expands the stub later with `/cuevik-docs:update`. If the markers are missing it stops rather than guess which lines to delete.

Initiation is complete when this PR is merged.

status

Status: Available · **Branch:** none · **PR to:** none · **Writes:** Nothing (report only) · **You:** Read the report

Read-only. It shows how far setup has got from what is merged on GitHub, and writes nothing. Every step also runs it at the start of its session. When a step starts, its story on the board moves to Working with today's start date, and the previous story gets the date its PR merged as its end date.

It starts with a progress line, one cell per step, such as `2/9 · next: 02-product-requirements`, then a row per step. The merged PR decides each row. If an initiation issue on the board disagrees, for example a story closed with no merged PR, it adds a line saying so but does not change the row.

cleanup

Status: Planned · **Branch:** none · **PR to:** none · **Writes:** Deletes merged local `init/*` branches · **You:** Confirm the list

Deletes the local `init/*` branches whose PR is merged. It skips and reports any that are not merged, and lists what it will delete and asks first. Run it any time, typically after `08-finalize` merges. GitHub has already deleted the remote branches.

To revise a document after its step is merged, use `/cuevik-docs:update <document>` instead of re-running the step.

6 cuevik-ship: deliver one issue at a time

Takes one idea, or one existing issue, from brainstorm to a merged code PR: seven steps and a cleanup, one session and one PR each. Run it in a project that has been through `00-bootstrap`, because it reads the board's ids from `.cuevik/config.json`. Every command is `/cuevik-ship:<name>`. `<n>` is the issue number and `<slug>` its short name. The line under each heading is generated from the branches-and-files table in section 8.

How it differs from cuevik-start

- **One issue at a time.** Each issue gets its own git worktree, so several issues can be in flight at once. Where worktrees live is a setting on your machine, not committed to the project.
- **One rule.** Files under `docs/ship/<n>-<slug>/` go to the issue's own branch, `ship/<n>-<slug>/issue`. Everything else goes to `main`. `docs/ship/` never reaches `main`.
- **The issue branch** holds only that folder and is never merged. `01-brainstorm` creates it, or `04-plan-intent` does for an issue that has none, such as a bug fix or a split story.
- **Where each step goes.** Steps 01, 04, 05 and 06 work on a branch under `ship/<n>-<slug>/` and their PRs go back into the issue branch. Steps 02 and 07 are cut from `main` and their PRs go to `main`. Step 03 writes to GitHub only: no branch, no PR.
- **Merged means final,** as in `cuevik-start`: each step checks that the previous step's PR is merged before it does anything.

- **References.** The issue description carries a `## References` section between `<!-- cuevik-ship:references -->` markers: links to the issue's files, never file content. Every command refreshes it, so do not edit between the markers.
- **Labels only.** `idea`, `epic`, `story` and `priority:*`. GitHub issue types are not used, because user-owned repos do not have them.

01-brainstorm

Status: Planned · **Branch:** `ship/<n>-<slug>/01-brainstorm` · **PR to:** `ship/<n>-<slug>/issue` · **Writes:** GitHub issue and brainstorming folder · **You:** Approve or reject, then merge

Takes an idea or an existing issue number.

- **Duplicates first.** Before it asks anything, it checks existing `idea` issues in any state, and stories, so a duplicate never gets a number.
- **Issue at the start.** For a new idea it asks for 2–3 sentences, files a GitHub issue labelled `idea` straight away, then creates the issue branch, the worktree and the brainstorming folder, so findings are saved from the first minute.
- **The folder.** `docs/ship/<n>-<slug>/brainstorming/` holds `brainstorm.md`, plus attachments and any other files found along the way.
- **An existing issue.** It refuses an epic, sends a bug to `04-plan-intent`, and accepts an existing story (step 03 then treats it as changed). It never closes a story that already existed.
- **The outcome** is the PR into the issue branch. If you reject the idea, that PR is the record, and the issue is closed as *not planned* once you say yes. An abandoned idea is closed the same way and cleaned up like a rejection.
- **The board.** An idea may land on the project board, and its card carries through when the idea becomes a story.

02-audit-prd

Status: Planned · **Branch:** `ship/<n>-<slug>/02-audit-prd` (cut from `main`) · **PR to:** `main` · **Writes:** `PRODUCT.md` and `PRD.md` changes · **You:** Review and merge

Checks the approved idea against `docs/PRODUCT.md` and `docs/PRD.md`, and ratifies it into new or changed requirements. It uses `/cuevik-docs:audit` for the check.

- **Cut from `main`,** not from the issue branch, and its PR goes to `main`. `PRODUCT.md` and `PRD.md` are shared by every issue, and requirement numbers (`PRD-NNN`) must be allocated in one place. Cutting from `main` also means no `docs/ship/` file can leak into the PR.
- **`Refs #n`, never `Closes`.** Merging this PR must not close the issue; steps 04–07 still need it.
- **The ratification record** is a machine-readable block in this PR's body, plus a `Docs PR:` line in the issue's References. The brainstorm file keeps only step 01's decision.
- **Rejection here** is a comment on the issue and closing it, with no PR.

03-create-backlog

Status: Planned · **Branch:** none · **PR to:** none · **Writes:** GitHub issues: epic and stories · **You:** Approve the list

Turns the ratified requirements into GitHub issues. It writes to GitHub only; it does not write `docs/BACKLOG.md`, which is what `/cuevik-start:07-backlog` does once at setup.

- **The idea becomes a story.** Its title becomes `PRD-NNN: <Title> (<Priority>)` and the `idea` label is removed. Epics and stories share the labels `epic`, `story` and `priority:*` with `cuevik-start`.
- **Finding the epic.** In order: the parent of existing stories in the same PRD section, then an `epic` issue citing that section, then `docs/BACKLOG.md`, then a new epic. If several candidates fit it asks, and it never moves a story to another parent without your yes.
- **Splitting.** An idea that covers several requirements becomes several stories. The original issue keeps the first ID in prerequisite order, and you can change that in the approval table. Each extra story goes under its own PRD section's epic and starts its own branch set at `04-plan-intent`, linking back to the original's brainstorming.
- **The board.** Issues are added to the project board only from a local session.
- **The gate for step 04.** Step 04 checks that the References have an `Epic:` line and that the issue no longer has the `idea` label.

04-plan-intent

Status: Planned · **Branch:** `ship/<n>-<slug>/04-plan-intent` · **PR to:** `ship/<n>-<slug>/issue` · **Writes:** `intent.md` in the work folder · **You:** Review and merge

States the problem and scope before any solution is proposed, in `intent.md` in the issue's work folder. It creates the issue branch and worktree when the issue has none: a bug fix or refactor starts here, and so does each extra story from a split.

05-design-spec

Status: Planned · **Branch:** `ship/<n>-<slug>/05-design-spec` · **PR to:** `ship/<n>-<slug>/issue` · **Writes:** `spec.md` in the work folder · **You:** Review and merge

Writes `spec.md` in the work folder: behaviour, data, rules and tests. If a later step changes an earlier file, the issue's References are refreshed.

06-build-plan

Status: Planned · **Branch:** `ship/<n>-<slug>/06-build-plan` · **PR to:** `ship/<n>-<slug>/issue` · **Writes:** `plan.md` in the work folder · **You:** Review and merge

Turns the spec into `plan.md`: a dependency-ordered task list that a fresh session can execute.

07-execute-plan

Status: Planned · **Branch:** `ship/<n>-<slug>/07-execute-plan` (cut from `main`) · **PR to:** `main` · **Writes:** The code · **You:** Review and merge the code PR

Builds the plan on a code branch cut from `main`, reading `plan.md` from the issue branch, and opens the code PR to `main`. That PR carries only the code, so no `docs/ship/` file reaches `main`. Its `Closes #n` is what closes the issue, and the final References refresh happens here.

cleanup

Status: Planned · **Branch:** none · **PR to:** none · **Writes:** Worktree, local branches, archive tag · **You:** Confirm the list

`/cuevik-ship:cleanup <issue#>` removes everything local for an issue and keeps what the links need.

- **Gate:** the code PR is merged, or the issue was closed as *not planned*. There is no override flag, and it refuses while any `ship/<n>-*` PR is still open.
- **Removes** the issue's worktree (it refuses if there are uncommitted or unpushed changes) and the local `ship/<n>-<slug>/*` branches. Removing the worktree also removes the local `docs/ship/<n>-<slug>/` folder, since `main` never has it.
- **Archives** the remote issue branch as the tag `ship-archive/<n>-<slug>` and then deletes the branch. The tag keeps the commits reachable, so the links in the References keep working.
- **Does not close the issue.** The code PR does. A split story is cleaned up on its own, per issue.
- **Lists everything** it will delete and asks first. Run it from the main checkout, never from inside the worktree it removes.

7 cuevik-docs: keep the documents true

Two commands for the source-of-truth documents named in `.cuevik/lineage.json`. `cuevik-start` and `cuevik-ship` both depend on this plugin, so it installs with them. Every command is `/cuevik-docs:<name>`.

audit

Status: Planned · **Branch:** none · **PR to:** none · **Writes:** A findings report · **You:** Read the report

Reads the project's documents once and runs three lenses over them:

- **Align.** Terms, goals, scope or acceptance criteria that do not cohere, and sections that are missing rather than wrong.
- **Drift.** Documents that contradict each other, the files on disk, or a decision already taken.
- **Absorb.** Two files that say the same thing twice, and which copy is better.

The lineage decides which documents are audited. `/cuevik-ship:02-audit-prd` calls it.

update

Status: Planned · **Branch:** `docs/update/<doc>` · **PR to:** `main` · **Writes:** The document, via PR · **You:** Review and merge

Revises one source-of-truth document after its step has merged. Use it any time reality diverges from a document, instead of re-running the step.

- The document's owner role drafts the change, and its reviewers (from the lineage) approve the PR.
- It then builds a downstream checklist: every document built from the one you changed. Review each flagged document, and do not mark the checklist complete until all of them are reviewed.
- Frozen documents, such as `docs/BACKLOG.md`, are skipped.

What a change to each document flags, from the default lineage:

When you change	It flags for review
`CONTRIBUTING.md`	nothing
`docs/PRODUCT.md`	`CONTRIBUTING.md`, `docs/PRD.md`, `docs/ARCHITECTURE.md`, `docs/TECH-STACK.md`, `docs/AI-TOOL-GUIDE.md`, `README.md`
`docs/PRD.md`	`CONTRIBUTING.md`, `docs/ARCHITECTURE.md`, `docs/TECH-STACK.md`, `docs/AI-TOOL-GUIDE.md`, `README.md`
`docs/ARCHITECTURE.md`	`CONTRIBUTING.md`, `docs/TECH-STACK.md`, `docs/AI-TOOL-GUIDE.md`, `README.md`
`docs/TECH-STACK.md`	`CONTRIBUTING.md`, `docs/AI-TOOL-GUIDE.md`, `README.md`
`docs/AI-TOOL-GUIDE.md`	`README.md`
`README.md`	nothing
`docs/BACKLOG.md`	nothing

8 Command reference

What each command does

Command	Title	What it does	Status
`/cuevik-start:00-bootstrap`	Bootstrap	Connects or creates the GitHub repo and project board, then lands the governance baseline in a reviewed PR.	Available
`/cuevik-start:01-product-concept`	Product Concept	Drafts the product concept with you: what it is, who it is for and why it exists.	Available
`/cuevik-start:02-product-requirements`	Requirements	Turns the concept into numbered, testable requirements (the PRD).	Planned

Command	Title	What it does	Status
`/cuevik-start:03-architecture`	Architecture	Designs the system: components, data, integrations and the decisions behind them.	Planned
`/cuevik-start:04-tech-stack`	Tech Stack	Locks the approved technologies and the build, test and lint commands.	Planned
`/cuevik-start:05-ai-tool-guide`	AI Tool Guide	Sets the rules for AI coding assistants and generates the files each one reads.	Planned
`/cuevik-start:06-readme`	README	Replaces the boilerplate README with the project's real entry point.	Planned
`/cuevik-start:07-backlog`	Initial Backlog	Derives epics and stories from the product docs and files them as GitHub issues.	Planned
`/cuevik-start:08-finalize`	Finalize Governance	Removes the initiation-only rules from CONTRIBUTING.md and hands over the permanent ones.	Planned
`/cuevik-start:status`	Status	Shows how far initiation has got, from what is merged on GitHub. Read-only.	Available
`/cuevik-start:cleanup`	Clean up	Deletes local `init/*` branches whose PR is merged, after listing them for your confirmation.	Planned
`/cuevik-ship:01-brainstorm`	Brainstorm	Takes an idea or an existing issue, checks it is not a duplicate, and explores it until you can approve or reject it.	Planned
`/cuevik-ship:02-audit-prd`	Audit PRD	Checks the approved idea against the product docs and ratifies it into new or changed requirements.	Planned
`/cuevik-ship:03-create-backlog`	Create Backlog	Files the requirements as an epic and stories on GitHub, splitting the idea when it covers several.	Planned
`/cuevik-ship:04-plan-intent`	Plan Intent	States the problem and scope, before any solution, in the issue's own work folder.	Planned
`/cuevik-ship:05-design-spec`	Design Spec	Writes the spec: behaviour, data, rules and tests.	Planned

Command	Title	What it does	Status
`/cuevik-ship:06-build-plan`	Build Plan	Turns the spec into a dependency-ordered task list that a fresh session can execute.	Planned
`/cuevik-ship:07-execute-plan`	Execute Plan	Builds the plan on a code branch and opens the code PR to `main`.	Planned
`/cuevik-ship:cleanup`	Clean up	Removes the issue's worktree and local branches and archives the remote branch as a tag, after listing them for your confirmation.	Planned
`/cuevik-docs:audit`	Audit	Reads your docs once and reports gaps (Align), contradictions (Drift) and duplication (Absorb).	Planned
`/cuevik-docs:update`	Update	Updates one source-of-truth document through a reviewed PR, using its owner and reviewers from the lineage, and flags downstream documents.	Planned

Branches and files (ship, docs and utility commands)

The nine numbered `cuevik-start` steps are not repeated here: see section 5. In `cuevik-ship`, `<n>` is the issue number and `<slug>` its short name.

Command	Branch	PR to	Writes	You
`/cuevik-start:status`	—	—	Nothing (report only)	Read the report
`/cuevik-start:cleanup`	—	—	Deletes merged local `init/*` branches	Confirm the list
`/cuevik-ship:01-brainstorm`	`ship/<n>-<slug>/01-brainstorm`	`ship/<n>-<slug>/issue`	GitHub issue and brainstorming folder	Approve or reject, then merge
`/cuevik-ship:02-audit-prd`	`ship/<n>-<slug>/02-audit-prd` (cut from `main`)	`main`	`PRODUCT.md` and `PRD.md` changes	Review and merge
`/cuevik-ship:03-create-backlog`	—	—	GitHub issues: epic and stories	Approve the list

Command	Branch	PR to	Writes	You
`/cuevik-ship:04-plan-intent`	`ship/<n>-<slug>/04-plan-intent`	`ship/<n>-<slug>/issue`	`intent.md` in the work folder	Review and merge
`/cuevik-ship:05-design-spec`	`ship/<n>-<slug>/05-design-spec`	`ship/<n>-<slug>/issue`	`spec.md` in the work folder	Review and merge
`/cuevik-ship:06-build-plan`	`ship/<n>-<slug>/06-build-plan`	`ship/<n>-<slug>/issue`	`plan.md` in the work folder	Review and merge
`/cuevik-ship:07-execute-plan`	`ship/<n>-<slug>/07-execute-plan` (cut from `main`)	`main`	The code	Review and merge the code PR
`/cuevik-ship:cleanup`	—	—	Worktree, local branches, archive tag	Confirm the list
`/cuevik-docs:audit`	—	—	A findings report	Read the report
`/cuevik-docs:update`	`docs/update/<doc>`	`main`	The document, via PR	Review and merge

9 Who owns which document

From the default lineage: who owns each document, who reviews a change to it, and what it is built from.

Document	Owner	Reviewers	Built from
`CONTRIBUTING.md`	Architect	Architect	`docs/TECH-STACK.md`
`docs/PRODUCT.md`	Product Owner	Product Owner	—
`docs/PRD.md`	Product Owner	Product Owner	`docs/PRODUCT.md`
`docs/ARCHITECTURE.md`	Architect	Architect, Product Owner	`docs/PRD.md`
`docs/TECH-STACK.md`	Architect	Architect	`docs/PRD.md`, `docs/ARCHITECTURE.md`
`docs/AI-TOOL-GUIDE.md`	Architect	Architect	`docs/ARCHITECTURE.md`, `docs/TECH-STACK.md`
`README.md`	Architect	Architect	`docs/PRODUCT.md`, `docs/PRD.md`, `docs/ARCHITECTURE.md`, `docs/TECH-STACK.md`, `docs/AI-TOOL-GUIDE.md`
`docs/BACKLOG.md`	Product Owner	Product Owner	`docs/PRODUCT.md`, `docs/PRD.md`, `docs/ARCHITECTURE.md`, `docs/TECH-STACK.md`, `docs/AI-TOOL-GUIDE.md`, `README.md`

10 Troubleshooting

A step stops with a message rather than guessing. Fix the cause and re-run it. `00-bootstrap` skips what it already did, so a re-run does not create anything twice.

You see	Cause and fix
`gh is not signed in`	Run `gh auth login`, then re-run.
`gh cannot read Projects for <owner>`	The token lacks the `project` scope. In a local session run `gh auth refresh -s project`. Cloud sessions cannot reach Projects.
`Uncommitted changes detected`	A step starts from a clean working tree. Commit or stash, then re-run.
`Could not fast-forward main`	Local `main` has diverged, or there is no network. Fix the pull error, then re-run.

You see	Cause and fix
Run `/cuevik-start:00-bootstrap` and merge its PR first	`.cuevik/config.json` or `.cuevik/lineage.json` is not on `main` yet.
The previous step's PR must be merged first	The message names the step. Merge that PR (an open PR does not count), then re-run.
A document is missing from `main`	An upstream document is not merged yet. Merge the step that writes it first.
The step is already complete	Its output is already final on `main`. Revise it with `/cuevik-docs:update`.
The step's branch already exists	A closed, unmerged PR leaves its branch behind. The step asks you to reuse it or delete it (after a `yes`); it never picks another name.
`This folder is inside the git repo at <path>`	Run from the project repo's root, or move the folder out of the parent repo. Never delete a `.git` folder yourself.
`This folder has files but is not a git repo`	Commit the files to a repo yourself, then re-run. Bootstrap never commits your files.
`origin points at <url>, which does not exist or you cannot access`	Fix or remove `origin`, then re-run.
`origin` is not on github.com	GitHub is the only supported host.
The default branch is not `main`, or you lack admin rights	Every step uses `main`. Bootstrap changes a repo setting and links a board, so it needs admin rights.
`This repo is already bootstrapped`	`.cuevik/` is already on `main`. To change the board, open a PR that edits `.cuevik/config.json`.
A `00-bootstrap` PR is already open	Merge it, or close it and delete its branch, then re-run.
The board needs a single-select field named `Status`	Add that field to the board, or choose another board.

You see	Cause and fix
The template board cannot be read	Name another template, choose an existing board, or a blank one. A blank board gets only `Todo`, `In Progress` and `Done`.
Linking the board fails	The step stops and shows GitHub's error. Fix the cause and re-run; it does not retry with another owner.
You asked for a second step in the same session	One step per session. Start a new session for the next step.

11 Known limits

- **GitHub only,** and a local Claude Code session for anything that touches Projects. Cloud sessions cannot reach GitHub Projects.
- **Approval is process-enforced.** GitHub does not let you approve your own PR, so for solo work the self-review checklist is the gate. Nothing in GitHub enforces it.
- **Not yet tested:** linking a user-owned board to an organisation-owned repo, and copying another user's template board.
- **Board copies:** bootstrap reports differences between a template board and its copy, but cannot see the settings inside each workflow (for example which Status "Item closed" sets).
- **Not yet verified:** creating sub-issue and blocked-by links from a cloud session, which `/cuevik-ship:03-create-backlog` relies on.
- **Plugin settings:** in one sandbox test a plugin setting reached a skill unsubstituted, cause unknown, so bootstrap asks for the template board instead. `cuevik-ship`'s worktree-folder setting uses the same mechanism and is untested.
- **Labels, not issue types.** GitHub issue types are not used, because user-owned repos do not have them.
- **`docs/BACKLOG.md` is a snapshot.** After setup, GitHub is the backlog.

Version history

Version	Date	Change
0.1	Unreleased	First version of the guide, covering `cuevik-start` 0.1, `cuevik-ship` 0.1 and `cuevik-docs` 0.1

Cuevik Plugins · Walkthrough · Generated from Cuevik-Plugins_Walkthrough.md by docs/guides/build_docs.py