

Started on	Saturday, 30 September 2023, 9:31 AM
State	Finished
Completed on	Saturday, 30 September 2023, 9:37 AM
Time taken	6 mins 7 secs
Marks	9.00/10.00
Grade	6.30 out of 7.00 (90%)

QUESTION 1

Correct
Mark 1.00 out of 1.00

Configure `webpack.config.js` to use plugin `ProgressPlugin` for extracting progress information:

```
const webpack = require('webpack');  
module.

exports

 ✓ = {  


plugins

 ✓ : [

new webpack.ProgressPlugin()

] ✓  
};
```

['ProgressPlugin']

[ProgressPlugin]

plugin

[webpack.ProgressPlugin()]

config

'ProgressPlugin'

QUESTION 2

Correct
Mark 2.00 out of 2.00

Configure `Babel` to enable the plugin `@babel/plugin-transform-for-of`:

```
{  


"plugins"

  
  ✓ :  
  [

"@babel/plugin-transform-for-of"

]  
  ✓  
}
```

QUESTION 3

Incorrect
Mark 0.00 out of 1.00

To install only production npm dependencies from `package.json` should be run `npm install`

`--only=prod`



QUESTION 4

Correct

Mark 2.00 out of 2.00

Configure the file `package.json` to run `node index.js` by the command `npm start`:

```
{
  "name": "test",
  "version": "1.0.0",
  "description": "demo of package.json",

  "scripts"
  ✓ : {
    "start"
    ✓ :
    "node index.js"
    ✓
  },
  "author": "IT Academy",
  "license": "ISC"
}
```

QUESTION 5

Correct

Mark 1.00 out of 1.00

ESLint will only use one of multiple configuration files in the same directory, according to the priority order:

1. `.eslintrc.js` ✓
2. `.eslintrc.cjs` ✓
3. `.eslintrc.yaml` ✓
4. `.eslintrc.yml` ✓
5. `.eslintrc.json` ✓
6. `package.json` ✓

`eslint.config.js``eslint.config.json`

QUESTION 6

Correct
Mark 2.00 out of 2.00

Configure **Babel** to enable the set of plugins **@babel/preset-react**:

```
{
  "presets":
  :
  ["@babel/preset-react"]
}
```

QUESTION 7

Correct
Mark 1.00 out of 1.00

Configure **webpack.config.js** below to specify:

- set the point where webpack looks to start building to **src/index.js**;
- instruct **webpack** to use the **css-loader** for every **.css** files.

module. exports = {
 entry : './src/index.js' ,
 module : {
 rules : [{ test: /\.css\$/, use: 'css-loader' }]
 }
};

config {load: /\.css\$/, with: 'css-loader' } loaders
./src/index.js export
{test: /\.css\$/, use: 'css-loader' } init

◀ React + TypeScript. Add TypeScript to existing application

Jump to... ▾

TypeScript ▶