PremiumCAD Design Request Form

Project Name:

Rafter/Truss Size and Spacing

(Show tape mesure in photo if possible)

Attic Space - Show existing roof rafter/truss for each roof structure (Show tape measure if possible)*

^¹Project Info→ ^²Structural Info→ ^³ Electrical Info

PROJECT INFORMATION * = Required Field ***** = Account Preference **AHJ INFORMATION HOMEOWNER INFORMATION** AHJ Name:* First Name: Utility Name:* Last Name:* Address:* Special AHJ/Utility Requirements (If Known) City, State, Zip:* Project's Assessor's Parcel #: CONTRACTOR INFORMATION Company Name:* Phone:* Address (Street, City, State, Zip):* Snow & Wind Loads (If Known) Snow Load: Wind Load: License Numbers:* **Project (Site) Photos Checklist:** PROJECT MANAGER Photos will be used to understand site conditions and project site and are essential to generate an accurate permit package. First Name:* Outility Meter Location (Zoomed out View)* Last Name:* Main Service Panel Location* Phone:* OClose-up of Main Service Panel Label* OClose-up of Main Breaker Application Type: OClose-up of Main Breaker Label Please select the appropriate racking application types. O Sub-Panel Main Breaker (If used) O Tilt-Up O Flush-Mount O Integrated Racking O Sub-Panel Location (If used) O Subpanel Location (If used) **Engineering Stamps:** O Close-up of Sub-Panel Breaker Label Structural Only Stamp OProposed Inverter Location (Zoomed out View) **Electrical Only Stamp** Array Location(s) (if possible) Structural & Electrical Both O Entire Roof with Obstructions (If possible) Wet Stamps / Hard Copy No. Of Copies: O Ground Mount Location (If applicable) **Delivery Address:**



[®]Project Info → [®]Pitched Roof Structural Info → [®]Electrical Info

ARRAY 1 - PITCHED ROOF APPLICATIONS

PITCHED ROOF & STRUCTURAL INFO	RACKING INFO								
Roof Material:*	Attachment Type:*								
Please select the appropriate roof material from the options below.	○ Flashed L-Foot ○ Tile Hook ○ Standoff								
(Asphalt) shingles Standing Seam Metal	O Integrated intoRacking O Standing Seam Clamp								
Corrugated Metal Clay S-Tile	Corrubracket Other:								
Flat Tile Rubber Membrane									
Wave Tile Other:	Racking Manufacturer:*								
Wood Shake									
Layers of Roof Material	Racking Model:*								
One O Two									
Structure Type:*	Attachment Manufacturer:*								
Please select the appropriate Structure Type from the options below.									
Truss (Wood) Knee Wall + Collar Tie	Attachment Model:*								
Metal Beam Supported Collar Tie (Wood)									
Interior bearing wall— Single Span Rafter (Wood)									
Purlins Wood Supported Strut	Maximum Rail Span:*								
Knee Wall Steel Frame	Please select the default maximum distance between mounting points accross the rail layout used for this project.								
Rafter Size:*	O 16" O 24" O 32" O 48" O 72" O 96" O Other:								
O 2x4 O 2x6 O 2x8 O 2x10 O Other:	Pitch (Degrees):*								
<u> </u>									
Rafter Spacing:*									
Please select the typical distance between each rafter (in inches):	Azimuth(s):*								
○ 12" ○ 14" ○ 16" ○ 24" ○ 48" ○ Other:									
Roof Structure Measurements:*									
A: B:									
B B B									



ARRAY 2 - PITCHED ROOF APPLICATIONS (Only if roof structure is different)

PITCHED ROOF & STRUCTURAL INFO	RACKING INFO
Roof Material:*	Attachment Type:*
Please select the appropriate roof material from the options below. (Asphalt) shingles Corrugated Metal Flat Tile Wave Tile Wood Shake	○ Flashed L-Foot ○ Tile Hook ○ Standoff ○ Integrated intoRacking ○ Standing Seam Clamp ○ Corrubracket ○ Other: Racking Manufacturer:*
Layers of Roof Material	Racking Model:
One O Two	
Structure Type:* Please select the appropriate Structure Type from the options below.	Attachment Manufacturer:*
Truss (Wood) Metal Beam Supported Interior bearing wall (Wood) Purlins Knee Wall + Collar Tie Collar Tie (Wood) Single Span Rafter (Wood) Wood Supported Strut Steel Frame	Attachment Model:* Maximum Rail Span:* Please select the default maximum distance between mounting points accross the rail layout used for this project. 16" 24" 32" 48" 72" 96" Other:
Rafter Size:* ○ 2x4 ○ 2x6 ○ 2x8 ○ 2x10 ○ Other:	Pitch (Degrees):*
Rafter Spacing:* Please select the typical distance between each rafter (in inches): 12" 14" 16" 24" 48" Other:	Azimuth(s):*
Roof Structure Measurements:*	
A: B:	
B B B	



^①Project Info → ^②Structural Info → ^③Electrical Info

ELECTRICAL INFORMATION

NEW EQUIPMENT INFORMATION	Inverter Location:*												
	Please select intended location of inverter and electrical equipment.												
Module Manufacturer & Model Number:*	1. O Exterior O Interior												
Module Manufacturer:	2. O House O Garage O Barn O Pole Mounted												
Model Number:	Other:												
Quantity:	3. North South East West NE NW SE SW												
String/Micro Manufacturer & Model Number:*	ONE ONW OSE OSW												
String/Micro Manaractarer & Moder Hamber.	Wire Transition Enclosure:*												
Inverter Manufacturer:	Please select the appropriate wire transition enclosure between modules and inverter.												
Model Number:	☐ Junction Box ☐ Soladeck ☐ Combiner Box ☐ None												
Quantity:													
	Combining AC Circuits:*												
Optimizer Manufacturer & Model Number (If Applicable):	Select how to combine the inverter(s) AC outputs. Multiple inverters or micros only.												
	O Soladeck (Rooftop) O (N) AC Panel Board												
Optimizer Manufacturer:	Existing Subpanel												
Model Number:													
Quantity:	Service AC Disconnect:*												
	Typically the utility requires a lockable utility disconnect for the AC output in case of an emergency or service.												
Inverter DC Disconnect Options (If Applicable):*	○ Yes ○ No												
O Utilize Integrated DC Disconnect	Utility Disconnect Location:*												
Utilize Standalone DC Disconnect (Rooftop or Ground Array)	Please describe the Utility Disconnect location.												
	1. O Exterior O Interior												
Standalone DC Disconnect Location (If Used):	2. O House O Garage O Barn O Pole Mounted												
1. O Exterior O Interior	Next to Utility Meter Other:												
2. O House O Garage O Barn O Pole Mounted	2 ONesth Oscath Office Ower												
Rooftop At Ground Array	3. O North O South O East O West O NE O NW O SE O SW												
Other:	ONE ONW OSE OSW												
2. Oblands OSauds OFace OWest	PV Revenue Meter:*												
3. North South East West NE NW SE SW	Is there a PV Revenue Meter? The Production meter measures and tracks the production for the solar array.												
3.1.2 3.1.1 3.2.2 3.1.1	Yes No (Net Meter)												



ELECTRICAL INFORMATION (Continued) Interconnection Location* Location of PV Meter:* Please select the electrical location the tap will occur. Select the location of the PV meter in reference to the AC disconnect. Between inverter and disconnect Existing Main Electrical New Tap Box O Between disconnect and point of interconnection (MEP, Tap, Etc.) Panel (MEP) Automatic Transfer Existing Meter **EXISTING EQUIPMENT INFORMATION** Switch (ATS) New Sub-Panel Existing Sub-Panel Meter Main Combo?* Renewable Meter Adapter New Main Electrical (RMA) at Meter Panel Upgrade O No (Yes (E)xisting Meter Location:* Main Electrical Panel Rating:* Write the Bus and main circuit breaker rating. 1. O Exterior OInterior Bus Rating (amps): 2. OMEP Location O Pole Mounted Main Breaker Rating (amps): Are there spaces available in the panel? 3. O North O South O East O West O NW OSE OSW ○ NE **Main Breaker Location:*** *Location of the Pole in relation to the house: O Top-fed O Center-fed O Bottom-fed *For pole mounted utility meters and main electrical panels Cardinal Direction: **Main Electrical Panel Location:*** Please select where the Main Electrical Panel is located. Distance: 1. O Exterior O Interior **Utility Entrance:*** 2. O House O Garage O Barn O Pole Mounted Other: Overhead Ounder Ground 3. O North O South O East O West **Existing Electrical Grounding:*** O NE ONW O SE Osw Current or Original Bond of existing electrical system? Please select from the options below. (N)ew Main Breaker Derating or Panel Upgrade: O Ground Rod O Ufer O Cold Water Pipe Write the new ratings that the main breaker will be derated to. Bus Rating (amps): **Project Notes & Special Requirements:** Main Breaker Rating (amps): Interconnection Strategy:* Please select the appropriate interconnection strategy from the choices below: Panel upgrades or choose "Backfeed Breaker" O Backfeed Breaker O Derate Main Breaker O Line Side Tap O Load Side Tap

A rough sketch or drawing of the solar panel layout on the project residence or site including roof measurements where possible and plan for equipment locations from the provided key. This sketch will be used to create the base site plan and array layout.									PNL AC PANELBOARD S AC DISCONNECT DSW DC DISCONNECT						MAIN	N ELEC	UE ME	AL PA	NEL	X ROOF OBSTRUCTION									
O I placed the modules on the roof sketch below																JUNG	CHON	I BOX											
Оі	want	the d	esigr	ner to	place	e the	modu	ules																					
От	he Sa	iles S	ketch	n is at	tache	ed as	a sep	oarate	doc	umen	t																		
																													\neg
																											N	\neg	-
																										W		TE	-
																											S	_	-
										1																			
																			A										

I DC/AC INVERTER

(UM) (E) UTILITY METER

M1 MODULE #

Sales Sketch:*

