

# How to Destroy MongoDB Replication on Windows

## How to Configure MongoDB Replica Set on Windows

### Prerequisites

- MongoDB installed on each node.
- Each instance must have a unique data folder and port.
- Nodes must be able to ping each other (use localhost for single-machine setup).
- Use different ports if running multiple instances on one machine.
- Ensure firewall allows traffic on the used ports.

### Step 1: Create Folders (for single-machine setup)

```
mkdir C:\mongodb\repl1\data
```

```
mkdir C:\mongodb\repl2\data
```

```
mkdir C:\mongodb\repl3\data
```

### Step 2: Create Config Files

Create the following files:

C:\mongodb\repl1\mongod.cfg:

systemLog:

destination: file

path: C:\mongodb\repl1\mongod.log

storage:

dbPath: C:\mongodb\repl1\data

net:

bindIp: 127.0.0.1

port: 27017

replication:

replSetName: rs0

Repeat similarly for repl2 (port 27018) and repl3 (port 27019).

# How to Destroy MongoDB Replication on Windows

## Step 3: Start All 3 MongoDB Instances

Open 3 Command Prompts:

```
mongod --config C:\mongodb\repl1\mongod.cfg
mongod --config C:\mongodb\repl2\mongod.cfg
mongod --config C:\mongodb\repl3\mongod.cfg
```

## Step 4: Initialize the Replica Set

Open mongosh on port 27017:

```
mongosh --port 27017
```

Then run:

```
rs.initiate({
  _id: "rs0",
  members: [
    { _id: 0, host: "localhost:27017" },
    { _id: 1, host: "localhost:27018" },
    { _id: 2, host: "localhost:27019" }
  ]
})
```

## Step 5: Verify

In mongosh:

```
rs.status()
```

You should see the replica set configuration and member states.

## Tips

## How to Destroy MongoDB Replication on Windows

- Use real hostnames or IPs for remote machines.
- Add priority: 0 and votes: 0 for hidden or non-voting members.
- You can install mongod as a Windows service using `mongod.exe --install`.