

Part 1: Understanding Percona XtraBackup

Percona XtraBackup is a hot backup tool provided by Percona that allows you to take backups without stopping MySQL.

✅ Step 1: Add Percona Repository

```
wget https://repo.percona.com/apt/percona-release_latest.generic_all.deb
sudo dpkg -i percona-release_latest.generic_all.deb
```

sudo apt update

enable the repo:

```
sudo percona-release setup pxb-80
```

✅ Step 2: Install XtraBackup

```
sudo apt install -y percona-xtrabackup-80
```

✅ Step 3: Verify Installation

```
xtrabackup --version
```

✅ Step 4: Create Backup Directory

```
sudo mkdir -p /backup/mysql
sudo chown -R mysql:mysql /backup/mysql
chmod 750 /backup/mysql
```

✅ Step 5: Create Backup User in MySQL

```
mysql -u root -p

CREATE USER 'backupuser'@'localhost' IDENTIFIED BY 'StrongPass@123';

GRANT RELOAD, LOCK TABLES, PROCESS, REPLICATION CLIENT
ON *.* TO 'backupuser'@'localhost';

GRANT BACKUP_ADMIN ON *.* TO 'backupuser'@'localhost';

FLUSH PRIVILEGES;
```

✅ Step 6: Take Your First Full Backup

```
xtrabackup \
--backup \
--user=backupuser \
--password='StrongPass@123' \
--target-dir=/backup/mysql/full_$(date +%F)
```

✅ Step 7: Prepare the Backup

Before restore always prepare :

```
xtrabackup --prepare --target-dir=/backup/mysql/full_2026-02-22
```

✅ Step 8: Restore (Testing Only – On UAT/Test Server)

⚠️ Do NOT test on production first.

Stop MySQL

```
systemctl stop mysqld
```

restore:

```
xtrabackup \  
--copy-back \  
--target-dir=/backup/mysql \  
--datadir=/var/lib/mysqlfix permission :
```

```
chown -R mysql:mysql /var/lib/mysql
```

```
start mysql
```

```
systemctl start mysql
```

Why Use XtraBackup?

- No downtime (Hot backup)
- Works for large databases
- Supports Incremental backups
- Industry standard for production

Core Concepts You Must Learn

Topic	Description
Full Backup	Complete database backup
Incremental Backup	Only changed data
Prepare Phase	Makes backup consistent
Restore Phase	Copy back to MySQL
LSN	Log Sequence Number
Redo Logs	Crash recovery

◆ Basic Full Backup

```
xtrabackup --backup --target-dir=/backup/full
```

◆ Prepare Backup

```
xtrabackup --prepare --target-dir=/backup/full
```

◆ Restore Backup

```
systemctl stop mysql  
xtrabackup --copy-back --target-dir=/backup/full  
chown -R mysql:mysql /var/lib/mysql  
systemctl start mysql
```

◆ Incremental Backup Example

Full

```
xtrabackup --backup --target-dir=/backup/full
```

Incremental

```
xtrabackup --backup \
```

```
--target-dir=/backup/inc1 \
```

```
--incremental-basedir=/backup/full
```

Prepare:

```
xtrabackup --prepare --apply-log-only --target-dir=/backup/full
```

```
xtrabackup --prepare --apply-log-only --target-dir=/backup/full --incremental-dir=/backup/inc1
```

```
xtrabackup --prepare --target-dir=/backup/full
```

Part 2: Tablespace Management in MySQL / Percona

Tablespace = Where MySQL stores table data physically.

1 System Tablespace (ibdata1)

Contains:

- Data dictionary
- Undo logs (old versions)
- Some table data (if file_per_table=OFF)

```
SHOW VARIABLES LIKE 'innodb_data_file_path';
```

2 File-Per-Table Tablespace (.ibd files)

Each table = Separate file.

```
innodb_file_per_table=1
```

Benefits:

- ✓ Easy space management
- ✓ Easy restore
- ✓ Better performance

3 General Tablespace (MySQL 5.7+)

Shared tablespace for multiple tables.

```
CREATE TABLESPACE ts1 ADD DATAFILE 'ts1.ibd';
```

```
CREATE TABLE test.t1 (  
  id INT  
) TABLESPACE ts1;
```

Undo Tablespace

Used for:

- Rollback
- MVCC

Check:

```
SHOW VARIABLES LIKE 'innodb_undo%';
```

Part 3: Table-Level Backup & Restore (Important for You)

Since you asked about **table restore earlier**, this is critical.

◆ Backup Single Table

```
xtrabackup --backup \  
--databases="mydb mydb.mytable" \  
--target-dir=/backup/table
```

◆ Restore Single Table (Advanced)

1 Drop table

```
DROP TABLE mydb.mytable;
```

2 Recreate structure

```
CREATE TABLE mydb.mytable (...);
```


3 Discard tablespace

```
ALTER TABLE mydb.mytable DISCARD TABLESPACE;
```

4 Copy .ibd file

5 Import tablespace

```
ALTER TABLE mydb.mytable IMPORT TABLESPACE;
```

 Works only when innodb_file_per_table=ON

Part 4: Production Best Practices (Very Important)

Backup Strategy

Type	Schedule
------	----------

Full	Weekly
------	--------

Type	Schedule
------	----------

Incremental	Daily
-------------	-------

Binlog	Real-time
--------	-----------

✅ Always Verify Backup

xtrabackup --prepare --export --target-dir=/backup/full

Test restore on UAT (as you prefer 👍).

✅ Monitor Backup Size

du -sh /backup/*

Part 5: Learning Plan (7 Days)

Day 1–2

- ✓ Install XtraBackup
- ✓ Take full backup
- ✓ Restore on test server

Day 3–4

- ✓ Incremental backups
- ✓ Practice prepare phase
- ✓ Understand LSN

Day 5

- ✓ Tablespace concepts
- ✓ ibdata vs ibd

Day 6

- ✓ Table-level restore
- ✓ Disaster recovery drill

Day 7

- ✓ Automate backup (cron)
- ✓ Monitoring + alerting

Part 6: Automation Example (Cron)

```
0 2 * * * /usr/bin/xtrabackup \  
--backup \  
--target-dir=/backup/$(date +%F)
```

Script to run the full backup restore :

1. Stop MySQL

```
systemctl stop mysql
```

2. Clean datadir

```
rm -rf /var/lib/mysql/*
```

3. Restore

```
xtrabackup --copy-back \
```

```
--target-dir=/backup/mysql \
```

```
--datadir=/var/lib/mysql
```

4. Fix permission

```
chown -R mysql:mysql /var/lib/mysql
```

5. Start MySQL

```
systemctl start mysql
```