QUESTION 7 AI ROAST GENERATOR

```
#include <iostream>
#include <vector>
#include <string>
#include <cstdlib>
#include <ctime>
#include <algorithm>

// Function to replace all occurrences of {name} with the actual user
name
std::string replaceName(std::string templ, const std::string& name) {
    std::string placeholder = "{name}";
    size_t pos = 0;
    while ((pos = templ.find(placeholder, pos)) != std::string::npos) {
        templ.replace(pos, placeholder.length(), name);
        pos += name.length();
    }
    return templ;
}

int main() {
    // Seed random number generator with current time for different
results each run
    srand(static_cast<unsigned int>(time(0)));

    // Store roast templates in a vector
    std::vector<std::string> roasts = {
        "{name} writes code so slow that even a turtle switched to
Python.",
        "If procrastination were an Olympic sport, {name} would already
have a gold medal.",
        "{name}'s debugging style is basically staring at the screen
until the bug gets embarrassed and leaves.",
        "{name}'s code runs so slowly that even dial-up internet feels
fast.",
        "If laziness had a brand ambassador, it would be {name}.",
        "{name} doesn't debug code — they negotiate with bugs.",
        "{name}'s GitHub has more empty commits than actual code.",
        "Scientists discovered a new unit of slowness — they named it
after {name}.",
        "{name} once Googled 'how to Google things' — twice.",
        "{name} thinks recursion is just a fancy word for confusion.",
        "The only loop {name} is good at is going in circles during
problem-solving.",
        "Even Stack Overflow gave up answering {name}'s questions.",
    };

    // Ask user for their name
    std::string name;
    std::cout << "========================================\n";
    std::cout << "       Welcome to the Roast Generator!  \n";
    std::cout << "========================================\n";
    std::cout << "Enter your name: ";
    std::getline(std::cin, name);

    // Handle empty input
    if (name.empty()) {
```

```
        std::cout << "No name entered. Defaulting to 'Mystery
Person'.\n";
        name = "Mystery Person";
    }

    // Randomly select a roast template
    int index = rand() % roasts.size();
    std::string roast = replaceName(roasts[index], name);

    // Display the roast
    std::cout << "\n🔥 Here's your roast, " << name << ":\n";
    std::cout << "----------------------------------------\n";
    std::cout << roast << "\n";
    std::cout << "----------------------------------------\n";

    return 0;
}
```