

Question 1 | Correct | Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int main() {
4      int V;
5      if (scanf("%d", &V) != 1) return 0;
6
7      int coins[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
8      int n = sizeof(coins) / sizeof(coins[0]);
9      int count = 0;
10
11     for (int i = 0; i < n; i++) {
12         if (V >= coins[i]) {
13             count += V / coins[i];
14             V %= coins[i];
15         }
16     }
17
18     printf("%d\n", count);
19     return 0;
20 }
```

	Input	Expected	Got	
✓	49	5	5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)

