Highest Priced Orders and Price Outliers:

In [13]:
```
import pandas as pd

df = pd.read_csv("/content/bookbazaar_orders_2026.csv")
df["Unit_Price"] = pd.to_numeric(df["Unit_Price"], errors="coerce")
```

In [14]:
```
print("Orders with invalid prices:")
print(df[df["Unit_Price"].isnull()][["Order_ID", "Product", "Unit_Price"]])
```

```
Orders with invalid prices:
   Order_ID          Product  Unit_Price
48  ORD0049  Space Explorers         NaN
```

In [15]:
```
highest_index = df["Unit_Price"].idxmax()
print("Highest-priced product:")
print(df.loc[highest_index, ["Product", "Unit_Price"]])
print("Maximum unit price:", df["Unit_Price"].max())
```

```
Highest-priced product:
Product       Introduction to Data Science
Unit_Price                           999.0
Name: 3, dtype: object
Maximum unit price: 999.0
```

In [16]:
```
print("All orders at the maximum price:")
print(df[df["Unit_Price"] == df["Unit_Price"].max()][["Order_ID", "Product", "Un
```

```
All orders at the maximum price:
   Order_ID                        Product  Unit_Price
3   ORD0004  Introduction to Data Science       999.0
12  ORD0013  Introduction to Data Science       999.0
14  ORD0015  Introduction to Data Science       999.0
19  ORD0020  Introduction to Data Science       999.0
21  ORD0022  Introduction to Data Science       999.0
65  ORD0066  Introduction to Data Science       999.0
82  ORD0083  Introduction to Data Science       999.0
```

In [17]:
```
Q1 = df["Unit_Price"].quantile(0.25)
Q3 = df["Unit_Price"].quantile(0.75)
IQR = Q3 - Q1
outliers = df[(df["Unit_Price"] < Q1 - 1.5 * IQR) | (df["Unit_Price"] > Q3 + 1.5
print("Price outliers found:", len(outliers))
print(outliers[["Order_ID", "Product", "Unit_Price"]])
```

```
Price outliers found: 0
Empty DataFrame
Columns: [Order_ID, Product, Unit_Price]
Index: []
```