Neural Networks

Vishal Patel

Spring 2025

Feature Engineering

CUSTOMER ID	PURCHASE DATE
1001	02-12-2015:05:20:39
1001	05-13-2015:12:18:09
1001	12-20-2016:00:15:59
1002	01-19-2014:04:28:54
1003	01-12-2015:09:20:36
1003	05-31-2015:10:10:02

- 1. Number of transactions (Frequency)
- 2. Days since the last transaction (Recency)
- 3. Days since the earliest transaction (Tenure)
- 4. Avg. days between transaction
- 5. # of transactions during weekends
- 6. % of transactions during weekends
- 7. # of transactions by day-part (breakfast, lunch, etc.)
- 8. % of transactions by day-part
- 9. Days since last transaction / Avg. days between transactions
- 10. ...




Create Features

Train Models



CUSTOMER ID	x_1	x_2	 x_j
1001			
1002			
1003			

Training Data




Domain Knowledge


Create Features

Train Models

Feature Engineering?

Training Data







 $egin{pmatrix} y_1 \ y_2 \ y_3 \ & \cdot \ & \cdot \ & \cdot \ & y_n \ \end{pmatrix}$

$$j = 36$$

Digit Recognition Program




Neural Network



Multilayer Perceptron

Terminology





Activation values for the input layer




Probability that a given input is that number

The Layers






Activation Function



$$w_1 = -0.17$$

 $w_2 = -2.09$
 $w_3 = +3.25$
 $w_4 = -0.05$
 $w_5 = -2.99$
 $w_6 = +1.11$


Sigmoid function



Activation value of a neuron:

$$\sigma(w_1a_1 + w_2a_2 + w_3a_3 + \dots + w_na_n + bias)$$

Activation Function



$$a_0^{(1)} = \sigma \left(w_{0,0} a_0^{(0)} + w_{0,1} a_1^{(0)} + \dots + w_{0,n} a_n^{(0)} + b_0 \right)$$


$$a^{(1)} = \sigma(Wa^{(0)} + b)$$

Rectified Linear Unit

Sigmoid

$$\sigma(a) = \frac{1}{1 + e^{-a}}$$


Slow learner



ReLU

 $ReLU(a) = \max(0, a)$

Neural Network: Model Parameters



64 * 12 + 12 * 12 + 12 * 10 *weights*

12 + 12 + 10biases


4,394


GPT-4 has ~1.8 trillion parameters!

Learning →

Finding the right weights and biases

The Cost Function





Weights and biases

Training data


Cost


Mean Squared Error (Quadratic cost), Cross-entropy cost, etc.

Input

Output


Backpropagation






Actual Output	Desired Output	Adj.
0.20	0	-
0.18	0	-
0.01	0	
0.78	0	-
0.88	1	+
0.32	0	-
0.15	0	-
0.08	0	-
0.05	0	
0.83	0	-

Resources



TensorFlow, Keras and deep learning, without a PhD







$$a_{0}^{(0)}$$
 $w_{0,0}$
 $v_{0,0}$
 $v_{0,1}$
 $v_{0,2}$
 $v_{0,2}$
 $v_{0,3}$
 $v_{0,4}$
 $v_{0,4}$

$$a_0^{(1)} = \sigma \left(w_{0,0} a_0^{(0)} + w_{0,1} a_1^{(0)} + \dots + w_{0,n} a_n^{(0)} + b_0 \right)$$

$$a^{(1)} = \sigma \left(W a^{(0)} + b \right)$$


import tensorflow as tf

Neural Network Tutorial


```
13_digits_recognition_model.ipynb
```

14_intro_neural_net.ipynb

batch, iterations, and epoch



7 passes through the entire dataset.



Fully Connected MLP

- Computationally expensive
- Spatial information is lost
- Sensitive to location of objects within an image



Convolutional Neural Networks (CNNs)



convolve

[kənˈvälv] ◀))

VERR rar

convolve (verb) · convolves (third person present) · convolved (past tense) · convolved (past participle)
convolving (present participle)


roll or coil together; entwine.

 mathematics combine (one function or series) with another by forming their convolution.


ORIGIN

late 16th century (in the sense 'enclose in folds'): from Latin convolvere 'roll together', from con- 'together' + volvere 'roll'.

Spatial Structure



Convolution




Filter = A **patch** of size 3x3 (in this example)

Instead of taking a straight sum of all pixels within a patch, a set of weights are created which are then used to take a weighted sums.

Multiple filters (i.e., set of weights) are used to extract different features.

Feature Extraction



Let's create a filter to identify the cross.

-1	1	-1	-1	-1	-1
-1	1	-1	-1	-1	-1
-1	1	-1	1	-1	-1
-1	1	1	1	1	-1
-1	-1	-1	1	-1	-1
-1	-1	-1	1	-1	-1

 -1
 1
 -1

 1
 1
 1


 -1
 1
 -1

Filter

Input

-1	1	-1	-1	-1	-1
-1	1	-1	-1	-1	-1
-1	1	-1	1	-1	-1
-1	1	1	1	1	-1
-1	-1	-1	1	-1	-1
-1	-1	-1	1	-1	-1

Input



Filter

$$(-1*-1) + (1*1) + (-1*-1)$$


+ $(-1*1) + (1*1) + (-1*1)$
+ $(-1*-1) + (1*1) + (-1*-1)$

$$1+1+1-1+1-1+1+1=5$$

-1	1	-1	-1	-1	-1
-1	1	-1	-1	-1	-1
-1	1	-1	1	-1	-1
-1	1	1	1	1	-1
-1	-1	-1	1	-1	-1
-1	-1	-1	1	-1	-1

-1	1	-1
1	1	1
-1	1	-1

5	-5	



Input

Pooling = Downsampling operation on a feature map

-3

-1

-1

9

CNN Tutorial

15_image_classification_cnn.ipynb