



KPLABS Course

HashiCorp Certified: Terraform Associate

Domain 3 - Terraform Provisioners

ISSUED BY

Zeal

REPRESENTATIVE

instructors@kplabs.in



Module 1: Understanding Provisioners in Terraform

1.1 Understanding the Challenge

Till now we have been working only on the creation and destruction of infrastructure scenarios.

Let's take an example:

We created a web-server EC2 instance with Terraform.

Problem: It is only an EC2 instance, it does not have any software installed.

What if we want a complete end to end solution?

1.2 Introducing Terraform Provisioners

Provisioners are used to execute scripts on a local or remote machine as part of resource creation or destruction.

Let's take an example:


On creation of Web-Server, execute a script which installs Nginx web-server.



Module 2: Types of Provisioners

Terraform has the capability to turn provisioners both at the time of resource creation as well as destruction.

There are two main types of provisioners:



2.1 Local Exec Provisioners

local-exec provisioners allow us to invoke a local executable after the resource is created.

One of the most used approaches of local-exec is to run ansible-playbooks on the created server after the resource is created.

Let's take an example:

```
provisioner "local-exec" {  
  command = "echo ${aws_instance.web.private_ip} >> private_ips.txt"  
}
```

2.2 Remote Exec Provisioners

Remote-exec provisioners allow invoking scripts directly on the remote server.

Let's take an example:

```
resource "aws_instance" "web" {  
  # ...  
  
  provisioner "remote-exec" {  
    .....  
  }  
}
```

Module 3: Provisioner Types

There are two primary types of provisioners:

Types of Provisioners	Description
Creation-Time Provisioner	Creation-time provisioners are only run during creation, not during updating or any other lifecycle If a creation-time provisioner fails, the resource is marked as tainted.
Destroy-Time Provisioner	Destroy provisioners are run before the resource is destroyed.

If when = destroy is specified, the provisioner will run when the resource it is defined within is destroyed.

```
resource "aws_instance" "web" {
  # ...

  provisioner "local-exec" {
    when      = destroy
    command   = "echo 'Destroy-time provisioner'"
  }
}
```

Module 4: Failure Behavior

By default, provisioners that fail will also cause the terraform apply itself to fail.

The `on_failure` setting can be used to change this. The allowed values are:


Allowed Values	Description
continue	Ignore the error and continue with creation or destruction.
fail	Raise an error and stop applying (the default behavior). If this is a creation provisioner, taint the resource.

```
resource "aws_instance" "web" {
  # ...

  provisioner "local-exec" {
    command     = "echo The server's IP address is ${self.private_ip}"
    on_failure = continue
  }
}
```

Module 5: Null Resource

The null_resource implements the standard resource lifecycle but takes no further action.



Join Our Discord Community

We invite you to join our Discord community, where you can interact with our support team for any course-based technical queries and connect with other students who are doing the same course.

Joining URL:

<http://kplabs.in/chat>

[illegible]