#### **NAME**

CUTEST cdhc threaded - CUTEst tool to evaluate the Hessian of the constraint part of the Lagrangian.

### **SYNOPSIS**

```
CALL CUTEST cdhc threaded( status, n, m, X, Y, lh1, H val, thread )
```

For real rather than double precision arguments, instead

```
CALL\ CUTEST\_cdhc\_threaded\_s(\ ...\ )
```

and for quadruple precision arguments, when available,

```
CALL CUTEST_cdhc_threaded_q( ... )
```

## **DESCRIPTION**

The CUTEST\_cdhc\_threaded subroutine evaluates the Hessian matrix of the constraint part of the Lagrangian function  $y^T c(x)$  for the problem decoded from a SIF file by the script *sifdecoder* at the point (x, y) = (X, Y). The matrix is stored as a dense matrix.

The problem under consideration is to minimize or maximize an objective function f(x) over all  $x \in R^n$  subject to general equations  $c_i(x) = 0$ ,  $(i \in 1, ..., m_E)$ , general inequalities  $c_i^l \le c_i(x) \le c_i^u$ ,  $(i \in m_E + 1, ..., m)$ , and simple bounds  $x^l \le x \le x^u$ . The objective function is group-partially separable and all constraint functions are partially separable.

# **ARGUMENTS**

The arguments of CUTEST\_cdhc\_threaded are as follows

#### status [out] - integer

the outputr status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error, 4 for an out-of-range thread,

n [in] - integer

the number of variables for the problem,

m [in] - integer

the total number of general constraints,

X [in] - real/double precision

an array which gives the current estimate of the solution of the problem,

Y [in] - real/double precision

an array which gives the Lagrange multipliers,

lh1 [in] - integer

the actual declared size of the leading dimension of H\_val (with lh1 no smaller than n),

**H\_val** [out] - real/double precision

a two-dimensional array which gives the value of the Hessian matrix of the constraint part of the Lagrangian function evaluated at X and Y,

thread [in] - integer

thread chosen for the evaluation; threads are numbered from 1 to the value threads set when calling CUTEST\_csetup\_threaded.

### **AUTHORS**

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

### **SEE ALSO**

CUTEst: a Constrained and Unconstrained Testing Environment with safe threads, N.I.M. Gould, D. Orban and Ph.L. Toint, Computational Optimization and Applications **60**:3, pp.545-557, 2014.

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited, N.I.M. Gould, D. Orban and Ph.L. Toint, ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, ACM TOMS, **21**:1, pp.123-160, 1995.

cutest\_cdh\_threaded(3M), sifdecoder(1)