Completed work & launch checklist

tento-agents / Resident OS - updated after implementing the remaining MVP code.

Where the project stands

The internal-work-order MVP is implemented and verified locally. It has not been deployed live. You chose Vercel for the frontend, Railway for the API and worker, and internal work orders only. You can add the service keys at the end.

The complete flow

Sign in -> choose your residence -> save a report -> background AI processing -> view status -> create an internal work order when evidence and capability support it.

Completed work

Status	What is now implemented
DONE	Removed the old labeling/reviewer workflows and obsolete specifications.
DONE	Real ticket submission with a saved ticket number and retry protection.
DONE	Authorised residence selection, resident history and status/detail pages.
DONE	Separate worker with leases, safe retries, restart recovery and duplicate protection.
DONE	Full autonomous safety, intake, retrieval, diagnosis, planning and policy checks.
DONE	Saved model/decision traces and source-backed policy configuration.
DONE	A validated in-house plan creates one saved internal work order.
DONE	Railway API/worker configs, smaller container image, migration runner and role scripts.
DONE	Supabase token-hook SQL, API type generation and updated setup documentation.

Local verification passed

309 tests, including five real PostgreSQL integration tests. Ruff lint/format passed. Python type checks passed across **105 files**. TypeScript, the Next.js production build and HTTP proxy tests passed. Fresh and populated legacy database upgrades passed. The container image builds and its runtime imports pass.

Model tests use scripted responses, not paid live calls. The PostgreSQL checks use an isolated local database. These results do not prove live Supabase, provider or hosting connectivity.

Finish these steps in order

The remaining items depend on your accounts, keys and actual property information. They cannot be truthfully marked done before those are supplied.

[ ] 1. Create the live services and add values

Create or select your Supabase project, Railway project and Vercel project. Add the values listed on page 3 to the correct service. Use separate restricted database logins for the API and worker.

Done when: The host environments contain valid values, and no secret is committed to Git or exposed in browser variables.

[ ] 2. Add real membership and property data

Create your organisation, property, building, unit, person and active tenancy records. Create the corresponding Supabase user. Install the token hook and set administrator-controlled membership metadata.

Done when: The user can sign in and the report form shows only their authorised current residence.

[ ] 3. Add real policy sources and in-house capability

Supply verified, versioned property documents. Import their exact policy spans using the source-import command. Configure the actual trades your in-house team can perform. Do not promote synthetic knowledge fixtures.

Done when: A real report retrieves applicable evidence and produces a validated plan. Missing evidence or capability returns abstention.

[ ] 4. Deploy and test Railway

Apply migrations using the administrator migration job. Deploy two services from the repository root: API with infra/railway/api.json and worker with infra/railway/worker.json. Give the API an HTTPS domain; the worker needs none.

Done when: The API health check passes and a saved report is processed by the correctly scoped worker.

[ ] 5. Deploy and test Vercel

Set the Vercel Root Directory to apps/web with workspace access enabled. Configure the API HTTPS origin and Supabase values. Test a preview before releasing production.

Done when: A real browser can sign in, save a report, see it in history and see its completed internal work order.

[ ] 6. Record live acceptance and recovery

Test normal/emergency reports, expired sessions, privacy, duplicate retries, missing evidence and provider failures. Configure backups, operational logs, provider spend limits and a rollback procedure. Save the tested source revision.

Done when: The production journey succeeds and you can diagnose failures or restore service.

Values to add at the end

A URL or identifier is configuration, not necessarily a secret. Keep passwords and provider keys in ignored local files or hosting secret settings.

Value	Where it belongs / purpose
DATABASE_URL	Railway API: resident_api login. Worker/import job: resident_worker login. Both point to the same pgvector database.
REDIS_URL	Railway API: its Redis service connection.
SUPABASE_URL	Railway API and Vercel: your Supabase project HTTPS URL.
SUPABASE_ANON_KEY	Vercel server: project key used for password sign-in. Never substitute a service-role key.
SUPABASE_JWT_AUDIENCE	Railway API: match issued tokens, usually authenticated.
ANTHROPIC_API_KEY	Railway worker. Also needed by the API only if you use the separate direct-analysis endpoint.
ANTHROPIC_MODEL	Worker, and direct-analysis API if used: exact model ID available to your account.
WORKER_ORG_ID	Worker: the organisation UUID it processes. One worker deployment serves one organisation.
API_BASE_URL	Vercel server: the Railway API HTTPS origin.
MIGRATION_DATABASE_URL	Explicit migration job only: administrator connection, never normal API/browser credentials.
OPENAI_API_KEY	Verified-source import job only: creates embeddings. The active retrieval query uses PostgreSQL lexical matching.

Not required for your chosen MVP

No vendor, email/notification, payments, Google or media-storage key is needed. TEST_DATABASE_URL is only for disposable local/CI integration tests. Hosting account access is separate from AI provider keys.

Supabase account membership

Install infra/auth/supabase-token-hook.sql in the Supabase Auth project and enable it as a Custom Access Token Hook. An administrator supplies app_metadata.resident_os with org_id, person_id and app_role. The API reads signed custom claims; ordinary user-editable profile fields cannot grant access.

The detailed, copyable reference is docs/KEYS-AND-SETUP.md. Read docs/DEPLOYMENT.md for database roles, migration adoption, source metadata and the exact Railway/Vercel setup.

Local testing and release notes

Use the repository guides for the detailed commands. Start the API, worker and frontend in separate terminals.

Local prerequisites

Python 3.12, Node.js 22, pnpm 11.19.0, PostgreSQL with pgvector and Redis. Install requirements.txt and the locked JavaScript dependencies. Load environment values into each shell; copying .env does not load them automatically.

Main commands

```
docker compose -f infra/docker-compose.dev.yml up -d
$env:PYTHONPATH="services/api/src;services/brain/src"
python -m api.migrate
python -m uvicorn api.main:app --port 8000

# Separate worker terminal, with its own environment
python -m api.worker

# Separate web terminal
pnpm dev:web
```

The migration job needs the administrator URL. Normal API and worker processes use restricted logins. A fresh database applies five migrations. Back up an existing database and rehearse the upgrade before production. The migration ledger makes repeat runs safe.

Checks before releasing changes

```
python -m ruff check services/api services/brain infra/seed
python -m mypy
python -m pytest -q
python scripts/export_openapi.py
pnpm generate:api
pnpm typecheck:web
pnpm build:web
python apps/web/scripts/check-proxies.py
```

What internal work orders mean

A work order is a real saved task for normal internal assignment. It does not mean a repair is completed or a visit is scheduled. Unsupported cases retain the resident report and abstain. The worker may rerun model calls after a crash; that can incur another provider charge.

Outside the chosen MVP

External vendor dispatch, outbound messages, media uploads, payments and additional dashboards remain optional future expansion. They are not launch requirements for the internal-work-order scope you selected.

Evidence and status

Based on the current source, documentation and checks run in this chat. Relevant references: README.md; docs/PRODUCT.md; docs/DEPLOYMENT.md; docs/KEYS-AND-SETUP.md; services/api/src/api/worker.py; services/brain/src/brain/production.py. No live hosting release or paid provider call has been performed.