

Ultrasonic Water Meter



Product Features

- Product application for water supply metering
- Pipe material: Copper
- Ultrasonic measurement, without mechanical wear, with excellent reliability and stability
- Accuracy level: Level 2
- Range ratio: R100/R125/R160/R250/R400
- Temperature grade: T30/T50/T70
- Compliant with national standard: GB/T 778 / ISO 4064
- Equipped with water droplet leakage and pipe burst alarm function
- Diversified communication interfaces: MBUS, RS485, pulse, LoRaWAN, NB-IoT, Zigbee, 4G

213E – Ultrasonic Water Meter



Product Parameters

Performance	Parameter				
Nominal diameter	DN15	DN20	DN25	DN32	DN40
Pipe Length	165mm	195mm	225mm	180mm	200mm
Q ₃ (m³/h)	2.5	4	6.3	10	16
Initial Flow Rate (L/h)	2	2	3	5	7
Range Ratio	Q3/Q1=100, 125, 160, 200, 250, 400				
Accuracy Class	Level 2				
Pressure Rating	MAP16	Pressure loss level			p40
Temperature Rating	T30, T50, T70; default T30				
Data Storage	24 months of historical data, (Data storage mode can be customized according to customer needs)				
Power-off protection	After a power outage, the accumulated flow and corresponding time recorded before the outage can be saved, Automatically restore metering function after power restoration				
Remote transmission method	Infrared, M-BUS, RS485, NB IoT, LORA, LoRaAWan, 4G, Sigfox, Pulse (configured according to requirements)				
Power supply	DC3.6V lithium battery				
Protection grade	IP68				
Work environment	Temperature: -15℃ ~ +55℃, Ambient relative humidity: < 90%				
Installation position	Horizontal or vertical				
Durability	Usage cycle ≥ 6 years				

Dimensions

Nominal diameter	DN15	DN20	DN25	DN32	DN40
Pipe Length	165mm	195mm	225mm	180mm	200mm
Q_3 (m³/h)	2.5	4	6.3	10	16
Initial Flow Rate (L/h)	2	2	3	5	7
Range Ratio	Q3/Q1=100, 125, 160, 200, 250, 400				
Accuracy Class	Level 2				

