

1 Introduction

This document will contain the implementation details for the design learning platform. It will be used to outline the implementation before it is developed.

2 Components

WIP

In this section, I will outline the relationship between the following components and the practical steps needed to establish the relationship:

1. Artha - Meaningful Programming Language
2. DAL - Design Abstraction Language
3. CSM - Computable Semantic Model
4. CSP - Computable Semantic Primitives
5. Engine - Semantic Reasoning Engine
6. CLP - Compressed Log Processor
7. SI - Synthesized Implementation

When discussing this framework, the core principles revolve around meaning. So I think I will start by establishing that meaning is constructed by narratives that use the primitive meaningful building blocks. The narratives themselves have meaning and structure and that structure is used to automatically build a semantic model written in the design abstraction language. Since the meaning was built from computable semantic primitives, which are themselves established using the DAL, the semantic model becomes executable and becomes a computable semantic model.

Once meaning has been established, now it can be used in another narrative. It is a compositional system where meaning is composed through narratives and used to compose more meaning. Since the meaning is built from computable semantic primitives and it has an unambiguous structure, it can be synthesized into an implementation. In the process, the meaning of the software system has been automatically developed in a programming language.

The engine reasons about the meaning using the structure established by the computable semantic model. Since the structure is unambiguous and meaningful, it is able to reason about it to enforce its own definition of correctness and to also identify missing or incorrect meaning. Through the synthesis and instrumentation, the necessary information needed to replay the execution is preserved using domain specific compression and the engine is able to diagnose any failures and enable the meaning to expand through root cause analysis. This process automatically manages the software system and enables a deterministic learning loop.

Since the meaning of the participant is specified as part of the narrative, its domain structure can also be included in that meaning. So the meaning is what CLP uses to perform the domain specific compression, the domain structure is part of its meaning. If you imagine a story, the description of the character (which is part of the meaning) can be as detailed and unambiguous as needed, in this case, that description can be extended to include the domain structure of the participant.

The meaning can also tell you more about the data (ex. how it changes) so that it can be exploited to optimally compress this. There is a difference between knowing a value is a float and knowing that it is a GPS coordinates latitude or ambient temperature. It also makes the data itself meaningful, for example, if its GPS coordinates, you know when there is movement and when there is no movement. Also, since the meaning is already known, the queries will be meaningful and the ingestion performance can be improved. There are lots of implications for this but I'll discuss them later in the domain specific compression section. Ultimately, I just see meaning as the elimination of ambiguity in the domain (which CLP benefits from) and this framework provides the means to fully eliminate ambiguity in the meaning.

Next, I will discuss how each component can be practically implemented.

2.1 Design Abstraction Language

The Design Abstraction Language (DAL) itself is just a structure that can be used to construct the meaning of a design. I've written a basic AST library that can be used to establish blocks and commands with arguments, this is sufficient for now. Its the structures that are built with this that define the meaning.

2.1.1 Structure

The structural specification enables the the construction of a block using braces. For example, the block can be used as follows to specify control flow logic for a behavior.

```
1 select {
2     # Specify control flow logic
3 }
```

2.1.2 Commands or Attributes

The command structure itself is specified as shown below. Each command is specified and in the bracket the arguments are provided. There can be keyword commands used by the design and then there are custom commands that reference more meaning.

```
1 # Built In
2 design("Design Name")
3
4 # Custom Command
5 command(
6     number=123,
7     string="String",
8     arrayArg=[12,33,12],
9     objArg={"a":1}
10 )
11
12 # Reusing structure to specify attributes
13 property(
14     name="type"
15     description="Data type of participant (list, object, str etc)"
16     type="string"
17     get="getType"
18 )
```

2.1.3 Control Flow

The control flow structure itself is specified as specified below. Currently, only if statements are supposed but not else if or else blocks. I need to extend the library to support this.

```
1 # Currently supported
2 if (boolean) {
3
4 }
```

This basic structure makes it possible to specify all the necessary attributes without making the AST implementation itself complicated. As I work through the reasoning and build the CSM, I will be using these structures specify the necessary meaning. If I run into features I can't support, I will return here and add to it.

2.1.4 Abstract Syntax Tree

The DAL script is parsed into an Abstract Syntax Tree(AST) that is then used by the validator. An example of a simple AST generated by a DAL script is provided below. In a full design specification, multiple dal files can be used to specify the behavior attributes, participant attributes etc.

2.1.5 Sample DAL Script

```
1 design("test")
2
3 behavior getName {
4     select {
5         goToBehavior(addBook)
6     }
7 }
8
9 behavior addBook {
10    #...
11    select {
12        goToBehavior(getName)
13    }
14 }
```

2.1.6 Sample AST

```
1 {
2     "type": "design",
3     "body": [
4         {
5             "type": "behavior",
6             "behaviorName": "getName",
7             "body": [
8                 {
9                     "type": "select",
10                    "args": [],
11                    "body": [
12                        {
13                            "type": "cmd",
14                            "command": "goToBehavior",
15                            "args": [
16                                {
17                                    "arg": null,
18                                    "type": "name",
19                                    "value": "addBook"
20                                }
21                            ]
22                        }
23                    ]
24                }
25            ]
26        },
27        {
28            "type": "behavior",
29            "behaviorName": "addBook",
30            "body": [
31                {
```

```

32         "type": "select",
33         "args": [],
34         "body": [
35             {
36                 "type": "cmd",
37                 "command": "goToBehavior",
38                 "args": [
39                     {
40                         "arg": null,
41                         "type": "name",
42                         "value": "getName"
43                     }
44                 ]
45             }
46         ]
47     }
48 ]
49 }
50 ],
51 "name": [
52     {
53         "arg": null,
54         "type": "string",
55         "value": "test"
56     }
57 ]
58 }

```

2.1.7 Modifying AST by injecting nodes

TODO — Implement feature to modify AST by injecting nodes

This is necessary because through the reasoning, the engine will make automatic modifications to the design by enforcing the designs own meaning. I am not talking about the actual types of changes yet, just the ability to add nodes.

2.2 Computable Semantic Primitives

I think this is the best place to start because it introduces how meaning is established with the DAL while also introducing the first entries into the semantic toolkit that can be used to construct narratives. So next, I will present the CSP for add and then I will discuss each part of it.

Meaning of Add

```
1  design("add")
2  type("primitive")
3
4  description("Adds two numbers and produces a result. The numbers must have type float
   ↪ or int and the result will be float or int type.")
5
6  narrative_structure {
7    # Example: store result of add cost_of_bagel and cost_of_coffee in total_cost
8    narrative_syntax(f"store result of add {addend1} and {addend2} in {resultName}")
9    success_narrative(f"Added {addend1} to {addend2} and resulted in {result}.")
10   fail_inv_id_1(f"Failed to add the two numbers because addend1 was not a float or
   ↪ int.")
11   fail_inv_id_2(f"Failed to add the two numbers because addend2 was not a float or
   ↪ int.")
12 }
13
14 participants {
15   participant(name="addend1", required="true")
16   participant(name="addend2", required="true")
17   participant(name="resultName", required="true")
18 }
19
20 returns {
21   participant(
22     name="result",
23     type="float" or "int",
24     description="Result of the addition"
25   )
26 }
27
28 behavior add {
29   # Get the addends from the world state
30   getFromWorldState(name=addend1, role="addend1")
31   getFromWorldState(name=addend2, role="addend2")
32   getFromWorldState(name=resultName, role="resultName")
33
34   # adds the two values and store result in the value of resultName
35   _add(result, addend1, addend2)
36
37   # Update the world state
38   updateWorldState(
39     name=resultName,
40     value=result
41   )
42 }
43
44 run (add)
45
46
```

```

47     invariants {
48         assert({
49             id:1,
50             participants: ["addend1"],
51             property: "type"
52             condition: "float" || "int"
53             description: "Addend1 must be a whole number or float.",
54             invalidValues: [
55                 {
56                     value: "string_value"
57                     description: "A string is provided as an addend."
58                 }
59             ]
60         }),
61         assert({
62             id:2,
63             participants: ["addend2"],
64             property: "type"
65             condition: "float" || "int"
66             description: "Addend2 must be a whole number or float.",
67             invalidValues: [
68                 {
69                     value: "string_value"
70                     description: "A string is provided as an addend."
71                 }
72             ]
73         })
74     }
75 }

```

Realization of meaning of transformation Add

```

1 def add(addend1, addend2):
2     return addend1 + addend2

```

Realization of attribute type

```

1 def getType(value):
2     return type(value).__name__

```

TODO: Explain the components of the CSP

- narrative_syntax
- participants
- result
- behavior
- invariants
- realization

2.3 Narrative

In this section, I will build intuition for the role that each component plays by speaking generally about narratives using semantics used by humans in english. I will use it to demonstrate how the narrative can be constructed in a structured form and how that meaning can be used to construct more meaning. Then I will demonstrate how the meaning of narratives can be reasoned about to identify if it is internally consistent or if it has incorrect or missing meaning. Then I will discuss how the components outlined in this document work toward the same goal for software systems.

Consider the following narrative and participants in the narrative. In this case, the world is defined with the librarian and shelf. The user interacts with the world through the librarian and narratives unfold.

Librarian

The librarian presents the user with the option to add a book or get a book from the library.

If the user selects the option to add a book, the librarian accepts a book by asking the user for the name and content. Then the librarian reads the first letter of the books name to place the book on the relevant shelf. Then the user is once again asked which action they want to take.

If the user selects the option to get a book, the librarian asks the user for the book name. The librarian reads the first letter of the book name and accesses the book from the relevant shelf. After the librarian provides the user the book, the user is once again asked which action they want to take.

Book

A book has a name and it has contents.

Shelf

A shelf has slots for books. The slots are labelled using letters.