PL/SQL - BASIC SYNTAX

https://www.tutorialspoint.com/plsql/plsql_basic_syntax.htm

Copyright © tutorialspoint.com

In this chapter, we will discuss the Basic Syntax of PL/SQL which is a **block-structured** language; this means that the PL/SQL programs are divided and written in logical blocks of code. Each block consists of three sub-parts

S.No	Sections & Description		
1	Declarations This section starts with the keyword DECLARE . It is an optional section and defines all variables, cursors, subprograms, and other elements to be used in the program.		
2	Executable Commands This section is enclosed between the keywords BEGIN and END and it is a mandatory section. It consists of the executable PL/SQL statements of the program. It should have at least one executable line of code, which may be just a NULL command to indicate that nothing should be executed.		
3	Exception Handling This section starts with the keyword EXCEPTION . This optional section contains exception s that handle errors in the program.		

Every PL/SQL statement ends with a semicolon; PL/SQL blocks can be nested within other PL/SQL blocks using **BEGIN** and **END**. Following is the basic structure of a PL/SQL block –

The 'Hello World' Example

```
DECLARE
  message varchar2(20):= 'Hello, World!';
BEGIN
```

```
dbms_output.put_line(message);
END;
/
```

The **end**; line signals the end of the PL/SQL block. To run the code from the SQL command line, you may need to type / at the beginning of the first blank line after the last line of the code. When the above code is executed at the SQL prompt, it produces the following result –

Hello World

PL/SQL procedure successfully completed.

The PL/SQL Identifiers

PL/SQL identifiers are constants, variables, exceptions, procedures, cursors, and reserved words. The identifiers consist of a letter optionally followed by more letters, numerals, dollar signs, underscores, and number signs and should not exceed 30 characters.

By default, **identifiers are not case-sensitive**. So you can use **integer** or **INTEGER** to represent a numeric value. You cannot use a reserved keyword as an identifier.

The PL/SQL Delimiters

A delimiter is a symbol with a special meaning. Following is the list of delimiters in PL/SQL –

Delimiter	Description
+, -, *, /	Addition, subtraction/negation, multiplication, division
%	Attribute indicator
•	Character string delimiter
•	Component selector
,	Expression or list delimiter
:	Host variable indicator
,	Item separator
"	Quoted identifier delimiter
=	Relational operator
@	Remote access indicator
;	Statement terminator
:=	Assignment operator

=>	Association operator
II	Concatenation operator
**	Exponentiation operator
<<,>>	Label delimiter beginandend
/*,*/	Multi-line comment delimiter beginnndend
	Single-line comment indicator
	Range operator
<,>,<=,>=	Relational operators
<>,'=, ~=, ^=	Different versions of NOT EQUAL

The PL/SQL Comments

Program comments are explanatory statements that can be included in the PL/SQL code that you write and helps anyone reading its source code. All programming languages allow some form of comments.

The PL/SQL supports single-line and multi-line comments. All characters available inside any comment are ignored by the PL/SQL compiler. The PL/SQL single-line comments start with the delimiter -- *doublehyphen* and multi-line comments are enclosed by /* and */.

```
DECLARE
    -- variable declaration
    message varchar2(20):= 'Hello, World!';
BEGIN
    /*
    * PL/SQL executable statement(s)
    */
    dbms_output.put_line(message);
END;
//
```

When the above code is executed at the SQL prompt, it produces the following result –

Hello World

PL/SQL procedure successfully completed.

PL/SQL Program Units

A PL/SQL unit is any one of the following -

PL/SQL block

- Function
- Package
- Package body
- Procedure
- Trigger
- Type
- Type body

Each of these units will be discussed in the following chapters.