



Service Lane ☆

1204.44 more

Rank: 55157 |

Problem

Submissions

Leaderboard


Editorial

Topics

RATE THIS CHALLENGE



Calvin is driving his favorite vehicle on the 101 freeway. He notices that the check engine light of his vehicle is immediately to avoid any risks. Luckily, a service lane runs parallel to the highway. The service lane varies in v



You will be given an array of widths at points along the road (*indices*), then a list of the indices of entry and exit point pair, calculate the maximum size vehicle that can travel that segment of the service lane safely.

For example, there are $n = 4$ measurements yielding $width = [2, 3, 2, 1]$. If our entry index, $i = 1$ and our exit index, $j = 3$ respectively. The widest vehicle that can fit through both is 2 . If $i = 2$ and $j = 4$, our widths are $[2, 1]$ and the widest vehicle that can fit through both is 1 .

Function Description

Complete the `serviceLane` function in the editor below. It should return an array of integers representing the maximum size vehicle that can travel through each segment of the highway described.

`serviceLane` has the following parameter(s):

- n : an integer denoting the size of the **cases** array
- cases**: a two dimensional array of integers where each element is an array of two integers representing the entry and exit indices. Consider the following example:



Input Format

The first line of input contains two integers, n and t , where n denotes the number of width measurements you have. The next line has n space-separated integers which represent the array $width[w_0, w_1 \dots, w_{n-1}]$.

The next t lines contain two integers, i and j , where i is the start index and j is the end index of the segment.

Constraints

- $2 \leq n \leq 100000$
- $1 \leq t \leq 1000$
- $0 \leq i < j < n$
- $2 \leq j - i + 1 \leq \min(n, 1000)$
- $1 \leq width[k] \leq 3$, where $0 \leq k < n$

Output Format

For each test case, print the number that represents the largest vehicle type that can pass through the entire segment between indexes i and j inclusive.

Sample Input

```
8 5
2 3 1 2 3 2 3 3
0 3
4 6
6 7
3 5
0 7
```

Sample Output

```
1
2
3
2
1
```

Explanation

Below is the representation of the lane:

```
| HIGHWAY | Lane | -> Width
0: |         | -- |         2
```

1:		---	3
2:		-	1
3:		--	2
4:		---	3
5:		--	2
6:		---	3
7:		---	3

1. **(0, 3):** From index **0** through **3** we have widths **2, 3, 1** and **2**. Nothing wider than **1** can pass all segments.
2. **(4, 6):** From index **4** through **6** we have widht **3, 2** and **3**. Nothing wider than **2** can pass all segments.
3. **(6, 7): 3, 3 → 3 .**
4. **(3, 5): 2, 3, 2 → 2**
5. **(0, 7): 2, 3, 1, 2, 3, 2, 3, 3 → 1.**