Product Catalogue

Demo Pumps Pvt. Ltd. · Document PC-01 · Version 1.0, effective 01-Apr-2026

1. About this catalogue

This catalogue lists the standard pumps and hydraulic motors made by Demo Pumps Pvt. Ltd.. Every model is available for OEM customers (machine makers who fit our pumps into their machines) and for after-market (AFT) customers who replace a pump on a machine they already own.

All figures are at 1,450 rpm with mineral hydraulic oil ISO VG 46 at 40 °C, unless a table says otherwise. Prices are list prices in INR before GST, valid from 01-Apr-2026.

2. Gear pumps (GP series)

External gear pumps for machine-tool coolant, lubrication and low-pressure hydraulics. Simple, robust and the best value for money.

Model	Flow (L/min)	Max pressure (bar)	Motor power (kW)	Weight (kg)	List price (INR)
GP-100	10	60	0.75	4.2	18,500
GP-200	20	80	1.5	6.8	26,900
GP-350	35	100	3.7	11.5	41,200
GP-500	50	120	5.5	16.0	58,700

3. Trochoid pumps (TP series)

Internal trochoid (gerotor) pumps: very quiet, small pulsation, ideal for spindle lubrication and precision machines. The TP series is our best seller to machine-tool OEMs.

Model	Flow (L/min)	Max pressure (bar)	Motor power (kW)	Noise (dB(A))	List price (INR)
TP-50	5	35	0.4	52	14,800
TP-80	8	40	0.75	54	19,600
TP-120	12	50	1.1	56	24,300

4. High-pressure pumps (HP series)

Piston pumps for presses, clamping systems and high-pressure coolant through the spindle.

Model	Flow (L/min)	Max pressure (bar)	Motor power (kW)	Weight (kg)	List price (INR)
HP-350	15	350	11	38	1,24,000
HP-700	25	700	22	64	2,36,500

The HP-700 gives the highest pressure in the range (700 bar). It needs a pressure relief valve set at or below 700 bar and a return-line filter of 10 micron or finer.

5. Hydraulic motors (HM series)

Orbital hydraulic motors for conveyors, winches, agricultural and construction machines.

Model	Displacement (cc/rev)	Max torque (Nm)	Max speed (rpm)	Max pressure (bar)	List price (INR)
HM-250	250	540	300	175	32,400
HM-400	400	860	190	175	45,900

6. How to choose a model

• Coolant or lubrication up to 10 bar: GP-100 or GP-200.

• Quiet precision lubrication: TP series (52 to 56 dB(A)).

• Presses and clamping above 300 bar: HP-350; above 350 bar: HP-700.

• Slow, high-torque rotation: HM-250 or HM-400.

• Always check the motor power: a pump on a smaller motor stalls at full pressure.

7. Ordering and lead times

Series	Standard lead time	Minimum order
GP and TP	2 weeks	1 piece
HP	6 weeks	1 piece
HM	4 weeks	2 pieces

Special shafts, flanges or seals add 2 weeks. Export orders add the shipping time (see Sales Terms and Discount Policy, document ST-03).