

Case Study 3: Movie Ticket Booking

Scenario:

A user books tickets for a movie by selecting seats and confirming the booking

MovieBooking.js

```
import React, { useState } from "react";

function SeatSelector(props) {
  return (
    <div style={{ margin: "10px" }}>
      <h3>{props.movie.title}</h3>
      <p>Timing: {props.movie.timing}</p>
      <p>Price per Seat: {"\u20B9"}{props.movie.price}</p>
      <div>
        {props.seats.map((seat) => (
          <button
            key={seat}
            onClick={() => props.selectSeat(seat)}
            style={{
              margin: "5px",
              padding: "10px",
              backgroundColor: props.selectedSeats.includes(seat) ? "lightgreen" : "lightgray",
            }}
          >
            {seat}
          </button>
        ))}
      </div>
    </div>
  );
}

function Summary(props) {
```

```

return (
  <div style={{ marginTop: "20px" }}>
    <h3>Booking Summary</h3>
    {props.selectedSeats.length === 0 ? (
      <p>No seats selected</p>
    ) : (
      <>
        <p>Selected Seats: {props.selectedSeats.join(", ")}</p>
        <p>Total Cost: {"\u20B9"}{props.selectedSeats.length * props.movie.price}</p>
        <button onClick={props.confirmBooking}>Confirm Booking</button>
      </>
    )}
    {props.confirmed && <h4>Booking Confirmed!</h4>}
  </div>
);
}

const MovieBooking = () => {
  const [selectedSeats, setSelectedSeats] = useState([]);
  const [confirmed, setConfirmed] = useState(false);
  const movie = {
    title: "Avengers: Endgame",
    timing: "7:00 PM",
    price: 150,
  };
  const seats = ["A1", "A2", "A3", "A4", "B1", "B2"];
  const selectSeat = (seat) => {
    if (selectedSeats.includes(seat)) {
      setSelectedSeats(selectedSeats.filter((s) => s !== seat));
    } else {
      setSelectedSeats([...selectedSeats, seat]);
    }
  }
}

```

```

    setConfirmed(false);
  };
  const confirmBooking = () => {
    if (selectedSeats.length > 0) {
      setConfirmed(true);
    }
  };
  return (
    <div style={{ padding: "20px" }}>
      <h2>Movie Ticket Booking</h2>
      <SeatSelector
        movie={movie}
        seats={seats}
        selectedSeats={selectedSeats}
        selectSeat={selectSeat}
      />
      <Summary
        movie={movie}
        selectedSeats={selectedSeats}
        confirmBooking={confirmBooking}
        confirmed={confirmed}
      />
    </div>
  );
};

export default MovieBooking;

```

App.js

```

import MovieBooking from "../components/MovieBooking";

function App() {
  return (
    <div className="App">

```

```
        <MovieBooking />
    </div>
);
}
export default App;
```