

Case Study 1: Online Food Ordering System

Scenario:

A customer browses a food delivery app. They can add food items to a cart, see the total cost, and finally place an order.

OnlineFood.js

```
import React, { useState } from "react";

function FoodCard(props) {

  return (

    <div style={{ border: "1px solid black", padding: "10px", margin: "10px" }}>

      <h3>{props.food.name}</h3>

      <p>Price: {`\u20B9`} {props.food.price}</p>

      <button onClick={() => props.addToCart(props.food)}>Add to Cart</button>

    </div>

  );
}

const OnlineFood = () => {

  const [cart, setCart] = useState([]);

  const [total, setTotal] = useState(0);

  const foods = [

    { id: 1, name: "Pizza", price: 200 },

    { id: 2, name: "Burger", price: 100 },

    { id: 3, name: "Pasta", price: 150 },

  ];

  const addToCart = (food) => {

    setCart([...cart, food]);

    setTotal(total + food.price);

  };

  return (

    <div style={{ padding: "20px" }}>

      <h2>Online Food Ordering System</h2>

      <div style={{ display: "flex" }}>

        <div style={{ flex: 1 }}>
```

```

    <h3>Menu</h3>

    {foods.map((food) => (
      <FoodCard key={food.id} food={food} addToCart={addToCart} />
    ))}
  </div>

  <div style={{ flex: 1, marginLeft: "20px" }}>
    <h3> Cart</h3>

    {cart.length === 0 ? (
      <p>No items in cart</p>
    ) : (
      cart.map((item, index) => <p key={index}>{item.name}</p>)
    )}

    <h4>Total: {"\u20B9"} {total}</h4>
  </div>
</div>

);
};

export default OnlineFood;

```

App.js

```

import OnlineFood from "../components/OnlineFood";

function App() {
  return (
    <div className="App">
      <OnlineFood />
    </div>
  )
}

export default App;

```